
Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL				
B1.0	**Vehicle Dimensions:**		**2490 WB**	**2640 WB**
B1.1	Overall Length mm	**CC**	4750	4988
		FSD	4925	5225
		HSD		
B1.1.1	Total length (mm) (for articulated / combination vehicles)		NA	
B1.2	Width mm		1742	
B1.3	Height (Unladen) (mm)		1961	1948
B1.4	Wheel base (mm)		2490	2640
B1.4.1	Axle spacing in case of multi axle vehicles.		NA	
B1.5	Wheel track (mm)			
B1.5.1	Front		1480	
B1.5.2	Rear		1395	
B1.5.3	Other axles (for articulated/combination vehicles)		NA	
B1.6	Body overhang (mm)			
B1.6.1	Front end		1197	
B1.6.2	Rear end	CC	863	951
		FSD / HSD	1038	1188
B1.7	Frame overhang mm (in case of vehicles without complete body)			
B1.7.1	Front end		937	
B1.7.2	Rear end		808	958
B1.8	Inner dimensions of room or platform (For goods carriage vehicles only)		Refer Annexure T7 – C	
B1.8.1	Length (mm)			
B1.8.2	Width (mm)			
B1.8.3	Height (mm)			
B1.9	Lateral projection		≤2.5mm	
B1.10	Cargo box dimensions (mm)		Refer Annexure T7 – C	
B1.10.1	Length			
B1.10.2	Width			
B1.10.3	Height			
B2.0	**Weights:**			
B2.1	Vehicle kerb weight kg		Refer Annexure T7 - B Details for Recommended load body Refer Annexure T7 – C	
B2.1.1	Front axle 1			
B2.1.2	Front axle 2			
B2.1.3	Rear axle			
B2.1.4	Trailer axle (applicable for articulated / combination vehicles)			
B2.1.5	Total			
B2.2	Gross vehicle weight kg (for rigid vehicles) (Front, Rear & Total)			
B2.2.1	Maximum permissible axle weights (kg)			
B2.2.2	Front axle			
B2.2.3	Rear axle			
B2.2.4	Other axle		NA	
B2.3	Gross combination weight kg (applicable for articulated / Tractor Trailer combination vehicles)		NA	
B2.3.1	Front axle		NA	
B2.3.2	Rear axle		NA	
B2.3.3	Trailer axle / other axles		NA	
B 2.3.4	If applicable, maximum mass of trailer whic5h may be coupled		NA	
B 2.3.5	Unbraked trailer		NA	
B2.4	Reference mass (for vehicles with GVW less than or equal to 3.5 ton) (kg.)		Refer Annexure T7-B	
B2.5	Seating capacity			

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL					
B2.5.1	Maximum (Including driver) for completely built vehicles	D+2			
B3.0	**Tyres:**				
B3.1	Make	**APOLLO**	**CEAT**	**APOLLO**	**CEAT**
B3.1.1	Brand(s) name(s) and/or Trade description(s)	APOLLO Endumaxx LT	CEAT WINMILE X3-R	Endu Maxx LT	CEAT MILAZE LT
B3.1.2	Tyres - Rolling Sound Emissions, Adhesion on Wet Surfaces, Rolling Resistance as per AIS:142	Compliance to Wet Surfaces & Rolling Resistance as per AIS 142			
B3.1.3	Tyre rolling Resistance	7.84 N/kN	7.86 N/kN	8.13 N/kN	9.61 N/kN
B3.1.4	Tyre Class (C1 / C2 / C3) as per AIS:142				
B3.1.4.1	Front	C2			
B3.1.4.2	Rear				
B3.1.5	Category of use (Normal / Special / Snow/Severe Snow)	Normal			
B3.1.7	Tyre Tread Pattern along with Drawing	Refer – SHL / 16 / 2022 – 2023 / 300002XXXX / TA / XXXX	Refer – SHL / 16 / 2022 – 2023 / 300002XXXX / TA / XXXX	Refer - TC7719XX000003XXXF	Refer - SHL/16/2022-2023/300002XXXX/TA/XXXX
B3.1.8	Identification: TAC No. / BIS License No. / E- Marking	CM/L - 756XXXX	CM/L - 372XXXX	CM/L-756XXXX	CM/L – 670007XXXX CM/L - 372XXXX
B3.2	No. and arrangement of wheels				
B3.2.1	Front	2	2	2	2
B3.2.2	Rear	2	2	2	2
B3.2.3	Spare wheel	1	1	1	1
B3.2.4	Identification: TAC No. / BIS License No. / E- Marking	NA			
B3.2.5	Others (For articulated / combination vehicles)				
B3.3	Tyre type (Radial/cross ply) (with Tube / Tubeless), size designation including ply rating, Speed rating, Load rating or Load index. Use symbols as per IS: 15633 / IS: 15636 as may be applicable.	7.00 R15 LT 12 PR 114/109 Q Radial Tube	7.00 R15 LT 12 PR 114/109 L Radial Tube	215/75 R15 LT 115/113 S Radial, Tubeless	215/75 R15 LT 115/113 S Radial, Tubeless
B3.3.1	Front wheel				
B3.3.2	Rear wheel				
B3.3.3	Spare wheel (Other than temporary use spare wheel)				
B3.3.4	Other (for articulated/combination vehicles)	NA			
B3.4	Rolling Radius				
B 3.4.1	Static rolling radius (only applicable for M2, M3, N and T category of vehicles.)	349 mm		325 mm	
B 3.4.2	Dynamic rolling radius, mm, as per IS 15633 / IS 15636	362 mm		339 mm	
B3.5	Inflation pressure – Unladen (kg/cm^2 / kPa)				
B3.5.1	Front, kg/cm^2	2.91 kg/cm2		2.56 kg/cm2	
B3.5.2	Rear, kg/cm^2	2.91 kg/cm2		2.56 kg/cm2	
B3.5.3	Other	NA			
B3.6	Inflation pressure – Laden (kg/cm^2 / kPa)				
B3.6.1	Front, kg/cm^2	3.61 kg/cm2		2.56 kg/cm2	
B3.6.2	Rear, kg/cm^2	6.77 kg/cm2		3.26 kg/cm2	
B3.6.3	Other	NA			
B3.7	Tyre Pressure Monitoring System (TPMS) / Run Flat Warning System as applicable for Run-Flat tyres - as per AIS-110 (If Provided)	NA			
B3.7.1	Make (If Applicable)	NA			
B3.7.2	Brief Description of the system	NA			
B3.8	Temporary Spare Wheel / RFT- as per AIS-110 (If Provided)	NA			
B3.8.1	Type as per AIS-110	NA			
B3.8.2	Make	NA			
B3.8.3	Size	NA			

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL						
B3.8.4	Load and speed rating		NA			
B3.8.5	Recommended max speed in Unladen condition		Limited to 80 Kmph, 60 Kmph & 40 Kmph with SLF			
B3.8.6	Recommended max speed Laden condition		Limited to 80 Kmph, 60 Kmph & 40 Kmph with SLF			
B4.0	**Transmission:**					
B4.1	Type (Manual / Automatic / semi-automatic) (Note: If automatic give all pertinent data)		Manual			
B4.2	Clutch Type (wet / Dry / Single plate / Multiplate / Hydraulic)		Dry / Single plate /Mechanical actuation			
B4.3	**Gear box**					
B4.3.1	Type		Fully synchronized 5 - forward gears with a Constant mesh reverse gear			
B4.3.2	Model name (if any)		XXX-XXX	YYYY-YY		
B4.3.3	Gear shifting control system (Sketch showing gear shifting arrangement)					
B4.3.4	No. of gears		Forward 5 + 1 Rev			
B4.4	Stall ratio of torque converter		NA			
B4.5.	**Sub transmission**		NA			
B4.5.1	Type		NA			
B4.5.2	Control system		NA			
B4.5.3	Gear ratio	High	4.62	4.60		
		Low	0.70	0.70		
B4.6	Final Drive (4x2 or 4x4 or 6x2 or 6x4 or others) Front / Rear / Both		(4 x 2) Rear			
B4.6.1	Type		Single Reduction, Hypoid, Semi-floating Banjo type			
B4.6.2	Reduction ratio		5.13			
B4.6.3	Differential type		Single Reduction, Hypoid, Semi-floating Banjo type			
B4.6.4	Final Drive ratio		5.13			
B4.7	Gear ratio / Gear box ratio / Overall ratio		**Gear Ratio**		**Overall Ratio**	
			RSB	**AVTEC**	**RSB**	**AVTEC**
	1st		4.62	4.60	23.70	21.44
	2nd		2.68	2.69	12.67	12.71
	3rd		1.51	1.49	7.34	7.25
	4th		1.0	1.0	4.56	4.56
	5th		0.70	0.71	3.64	3.67
	6th		-			
	Over drive		-			
	Reverse		4.39	4.38	20.46	20.44
B4.8	Hydraulic transmission		NA			
B4.8.1	Type		--			
B5.0	**Number of axles :**		2			
B5.1	Steered		1			
B5.2	Non-steered		1			
B5.3	Driven		1			
B5.4	Non-driven		1			
B6.0	**Front axle**					
B6.1	Type (Single / Multi / Retractable)		Single			
B6.2	Toe-in / Toe out (mm)		1 to 3 mm			
B6.3	Camber angle		0.5º (+1°,-0.5°)			
B6.4	Caster angle		10.55° (+1°/- 3°)			
B6.5	King pin angle		9°±15’			
B7.0	**Rear axle:**					
B7.1	Type (Single/Tandem/Tridem/Multi/Retractable)		Single			
B7.2	Toe-in/ Toe out mm, if applicable		-			
B7.3	Camber angle, if applicable		-			

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL			
B7.4	Caster angle, if applicable	-	
B7.5	King pin angle, if applicable	-	
B8.0	**Steering system:**		
B8.1	Make	1. XXXX Pvt.Ltd 2. YYYY Pvt.Ltd	
B8.1.1	Type (Manual / Power assisted – Hydraulic / Power assisted – Electric / Other)	Power assisted – Hydraulic	
B8.2	**Steering wheel**		
B8.2.1	Identification Mark / Part No./Drawing No.	X0H001XX	
B8.2.2	Position (center/offset)	0	
B8.2.3	Outside dia. (mm)	389mm	
B8.2.4	**Steering column**		
B8.2.4.1	Make	M/s. XXXXXXX Ltd	
B8.2.4.2	Type / Model	Tiltable Steering column with 4 lobe I shaft design	
B8.2.4.3	Detailed drawing with material specifications	FZY0XX00	
B 8.2.4.1	Air Bag – Part No/ID No/Drawing No, Make	NA	
B 8.2.4.2	Air Bag deployment time as per IS 11939/AIS 96/AIS 98 for steering impact	NA	
B8.2.5	**Intermediate shaft**		
B8.2.5.1	Make	M/s. Rane NSK Steering systems Ltd	
B8.2.5.2	Type / Model	4 lobe design	
B8.2.5.3	Detailed drawing with material specifications	FZY0XX00	
B8.3	Maximum No. of rotation of steering wheel from lock to lock	1. XXXX - 4.1 2. YYYY - 4.1	
B8.4	Details of single / multiple combinations to be given in the form of an Annexure with reference to IS: 11939 –1996	NA	
B8.5	Detailed drawing of the mounting arrangement of Steering control assembly showing vertical / tilt / actual angle.	FZY0XX00	
B8.6	Offset of steering column with respect to the seat	0	
B8.7	**Steering Gear**		
B8.7.1	Type of steering gear (Re-circulating ball / Worm & Roller / Rack & Pinion / Others)	Re-circulating ball type	
B8.7.2	Make	1. XXXX India Pvt.Ltd 2. YYYY India Pvt.Ltd	
B8.7.3	Steering gear ratio	1. XXXX – 17.8:1 2. YYYY – 18.2 :1	
B8.8	**Wheel lock angle (deg.)**	**Inner**	**Outer**
B8.8.1	Left	39	25
B8.8.2	Right	39	25
B8.9	**Power Assistance**		
B8.9.1	Type of assistance	Hydraulic	
B8.9.2	Make	XXXX & YYYY	
B8.9.3	Identification No./ Part No.	1. XXXX - FZZ00XXX 2. YYY - FZZ00XXX	
B8.9.4	Pressure setting (kg/cm^2 / bar / kPa)	1. XXXX – 105 Bar Max 2. YYYY – 120 Bar Max	
B8.10	Min turning circle diameter (mm) (as per IS:12222)	**2490 WB**	**2640 WB**
		10.0 m	10.9 m
B8.11	Min. turning circle clearance diameter (mm)	11.0m	11.9 m
B8.12	Coordinates of point defining test turning circle. (Applicable in case of vehicles without complete body which does not cover this point)	NA	
B9.0	**Clearance (Requirement as per AIS-053, If applicable):**	**2490 WB**	**2640 WB**
B9.1	Minimum road clearance (For other than M1)	214/206	193 / 185
B9.2	Road clearance from floor (for buses)	**NA**	

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL				
B9.3	Approach angle, deg		20.5°	19.4°
B9.4	Departure angle, deg		23.1°	23.5°
B9.5	Ramp-over angle, deg		29.2°	26.7°
B9.6	Minimum Ground Clearance as per IS 9435:2004		214 / 206	193 / 185
B10.0	**Max. stable inclination (For buses as per AIS –031):**		NA	
B10.1	Left		--	
B10.2	Right		--	
B11.0	**Suspension :**		**2490 WB**	**2640 WB**
B11.1	Type and description (Leaf / Coil / Air / Semi-pneumatic/ Torsion bar)		Leaf	
B11.1.1	Front		Parabolic spring- Rigid axle suspension	
B11.1.2	Rear		Semi elliptic spring- Rigid axle suspension	
B11.2	Make			
B11.2.1	Front		Jamna auto industries ltd	
B11.2.2	Rear		Jamna auto industries ltd	
B11.3	Type of spring		Yes	
B11.3.1	Front		parabolic type	
B11.3.2	Rear		Semi elliptic type	
B11.4	If leaf spring		Yes	
B11.4.1	Main spring		Front : parabolic type Rear : Semi elliptic type	
B11.4.1.1	Stack height, at center		Front: 46mm & Rear: 70mm	Front: 51mm & Rear: 91mm
B11.4.1.2	Width at the center point / stack point		Front & Rear: 65mm	Front & Rear: 65mm
B11.4.1.3	Flat length		Front:1055 ± 3mm &Rear: 1140 ± 3.5mm	Front:1055 ± 3mm &Rear: 1180 ± 3.5mm
B11.4.1.4	Free camber		Front: 65mm± 6mm & Rear: 125mm ± 6mm	Front: 74mm± 6mm & Rear: 107mm ± 6mm
B11.4.1.5	No. of leaves	No. of leaves	Front: 3 & Rear: 6	Front: 5 & Rear: 8
		No. of spacers	Front: 2 & Rear: 1	Front: 4 & Rear: 0
B11.4.2	Auxiliary Spring		NA	
B11.4.2.1	Stack height at, at center		--	
B11.4.2.2	Width at the center point / stack point		--	
B11.4.2.3	Flat length		--	
B11.4.2.4	Free camber		--	
B11.4.2.5	No. of leaves		--	
B12.0	**Suspension- Shock absorber:**			
B12.1	Type and Number			
B12.1.1	Front		Double acting hydraulic type – 2 No.s	
B12.1.2	Rear		Double acting hydraulic type – 2 No.s	
B13.0	**Suspension- Stabilizer:**			
B13.1	Front		NA	Yes
B13.2	Rear		NA	NA
B14.0	**Chassis frame:**			
B14.1	Type		Drooped & cranked, variable C section ladder frame	
B15.0	**Displays and tell tales:** (Indicate the type and if the tell tales provided and whether they are symbols or letter. (AIS-071 part 1 and 2 or corresponding Indian Standard))			
B15.1	Head lamp – upper / lower control		0 – 3 Switch provided	
B15.2	Ignition cut-off		Not Provided	
B15.3	Turn signal		Green Color - LH and RH Direction Symbol	
B15.4	Fuel Gauge		LED Bars	
B15.5	Engine coolant temperature		Red Color – Thermometer Symbol	
B15.6	Engine low oil pressure		Red Color – Oil Tank Symbol	
B15.7	High beam indicator		Blue Color – High Beam Symbol	
B15.8	Electrical charge indicator (Battery charge)		Red Color – Battery Symbol	

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL									
B15.9	Brake failure	Red Color – Parking and Oil symbol together							
B15.10	Front fog light, if provided	Not applicable.							
B15.11	Rear fog light, if provided	Not applicable.							
B15.12	Horn	On steering Wheel							
B15.13	ABS	Red Color – ABS function alert							
B 15.14	Seat Belt Reminder	Not Applicable							
B 15.15	Others (such as, Airbag, HVAC, Content gauge, LPG / CNG changeover switch etc.,)	Not Applicable							
B16.0	**Hood latch:**	**NA**							
B16.1	Make	--							
B16.2	Type	--							
B16.3	Identification No. / Part No.	--							
B17.0	**Wheel guard** (IS 13943 for passenger cars)								
B17.1	Dimension C	X5F00258							
B17.2	Dimension p								
B17.3	Dimension q								
B18.0	**External Projections**								
B18.1	Ornaments	Bumper, Door cladding & body fender.							
B18.2	Projection for head light	NA							
B18.3	Radiator grills (Applicable of on external surface)	NA							
B18.3.1	Gap between individual elements								
B18.3.2	Radius of curvature of individual element	>2.5 mm							
B18.4	Body Panel (In case of radius of curvature of folds in body panels are less than 2.5mm the scaled drawing of folds contour and H value as per IS 13942 is required to be submitted)	NA							
B18.5	Radius of curvature of lateral Rain/Air deflector	NA							
B19.0	**Speedometer:**	7.00 R15 LT				215/75 R15 LT			
B19.1	Type	Electronic							
B19.2	Make, and Identification No. / Part No./ Drawing No.	Pricol Limited	Minda stoneridge	Pricol Limited	Minda stoneridge	Pricol Limited	Minda stoneridge		
		FL102XXX	FL103XXX	FL104XXX	FL103 XXX	FL102XXX	FL103XXX		
B19.3	Range	0 - 130 km/h							
B19.4	Major marking	NA (Digital Indicator)							
B19.5	Minor marking	NA (Digital Indicator)							
B19.6	Speedometer ratio, Pulses / km RAR	2440		2424		2590			
B19.7	Ratio of Speedo drive	0.60		0.60		0.64			
B20.0	**Odometer: (only in case of CNG buses)**	NA							
B20.1	Make	--							
B20.2	Type and Identification No. / Part No.	--							
B21.0	**Safety belt anchorages - specifications**								
B21.1	Design of the type of belts and retractors authorized for fit to the anchorages with which vehicle is equipped:								
	Anchorage Position				**Anchorage on (*)**				
					Vehicle Structure	**Seat Structure**			
	Front	Right hand Seat	Lower anchorage	Outboard Inboard	Anchored on BIW	--			
			Upper anchorage			--			
		Middle Seat	Lower anchorage	Right Left	Anchored on BIW	--			
			Lower anchorage			--			
		Left hand Seat	Lower anchorage	Outboard Inboard	Anchored on BIW	--			

Manufacturer signature: _____ Test agency: _____

<table>
<tr><th colspan="7">Table 3 of AIS 007 (Revision 5)
TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL</th></tr>
<tr><td></td><td></td><td></td><td>Upper anchorage</td><td></td><td></td><td>--</td></tr>
<tr><td></td><td>Rear</td><td>NA</td><td>NA</td><td>NA</td><td>NA</td><td>NA</td></tr>
<tr><td>B21.2</td><td colspan="3">Section views of all the seat belt anchorages.</td><td colspan="3" rowspan="2">BWR04501</td></tr>
<tr><td>B21.3</td><td colspan="3">Reference point on body used for vehicle and seat co-ordinate measurement, X, Y, Z co-ordinates of all the seat belt anchorage points.</td></tr>
<tr><td>B21.4</td><td colspan="3">Weight of seats</td><td colspan="3">Driver seat : 11.5 Kg & Co-driver seat : 11Kg</td></tr>
<tr><td>B21.5</td><td colspan="3">C.G. of seats (Sketch, showing the C.G. location from reference point or from seat anchorage point)</td><td colspan="3">ZZZZZZZZZZ</td></tr>
<tr><td>B22.0</td><td colspan="3">Seats, their anchorages and head restraints</td><td colspan="3"></td></tr>
<tr><td>B22.1</td><td colspan="3">Seats, their anchorages and head restraints – specifications for M1 category.</td><td colspan="3">NA</td></tr>
<tr><td>B22.1.1</td><td colspan="3">Description of seats</td><td colspan="3">--</td></tr>
<tr><td>B22.1.1.1</td><td colspan="3">Make</td><td colspan="3">--</td></tr>
<tr><td>B22.1.1.2</td><td colspan="3">Number of seats fitted or capable of being fitted with head restraints, adjustable or not adjustable.</td><td colspan="3">--</td></tr>
<tr><td>B22.1.1.3</td><td colspan="3">Description of the adjustment, displacement and locking systems of the seat or of its parts and a description of occupant protection system against displacement of luggage.</td><td colspan="3">--</td></tr>
<tr><td>B22.1.2</td><td colspan="3">Description of seat anchorage</td><td colspan="3">--</td></tr>
<tr><td>B22.1.2.1</td><td colspan="3">Longitudinal / Vertical (If applicable) position of the seats during the tests.</td><td colspan="3">--</td></tr>
<tr><td>B22.1.2.2</td><td colspan="3">Drawings, diagrams and plans of the seats, their anchorages on the vehicle, the floor layout, the adjustment and displacement system of the seats and their parts, and their locking devices and of additional occupant protection system against displacement of luggage.</td><td colspan="3">--</td></tr>
<tr><td>B22.1.2.3</td><td colspan="3">In the case of seats fitted with head restraints, the head restraint shall be shown on all drawings, diagrams and photographs.</td><td colspan="3">--</td></tr>
<tr><td>B22.1.3</td><td colspan="3">Seat Drawings showing ‘H point co-ordinates with respect to reference point on body shell</td><td colspan="3">--</td></tr>
<tr><td>B22.1.4</td><td colspan="3">All designed positions i.e. Slider, Height Adjuster, Manikin settings, Torso Angle etc.</td><td colspan="3">--</td></tr>
<tr><td>B22.1.5</td><td colspan="3">Seat anchorage co-ordinates with respect to reference point on body shell to be shown on floor drawing.</td><td colspan="3">--</td></tr>
<tr><td>B22.1.6</td><td colspan="3">Seat Identification No. / Part No/Drawing Number.:
<table><tr><th>Description</th><th>Make</th><th>ID Number/ Part Number/Drawing number (Seat Manufacturer/ Vehicle Manufacturer)</th><th>Weight (kg)</th></tr><tr><td></td><td></td><td></td><td></td></tr></table></td><td colspan="3">--</td></tr>
<tr><td>B22.2</td><td colspan="3">Seats, their anchorages and head restrains
(For passenger vehicles of categories other than M1 and goods vehicles of category N).</td><td colspan="3"></td></tr>
</table>

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL				
B22.2.1	Make	XXXXX YYYY		
B22.2.2	Brief description and drawings of the seat type, its attachment fittings and its adjustment, displacement and locking systems including the minimum distance between fitting points.	D+1		
B22.2.3	Position and arrangement of seats including seat layout.	XXXXXXYY		
B22.2.4	Seats if any which incorporate a safety belt anchorage.	NA		
B22.2.5	Driver Seat and Front Passenger Seat drawings, their anchorages on the vehicle, the floor layout, the adjustment and displacement system of the seats and their parts, and their locking devices, drawings showing 'H point co-ordinates and seat anchorage co-ordinates with respect to reference point on vehicle			
B22.2.6	Seat Identification No. / Part No/Drawing Number.:			
	Description	Make	ID Number/ Part Number/Drawing number (Seat Manufacturer/ Vehicle Manufacturer)	Weight (kg)
	Driver seat	XXXX YYY	XXXXXXXX	11.5
	Co-Driver Backrest	XXXX YYY	XXXXXXXX	11
	Co-Driver Cushion	XXXX YYY	XFXXXXXX	
B23.0	**Rear Under run Protective device**	**NA**		
B23.1	Height of lower edge of the device from the ground (mm).	-		
B23.2	Width of the device (mm).	-		
B23.3	Drawing of the rear under-run protective device with dimensions. RUPD cross section, material details etc.	-		
B23.4	Installation drawing showing rear extremity of vehicle, chassis rear overhang, chassis cross section details~~.~~ tyre details (size, make, unladen pressure) etc., distance between tyre & RUPD RH & LH, frame rear width, P1, P2 points.	-		
B23.5	RUPD Material with specific grade	-		
B24.0	**Lateral Protection (Side Guards)**	**NA**		
B24.1	Height of the lower edge of the Side Guard (mm).	-		
B24.2	Drawing of the lateral protection device with dimensions. LPD cross section, material details with grade etc.	-		
B24.3	Distance between tyre & LPD front, rear, RH & LH, distance between supports of LPD, distance between device & load body.			
B25.0	**Controls - Specify method of operation, hand operated – left / right, foot operated – left / right Ref. SS12.1 or corresponding Indian Standard).**	-		
B25.1	Ignition	Hand operated [Rotary Switch RHS]		
B25.2	Horn	Hand operated [Horn pad on steering wheel]		
B25.3	Lamps (Head lamp, Tail lamp, Parking lamp and Number plate lamp)	Hand operated [Rotary switch – RHS]		
B25.4	Turn signal	Hand operated [Swivel arm switch – RHS]		
B25.5	Transmission shift lever	Hand operated [LHS]		
B25.6	Wind shield wiper	Hand operated [Swivel arm switch – LHS]		
B25.7	High beam/low beam	Hand operated [Swivel arm switch – RHS]		
B25.8	Parking brake	Hand operated [LHS]		
B25.9	Master switch for electrical	NA		
B25.10	Hazard warning signal	Hand operated [Push button Switch -LHS]		

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL			
B25.11	Service Brake	Foot operated	
B25.12	Accelerator Pedal (Floor hinged/hanging type)	Foot operated – [Floor hanging Type]	
B25.13	Others	NA	
B26.0	**Safety glass**		
B26.1	**Front wind shield (laminated)**		
B26.1.1	Make	XXXXXX	
B26.1.1.1	BIS License number	CM/L 658XXXX	
B26.1.2	Identification: TAC No. / BIS License No. / E- Marking	CM/L 658XXXX	
B26.1.3	Type (flat/curved, clear/tinted)	Laminated	
B26.1.4	Thickness (mm)	4.66mm	
B26.1.5	Rake Angle	42.06°	
B26.1.6	Method of fixing (for approval of Demisting / Defrosting system)	NA	
B26.2	**Side Windows (Left & Right)**		
B26.2.1	Make	XXXX Ltd.	
B26.2.1.1	BIS License number	CM/L 658XXXX	
B26.2.2.	Identification: TAC No. / BIS License No. / E- Marking	CM/L 658XXXX	
B26.2.3	Type (flat/curved, clear/tinted, toughened/ laminated)	Curved, Tinted, toughened	
B26.2.4	Thickness mm	3.4mm	
B26.2.5	Colour	Clear	
B26.3	**Rear Window**		
B26.3.1	Make	XXXX	YYYY
B26.3.1.1	BIS License number	CM/L 658XXXX	CM/L 620013XXXX
B26.3.2	Identification: TAC No. / BIS License No. / E- Marking	CM/L 658XXXX	CM/L 620013XXXX
B26.3.3	Type (flat/curved, clear/tinted, toughened/ laminated)	Flat	
B26.3.4	Thickness mm	3.5mm	3.5mm
B26.3.5	Radius of curvature (if curved)	FLAT GLASS	
B26.4	**Sun / Moon roof glass**	NA	
B26.4.1	Make	NA	
B26.4.2	Identification: TAC No. / BIS License No. / E- Marking	NA	
B26.4.3	Type (Toughened / Laminated)	NA	
B26.4.4	Thickness mm	NA	
B26.4.5	Colour	NA	
B27.0	**Rear view mirror : [As applicable to the category of vehicle]**		
B27.1	**Interior mirror (Class-I)**	Optional	
B27.1.1	Make	XXXX	
B27.1.2	Identification: TAC No. / BIS License No. / E- Marking	A94506 / E12 01 5480	
B27.1.3	Area of mirror and radius of curvature of reflecting surface	0	
B27.2	**Main mirror (Large) (Class-II)**	NA	
B27.2.1	Make	NA	
B27.2.2	Identification: TAC No. / BIS License No. / E- Marking	NA	
B27.2.3	Area of mirror and radius of curvature of reflecting surface	NA	
B27.3	**Main mirror (Small) (Class-III)**		
B27.3.1	Make	XXXXXYY	

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL				
B27.3.2	Identification: TAC No. / BIS License No. / E- Marking	RXZ562 (M0XX)		
B27.3.3	Area of mirror and radius of curvature of reflecting surface	Area of mirror 0.021m2 Radius of curvature of reflecting surface R1100+201SPH		
B27.4	**Wide angle mirror (Class-IV)**	NA		
B27.4.1	Make	NA		
B27.4.2	Identification: TAC No. / BIS License No. / E- Marking	NA		
B27.4.3	Area and radius of curvature of the mirror glass reflecting surface	NA		
B27.5	**Close proximity mirror (Class-V)**	NA		
B27.5.1	Make	NA		
B27.5.2	Identification: TAC No. / BIS License No. / E- Marking	NA		
B27.5.3	Area and radius of curvature of the mirror glass reflecting surface	NA		
B27.6	**Front mirror (Class-VI)**	NA		
B27.6.1	Make	NA		
B27.6.2	Identification: TAC No. / BIS License No. / E- Marking	NA		
B27.6.3	Area and radius of curvature of the mirror glass reflecting surface	NA		
B27.7	Devices for indirect vision other than mirrors:	NA		
B27.7.1	Make	NA		
B27.7.2	Identification: TAC No. / BIS License No. / E- Marking	NA		
B27.7.3	Area and radius of curvature of the mirror glass reflecting surface	NA		
B27.8	Brief drawing showing installation dimensions of all mirrors provided on the vehicle and drivers ocular point angle with RH mirror	VFT0XXXX		
B28.0	**Information on safety belt / restraint system:**			
B28.1	Safety belt	Provided		
B28.1.1	Make of seat belt	Samsung		
B28.1.2	Type and configuration	Three-point seat belt with ELR for driver & co-driver outboard, Two point static lap belt for Center seat.		
B28.1.3	Identification No. / Part No.	**Description**	**Make**	**Part number**
		Buckle RH	Samsung	FWS00XXX
		Buckle LH	Samsung	FWS00XXX
		Tounge (ELR & STATIC)	Samsung	FWS00XXX
		Belt anchorage top	Samsung	FWS00XXX
		Buckle CTR	Samsung	FWS01XXX
		Lap Tounge	Samsung	FWS01XXX
B28.2	**Restraint system**			
B28.2.1	Make	Samsong Industries Ltd		
B28.2.2	Type and configuration	Three-point seat belt with ELR for driver & co-driver outboard, Two point static lap belt for Center seat.		
B28.2.3	Identification No. / Part No.	Description	Make	Part number
		Buckle RH	Samsung	FWS00XXX
		Buckle LH	Samsung	FWS00XXX
		Tounge (ELR & STATIC)	Samsung	FWS00XXX
		Belt anchorage top	Samsung	FWS00XXX
		Buckle CTR	Samsung	FWS00XXX
		Lap Tounge	Samsung	FWS00XXX
B28.2.4	Drawings of the relevant parts of the vehicle structure and any seat anchorage reinforcements.	XXXYYYXX		
B28.2.5	Drawings of seat, showing its structure, adjustment system and fixing components, with an indication of the materials used.	XXXXXXXX		

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL					
B28.2.6	Drawing or photograph of the restraint system as installed.			NA	
B28.2.7	Drawing showing the installation of belts on the vehicle.			XXXXXYYY	
B28.3	**Safety belts and / or other restraint systems :**				
B28.3.1	Number and position of safety belts and restraint systems and seats on which they can be used :				
	Row of Seat	Location*	Type of seat belt	Variant (if applicable)	Belt adjustment device for height (Indicate yes/no/ optional)
	First row of Seats	L	3 pt ELR	No	No
		C	Lap Belt	No	No
		R	3 pt ELR	No	No
	Second row of seats	L	NA	No	No
		C	NA	No	No
		R	NA	No	No
	The table may be extended as necessary for vehicles with more than two rows of seats there are more than three seats across the width of the vehicle. * (L = left-hand side, R= right-hand side, C= Center)				
B28.4	**Emergency exit**			**NA**	
B28.4.1	Position			--	
B28.4.2	Size			--	
B29.0	**Fuel tank :**				
B29.1	Make			M/s. XXXXYYYY	
B29.2	Material (Metallic / Plastic etc.)			Metallic	
B29.3	Nominal thickness mm			1.0mm	
B29.4	Capacity, Litre			40 Lts, 30 Lts	
B29.5	Detailed drawing of the fuel tank assembly with material specifications			FHSXXXXY FHSXXXXY	
B29.6	Detailed drawing indicating the position / location of the fuel tank(s) in the vehicle.			A5LXXX00 (50 LTS) A5LXXX00 (40 LTS)	
B29.7	Identification No. / Part No.			FHS00544 FfffXXXcdHXXS00744	
B30.0	**Wheel rim:**				
B30.1	**Front**				
B30.1.1	Make			M/s. XXXXYYYY Limited	
B30.1.1.1	BIS license Number			CM/L-670XXXXXX4 (Chennai)	
B30.1.2	Part number of wheel rim supplier			X5E06XXXX / X5E1XXXX	
B30.1.3	Size			5.5J x 15	
B 30.1.4	Type (Alloy / Sheet metal / spoke)			Sheet metal (Steel)	
B30.2	**Rear**				
B30.1.1	Make			M/s. XXXXYYYY Limited	
B30.1.1.1	BIS license Number			CM/L-6XXXXX14 (Chennai)	
B30.1.2	Part number of wheel rim supplier			X5EXXX00 / X5XXXX00	
B30.1.3	Size			5.4J x 14	
B 30.1.4	Type (Alloy / Sheet metal / spoke)			Sheet metal (Steel)	
B30.3	**Others**				
B30.1.1	Make			M/s. XXXXYYYY Limited	
B30.1.1.1	BIS license Number			CM/L-670XXXXXX4 (Manam)	
B30.1.2	Part number of wheel rim supplier			X5E0XX00 / X5E1XX00	
B30.1.3	Size			5.4J x 14	
B 30.1.4	Type (Alloy / Sheet metal / spoke)			Sheet metal (Steel)	
B31.0	**Door, Door locks and hinges:**				
B31.1	Doors				
B31.1.1	No. of doors			2	
B31.1.2	Position and type of door			Front Side door, hinged	

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL		
B31.1.3	Detailed drawing of the door including location of the door strengthening bars, Dimensions of door reinforcements from door lower edge, cross section of the bars, material specification of the bar and door sheet metal, number of reinforcements and details of welding / bolting etc., (for side door impact test)	--
B31.2	**Door lock / latch**	
B31.2.1	**Front**	
B31.2.1.1	Make	XXXYYY Pvt ltd.
B31.2.1.2	Identification No. / Part No.	X7K00XXXX
B31.2.2	**Rear**	**NA**
B31.2.2.1	Make	NA
B31.2.2.2	Identification No. / Part No.	NA
B31.3	**Door hinge**	
B31.3.1	**Front**	
B31.3.1.1	Make	XXXYYY Pvt ltd.
B31.3.1.2	Identification No. / Part No.	FDTXXX13
B31.3.2	**Rear**	**NA**
B31.3.2.1	Make	NA
B31.3.2.2	Identification No. / Part No.	NA
B32.0	**Wheel nut, Wheel cap and Hub cap:**	
B32.1	**Wheel Nut (s) / Bolt (s)**	
B32.1.1	Make	M/s. XXXXX Fasteners
B32.1.2	Size	M13 x 1.4
B32.1.3	No. per wheel	5
B32.1.4	Tightening torque on vehicle (recommended by Vehicle Manufacturer)	160 – 170 Nm
B32.1.5	Detailed dimensional drawing along with material specifications	X5M00YYY, X5M0YYYY
B32.2	**Wheel cap (if provided)**	**NA**
B32.2.1	Detailed dimensional drawing along with material specifications	NA
B32.3	**Hub cap**	
B32.3.1	Make	Ashok Leyland Ltd
B32.3.2	Method of fitment (Press/bolted/others)	Press
B32.3.3	Brief dimensional drawing along with press fit diameter as applicable	FKCXXX13
B33.0	**Towing devices:**	NA
B33.1	Type	NA
B33.2	Make	NA
B33.3	Capacity	NA
B34.0	**Coupling devices (for trailers) :**	NA
B34.1	Make	NA
B34.2	Identification mark	NA
B34.3	Type of coupling device for mechanical	NA
B34.4	Type of coupling device for electrical	NA
B34.5	Type of coupling device for brake	NA
B34.6	Dia. Of king pin (mm)	NA
B35.0	**Spray Suppression System**	NA
B35.1	Make	NA
B35.2	Type (Water separator / Pulveriser)	NA
B35.3	Identification No. / Part No.	NA
B35.4	Size	NA
B35.5	Detailed engineering drawing as specified in AIS – 013 or photographs showing the mounting details with dimensions.	NA

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL		
B36.0	**Interior Fittings as per IS 15223 or AIS - 047, as applicable**	
B36.1	Instrument Panel (Dash Board)	
B36.2	Make	TXXO IPD
B36.3	Identification No. / Part No./ Drawing No.	BEXX3201
B36.4	Drawing showing the mounting details, overall size and all control switches with dimensions	BWR0XX01
B36.5	Additional details for interior fitting tests to be given (if test is already conducted, this information need not be submitted).	NA
B36.5.1	Instrument Panel Variants with photographs (With / without Airbag, Music system, AC)	NA
B36.5.2	Material used for instrument Panel	PPTYY & PCXXS
B36.5.3	Drawings	
B36.5.3.1	Instrument Panel mounting (With hardware details)	BWRXXYY1
B36.5.3.2	'H' point co-ordinates for each seating position	BWRXXYY1
B36.5.3.3	Cross sectional drawings for each projection more than 3.2	NA
B36.5.3.4	Cross sectional Drawing of Gear shift lever (Knob)	FXA0XXYY (Non AC) / FXA0XXYY (AC)
B36.5.3.5	Drawing of Grab handle with cross section	F0C0XYZ8
B36.5.3.6	Drawing of Sun visor with details of metal wire used	X1E00XYZ (LH) / X1E00XYZ (RH)
B36.5.3.7	Drawing of lamp assembly mounted at roof	FL804XYZ
B36.5.3.8	Drawing of Cigarrete lighter/ charging point	FSC01XYZ
B36.5.3.8	Any other fitment	--
B37.0	**Bumper (for M1 category vehicle):**	NA
B37.1	Make	NA
B37.2	Identification No. / Part No./Drawing No.	NA
B37.3	Installation drawing showing location of Bumper in the front and rear, fitment of the Bumper, dimensions of Bumper, mounting points, details of mounting fasteners and additional fitments on it.	NA
B37.4	Material of Bumper with details (metallic / non-metallic)	NA
B37.5	Test method to be adopted by the test agency (Pendulum impact test, Component level vibration test, or Vehicle level four poster test)	NA
B 38.0	**Flammability requirements of interior materials as per IS: 15061, as applicable.**	
B 38.1	**Seat Upholstery**	
B 38.1.1	Make	M/s. XXXXYYY
B 38.1.2	Material and Composition	Vinyl
B 38.1.3	Identification No. / Part No./Drawing No.	FWR0XYZ0
B 38.2	**Roof lining**	
B 38.2.1	Make	Supreme
B 38.2.2	Material and Composition	PU + Glass fiber + Non woven Fabric FM60XYZ8
B 38.2.3	Identification No. / Part No./Drawing No.	
B 38.3	**Floor lining**	
B 38.3.1	Make	UNXXYY PVT LTD.
B 38.3.2	Material and Composition	Carpet type – Non Woven Fabric
B 38.3.3	Identification No. / Part No./Drawing No.	FGM00XY8 MAIN FLOOR MAT FGM00XY8 CO-DRIVER MAT FGM00XY8 DRIVER SIDE MAT
B 38.4	**Side wall lining**	**NA**
B 38.4.1	Make.	--
B 38.4.2	Material and Composition	--
B 38.4.3	Identification No. / Part No./Drawing No.	--

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL		
B 38.5	**Rear wall lining**	**NA**
B 38.5.1	Make	--
B 38.5.2	Material and Composition	--
B 38.5.3	Identification No. / Part No./Drawing No.	--
B 38.6	**Interior lining of luggage racks**	**NA**
B 38.6.1	Make	--
B 38.6.2	Material and Composition	--
B 38.6.3	Identification No. / Part No./Drawing No.	--
B 38.7	**Heating and ventilation pipe**	**NA**
B 38.7.1	Make	--
B 38.7.2	Material and Composition	--
B 38.7.3	Identification No. / Part No./Drawing No.	--
B 38.8	**Curtain / Blinds / Hanging material**	**NA**
B 38.8.1	Make	--
B 38.8.2	Material and Composition	--
B 38.8.3	Identification No. / Part No./Drawing No.	--
B 38.9	**Material for Luminaries**	**NA**
B 38.9.1	Make	--
B 38.9.2	Material and Composition	--
B 38.9.3	Identification No. / Part No./Drawing No.	--
B 38.10	**Separation wall**	**NA**
B 38.10.1	Make	--
B 38.10.2	Material and Composition	--
B 38.10.3	Identification No. / Part No./Drawing No.	--
B39.0	**Hand holds (as per AIS - 046)**	
B39.1	No. of hand holds	2
B39.2	Details and dimension of hand hold indicating length, clearance between the hand hold and body and cross sectional area of every hand hold (if required, details may be provided as a separate Annexure)	F0CXYZ68
B39.2.1	Make	XXXX YYYY COMPONENTS LTD.
B39.2.2	Identification No. / Part No./Drawing No.	FGM00XYZ
B39.2.3	Type (Grab handle / Strap / Hand Rail)	GRAB HANDLE
B39.2.4	Material	PP XYZ
B39.2.5	Size	REF DRAWING NO. F0XYZ468
B39.3	Installation drawing of hand hold, showing location of mounting for every seating position, passengers details of mounting fasteners and additional fitments on it.	F0C0XYZ8
B 40.0	**Arrangement of front controls (For M1 category as per AIS – 035)**	**NA**
B 40.1	Distance between the contour points of the orthogonal projections on to plane “P” of the accelerator pedal and service brake pedal bearing surfaces, “E” in mm.	--
B 40.2	Distance between the projection of the service brake pedal on to the reference plane “P”, to the right, “H” in mm.	--
B 40.3	Distance between the projection of the service brake pedal on to the0 reference plane “P”, to the left, “J” in mm.	--
B 40.4	Drawing showing the parts and arrangement of the foot controls along with dimensions “E”, “H” and “J”	--
B41.0	**Statutory Plates – Vehicle Identification Number (As per AIS - 065)**	

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL		
B41.1	Drawings and/or photographs of the locations of the statutory plates and inscriptions and of the vehicle identification number	X4W0XYZ4 / VFT0XYZ2
B41.2	Drawings and / or photographs of the official part of the plates and inscriptions (completed example with dimensions)	X4WXYZ44
B41.3	Drawings and / or photographs of the Body Builder's Plates and its location on the vehicle	NA
B41.4	World Manufacturer's Identifier (WMI) code and its location in Vehicle Identification Number (VIN)	1st, 2nd& 3rdCharacters of 17 Characters VIN
B41.5	Location of Vehicle Descriptor Section (VDS) in Vehicle Identification Number (VIN)	4thto 9thCharacter of 17 Characters VIN
B41.6	Location of Vehicle Indicator Section (VIS) in Vehicle Identification Number (VIN)	10thto 17thCharacter of 17 Characters VIN
B41.7	Height of characters in VIN (mm)	4 mm (min in Plate) / 7 mm (min)
B42.0	**Window retention and release for Buses as per IS: 13944**	**NA**
B42.1	**Window safety glass**	**--**
B42.1.1	Method of Window Fixing (sliding or sealed or opening outside etc.)	--
B42.1.2	Brief description of the Provision for emergency exit provided in case of sealed windows	--
B42.1.3	Name of the Window Manufacturer	--
B42.2	Drawing (including Drawing no. & Revision no.) including Plan view, Elevation, LH, RH view of vehicle showing the dimensions of all windows, seating layout and location of emergency exit.	--
B42.3	Detailed brief dimensional drawing of emergency exit indicating its location(s)	--
B42.4	Number of passenger compartment doors provided in addition to driver's door.	--
B42.5	Dimensions Emergency exit identification	--
B42.5.1	Number(s) and Dimensions of Roof Exit (if provided)	--
B42.6	Dimensions of the instructions describing each motion necessary to unlatch and open the exit are provided from the release mechanism.	--
B 43.0	**Front Under run Protective devices as per AIS: 069**	**NA**
B 43.1	Drawing of the vehicle parts relevant to the front under run protection, i.e, drawing of the vehicle and/or chassis with position and mounting and/or fitting of the front under run protective device. Mentioning material details of FUPD & mounting hardware. If the under-run protection is by no special device, the drawing should clearly show as how the required dimensions are met.	--
B 43.2	In the case of special device, full description and/or drawing of the front under run protection (including mountings and fittings). & material details, distance of P1 & P2 points from center & tyres.	--
B43.3	Installation drawing of the FUPD with dimensions like cross section, distance between tyre & FUPD RH side & LH side, distance between front extremity & FUPD, width of FUPD, ID marking of FUPD, Width measured from the outermost points of access steps to driver cabin etc.	--
B 44.0	**Coupling Device (for T Category)**	NA
B 44.1	Trade name or mark / approval No(s):	--
B 44.2	Type (Mechanical / Close):	--

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL		
B 44.3	Class of coupling device	--
B 44.4	Maximum permissible static mass on coupling ball (kg)	--
B 44.5	Maximum permissible static vertical load on coupling ball (kgf)	--
B 44.6	Drawing showing details of mounting points on the vehicle	--
B 44.7	D..... kN Dc..... kN S..... kg U.....tonnes V..... …kN	--
B 45.0	**Make of the rear marking plate:**	--
B 45.1	Rear marking plate type:	--
B 45.2	Rear marking plate class:	--
B 45.3	Position and nature of the marking:	--
B46.0	**Child Restraint system (CRS) ;**	--
B46.1	Seating Positions for Child restraint system (As per AIS-072)	

Mass Group	Seating Position (or other site)				
	Front Passenger	Rear Outboard	Rear Centre	Intermediate Outboard	Intermediate Centre
Group 0 up to 10 kg	NA	NA	NA	NA	NA
Group 0+ up to 13 kg	NA	NA	NA	NA	NA
Group I 9 to 18 kg	NA	NA	NA	NA	NA
Group II 15 to 25 kg	NA	NA	NA	NA	NA
Group III 22 to 36 kg	NA	NA	NA	NA	NA

Key of letters to be inserted in the above table:

U = Suitable for "universal" category restraints approved for use in this mass group.

UF = Suitable for forward-facing "universal" category restraints approved for use in this mass group.

L = Suitable for particular child restraints given on attached list. These restraints may be of the "specific vehicle", "restricted" or "semi-universal" categories.

B = Built-in restraint approved for this mass group.

X = Seat position not suitable for children in this mass group.

B46.2	Details of CRS (To be provided if the CRS is not of Universal category (U/UF))	--
B46.3	Category of CRS(Semi Universal, Restricted or specific vehicle)	--
B46.4	Belt type: (adult) three-point belt (adult) lap belt/ special type belt/retractor;	--
B46.5	Trade name or mark	--
B46.6	Manufacturer's designation of the child restraint.	--
B46.7	Drawings, Diagrams and plans of the child restraint, including any retractor, chair assembly, impact shield fitted;	--
B46.8	Drawings, Diagrams and plans of the vehicle structure and the seat structure, as well as of the adjustment system and the attachments, including any energy absorber fitted;	--
B46.9	Photographs of the child restraint and/or vehicle structure and seat structure;	--
B47.0	**Head-On Collision as per AIS :96 and Off-set frontal collision as per AIS:98**	NA
B47.1	Brief description of the vehicle type as regards its structure, dimensions, lines and constituent materials:	--

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL		
B47.2	Description of the protective system installed in the vehicle:	--
B47.3	Description of interior arrangements or fittings that might affect the tests:	--
B47.4	(Photographs and/or diagrams and drawings permitting the basic identification of the type(s) of vehicle and its possible variants which are covered by the approval)	--
B48.0	**Side-Impact resistance as per AIS: 99**	NA
B48.1	A detailed description, including photographs and/or drawings, of the vehicle type with respect to the structure, the dimensions, the design and the constituent materials, the side walls of the passenger compartment (exterior and interior), including specific details of the protection system, where applicable:	--
B 51.0 **B49.0**	**Pedestrian protection as per AIS-100:** The distance, measured longitudinally on a horizontal plane, between the transverse centerline of the front axle & the R point of the driver's seat is less than 1100 mm (Yes / No).	NA
B49.1	Drawing of Bonnet & wings/ fender including material details	--
B49.2	Drawing / Images of position & arrangement of Engine	--
B49.3	Drawing/ Images of Under bonnet (Engine house) Components.	--
B49.4	Drawing mentioning ground levels for correct ride attitude of the vehicle.	--
B49.5	If lower bumper height is greater than, or equal to 425 mm and less than 500 mm, then test to be conducted with lower leg form or upper leg form	--
B49.6	Identified zones of the bonnet top where the HIC must not exceed 1,000 (HIC1000 Zone) & 1,700 (HIC1700 Zone) respectively with drawing of the complete test impact area with 1000 and 1700 HIC zones mark on it.	--
B50.0	**Speed Governor (As applicable)**	
B50.1	Type of Speed Governor (SLD / SLF)	SLF
B50.2	Speed Limiting Device (SLD) [For vehicles with max. speed above 80 kmph in unladen condition as per AIS-018]	NA
B50.3	Make	M/s. XXXYYY
B50.4	Model	DXM 8.1AP
B50.5	Identification: TAC No. / BIS License No.	AL Development ID : F6NXYZW1 AL Production ID : F6NXYZW0
B50.6	SLD approved for speed/s (Annexure to be provided including information for every Vehicle Model / Variants indicating various SLD approved speeds contributed due to declared transmission options)	--
B51.0	**Temporary Cabin for drive away chassis :**	NA
B51.1	Width of the temporary cabin (mm)	--
B51.2	Height of the temporary cabin (from seat top surface to canopy) (mm)	--
B51.3	Depth or Length of the temporary cabin (Clearance from the rear most back rest when the seat is taken at the rear-most position) (mm)	--
B51.4	Windshield type	--

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL				
B51.5	Drawing showing the mounting and relevant dimensions	--		
B52.0	**AIS-029 Survival Space for the Protection of the Occupants of the Cab of a Commercial Vehicle**			
B52.1	Drawing showing R-Point height for vehicle w.r.t ground & fiducial point on the vehicle for driver	VFT0XYZ2		
B52.2	**Cabin & Mounts Construction Details :**			
B52.3	Construction: Integrated / Attached with Mounts	4 Mounts, Fixed CABIN		
B52.4	If attached with mounts: Number of cabin mounts: Cabin type: Tiltable / Fixed	Day		
B52.5	Cabin Size: Day / Sleeper / High-Roof / Low Roof / Extended Day Cab / Any combination	B4Z8XYZ1 B0Y7XYZ0		
B52.6	Detailed drawings showing construction details of the cabin in sufficient details alongwith list of materials used in construction of the cabin	B4Z8XYZ1		
B52.7	Drawings of vehicle, showing the position of the cab on the vehicle and the manner of its attachment, and by sufficiently detailed drawings relating to the structure of the cab,	B4Z8XYZ1 B0Y7XYZ0		
B52.8	Layout drawings for different types of cabin mounts available alongwith their position on chassis/frame, material properties of the mounts, attachment details, fastener details etc.			
B52.9	**Interior Space & Standard Fitments**			
B52.10	Layout drawings of the seating layout inside the cabin showing designated position of driver, co-driver, additional passengers, sleeper berths, second row seating positons etc.	BWR0XYZ1		
B52.11	Individual drawings of the driver & other seats showing normal position of use along with adjustment positions clearly identified	--		
B52.12	Layout drawings of the steering mechanism in mounted position along with normal position of use & adjustment positions clearly identified	FZY02XYZ – Upper Column FZY04XYZ – Intermediate column		
B 55.0	**Information for Speed alert**	NA		
B 55.1	Details of audible alert (Alert above 80 km/h)	--		
B 55.2	Details of audible alert Continuous /intermittent.(Alert above 120 km/h)	--		
B 55.3.	if intermittent, Interval between Alerts	--		
B 56.0	**Information for Safety belt reminder**	NA		
B 56.1.	Whether Visual warning for Safety belt reminder provided	--		
B 56.2.	Whether audible warning for Safety belt reminder provided	--		
B 57.0	**Information for manual over-ride (Door, Door locks and hinges) (Yes/No):**	N0		
B 58.0	Information for Reverse Parking Alert System			
B 58.1.	Type of System (Sensor based / Camera based system)	Sensor		
B 58.2.	Sensor based system-(as applicable) information	Ultrasonic Sensor		
B 58.2.1	Make	XXXXX YYYYY Ltd		
B 58.2.2	Identification No. / Part No.	**Description**	**AL Part No.**	**Hella Part No**
		Sensor	FVG00XYZ	015.ABS-00
		ECU	FVG01XYZ	015.ABS-01
		Buzzer	X4Z00XYZ	015.ABS-00

Manufacturer signature: _____ Test agency: _____

Table 3 of AIS 007 (Revision 5) TECHNICAL SPECIFICATION – FOUR WHEELERS AND ABOVE PART B - VEHICLE OVERALL		
B 58.2.3	Number of sensors and mounting location	Option 1: 4 Sensors mounted on Tail Lamp bracket and load body Option 2: 3 Sensors mounted on Tail Lamp bracket and load body
B 58.3.	Camera based System (as applicable)	NA
B 58.3.1	Make	NA
B 58.3.2	Identification No. / Part No.	NA
B 58.3.3	Camera mounting location	NA
B 58.3.4	Display Make	NA
B 58.3.5	Display Identification No. / Part No.	NA
B 58.3.6	Display location	NA
B 58.3.1	Make	NA

Manufacturer signature: _____ Test agency: _____

Manufacturer signature: _____ Test agency: _____