Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.0	Description of energy converters and power plant. (In the case of a vehicle that can run either on petrol, diesel, etc., or also in combination with another fuel, items shall be repeated.1)	Diesel
1.1.	Engine Manufacturer:	Ashok Leyland Limited
1.1.1.	Manufacturer's engine model code (as marked on the engine, or other means of identification)	Model Code: ALXYZABC0 Enclosure – 4A
1.1.2.	Location of engine model code and engine serial number on block / crankcase (drawing to be attached)	Engine Model Code Location - On Engine Head Cover Engine Serial Number Location - On Engine Block Refer Enclosure – 4A
1.2.	Internal combustion engine:	
1.2.1.	Specific engine information	
1.2.1.1.	Working principle: positive ignition / compression-ignition, four-stroke / two-stroke / rotary cycle (DI/IDI) (NA/TC/TCIC/Any other)	Compression Ignition, four-stroke, DI, TCIC
1.2.1.2.	Number, arrangement of cylinders:	3, Inline
1.2.1.2.1.	Bore----------(mm)	80
1.2.1.2.2.	Stroke: ----------(mm)	98
1.2.1.2.3.	Firing order:	1-2-3
1.2.1.3.	Engine capacity:----------(cm^3)	1468
1.2.1.4.	Volumetric compression ratio (specify tolerance)	17.5±1.0 : 1
1.2.1.5.	Drawings of combustion chamber and piston crown and, in the case of positive ignition engine, piston rings:	Refer Enclosure – 4B
1.2.1.5.1	Vehicle with Defeat Device Yes / No	No
1.2.1.5.2	If yes – Details of the Defeat device	NA
1.2.1.6.	Normal engine idling speed (specify tolerance):	700 ± 100 rpm
1.2.1.6.1.	Carbon monoxide in % and HC (n hexane equivalent) in PPM content by volume in the exhaust gas with the engine idling,(for SI engines only)	NA
1.2.1.7.	High idle engine speed (specify tolerance): -	NA
1.2.1.7.1	High Idle Lambda value (1± 0.03) or as specified by the vehicle manufacturer)	NA
Vehicles can be fuelled with both petrol and a gaseous fuel but if the petrol system is fitted for emergency purposes or starting only and the petrol tank cannot contain more than 5 litres of petrol, they will be regarded for the test as vehicles which can only run a gaseous fuel.		
1.2.1.8.	Maximum net power:..... kW at min^{-1}	55.1 KW @ 3100 ± 50 rpm
1.2.1.9.	Maximum permitted engine speed as prescribed by the manufacturer- min^{-1}	3500 rpm
1.2.1.10.	Maximum net torque: ……Nm at: -------min^{-1} …(manufacturer's declared value)	170 Nm @ 1600 – 2400 rpm
1.2.1.11	Maximum rated speed (Specify tolerance)	3100 rpm ± 50 rpm
1.2.1.12	Minimum rated speed (Specify tolerance)	1000 rpm ± 100 rpm
1.2.1.13	Engine Performance Declared speed and powers of the engine submitted for type approval) (Speeds to be agreed with the testing agency)	
1.2.1.13.1	Engine Power Table	

Measurement point*	Engine speed rpm	New Power kW**
(1)	1100	15.5
(2)	1600	32.0
(3)	2000	40.5
(4)	2400	48.0

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms			
	(5)	2800	52.6
	(6)	3000	53.5
	(7)	3100	55.1
	* See reference in AIS 137 ** Net power according to AIS 137		
	Note: In case, if data regarding the Moment of Inertia, is required by the test agency for carrying out the Full Throttle performance test for both the CI / SI engines, the same shall be provided by the manufacturer.		
1.2.2.	Fuel		
1.2.2.1	Type of fuel used : Mono Fuel / Bi-Fuel / Flex Fuel / Dual Fuel		Mono Fuel
1.2.2.2	Fuel type: Diesel / Gasoline / LPG / CNG / Biomethane / Bio-H_2 methane / HCNG / Biogas / LNG / Ethanol ((E85) / (E100)) /ED (95) Flex fuel Methanol M15 / M100 / MD95 / Biodiesel up to 100% / Hydrogen.		Diesel
1.2.2.3	Maximum amount of biofuel acceptable in fuel (manufacturer's declared value): per cent by volume		7%
1.2.3.	Fuel feed		
1.2.3.1	By fuel injection (compression-ignition only): (Yes/No)		Yes
1.2.3.1.1	System description:		Unit Pump Common Rail Direct Injection system
1.2.3.1.2	Working principle: direct-injection/pre-chamber/swirl Chamber		Direct Injection
1.2.3.1.3	Injection pump		
1.2.3.1.3.1	Make(s):		M/s. XXXXYYY
1.2.3.1.3.2	Type(s) & Identification Number:		Plunger Type & FHL0XYZ0
1.2.3.1.3.3	Maximum fuel delivery in (mm^3 /Stroke) or (kg/hr) with tolerance at max net power engine speed (min^{-1}) or characteristic diagram: If boost control is supplied, state the characteristics fuel delivery and boost pressure versus engine speed		13.5 ± 1 kg/hr @ 3300 rpm
1.2.3.1.3.4	Injection advance curve (Specify the tolerances):		ECU Controlled
1.2.3.1.4	Governor		ECU Controlled
1.2.3.1.4.1	Cut-off point:		
1.2.3.1.4.1.1	Cut-off point under load:…(min^{-1})		3300
1.2.3.1.4.1.2	Cut-off point without load (Maximum no-load speed)…(min-1)		3600 ± 100 rpm
1.2.3.1.5	Injector(s):		
1.2.3.1.5.1	Make(s):		M/s. XXXXYYY
1.2.3.1.5.2	Type(s) & Identification Number:		Multi-Hole Injectors (7 holes) FKXXYYZZ
1.2.3.1.5.3	Opening pressure (kPa) (specify the tolerances) or characteristic diagram		15000 to 23000 kPa
1.2.3.1.5.4	**Injection piping**		
1.2.3.1.5.4.1	Length and internal diameter…(mm)		Length (Pump to Rail) - 130± 3 Length (Rail to Injectors) - 193.5± 3 Internal Diameter – 3mm
1.2.3.1.5.4.2	Common rail make & type		M/s. XXXXYYY, Hot Forged Rail Type
1.2.3.1.6	Cold start system		NA
1.2.3.1.6.1	Make(s):		NA
1.2.3.1.6.2	Type(s) & Identification Number:		NA
1.2.3.1.6.3	Description:		NA
1.2.3.1.7	Auxiliary starting aid		NA
1.2.3.1.7.1	Make(s):		NA
1.2.3.1.7.2	Type(s):		NA
1.2.3.1.7.3	System description:		NA
1.2.3.1.8	**Electronic controlled injection: (Yes/No)**		Yes

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.2.3.1.8.1	Make(s):	M/s. XXXXYYY
1.2.3.1.8.2	Type(s):	Common Rail, Direct Injection with Pressure Sensor, Controlled by ECU
1.2.3.1.8.3	Description of the system (in the case of systems other than continuous injection, give equivalent details):	NA
1.2.3.1.8.3.1	Make and type of the control unit:	M/s. XYZX and Electronic Control Unit
1.2.3.1.8.3.2	Make and type of the fuel regulator:	M/s. XYZX and Fuel metering Pump with in-built Inlet Metering Valve
1.2.3.1.8.3.3	Make and type of air-flow sensor:	M/s. Continental and Active type
1.2.3.1.8.3.4	Make and type of fuel distributor:	M/s. Delphi-TVS and Metering type
1.2.3.1.8.3.5	Make and type of throttle housing:	M/s. Padmini and Butterfly Valve type
1.2.3.1.8.3.6	Make and type of water temperature sensor:	M/s. Continental and Thermistor Type
1.2.3.1.8.3.7	Make and type of air temperature sensor:	M/s. Continental and Thermistor Type
1.2.3.1.8.3.8	Make and type of air pressure sensor:	M/s. Continental and Piezo Resistance Type
1.2.3.2	**By fuel injection (positive ignition only): (Yes/No)**	No
1.2.3.2.1	Working principle: intake manifold (single/multi-point)/direct injection/other (specify)	NA
1.2.3.2.2	Make(s) of Injection Pump :	NA
1.2.3.2.3	Type(s) & Identification Number of Injection Pump:	NA
1.2.3.2.4	System description (in the case of systems other than continuous injection give equivalent details):	NA
1.2.3.2.4.1	Make and type of the control unit:	NA
1.2.3.2.4.2	Make and type of the fuel regulator:	NA
1.2.3.2.4.3	Make and type of the air-flow sensor:	NA
1.2.3.2.4.4	Make and type of the micro-switch:	NA
1.2.3.2.4.5	Make and type of the throttle housing:	NA
1.2.3.2.4.6	Make and type of the water temperature sensor:	NA
1.2.3.2.4.7	Make and type of the air temperature sensor:	NA
1.2.3.2.5	Injectors: Opening pressure (Specify the tolerances):..... (kPa) or characteristic diagram:	NA
1.2.3.2.5.1	Make(s):	NA
1.2.3.2.5.2	Type(s):	NA
1.2.3.2.5.3	Identification Number	NA
1.2.3.2.5.4	Maximum fuel delivery in (kg/hr) with tolerance at max net power engine speed (min-1) or characteristic diagram: If boost control is supplied, state the characteristics fuel delivery and boost pressure versus engine speed	NA
1.2.3.2.5.5	Cut-off point under load (min-1)	NA
1.2.3.2.6	Injection timing:	NA
1.2.3.2.7	Cold start system:	NA
1.2.3.2.7.1	Operating principle(s):	NA
1.2.3.2.7.2	Operating limits/settings(Specify the tolerances)	NA
1.2.3.3	Feed pump	
1.2.3.3.1	Pressure (Specify the tolerances).....(kPa) or characteristic diagram:	320 ± 50 kPa
1.2.4	Electrical system	
1.2.4.1	Rated voltage:…V, positive/negative ground	12V, Negative Ground
1.2.4.2	Generator/ Alternator	Alternator
1.2.4.2.1	Type:	DC – Alternator with Voltage regulator
1.2.4.2.2	Nominal output: …VA	1205 VA (For Non AC Variants) 850 Amps 1745 VA (For AC Variants) 120 Amps
1.2.5	Ignition	NA
1.2.5.1	Make(s):	NA
1.2.5.2	Type(s):	NA
1.2.5.3	Working principle:	NA

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms			
1.2.5.4	Ignition advance curve or map(Specify the tolerances):	NA	
1.2.5.5	Static ignition timing (Specify the tolerances):.....degrees before TDC	NA	
1.2.5.6	Spark plugs	NA	
1.2.5.6.1	Make	NA	
1.2.5.6.2	Type	NA	
1.2.5.6.3	Identification number	NA	
1.2.5.6.4	Gap setting----------(mm)	NA	
1.2.5.6.5	Nominal resistance (kilo ohm) (if resistive type)	NA	
1.2.5.7	Ignition coil(s)	NA	
1.2.5.7.1	Make	NA	
1.2.5.7.2	Type	NA	
1.2.5.7.3	Identification number	NA	
1.2.5.8	**Ignition condenser**	NA	
1.2.5.8.1	Make	NA	
1.2.5.8.2	Type	NA	
1.2.5.8.3	Identification number	NA	
1.2.5.9	**EMI suppressor cap / Device / Electronic unit**	NA	
1.2.5.9.1	Make	NA	
1.2.5.9.2	Type (Resistive/Capacitive)	NA	
1.2.5.9.3	Identification number	NA	
1.2.5.9.4	Nominal resistance (kilo ohm)	NA	
1.2.5.9.5	Terminology and Drawing of interference Suppression equipment	NA	
1.2.5.10	**H.T. Cable**	NA	
1.2.5.10.1	Make and Place	NA	
1.2.5.10.2	Type (Resistive/Non-resistive)	NA	
1.2.5.10.3	Length (mm) (if resistive type)	NA	
1.2.5.10.4	Outside dia. (mm) (if resistive type)	NA	
1.2.5.10.5	Nominal resistance kilo ohm, (if resistive type)	NA	
1.2.5.11	**Radiator**		
1.2.5.11.1	Radiator drawing(s)	Refer enclosure 4C2 & 4C4	Refer enclosurev 4C1 & 4C3
1.2.5.11.2	Make	Mahle Behr	Tata Toyo
1.2.5.11.3	Type (s)	Cross flow	
1.2.5.11.4	Relief valve pressure setting	0.9 kg/cm2	
1.2.5.12	Fan characteristics (Fan power, kW) Enclose the fan power curve corresponding to full load (v/s engine speed).	Electric Fan – 0.449 kW (NON AC), 0.5165 kW (AC)	
1.2.5.12.1	Make (s)	M/s. XXXX	
1.2.5.12.1.1	Number of blades and Identification/Part No	9	
1.2.5.12.1.2	Material of blades (metal / plastic)	Plastic	
1.2.5.12.2	Type(s) [Fixed / Viscous / Electrical driven]	Electrical driven	
1.2.5.12.3	Drive ratio	NA	
1.2.5.12.4	Fan diameter (mm)	360	
1.2.5.12.5	Max. Speed of fan (in rev/min)	3200 ± 150 (Non-AC) 3400 ± 150 (AC)	
1.2.5.13	Radiator core open area (cm^2)	1906 cm2	
1.2.6	Cooling system: liquid/air	Liquid	
1.2.6.1	Nominal setting of the engine temperature control mechanism (^{O}C)::	85 deg C	
1.2.6.2	Liquid	Yes	
1.2.6.2.1	Nature of liquid:	Option 1: Water + 70 % Antifreeze coolant capacity: approx..8 L Option 2 : Water + 60 % Antifreeze coolant capacity: approx..8 L	

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms			
		Option 3 : Water + 50 % Antifreeze coolant capacity : approx..8 L	
1.2.6.2.2	Circulating pump(s): (Yes/No)	Yes	
1.2.6.2.3	Characteristics of Circulating pump	Pump Discharge of 130 lpm @ 0.9 Bar at rotational speed of 4177 ± 25 rpm	
1.2.6.2.3.1	Make(s):	XXXXX Fasteners Ltd	
1.2.6.2.3.2	Type(s):	Impeller Type	
1.2.6.2.4	Drive ratio(s):	1: 1.12	
1.2.6.2.5	Description of the fan and its drive mechanism:	Electric Fan , Motor Driven	
1.2.6.3	Air		
1.2.6.3.1	Blower: (Yes/No)	No	
1.2.6.3.2	Characteristics of blower	NA	
1.2.6.3.2.1	Make(s):	NA	
1.2.6.3.2.2	Type(s):	NA	
1.2.6.3.3	Drive ratio(s):	NA	
1.2.7	Intake system:		
1.2.7.1	Pressure charger: (Yes/No) Turbocharger / Supercharger	Yes, Turbo charger	
1.2.7.1.1	Make(s):	M/s. XYZ, India	
1.2.7.1.2	Type(s) & Identification Number:	Waste Gate with Vacuum Actuator, X3M1XXXX	
1.2.7.1.3	Description of the system (maximum charge pressure:.....(kPa), waste-gate, if applicable)	Waste gate turbocharger with vacuum actuator Maximum Charge pressure - 145 kPa	
1.2.7.2	Inter-cooler: (Yes/No)	Yes	
1.2.7.2.1	Type: air-air / air-water	Air – Air	
1.2.7.2.1.1	Make :	Mahle Behr	Tata Toyo
1.2.7.2.2	Identification Number:	B1V42XXX	B1V42YYY
1.2.7.2.2.1	Air pressure drop across the intercooler	15 kPa	
1.2.7.3	Intake depression at rated engine speed and at 100 per cent load (Specify location of measurement) Minimum allowable:… (kPa) Maximum allowable:… (kPa)	Minimum : 0 kPa Maximum : 6.0 kPa (at 150 mm from TC compressor inlet)	
1.2.7.4	Description and drawings of inlet pipes and their accessories (plenum chamber, heating device, additional air intakes, etc.):	Intake manifold with Electronic throttle valve Refer Enclosure 4D	
1.2.7.4.1	Intake manifold description including dimensional drawings and/or photographs):	Aluminium Intake manifold with pressure sensor Refer Enclosure 4D	
1.2.7.4.2	Air filter, Dimensional drawings	Refer Enclosure 4E	
1.2.7.4.2.1	Make(s):	M/s. Fleet guard	
1.2.7.4.2.2	Type(s) & Identification Number:	Dry Type, Air Filter Assembly – B0EXXX01 Air Filter Element – FG80XXX0	
1.2.7.4.3	Intake silencer, Dimensional drawing	NA	
1.2.7.4.3.1	Make(s):	NA	
1.2.7.4.3.2	Type(s) & Identification Number:	NA	
1.2.8	Exhaust system		
1.2.8.1	Description and Dimensional drawing of the exhaust manifold:	Cast iron manifold with adaptation for Turbocharger and EGR inlet Refer Enclosure 4F	
1.2.8.2	Description and drawing with dimensions of the exhaust system:(Description with general arrangement of exhaust system along with its routing indicating the lengths of exhaust pipe, tail pipe and	Exhaust system with Lean NOx Trap (LNT), Diesel Particulate Filter (DPF) and Passive Selective Catalytic Reduction Catalyst (pSCR). Temperature Sensors are provided before and after LNT, Differential Pressure Sensor provided across DPF and O2 sensors provided before and after LNT-DPF assembly	

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
	exhaust outlet location, indicated in a Schematic dimensional drawing.)	Refer Enclosure 4G
1.2.8.2.1	Effective volume of exhaust-system (specify the tolerance & range) in liters (from exhaust manifold / TC outlet to tail pipe end), Enclose the exhaust system dimensional drawing and indicate the volume of each parts clearly	13.05 ± 1 litre Refer Enclosure 4G
1.2.8.2.2.	Description and drawing of the exhaust Muffler/Silencer:	NA
1.2.8.2.2.1	Type(s) & Identification Number:	NA
1.2.8.2.2.1.1	Make	NA
1.2.8.2.2.2	Number:……	NA
1.2.8.2.3	Internal diameter of exhaust pipe (mm)(min)	diameter 50.8 mm 1.5 mm thickness Refer Enclosure 4G
1.2.8.2.4	Minimum distance between exhaust pipe(s) and the fuel line	>150 mm
1.2.8.2.5	Auxiliary Noise shields for compliance to IS 3028 and / OR AIS-020 (If Provided)	NA
1.2.8.2.5.1	Material	NA
1.2.8.2.5.2	Layout of noise shield / Photographs / Diagram Showing arrangements indicating fitment on vehicle.	NA
1.2.8.3	Maximum allowable exhaust back pressure at rated engine speed and at 100 per cent load (location of measurement): … (kPa)	30.0 kpa (150 mm after Turbocharger)
1.2.9	Minimum cross-sectional areas of inlet and outlet ports:	Inlet – 31.5 mm x 40.5 mm Outlet – 24.0 mm x 28.0 mm
1.2.10	**Valve timing or equivalent data:**	
1.2.10.1	Max. lift of valves	
1.2.10.1.1	Inlet (mm)	8.00
1.2.10.1.2	Exhaust (mm)	8.00
1.2.10.2	Angle of valves / port (w.r.t. top dead center)	
1.2.10.2.1	Inlet	
1.2.10.2.1.1	Opening	17° bTDC
1.2.10.2.1.2	Closing	51° aBDC
1.2.10.2.2	Exhaust	
1.2.10.2.2.1	Opening	66° bBDC
1.2.10.2.2.2	Closing	25° aTDC
1.2.10.2.3	Transfer	NA
1.2.10.2.3.1	Opening	NA
1.2.10.2.3.2	Closing	NA
1.2.10.3	Reference and/or setting ranges (Specify the tolerances):	On Cold Engine
1.2.10.4	Valve gap (Hot or Cold as applicable)	
1.2.10.4.1	Inlet	0.3 to 0.4 mm
1.2.10.4.2	Exhaust	0.3 to 0.4 mm
1.2.10.5	Distribution by ports	NA
1.2.10.5.1	Volume of crank-case cavity with piston at TDC	NA
1.2.10.5.2	Reed valve fitted (Yes / No)	No
1.2.10.5.3	Description of inlet ports, scavenging and exhaust ports with corresponding timing.	NA
1.2.11	Measures taken against air pollution:	
1.2.11.1	Device for recycling crankcase gases (description and drawings):	Closed Loop Crankcase ventilation with external oil separator Refer Enclosure 4J
1.2.11.2	Additional pollution control devices - Lean NOx Trap/SCR/Lean NOx Catalyst (if any, and if not covered by another heading:	Lean NOx Trap (LNT) and Diesel Particulate Filter (DPF) integrated and Passive Selective catalytic reduction (pSCR)
1.2.11.2.1	Catalytic converter: (Yes/No) DOC+DPF / DOC+SDPF / LNT+DPF /LNT+SDPF / GPF / Any Other	Yes, LNT+DPF

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.2.11.2.1.1	Catalytic converter Make Canner / Loader	Canner - M/s. Sharda Motor Industries Limited (SMIL) Loader - M/s. BASF
1.2.11.2.1.2	Catalytic converter Identification Number	FZL1XXYY
1.2.11.2.1.2.1	Unique Identification (Serial No. or Month and Year of Manufacturing or Batch No. or any other means of identification)	XXX / DDMMYY / X (Serial No. / Date / Shift)
1.2.11.2.1.3	Number of catalytic converters and elements (provide the information below for each separate unit:	Catalytic Converter – 1No Element – 1 No.
1.2.11.2.1.4	Dimensions (mm) and shape of the catalytic converter(s) (volume, etc.):	Dimension - 102.2 mm x 187.0 mm x 105.0 mm (LXBxH) Volume - 1.6 Litre Shape - Elliptical Refer Enclosure 4G
1.2.11.2.1.5	Type of catalytic action:	Adsorption, desorption and regeneration
1.2.11.2.1.5.1	Regeneration type for LNT (periodic / continuous):	Continuous
1.2.11.2.1.6	Total charge of precious metal: (g/vehicle)	6.68 g/Vehicle
1.2.11.2.1.7	Relative concentration (%): Pt: Rh:Pd	90% : 5% : 5%
1.2.11.2.1.8	Substrate (structure and material):	Structure: Oval shape, Honey Comb type Material: Cordierite.
1.2.11.2.1.9	Cell density:.....cells per sq. inch / cm	300 CPSI
1.2.11.2.1.10	Type of casing for catalytic converter(s):	Gap Bulk Density (GBD) Type
1.2.11.2.1.11	Diagram indicating the arrangement and Positioning of the catalytic converter(s) (place and reference distances in the exhaust system):	Refer Enclosure 4G
1.2.11.2.1.12	Heat shield: (Yes/No)	Yes
1.2.11.2.1.13	**Selective Catalytic Reduction (SCR) and its components**:.....	
1.2.11.2.1.13.1	Principle and Characteristics:	Passive selective catalytic reduction (pSCR) is a promising approach for the control of NOX emissions in lean burn systems. By periodically decreasing the AFR to fuel-rich levels, ammonia (NH3) can be produced and stored on a downstream SCR catalyst for the reduction of NOX during normal lean operation.
1.2.11.2.1.13.2	Make:	Canner - M/s. XXXX Loader - M/s. YYYY
1.2.11.2.1.13.3	Type and Identification number:	Type - Passive NOx Reduction and FWH0YYYY
1.2.11.2.1.13.3.1	Total charge of precious metal:	211 g/vehicle (Cu Wash coat 90%)
1.2.11.2.1.13.3.2	Substrate (structure and material):	Structure: Oval shape, Honey Comb type Material: Cordierite
1.2.11.2.1.13.3.3	Relative Concentration (%):	0%:0%:0% (Pt:Pd:Rh)
1.2.11.2.1.13.3.4	Dimensions and shape of the SCR (volume, etc.):	Dimension: 102.2 mm x 187.0 mm x 105.0 mm (LxBxH) Volume: 1.6 Litre Shape : Elliptical
1.2.11.2.1.13.3.5	Unique Identification (Serial No or Month and year of Manufacturing or Batch No. or any other means of identification)	XXX / DDMMYY / X (Serial No. / Date / Shift)
1.2.11.2.1.13.4	Dosing ECU:	No
1.2.11.2.1.13.4.1	Make:	NA
1.2.11.2.1.13.4.2	Identification number:	NA
1.2.11.2.1.13.4.3	Calibration Identification number:	NA

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.2.11.2.1.13.4.4	Calibration Verification Number:	NA
1.2.11.2.1.13.4.5	**Urea Dosing Unit**:	No
1.2.11.2.1.13.4.5.1	Dosing Unit:	NA
1.2.11.2.1.13.4.5.1.1	Make:	NA
1.2.11.2.1.13.4.5.1.2	Type and Identification number:	NA
1.2.11.2.1.13.4.5.2	Supply Unit:	NA
1.2.11.2.1.13.4.5.2.1	Make:	NA
1.2.11.2.1.13.4.5.2.3	Type and Identification number	NA
1.2.11.2.1.13.4.5.3	Dosing Injector:	NA
1.2.11.2.1.13.4.5.3.1	Make:	NA
1.2.11.2.1.13.4.5.3.2	Type and Idetification number :	NA
1.2.11.2.1.13.4.6	NOx Sensor (Before /After of SCR):	No
1.2.11.2.1.13.4.6.1	Make:	NA
1.2.11.2.1.13.4.6.2	Type and Identification number:	NA
1.2.11.2.1.13.4.7	Ad Blue Tank:	No
1.2.11.2.1.13.4.7.1	Tank Capacity (l) with minimum-maximum :	NA
1.2.11.2.1.13.4.7.2	Location :	NA
1.2.11.2.1.14	Regeneration systems/method of exhaust after-treatment systems, description:	Periodic regeneration triggered by DPF soot load threshold, estimated with pressure difference across DPF. Exhaust temperature increase for DPF regeneration triggered by post-injection and after burning of fuel in exhaust system
1.2.11.2.1.14.1	The number of Type I operating cycles, or equivalent engine test bench cycles, between two cycles where regenerative phases occur under the conditions equivalent to Type I test (Distance "D" in t AIS 137:	65 cycles
1.2.11.2.1.14.1.1	Number of Type I operating cycles for Regeneration (Distance “d” in AIS 137)	2 cycles
1.2.11.2.1.14.2	Description of method employed to determine the number of cycles between two cycles where regenerative phases occur:	Soot load determined by pressure difference across diesel particulate filter (DPF)
1.2.11.2.1.14.3	Parameters to determine the level of loading required before regeneration occurs (i.e. temperature, pressure etc.):	Engine Soot Model
1.2.11.2.1.14.4	Description of method used to load system in the test procedure described in AIS 137	Type I Operating cycle on chassis dynamometer
1.2.11.2.1.14.5	Normal operating temperature range (°C):	400 to 500 °C
1.2.11.2.1.14.6	Consumable reagents (where appropriate)	NA
1.2.11.2.1.14.7	Type and concentration of reagent needed for catalytic action (where appropriate):	NA

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.2.11.2.1.14.8	Normal operational temperature range of reagent (where appropriate):	NA
1.2.11.2.1.14.9	International standard (where appropriate):	NA
1.2.11.2.1.14.10	Frequency of reagent refill: continuous/maintenance (where appropriate):	NA
1.2.11.2.1.14.11	Normal operating temperature range (°C):	NA
1.2.11.2.2	**Oxygen sensor: (Yes/No)**	Yes
1.2.11.2.2.1	Type	Wide band lambda
1.2.11.2.2.2	Location of oxygen sensor:	Upstream of LNT and downstream of DPF
1.2.11.2.2.3	Control range of oxygen sensor (Specify the tolerances):	0.8 to 9 λ
1.2.11.2.2.4	Make of oxygen sensor:	XXXXXXXX
1.2.11.2.2.5	Identification / Part number	YYYYYYY
1.2.11.2.3	Air injection: (Yes/No)	No
1.2.11.2.3.1	Type (pulse air, air pump, etc.) & Identification Number:	NA
1.2.11.2.4	Exhaust gas recirculation (EGR): (Yes/No)	Yes (Integrated with EGR Cooler)
1.2.11.2.4.1	Make and number of EGR's :	M/s. Paxxxx and One
1.2.11.2.4.2	Type (Cooled / Non-cooled/Progressive/ On-Off/ Any Other)	Cooled, Progressive
1.2.11.2.4.3	Identification Number:	FEW0XXYY
1.2.11.2.4.4	Characteristics (flow rate, etc.):	Flow rate 101 kg/hr (Maximum)
1.2.11.2.4.5	Water cooled system: (Yes/No)	Yes
1.2.11.2.4.5.1	EGR Cooler Make and Identification Number	M/s. XXXXXX and FEW0YYYY
1.2.11.2.5	Evaporative emission control system: (Yes / No) Type: Make and Identification/Part number:	No
1.2.11.2.5.1	Detailed description of the devices and their state of tune:	NA
1.2.11.2.5.2	Drawing with dimensions of the evaporative control system (including fuel hoses length and diameter):	NA
1.2.11.2.5.3	Drawing with dimensions of the carbon canister:	NA
1.2.11.2.5.3.1	Canister Make :	NA
1.2.11.2.5.3.2	Canister Identification/ Part number :	NA
1.2.11.2.5.3.3	Unique Identification (Serial No. or Month and Year of Manufacturing or Batch No. or any other means of identification)	NA
1.2.11.2.5.4	Mass of dry charcoal:……g	NA
1.2.11.2.5.5	Canister working capacity:……..g	NA
1.2.11.2.5.6	Canister bed volume:……litre	NA
1.2.11.2.5.7	Canister Purge and vent strategy description:	NA
1.2.11.2.5.8	Purge valve make and Identification Number	NA
1.2.11.2.5.9	Fuel tank pressure control valve : (Yes/No)	NA
1.2.11.2.5.9.1	Make and Identification Number	NA
1.2.11.2.5.9.2	Operating pressure (kPa)	NA
1.2.11.2.5.10	Liquid fuel hoses material :	NA
1.2.11.2.5.11	Schematic drawing with dimensions of the fuel tank with indication of capacity and material:	NA
1.2.11.2.5.12	Drawing of the heat shield between tank and exhaust system:	NA
1.2.11.2.5.13	Regeneration system/method. Description and/or drawing (Periodic / Continuous)	NA
1.2.11.2.6	Particulate trap: (Yes/No)	Yes

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms				
1.2.11.2.6.1	Number of Particulate trap and elements (provide the information below for each separate unit:	Particulate Trap - 1No. Element - 1No.		
1.2.11.2.6.2	Make and Identification Number Canner & Loader	Canner - M/s. Sharda Motor Industries Limited (SMIL) Loader - M/s. BASF FZL1XXYY		
1.2.11.2.6.2.1	Unique Identification (Serial No. or Month and Year of Manufacturing or Batch No. or any other means of identification)	XXX / DDMMYY / X (Serial No. / Date / Shift)		
1.2.11.2.6.3	Dimensions and shape of the particulate trap (capacity):	Dimension : 102.2 mm x 187.0 mm x 141.0 mm (LXBxH) Shape : Oval shape Capacity : 2.1 Litre		
1.2.11.2.6.4	Type and design of particulate trap: Volume in litres	Type : Periodic Regeneration Type Design : Cross flow type design Volume : 2.1 Litres		
1.2.11.2.6.5	Location of the particulate trap (reference distances in the exhaust line):	Refer Enclosure 4G		
1.2.11.2.6.6	Total charge of precious metal:	0.81 g/vehicle		
1.2.11.2.6.7	Relative concentration (%): Pt:Pd:Rh	90% : 10% : 0		
1.2.11.2.6.8	Substrate (structure and material):	Structure - Oval shape, Honey Comb type Material - Silicon Carbide		
1.2.11.2.6.8.1	Cell density (CPSI)	300 CPSI		
1.2.11.2.7	Electronic Control Unit (ECU)	Yes		
1.2.11.2.7.1	Make & number of ECU's	M/s. XXXX & One		
1.2.11.2.7.2	Identification number	Delphi ID : XSSSZ 5.1XX, AL Development ID : F6NXXYYZ AL Production ID : F6NXXYYZ		
1.2.11.2.7.3	Calibration Identification Number	P15D4BS6UP80LNT1		
1.2.11.2.7.4	Calibration Verification Number	**Version**	**7.00 R15**	**215/75 R15 LT**
		Version 00	A4 9D CF BZ	9D 56 DA 0Y
1.2.11.2.8	On-board-diagnostic (OBD) system: ((Yes/No))	Yes		
1.2.11.2.8.1	Written description and/or drawing of the Malfunction Indicator (MI):	Refer Enclosure 4K		
1.2.11.2.8.2	List and purpose of all components monitored by the OBD system:	Refer Enclosure 4K		
1.2.11.2.8.3	Written description (general working principles) for:	Refer Enclosure 4K		
1.2.11.2.8.3.1	Positive ignition engines	NA		
1.2.11.2.8.3.1.1	Catalyst monitoring:	NA		
1.2.11.2.8.3.1.2	Misfire detection:	NA		
1.2.11.2.8.3.1.3	Oxygen sensor monitoring:	NA		
1.2.11.2.8.3.1.4	Other components monitored by the OBD system:	NA		
1.2.11.2.8.3.	Compression-ignition engines	Yes		
1.2.11.2.8.3.2.1	Catalyst monitoring	Refer Enclosure 4K		
1.2.11.2.8.3.2.2	Particulate traps monitoring:	Refer Enclosure 4K		
1.2.11.2.8.3.2.3	Electronic fueling system monitoring:	Refer Enclosure 4K		
1.2.11.2.8.3.2.4	NOx control system monitoring (SCR/LNT/NOx absorber):	Refer Enclosure 4K		
1.2.11.2.8.3.2.5	Other components monitored by the OBD system:	Refer Enclosure 4K		

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms							
1.2.11.2.8.4	Criteria for MI activation (fixed number of driving cycles or statistical method):				Refer Enclosure 4K		
1.2.11.2.8.5	List of all OBD output codes and formats used (with explanation of each):				Refer Enclosure 4K		
1.2.11.2.8.5.1	OBD Communication protocol standard				Refer Enclosure 4K		
1.2.11.2.8.6	The following additional information shall be provided by the vehicle manufacturer for the purposes of enabling the manufacture of OBD-compatible replacement or service parts and diagnostic tools and test equipment, unless such information is covered by intellectual property rights or constitutes specific know-how of the manufacturer or or its supplier(s).						
1.2.11.2.8.6.1	A description of the type and number of the pre-conditioning cycles used for the original type approval of the vehicle.				3 EUDC		
1.2.11.2.8.6.2	A description of the type of the OBD demonstration cycle used for the original type-approval of the vehicle for the component monitored by the OBD system.				Refer Enclosure 4K		
1.2.11.2.8.6.3	A comprehensive document describing all sensed components with the strategy for fault detection and MI activation (fixed number of driving cycles or statistical method), including a list of relevant secondary sensed parameters for each component monitored by the OBD system. A list of all OBD output codes and format used (with an explanation of each) associated with individual emission related power-train components and individual non-emission related components, where monitoring of the component is used to determine MI activation. In particular, a comprehensive explanation for the data given in service $05 Test ID $21 to FF and the data given in service $06 shall be provided. In the case of vehicle types that use a communication link in accordance with ISO 15765-4 "Road vehicles – Diagnostics on Controller Area Network (CAN) – Part 4: Requirements for emissions-related systems", a comprehensive explanation for the data given in service $06 Test ID $00 to FF, for each OBD monitor ID supported, shall be provided.				Refer Enclosure 4K		
1.2.11.2.8.6.4	The information required by this paragraph may, for example, be defined by completing a table as follows, which shall be attached to this annex:				Refer Enclosure 4K		
Component	**Fault code**	**Monitoring strategy**	**Fault detection criteria**	**MI activation criteria**	**Secondary parameters**	**Preconditioning**	**Demonstration test**
Catalyst	P0420	Oxygen sensor 1 and 2 signals	Difference between sensor 1 and sensor 2 signals	3rd cycle	Engine speed, engine load, A/F mode, catalyst temperature	Two Type I cycles	Type I
1.2.11.2.8.6.5	OBD vehicle family if any				AL XYZ engine family		
1.2.11.2.8.6.5.1	Parameters defining the OBD family (to be attached) (in reference with AIS 137)				Refer OBD Family - Annexure		
1.2.11.2.9	Torque limiter (Yes/No) (Applicable for OBD)				No		
1.2.11.2.9.1	Description of the torque limiter activation:				NA		
1.2.11.2.9.2	Description of the full load curve limitation:				NA		
1.2.11.2.10	Other systems (description and operation):				NA		
1.2.11.2.10.1	Systems to ensure the correct operation of NOx control measures				NA		

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.2.11.2.10.2	Driver inducement system if applicable	NA
1.2.11.2.10.2.1	Vehicle with permanent deactivation of the driver inducement, for use by the rescue services [Note: cross-reference to be determined]. : (Yes/No)	NA
1.2.11.2.10.2.2	Activation of the creep mode disable after restart /disable after fueling /disable after parking	NA
1.2.11.2.102.3	Lowest concentration of the active ingredient present in the reagent that does not activate the warning system (CD min): %(vol)	NA
1.2.11.2.10.2.4	When appropriate, manufacturer reference of the Documentation for installing in a vehicle the systems to ensure the correct operation of NOx control measures	NA
1.2.12	Details of any devices designed to influence fuel economy (if not covered by other items):	NA
1.2.13	LPG fuelling system: (Yes/No)	No
1.2.13.1	Electronic engine management control unit for LPG fuelling	NA
1.2.13.1.1	Make(s):	NA
1.2.13.1.2	Type and Identification Number :	NA
1.2.13.1.3	Calibration Identification Number	NA
1.2.13.1.4	Calibration Verification Number (CVN)	NA
1.2.13.2.1	Description of the safeguarding of the catalyst at switch-over from petrol to LPG or back:	NA
1.2.13.2.2	System layout (electrical connections, vacuum connections, compensation hoses, etc.)	NA
1.2.14	NG fuelling system: (Yes/No)	No
1.2.14.1	Approval number	NA
1.2.14.2	Electronic engine management control unit for NG fuelling	NA
1.2.14.2.1	Make(s):	NA
1.2.14.2.2	Type and Identification Number :	NA
1.2.14.2.3	Calibration Identification Number	NA
1.2.14.2.4	Calibration Verification Number (CVN)	NA
1.2.14.2.5	Emission-related adjustment possibilities:	NA
1.2.14.3	Further documentation:	NA
1.2.14.3.1	Description of the safeguarding of the catalyst at switch-over from petrol to NG or back	NA
1.2.14.3.2	System layout (electrical connections, vacuum connections, compensation hoses, etc.):	NA
1.2.15	Hydrogen fuelling system: (Yes/No)	No
1.2.15.1	Electronic engine management control unit for hydrogen fuelling	NA
1.2.15.1.1	Make(s):	NA
1.2.15.1.2	Identification Number :	NA
1.2.15.1.3	Calibration Identification Number	NA
1.2.15.1.4	Calibration Verification Number (CVN)	NA
1.2.15.1.5	Emission-related adjustment possibilities:	NA
1.2.15.2	Further documentation	NA
1.2.15.2.1	Description of the safeguarding of the catalyst at switch-over from petrol to hydrogen or back:	NA
1.2.15.2.	System lay-out (electrical connections, vacuum connections compensation hoses, etc.):	NA
1.2.16	H2NG fuelling system: (Yes/No)	No
1.2.16.1	Percentage of hydrogen in the fuel (maximum specified by the manufacturer)	NA
1.2.16.2	Electronic engine management control unit for H2NG fuelling	NA
1.2.16.2.1	Make(s):	NA

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.2.16.2.2	Identification Number :	NA
1.2.16.2.3	Calibration Identification Number	NA
1.2.16.2.4	Calibration Verification Number (CVN)	NA
1.2.16.2.5	Emission-related adjustment possibilities:	NA
1.2.16.3	Further documentation	NA
1.2.16.3.1	Description of the safeguarding of the catalyst at switch-over from petrol to H2NG or back:	NA
1.2.16.3.2	System lay-out (electrical connections, vacuum connections compensation hoses, etc.):	NA
1.3.	Electric motor(Traction)	No
1.3.1.	Type (winding, excitation):	NA
1.3.1.1.	Maximum hourly output: kW(manufacturer's declared value)	NA
1.3.1.1.1.	Maximum net power:kW(manufacturer's declared value)	NA
1.3.1.1.2.	Maximum 30 minutes power: kW (manufacturer's declared value)	NA
1.3.1.2.	Operating voltage: V	NA
1.3.1.3	Make and Identification Number:	
1.3.2.	Battery (Traction)	NA
1.3.2.1.	Number of cells:	NA
1.3.2.2.	Mass: ……(kg)	NA
1.3.2.3.	Capacity: Ah (Amp-hours)	NA
1.3.2.4.	Position:	NA
1.4.	Engines or motor combinations	NA
1.4.1.	Hybrid Electric Vehicle: (Yes/No)	No
1.4.2.	Category of Hybrid Electric vehicle Off Vehicle Charging/Not Off Vehicle Charging[9]	NA
1.4.3.	Operating mode switch: with/without	NA
1.4.3.1.	Selectable modes	NA
1.4.3.1.1.	Pure electric: (Yes/No)	NA
1.4.3.1.2.	Pure fuel consuming: (Yes/No)	NA
1.4.3.1.3.	Hybrid modes: (Yes/No) (if yes, short description)	NA
1.4.4.	Description of the energy storage device: (traction battery, capacitor, flywheel/generator...)	NA
1.4.4.1.	Make(s):	NA
1.4.4.2.	Type(s) :	NA
1.4.4.3.	Identification number:	NA
1.4.4.4.	Kind of electrochemical couple:	NA
1.4.4.5.	Energy: ..... (for battery: voltage and capacity Ah in 2 h, for capacitor: J)	NA
1.4.4.6.	Charger: on board/external/without	NA
1.4.5.	Electric machines (describe each type of electric machine separately)	NA
1.4.5.1.	Make:	NA
1.4.5.2.	Type:	NA
1.4.5.3.	Primary use: traction motor/generator	NA
1.4.5.3.1.	When used as traction motor: mono motor / multi motors (number):	NA
1.4.5.4.	Maximum power: kW	NA
1.4.5.5.	Working principle:	NA
1.4.5.5.1.	Direct current/alternating current/number of phases:	NA
1.4.5.5.2.	Separate excitation/series/compound	NA
1.4.5.5.3.	Synchronous/asynchronous	NA
1.4.6.	Control unit	NA
1.4.6.1.	Make:	NA
1.4.6.2.	Type :	NA
1.4.6.3.	Identification number:	NA

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.4.7.	Power controller	NA
1.4.7.1.	Make:	NA
1.4.7.2.	Type:	NA
1.4.7.3.	Identification number:	NA
1.4.8.	Vehicle electric range..... km (according to AIS 137):	NA
1.4.9.	Manufacturer's recommendation for preconditioning:	NA
1.5.	**CO2 (g/km) (Applicable for category M1 with GVW<3.5 T)**	NA
1.5.1	Declared : **(rounded to 3 decimal places)**	NA
1.5.2	Fuel consumption (l/100 km) for Petrol, LPG or Diesel and (kg/100km) for CNG and (kWh/100 km) for Electric Driven Vehicles(Applicable for category M1 with GVW<3.5 T) (rounded to 3 decimal places)*	NA
1.5.2.1	Fuel Equivalent Fuel Consumption (Actual Fuel)	NA
1.5.2.2	Petrol Equivalent Fuel Consumption (Petrol Equivalent)	NA
1.5.2.3	*calculated on the declared CO2	NA
1.5.2.4	CO2 Reducing technologies Available (Yes/No)	No
1.5.2.4.1	Regenerative braking	NA
1.5.2.4.2	Start-Stop System	NA
1.5.2.4.3	Tyre pressure monitoring system	NA
1.5.2.4.4	6 or more Speed Transmission	NA
1.5.2.4.5	Any other technology (manufacture to enclose detail)	NA
1.5.3	Electric energy consumption for electric vehicles Wh/km	NA
1.5.3.1	Electric energy consumption for pure electric vehicles Wh/km	NA
1.5.3.2	Electric energy consumption for externally chargeable hybrid electric vehicles	NA
1.5.3.2.1	Electric energy consumption (condition A, combined) Wh/km	NA
1.5.3.2.2	Electric energy consumption (condition B, combined) Wh/km	NA
1.5.3.2.3	Electric energy consumption (weighted combined) ….Wh/km	NA
1.6	Temperatures permitted by the manufacturer	NA
1.6.1.	Cooling system	Yes
1.6.1.1.	Liquid cooling	Yes
1.6.1.1.1.	Maximum temperature at outlet: …….(°C)	100 °C
1.6.1.2.	Air cooling	NA
1.6.1.2.1.	Reference point:	NA
1.6.1.2.2.	Maximum temperature at reference point: …….(°C)	NA
1.6.2.	Maximum outlet temperature of the inlet intercooler: .. (°C)	45 °C
1.6.3.	Maximum exhaust temperature at the point in the exhaust pipe(s) adjacent to the outer flange(s) of the exhaust manifold: …(°C)	740 °C
1.6.4.	Fuel temperature	
1.6.4.1.	Minimum: .. (°C)	- 8
1.6.4.2.	Maximum: .. (°C)	42
1.6.5.	Lubricant temperature	
1.6.5.1.	Minimum: …(°C)	- 5
1.6.5.2.	Maximum: …(°C)	120
1.7	Lubrication system	Yes

Manufacturer signature: _____ Test agency: _____

Table 04E of AIS 007 (Revision 5) TECHNICAL SPECIFICATIONS FOUR WHEELER AND ABOVE WITH GVW≤3500 kg for BS VI Norms		
1.7.1	Description of the system	Forced Lubrication system
1.7.1.1	Position of the lubricant reservoir:	Sump beneath crankcase
1.7.1.2	Feed system (by pump/injection into intake/mixing with fuel, etc.)	Pump
1.7.2	Lubricating pump	Yes
1.7.2.1	Make(s):	M/s. ZXWA
1.7.2.2	Type(s):	XXYY Type
1.7.3	Mixture with fuel	No
1.7.3.1	Percentage:	
1.7.4	Oil cooler: (Yes/No)	Yes
1.7.4.1	Drawing(s):…, or	Enclosure 4L
1.7.4.1.1	Make(s):	M/s. XXYY or Any other equivalent
1.7.4.1.2	Type(s):	DONUT
2.0	Transmission	
2.1	Moment of inertia of engine flywheel:	0.1212 kg/m2
2.1.1	Additional moment of inertia with no gear engaged:	0.4565 kg/m2
2.2	Clutch (type):	Diaphragm
2.2.1	Maximum torque conversion:	1.5 times
2.3	Transmission Control Unit (ECU) (Yes/No):	No
2.3.1	Type and Identification Number :	NA
2.3.2	Calibration Identification Number	NA
2.3.3	Calibration Verification Number (CVN)	NA
3.0	Vehicle Family	
3.1	OBD IUPR Family if any	XX+XYY
3.2	In-Service family if any	XXYYS OBD II

Manufacturer signature: _____ Test agency: _____