ASHOK LEYLAND

Table 07 of AIS 007 (Revision 5) BRIEF TECHNICAL SPECIFICATIONS FOR MOTOR VEHICLES				
A. Manufacturer's name and address	**Ashok Leyland Limited,** No:1, Sardar Patel, Road, Guindy, Chennai – 600 032.			
Importer's name and address (in case of CBU)	NA			
Vehicle data				
Basic model	**BADA DOST i9 TNZX**			
Type / Description	Fully built vehicle, D+2, Non AC, 3.39 Ton GVW			
Category of the vehicle	N1			
Variant(s)	BADA DOST i8 TNZX			
Type / Description				
Category of variant(s) as per IS 14272:2011	N1			
Engine				
Make	**Ashok Leyland Limited** Hosur Factory Unit I, 175 Hosur Sipcot Industrial Complex, Rajaji Nagar, Hosur– 635 126.			
Model name / identification	ALXYZABC0			
Type	Compression Ignition			
Bore x stroke (mm)	80 X 98			
No. of cylinders	3			
Displacement (cm^3)	1468 cc			
Compression ratio	16.5±1.0 : 1			
Max. Engine output (KW @ rpm)	55.1 Kw @ 3300 rpm			
Max. Torque (Nm @ rpm)	170Nm @ 1600 to 2400 rpm			
Air cleaner type	Dry type			
Type of Fuel	Diesel			
Clutch				
Type	Dry / Single plate/Mechanical actuation			
Gear box				
Make and model	**RSB Transmission (T210R)**		**AVTEC (A5M210)**	
Type	Manual gearbox with fully synchro mesh & Rev with sliding mesh			
No. of gears	5 Forward and 1 Reverse			
Gear ratio	**Gear Ratio**	**Overall Ratio**	**Gear Ratio**	**Overall Ratio**
1st	4.62	4.60	21.53	21.44
2nd	2.68	2.69	12.67	12.71
3rd	1.51	1.49	7.34	7.25
4th	1.0	1.0	4.56	4.56
5th	0.70	0.71	3.64	3.67
Reverse	4.39	20.36	4.38	20.34
Drive Axle (Front / Rear / All)	Rear			
Front axle ratio	NA			
Rear axle ratio	5.13 : 1			
Steering				
Type / Description	Re-circulating ball type			
Steering Gear Ratio	1. XXXX Pvt.Ltd 2. YYYY Pvt.Ltd			
Steering wheel diameter mm	400mm			
Frame				
Long member size (mm)	**2490 WB**		**2640 WB**	
	4435 mm		4735 mm	
Number of cross members	7 - Total (Bolted & Rivited)			
Suspension				
Type				
Front	Front and Rear rigid leaf suspension			
Rear				
Spring – Front	Leaf spring			
Spring – Rear				
Anti-roll bar				

Manufacturer signature: _____ Test agency: _____

Table 07 of AIS 007 (Revision 5) BRIEF TECHNICAL SPECIFICATIONS FOR MOTOR VEHICLES					
Front		Yes			
Rear		NA			
Shock absorbers					
Front		Double acting hydraulic 2 No's			
Rear					
Brake					
Service brake Type (Mechanical/hydraulic/air/air assisted/vacuum assisted/others)		Vacuum assisted hydraulic			
Auto Slack Adjuster Fitted (Yes / No / Optional)		Yes (Automatic wear adjustment)			
Anti-Lock braking system Provided(Yes/No/Optional)		Optional			
Front (Disc / Drum)		Disc			
Rear (Disc / Drum)		Drum			
Total braking area (cm²)		Front axle-254 sq.cm Rear axle-580 sq.cm			
Parking brake type		Mechanical			
Secondary brake type		Un failed part of the service brake			
Wheels and tyres		**Apollo**	**Ceat**	**Apollo**	**Ceat**
Wheel rim size					
Front		5.4J x 14			
Rear					
Tyre size designation including ply rating		7.00 R15 LT 12 PR		215/75 R15 LT	
Speed index					
Front		Q	L	S	S
Rear					
Load index / Load rating					
Front		114/109	114/109	115/113	115/113
Rear					
Tyre Type (Radial / Cross / Tube / Tubeless)					
Front		Radial, Tube Type		Radial, Tubeless	
Rear					
Laden Tyre pressure (kg/cm2 /kPa/ psi)					
Front		3.61 kg/cm2		2.56 kg/cm2	
Rear		6.77 kg/cm2		3.26 kg/cm2	
Electrical system					
System voltage (V)		12 V			
Battery rating (Ah)		50 Ah			
Wiper motor		XYZ Ltd.			
Wiping system (Brief description)		Twin blade, Tandem Pattern			
Fuel tank					
Material		Metallic			
Capacity (l)		50 lts , 40 lts			
Dimensions		**2490WB**		**2640WB**	
Wheel base (mm)		2490		2640	
Overall width (mm)		1842			
Overall Length (mm)	CC	4750		4988	
	FSD / HSD	4925		5225	
Overall height (mm)		1961		1948	
Wheel Track (mm)					
Front track (mm)		1480			
Rear track (mm)		1395			
Minimum Ground Clearance as per IS 9435:2004 (mm) (M1)		NA			
		2490WB		**2640WB**	
Min. ground clearance (mm) (other than M1)		214 / 193		193 / 185	
Maximum gradeability in 1st gear		GVW 2890 kg		GVW 3390 kg	
		10 Deg		8.5 Deg	

Manufacturer signature: _____ Test agency: _____

Table 07 of AIS 007 (Revision 5) BRIEF TECHNICAL SPECIFICATIONS FOR MOTOR VEHICLES											
Dimensions			**L**	**W**	**H**	**L**	**W**	**H**			
		FSD	2951	1750	490	3250	1750	490			
		HSD	2983	1819	1092	3283	1819	1092			
	Container (As per Annexure T7 – B)	Type 1	2951	1750	1850	3250	1750	1850			
		Type 2			1950			1950			
	Tipper (As per Annexure T7 – B)	Tipper	3180	1760	668	3060	1750	709			
Load body platform area (l x b) (mm)		FSD	4.8 m^2			5.3 m^2					
		HSD	5.0 m^2			5.5 m^2					
Body overhang (mm)			**2490 WB**			**2640 WB**					
Front end			1297								
Rear end		CC	863			951					
		FSD / HSD	938			1188					
Frame overhang mm (in case of vehicles without complete body)											
Front end			937								
Rear end			808			958					
Weights			Base	Variant 1	Variant 2	Variant 3	Variant 4				
Maximum GVW kg (for rigid vehicles)			Refer Annexure T7 – A Details for Recommended load body - Refer Annexure T7 - B								
Maximum Permissible FAW											
Maximum Permissible RAW											
Other axle			-	-		-	-				
Maximum GCW kg (for articulated / combination Vehicles)			-	-		-	-				
Maximum Permissible FAW			-	-		-	-				
Maximum Permissible RAW			-	-		-	-				
Other axle			-	-		-	-				
Kerb weight with 90% fuel (With spare wheel, tools, etc.) (kg)			-	-		-	-				
Front axle			-	-		-	-				
Rear axle			-	-		-	-				
Other axle			-	-		-	-				
Total			-	-		-	-				
CO2 (g/km) (Applicable for category M1 with GVW<3.5 T)											
Declared (Rounded to 3 decimal places)			NA	NA		NA	NA				
Fuel consumption (l/100 km) for Petrol, LPG or Diesel and (kg/100km) for CNG and (kWh/100 km) for Electric Driven Vehicles (Applicable for category M1 with GVW<3.5 T) (Rounded to 3 decimal places)*											
Fuel Equivalent Fuel Consumption (Actual Fuel)			NA	NA		NA	NA				
Petrol Equivalent Fuel Consumption (Petrol Equivalent)			NA	NA		NA	NA				
*calculated on the declared CO2											
Vehicle Max Speed in unladen condition (km/h)			Limited to 80 Kmph, 60 Kmph & 40 Kmph with SLF								
Vehicle Max Speed in laden condition (km/h)			Limited to 80 Kmph, 60 Kmph & 40 Kmph with SLF								
Seating											
Seating capacity			D+2								
Sketch showing seating layout with vehicle dimensions (mm) (All category of vehicles)			BWXY4501								

Manufacturer signature: _____ Test agency: _____

Manufacturer signature: _____ Test agency: _____

ANNEXURE T7 - A																	
S. No	Vehicle Model	FSD						HSD						FAW (Kg)	RAW (Kg)	GVW (Kg)	
		FAW (Kg)	RAW (Kg)	ULW (Kg)	F/R Ratio	Reference Mass (Kg) (ULW+150Kg)	Equivalent Inertia (Kg) as per AIS 137 - Part 3	FAW (Kg)	RAW (Kg)	ULW (Kg)	F/R Ratio	Reference Mass (Kg) (ULW+150Kg)	Equivalent Inertia (Kg) as per AIS 137 - Part 3				
Base Model																	
1	BADA DOST i9 TNZX	1011	613	1624	1.65	1774	1810	1021	671	1692	1.52	1842	1810	1493	1897	3390	
2	BADA DOST i8 TNZX	1011	613	1624	1.65	1774	1810	1021	671	1692	1.52	1842	1810	1425	1465	2890	

ANNEXURE T7 – A																			
S. No	Vehicle Model	CAB CHASSIS VARIANTS				FSD		HSD		Recommended Load Body						FAW (Kg)	RAW (Kg)	GVW (Kg)	
										Type 1		Type 2		Tipper					
		FAW (Kg)	RAW (Kg)	ULW (Kg)	F/R Ratio	Reference Mass (Kg) (ULW+150Kg)	Equivalent Inertia (Kg) as per AIS 137 - Part 3	Reference Mass (Kg) (ULW+150Kg)	Equivalent Inertia (Kg) as per AIS 137 - Part 3	Reference Mass (Kg) (ULW+150Kg)	Equivalent Inertia (Kg) as per AIS 137 - Part 3	Reference Mass (Kg) (ULW+150Kg)	Equivalent Inertia (Kg) as per AIS 137 - Part 3	Reference Mass (Kg) (ULW+150Kg)	Equivalent Inertia (Kg) as per AIS 137 - Part 3				
3	BADA DOST i9 TNZX CC	989	479	1468	2.06	1774	1810	1842	1810	1843	1810	1848	1810	1908	1930	1493	1997	3490	
4	BADA DOST i8 TNZX CC	989	479	1468	2.06	1774	1810	1842	1810	1843	1810	1848	1810	1908	1930	1425	1465	2890	

Manufacturer signature: _____ Test agency: _____

Manufacturer signature: _____ Test agency: _____