

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY



Name	SRIRAM S
Roll No	241001269
DEPT	INFORMATION TECHNOLOGY
SEC	E

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## Definition of a Relational Database

A relational database is a collection of relations or two-dimensional tables.

## Terminologies Used in a Relational Database

1. A single **ROW** or table representing all data required for a particular employee. Each row should be identified by a primary key which allows no duplicate rows.
2. A **COLUMN** or attribute containing the employee number which identifies a unique employee. Here Employee number is designated as a primary key ,must contain a value and must be unique.
3. A column may contain foreign key. Here Dept\_ID is a foreign key in employee table and it is a primary key in Department table.
4. A Field can be found at the intersection of a row and column. There can be only one value in it. Also it may have no value. This is called a null value.

EMP ID	FIRST NAME	LAST NAME	EMAIL
100 101	King	Steven	Sking
102 103	John	Smith	Jsmith
	Neena	Bai	Neenba
	Eex	De Haan	Ldehaan

## Relational Database Properties

### A relational database :

- Can be accessed and modified by executing structured query language (SQL) statements.
- Contains a collection of tables with no physical pointers.
- Uses a set of operators

## Relational Database Management Systems

RDBMS refers to a relational database plus supporting software for managing users and processing SQL queries, performing backups/restores and associated tasks. (Relational Database Management System) Software for storing data using SQL (structured query language). A relational database uses SQL to store data in a series of tables that not only record existing relationships between data items, but which also permit the data to be joined in new relationships. SQL (pronounced 'sequel') is based on a system of algebra developed by E F Codd, an IBM scientist who first defined the relational model in 1970. Relational databases are optimized for storing transactional data, and the majority of modern business software

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

applications therefore use an RDBMS as their data store. The leading RDBMS vendors are Oracle, IBM and Microsoft.

The first commercial RDBMS was the Multics Relational Data Store, first sold in 1978.

INGRES, Oracle, Sybase, Inc., Microsoft Access, and Microsoft SQL

Server are well-known database products and companies.Others include PostgreSQL, SQL/DS, and RDB.

A relational database management system (RDBMS) is a program that lets you create, update, and administer a relational database. Most commercial RDBMS's use the Structured Query Language (SQL) to access the database, although SQL was invented after the development of the relational model and is not necessary for its use.

The leading RDBMS products are Oracle, IBM's DB2 and Microsoft's SQL Server. Despite repeated challenges by competing technologies, as well as the claim by some experts that no current RDBMS has fully implemented relational principles, the majority of new corporate databases are still being created and managed with an RDBMS.

## SQL Statements

1. Data Retrieval(DR)
2. Data Manipulation Language(DML)
3. Data Definition Language(DDL)
4. Data Control Language(DCL)
5. Transaction Control Language(TCL)

TYPE	STATEMENT	DESCRIPTION
DR	SELECT	Retrieves the data from the database
DML	1.INSERT 2.UPDATE 3.DELETE 4.MERGE	Enter new rows, changes existing rows, removes unwanted rows from tables in the database respectively. Sets up, changes and removes data
DDL	1.CREATE 2.ALTER 3.DROP 4.RENAME 5.TRUNCATE	structures from tables.
TCL	1.COMMIT 2.ROLLBACK 3.SAVEPOINT 1.GRANT 2.REVOKE	Manages the changes made by DML statements. Changes to the data can be grouped together into logical transactions. Gives or removes access rights to both the oracle database and the structures within it.
DCL		

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## DATA TYPES

### 1. Character Data types:

- Char – fixed length character string that can vary between 1-2000 bytes
  - Varchar / Varchar2 – variable length character string, size ranges from 1-4000 bytes. It saves disk space (only length of the entered value will be assigned as the size of column)
  - Long - variable length character string, maximum size is 2 GB
2. Number Data types : Can store +ve,-ve,zero,fixed point, floating point with 38 precision.

- Number – {p=38,s=0}
- Number(p) - fixed point

3. Number(p,s) – floating point (p=1 to 38,s= -84 to 127)
- Date Time Data type: used to store date and time in the table.

DB uses its own format of storing in fixed length of 7 bytes for century, date, month, year, hour, minutes, and seconds.

- Default data type is “dd-mon-yy”
- New Date time data types have been introduced. They are

TIMESTAMP-Date with fractional seconds

INTERVAL YEAR TO MONTH-stored as an interval of years and months

INTERVAL DAY TO SECOND-stored as an interval of days to hour's minutes and seconds

4. Raw Data type: used to store byte oriented data like binary data and byte string.

5.

- Other :

- CLOB-stores character object with singlebyte character.
- BLOB-stores large binary objects such as graphics, video, sounds.
- BFILE-stores file pointers to the LOB's.

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **EXERCISE-1** **Creating and Managing Tables**

### **OBJECTIVE**

After the completion of this exercise, students should be able to do the following:

- Create tables
- Describing the data types that can be used when specifying column definition
- Alter table definitions
- Drop, rename, and truncate tables

### **NAMING RULES**

Table names and column names:

- Must begin with a letter
- Must be 1-30 characters long
- Must contain only A-Z, a-z, 0-9, \_, \$, and #
- Must not duplicate the name of another object owned by the same user
- Must not be an Oracle server reserved words
- 2 different tables should not have same name.
- Should specify a unique column name.
- Should specify proper data type along with width
- Can include “not null” condition when needed. By default it is ‘null’.

### **The CREATE TABLE Statement**

**Table:** Basic unit of storage; composed of rows and columns

**Syntax: 1** Create table table\_name(column\_name1 data\_type (size)  
column\_name2 data\_type (size)....);

**Syntax: 2** Create table table\_name (column\_name1 data\_type (size) constraints,  
column\_name2 data\_type constraints ...);

### **Example:**

Create table employees ( employee\_id number(6), first\_name varchar2(20), .. job\_id  
varchar2(10), CONSTRAINT emp\_emp\_id\_pk PRIMARY KEY (employee\_id));

### **Tables Used in this course**

---

### **Creating a table by using a Sub query**

---

### **SYNTAX**

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
//CREATE TABLE table_name(column_name type(size)...);  
Create table table_name as select column_name1,column_name2,.....column_namen  
  
from  
table_name where predicate;
```

## AS Subquery

Subquery is the select statement that defines the set of rows to be inserted into the new table.

### Example

```
Create table dept80 as select employee_id, last_name, salary*12 Annsal, hire_date
```

```
from employees where dept_id=80;
```

## The ALTER TABLE Statement

The ALTER statement is used to

- Add a new column
- Modify an existing column
- Define a default value to the new column
- Drop a column
- To include or drop integrity constraint.

## SYNTAX

```
ALTER TABLE table_name ADD /MODIFY(Column_name type(size));
```

```
ALTER TABLE table_name DROP COLUMN (Column_name);
```

```
ALTER TABLE ADD CONSTRAINT Constraint_name PRIMARY KEY (Column_Name);
```

### Example:

---

```
Alter tabledept80 add (job_id varchar2(9));  
Alter tabledept80 modify (last_name varchar2(30));  
Alter tabledept80 drop column job_id;
```

#### NOTE:

Once the column is dropped it cannot be recovered.

## DROPPING A TABLE

- All data and structure in the table is deleted.
- Any pending transactions are committed.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- All indexes are dropped.
- Cannot roll back the drop table statement.

### Syntax:

**Drop table *tablename*;**

### Example:

Drop tabledept80;

## **RENAMING A TABLE**

~~To rename a table or view.~~

### Syntax

**RENAMEold\_name to new\_name**

### Example:

---

Rename dept to detail\_dept; **TRUNCATING  
A TABLE**

~~Removes all rows from thetable. Releases the storage spaceused by that table.~~

### Syntax

**TRUNCATE TABLE *table\_name*;**

### Example:

---

TRUNCATE TABLE copy\_emp;

### Find the Solution for the following:

---

Create the following tables with the given structure.

## **EMPLOYEES TABLE**

NAME	NULL?	TYPE
Employee_id	Not null	Number(6)
First Name		Varchar(20)
Last Name	Not null	Varchar(25)

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Email	Not null	Varchar(25)
Phone Number		Varchar(20)
Hire date	Not null	Date
Job_id	Not null	Varchar(10)
Salary		Number(8,2)
Commission_pct		Number(2,2)
Manager_id		Number(6)
Department_id		Number(4)

CREATE TABLE EMPLOYEE (

```

Employee_id NUMBER(6) NOT NULL,
First_Name VARCHAR2(20),
Last_Name VARCHAR2(25) NOT NULL,
Email VARCHAR2(25) NOT NULL,
Phone_Number VARCHAR2(20),
Hire_date DATE NOT NULL,
Job_id VARCHAR2(10) NOT NULL,
Salary NUMBER(8,2),
Commission_pct NUMBER(2,2),
Manager_id NUMBER(6),
Department_id NUMBER(4)
);
```

## DEPARTMENT TABLE

NAME	NULL?	TYPE
Dept_id	Not null	Number(6)
Dept_name	Not null	Varchar(20)
Manager_id		Number(6)
Location_id		Number(4)

CREATE TABLE DEPARTMENT (

```

Dept_id NUMBER(6) NOT NULL,
Dept_name VARCHAR2(20) NOT NULL,
Manager_id NUMBER(6),
Location_id NUMBER(4)
);
```

## JOB\_GRADE TABLE

NAME	NULL?	TYPE
Grade_level		Varchar(2)
Lowest_sal		Number
Highest_sal		Number

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
CREATE TABLE SAL_GRADE (
    Grade_level VARCHAR2(2),
    Lowest_sal NUMBER,
    Highest_sal NUMBER
);
```

## LOCATION TABLE

NAME	NULL?	TYPE
Location_id	Not null	Number(4)
St_addr		Varchar(40)
Postal_code		Varchar(12)
City	Not null	Varchar(30)
State_province		Char(25)
Country_id		

```
CREATE TABLE LOCATION (
    Location_id NUMBER(4) NOT NULL,
```

```
    St_addr      VARCHAR2(40),
    Postal_code   VARCHAR2(12),
    City          VARCHAR2(30) NOT NULL,
    State_province VARCHAR2(25),
    Country_id    CHAR(2)
```

);

1. Create the DEPT table based on the DEPARTMENT following the table instance chart below. Confirm that the table is created.

Column name	ID	NAME
Key Type		
Nulls/Unique		
FK table		
FK column		
Data Type	Number	Varchar2
Length	7	25

```
CREATE TABLE DEPT (ID NUMBER(7), NAME VARCHAR2(25));
```

2. Create the EMP table based on the following instance chart. Confirm that the table is created.

Column name

Key Type	ID	LAST_NAME	FIRST_NAME	DEPT_ID
Nulls/Unique				
FK table				
FK column				

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Data Type	Number	Varchar2	Varchar2	Number
Length	7	25	25	7

```
CREATE TABLE EMPLOYEE_SIMPLE (
    ID      NUMBER(7),
    LAST_NAME  VARCHAR2(25),
    FIRST_NAME VARCHAR2(25),
    DEPT_ID   NUMBER(7)
);
```

With enhancements

```
CREATE TABLE EMPLOYEE_SIMPLE (
    ID      NUMBER(7) PRIMARY KEY,
    LAST_NAME VARCHAR2(25) NOT NULL,
    FIRST_NAME VARCHAR2(25),
    DEPT_ID   NUMBER(7),
    CONSTRAINT fk_dept
        FOREIGN KEY (DEPT_ID) REFERENCES DEPT(ID)
);
```

3.

Modify the EMP table to allow for longer employee last names. Confirm the modification.(Hint: Increase the size to 50)

```
ALTER TABLE EMP MODIFY LAST_NAME VARCHAR2(50);
```

4. Create the EMPLOYEES2 table based on the structure of EMPLOYEES table. Include Only the Employee\_id, First\_name, Last\_name, Salary and Dept\_id coloumns. Name the columns Id, First\_name, Last\_name, salary and Dept\_id respectively.

```
CREATE TABLE EMPLOYEES2 AS
```

```
SELECT
```

```
Employee_id AS Id,
First_name,
Last_name,
Salary,
Dept_id
```

```
FROM EMPLOYEES
```

```
WHERE 1=0;
```

WHERE 1=0 ensures **no data is copied**, only the structure.

5. Drop the EMP table.

```
DROP TABLE EMP;
```

6. Rename the EMPLOYEES2 table as EMP.

```
RENAME EMPLOYEES2 TO EMP;
```

7. Add a comment on DEPT and EMP tables. Confirm the modification by describing the table.

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

COMMENT ON TABLE DEPT IS 'This table stores department information';  
COMMENT ON TABLE EMP IS 'This table stores employee details';

8. Drop the First\_name column from the EMP table and confirm it.

**ALTER TABLE EMP DROP COLUMN First\_name;**

**DESC EMP;**

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **EXERCISE-2**

### **MANIPULATING DATA**

#### **OBJECTIVE**

After the completion of this exercise the students will be able to do the following

- Describe each DML statement
- Insert rows into tables
- Update rows into table
- Delete rows from table
- Control Transactions

A DML statement is executed when you:

- Add new rows to a table
- Modify existing rows
- Removing existing rows

A transaction consists of a collection of DML statements that form a logical unit of work.

#### **To Add a New Row**

INSERT Statement

#### **Syntax**

INSERT INTO table\_name VALUES (column1 values, column2 values, ..., columnn values);

#### **Example:**

INSERT INTO department (70, 'Public relations', 100, 1700);

#### **Inserting rows with null values**

**Implicit Method:** (Omit the column)

INSERT INTO department VALUES (30, 'purchasing');

**Explicit Method:** (Specify NULL keyword)

INSERT INTO department VALUES (100, 'finance', NULL, NULL);

#### **Inserting Special Values**

#### **Example:**

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Using SYSDATE

```
INSERT INTO employees VALUES (113,'louis', 'popp', 'lpopp','5151244567',
'ac_account', 6900, NULL, 205, 100);SYSDATE,
```

## Inserting Specific Date Values

Example:

```
INSERTINTO employees VALUES ( 114,'den', 'raphealy', 'drapheal', '5151274561',
TO_DATE('feb 3,1999','mon, dd ,yyyy'), 'ac_account', 11000,100,30);
```

## To Insert Multiple Rows

& is the placeholder for the variable value

Example:

```
INSERT INTO department VALUES(&dept_id, &dept_name, &location);
```

## Copying Rows from another table

Using Subquery

Example:

```
INSERINTO sales_reps(id, name, salary, commission_pct)
SELECT employee_id, Last_name, salary, commission_pct
FROMemployees
WHEREjod_id LIKE '%REP');
```

## CHANGING DATA IN A TABLE

UPDATE Statement

Syntax1:(to update specific rows )

```
UPDATE table_name SET column=value WHERE condition;
```

Syntax 2: (To update all rows)

```
UPDATE table_name SET column=value;
```

## Updating columns with a subquery

---

```
UPDATE employees SET
job_id= (SELECT job_id
FROM employees WHERE
employee_id=205) WHERE
employee_id=114;
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## REMOVING A ROW FROM A TABLE

### DELETE STATEMENT

#### Syntax

DELETEFROM table\_name WHERE conditions;

#### Example:

DELETE FROM department WHERE dept\_name='finance';

#### Find the Solution for the following:

1. Create MY\_EMPLOYEE table with the following structure

NAME	NULL?	TYPE
ID	Not null	Number(4)
Last_name		Varchar(25)
First_name		Varchar(25)
Userid		Varchar(25)
Salary		Number(9,2)

CREATE TABLE STAFF ( ID  
NUMBER(4) NOT NULL,  
Last\_name VARCHAR2(25),  
First\_name VARCHAR2(25),  
Userid VARCHAR2(25),  
Salary NUMBER(9,2)

);

2. data. Add the first and second rows data to MY\_EMPLOYEE table from the following sample

ID	Last_name	First_name	Userid	salary
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860
3	Buri	Ben	bburi	1100
4	Newman	Chad	cnewman	750
5	Ropebur	Audrey	aropebur	1350

INSERT INTO MY\_EMPLOYEE (ID, Last\_name, First\_name, Userid, Salary)  
VALUES (1, 'Patel', 'Ralph', 'rpatel', 895);  
INSERT INTO MY\_EMPLOYEE (ID, Last\_name, First\_name, Userid, Salary)  
VALUES (2, 'Dancs', 'Betty', 'bdancs', 860);

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

3. Display the table with values.

```
SELECT * FROM MY_EMPLOYEE;
```

4. Populate the next two rows of data from the sample data. Concatenate the first letter of the first\_name with the first seven characters of the last\_name to produce Userid.

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)  
VALUES (
```

```
    3,  
    'Biri',  
    'Ben',  
    SUBSTR('Ben', 1, 1) || SUBSTR('Biri', 1, 7),  
    1100  
)
```

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)  
VALUES (
```

```
    4,  
    'Newman',  
    'Chad',  
    SUBSTR('Chad', 1, 1) || SUBSTR('Newman', 1, 7),  
    750  
)
```

5. Make the data additions permanent.

```
COMMIT;
```

6. Change the last name of employee 3 to Drexler.

```
UPDATE MY_EMPLOYEE  
SET Last_name = 'Drexler'  
WHERE ID = 3;
```

7. Change the salary to 1000 for all the employees with a salary less than 900.

```
UPDATE MY_EMPLOYEE  
SET Salary = 1000  
WHERE Salary < 900;
```

8. Delete Betty dancs from MY\_EMPLOYEE table.

```
DELETE FROM MY_EMPLOYEE  
WHERE First_name = 'Betty' AND Last_name = 'Dancs';
```

9. Empty the fourth row of the emp table.

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

UPDATE MY\_EMPLOYEE SET Last\_name = NULL, First\_name = NULL,  
Userid = NULL, Salary = NULL WHERE ID = 4;

## **EXERCISE-3**

### **INCLUDING CONSTRAINTS**

#### **OBJECTIVE**

After the completion of this exercise the students should be able to do the following

- • Describe the constraints

WhataCrere Iantete agnrdit my caoinntsatirna tihnet sc?onstraints

- Constraints enforce rules at the table level.
- Constraints prevent the deletion of a table if there are dependencies

The following types of integrity constraints are valid

a) **Domain Integrity**

- ✓ NOT NULL
- ✓ CHECK

b) **Entity Integrity**

- ✓ UNIQUE
- ✓ PRIMARY KEY

c) **Referential Integrity**

- ✓ FOREIGN KEY

✓ Constraints can be created in either of two ways

1. At the same time as the table is created
2. After the table has been created.

#### **Defining Constraints**

Create table tablename(column\_name1 data\_type constraints, column\_name2 data\_type constraints...);

**Example:**

---

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Create table employees ( employee\_id number(6), first\_name varchar2(20), ..job\_id varchar2(10), CONSTRAINT emp\_emp\_id\_pk PRIMARY KEY (employee\_id));

## Domain Integrity

---

This constraint sets a range and any violations that take place will prevent the user from performing the manipulation that caused the breach. It includes:

### NOT NULL Constraint

While creating tables, by default the rows can have null values. The enforcement of not null constraint in a table ensures that the table contains values.

### Principle of null values:

- o Setting null value is appropriate when the actual value is unknown, or when a value would not be meaningful.
- o A null value is not equivalent to a value of zero.
- o A null value will always evaluate to null in any expression.
- o When a column name is defined as not null, that column becomes a mandatory i.e., the user has to enter data into it.
- o Not null Integrity constraint cannot be defined using the alter table command when the table contains rows. **Example** CREATE TABLE employees (employee\_id number (6), last\_name varchar2(25) NOT NULL, salary number(8,2), commission\_pct number(2,2), hire\_date date constraint emp\_hire\_date\_nn NOT NULL'....); **CHECK** Check constraint can be defined to allow only a particular range of values. When the manipulation violates this constraint, the record will be rejected. Check condition cannot contain sub queries.  
CREATE TABLE employees (employee\_id number (6), last\_name varchar2 (25) NOT NULL, salary number(8,2), commission\_pct number(2,2), hire\_date date constraint emp\_hire\_date\_nn NOT NULL'..., CONSTRAINT emp\_salary\_mi CHECK(salary > 0));

## Entity Integrity

Maintains uniqueness in a record. An entity represents a table and each row of a table represents an instance of that entity. To identify each row in a table uniquely we need to use this constraint. There are 2 entity constraints:

### a) Unique key constraint

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

It is used to ensure that information in the column for each record is unique, as with telephone or driver's license numbers. It prevents the duplication of value with rows of a specified column in a set of column. A column defined with the constraint can allow null value. If unique key constraint is defined in more than one column i.e., combination of column cannot be specified. Maximum combination of columns that a composite unique key can contain is 16.

### **Example:**

```
CREATETABLE employees (employee_id number(6), last_name varchar2(25) NOT NULL,email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date constraintemp_hire_date_nn NOT NULL' COSTRAINT emp_email_uk UNIQUE(email));
```

### **PRIMARY KEY CONSTRAINT**

A primary key avoids duplication of rows and does not allow null values. Can be defined on one or more columns in a table and is used to uniquely identify each row in a table. These values should never be changed and should never be null. A table should have only one primary key. If a primary key constraint is assigned to more than one column or combination of columns is said to be composite primary key, which can contain 16 columns

### **Example:**

---

```
CREATETABLE employees(employee_id number(6) , last_name varchar2(25) NOT NULL,email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date constraintemp_hire_date_nnNOT NULL, Constraint emp_id pk PRIMARY KEY (employee_id),CONSTRAINTemp_email_uk UNIQUE(email));
```

### **c)Referential Integrity**

It enforces relationship between tables. To establish parent-child relationship between 2 tables having a common column definition, we make use of this constraint. To implement this, we should define the column in the parent table as primary key and same column in the child table as foreign key referring to the corresponding parent entry.

### **Foreign key**

---

A column or combination of columns included in the definition of referential integrity, which would refer to a referenced key.

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **Referenced key**

It is a unique or primary key upon which is defined on a column belonging to the parent table.  
Keywords:

**FOREIGN KEY:** Defines the column in the child table at the table level constraint.

**REFERENCES:** Identifies the table and column in the parent table.

**ON DELETE CASCADE:** Deletes the dependent rows in the child table when a row in the parent table is deleted.

**ON DELETE SET NULL:** converts dependent foreign key values to null when the parent value is removed.

```
CREATE TABLE employees (employee_id number(6), last_name varchar2(25) NOT
NULL, email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date
constraint emp_hire_date_nn NOT NULL, Constraint emp_id_pk PRIMARY KEY
(employee_id),CONSTRAINT emp_email_uk UNIQUE(email),CONSTRAINT emp_dept_fk
FOREIGN KEY (department_id) references departments(dept_id));
```

## **ADDING A CONSTRAINT**

Use the ALTER to

- Add or Drop a constraint, but not modify the structure
- Enable or Disable the constraints
- Add a not null constraint by using the Modify clause

## **Syntax**

```
ALTER TABLE table_name ADD CONSTRAINT Cons_name type(column name);
```

### **Example:**

```
ALTER TABLE employees ADD CONSTRAINT emp_manager_fk FOREIGN KEY
(manager_id) REFERENCES employees (employee_id);
```

## **DROPPING A CONSTRAINT**

### **Example:**

```
ALTER TABLE employees DROP CONSTRAINT emp_manager_fk;
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## CASCADE IN DROP

- The CASCADE option of the DROP clause causes any dependent constraints also to be dropped.

### Syntax

```
ALTER TABLE departments DROP PRIMARY KEY|UNIQUE (column)| CONSTRAINT  
constraint_name CASCADE;
```

## **DISABLING CONSTRAINTS**

---

- Execute the DISABLE clause of the ALTER TABLE statement to deactivate an integrity constraint
- Apply the CASCADE option to disable dependent integrity constraints.

### Example

```
ALTER TABLE employees DISABLE CONSTRAINT emp_emp_id_pk CASCADE;
```

## **ENABLING CONSTRAINTS**

- Activate an integrity constraint currently disabled in the table definition by using the ENABLE clause.

### Example

```
ALTER TABLE Employees ENABLE CONSTRAINT emp_emp_id_pk CASCADE;
```

## **CASCADING CONSTRAINTS**

The CASCADE CONSTRAINTS clause is used along with the DROP column clause.

It drops all referential integrity constraints that refer to the primary and unique keys defined on the dropped columns.

This clause also drops all multicolumn constraints defined on the dropped column.

### **Example:**

**Assume table TEST1 with the following structure**

```
CREATE TABLE test1 ( pk number PRIMARY KEY,fk number, col1 number,col2 number,  
CONSTRAINT fk_constraint FOREIGN KEY(fk) references test1, CONSTRAINT ck1 CHECK  
(pk>0 and col1>0), CONSTRAINT ck2 CHECK (col2>0));
```

**An error is returned for the following statements**

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

ALTER TABLE test1 DROP (pk);

ALTER TABLE test1 DROP (col1);

**The above statement can be written with CASCADE CONSTRAINT**  
ALTER TABLE test1 DROP(pk) CASCADE CONSTRAINTS;

**(OR)**

ALTER TABLE test1 DROP(pk, fk, col1) CASCADE CONSTRAINTS;

### **VIEWING CONSTRAINTS**

Query the USER\_CONSTRAINTS table to view all the constraints definition and names.

**Example:**

---

SELECT constraint\_name, constraint\_type, search\_condition FROM user\_constraints  
WHERE table\_name='employees';

**Viewing the columns associated with constraints**

---

SELECT constraint\_name, constraint\_type, FROM user\_cons\_columns  
WHERE table\_name='employees';

### **Find the Solution for the following:**

1. Add a table-level PRIMARY KEY constraint to the EMP table on the ID column. The constraint should be named at creation. Name the constraint my\_emp\_id\_pk.

**ALTER TABLE EMP ADD CONSTRAINT my\_emp\_id\_pk PRIMARY KEY (ID);**

To check null and duplicates

**SELECT \* FROM EMP WHERE ID IS NULL;**

**SELECT ID, COUNT(\*) AS count  
FROM EMP  
GROUP BY ID  
HAVING COUNT(\*) > 1;**

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

2. Create a PRIMARY KEY constraint to the DEPT table using the ID column. The constraint should be named at creation. Name the constraint my\_dept\_id\_pk.

**ALTER TABLE DEPT ADD CONSTRAINT my\_dept\_id\_pk PRIMARY KEY (ID);**

3. Add a column DEPT\_ID to the EMP table. Add a foreign key reference on the EMP table that ensures that the employee is not assigned to nonexistent department. Name the constraint my\_emp\_dept\_id\_fk.

**ALTER TABLE EMP ADD DEPT\_ID NUMBER;**

**ALTER TABLE EMP  
ADD CONSTRAINT my\_emp\_dept\_id\_fk  
FOREIGN KEY (DEPT\_ID)  
REFERENCES DEPT(ID);**

4. Modify the EMP table. Add a COMMISSION column of NUMBER data type, precision 2, scale 2. Add a constraint to the commission column that ensures that a commission value is greater than zero.

**ALTER TABLE EMP ADD COMMISSION NUMBER(2, 2);**

**ALTER TABLE EMP  
ADD CONSTRAINT emp\_commission\_check  
CHECK (COMMISSION > 0);**

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **EXERCISE-4**

### **Writing Basic SQL SELECT Statements**

#### **OBJECTIVES**

After the completion of this exercise, the students will be able to do the following:

- List the capabilities of SQL SELECT Statement
- Execute a basic SELECT statement

#### **Capabilities of SQL SELECT statement**

A SELECT statement retrieves information from the database. Using a select statement, we can perform



Projection: To choose the columns in a table



Selection: To choose the rows in a table

Joining: To bring together the data that is stored in different tables

#### **Basic SELECT Statement**

##### **Syntax**

```
SELECT*|DISTINCT Column_name| alias  
` FROM table_name;
```

##### **NOTE:**

DISTINCT—Suppress the duplicates.

Alias—gives selected columns different headings.

##### **Example: 1**

```
SELECT*FROMdepartments;
```

##### **Example: 2**

```
SELECTlocation_id,department_id FROM departments;
```

#### **Writing SQL Statements**

- • • SQL statements are not case sensitive
- SQL statements can be on one or more lines.
- Keywords cannot be abbreviated or split across lines
- Clauses are usually placed on separate lines
- Indents are used to enhance readability

#### **Using Arithmetic Expressions**

Basic Arithmetic operators like \*, /, +, - can be used

##### **Example:1**

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

SELECT last\_name, salary, salary+300 FROM employees;

### Example:2

SELECT last\_name, salary, 12\*salary+100 FROM employees;

The statement is not same as

SELECT last\_name, salary, 12\*(salary+100) FROM employees;

### Example:3

SELECT last\_name, job\_id, salary, commission\_pct FROM employees;

### Example:4

SELECT last\_name, job\_id, salary, 12\*salary\*commission\_pct FROM employees;

### Using Column Alias

- To rename a column heading with or without AS keyword.

### Example:1

SELECT last\_name AS Name  
FROM employees;

### Example: 2

SELECT last\_name "Name" salary \* 12 "Annual Salary"  
FROM employees;

### Concatenation Operator

- Concatenates columns or character strings to other columns
- Represented by two vertical bars (||)
- Creates a resultant column that is a character expression

### Example:

SELECT last\_name || job\_id AS "EMPLOYEES JOB" FROM employees;

### Using Literal Character String

- A literal is a character, a number, or a date included in the SELECT list.
- Date and character literal values must be enclosed within single quotation marks.

### Example:

SELECT last\_name || 'is a' || job\_id AS "EMPLOYEES JOB" FROM employees;

### Eliminating Duplicate Rows

- Using DISTINCT keyword.

### Example:

SELECT DISTINCT department\_id FROM employees;

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## Displaying Table Structure

- Using DESC keyword.

### Syntax

DESCtable\_name;

### Example:

DESCEmployees;

### Find the Solution for the following:

**True OR False** The following statement executes successfully.

#### 1Id. identify the Errors

```
SELECT employee_id, last_name  
sal*12 ANNUAL SALARY  
FROM employees;
```

### Queries

```
SELECT employee_id, last_name,  
      salary * 12 AS annual_salary  
FROM employees;
```

2. Show the structure of departments the table. Select all the data from it.

**DESC departments;**

**SELECT \* FROM departments;**

3. Create a query to display the last name, job code, hire date, and employee number for each employee, with employee number appearing first.

**SELECT employee\_id, last\_name, job\_id, hire\_date FROM employees;**

4. Provide an alias STARTDATE for the hire date.

**SELECT employee\_id, last\_name, job\_id, hire\_date AS STARTDATE  
FROM employees;**

5. Create a query to display unique job codes from the employee table.

**SELECT DISTINCT job\_id FROM employees;**

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

6. Display the last name concatenated with the job ID , separated by a comma and space, and name the column EMPLOYEE and TITLE.

```
SELECTlast_name || ',' ||job_idAS"EMPLOYEEANDTITLE"  
FROM employees;
```

7. Create a query to display all the data from the employees table. Separate each column by a comma. Name the column THE\_OUTPUT.

```
SELECT
```

```
employee_id || ',' ||  
first_name || ',' ||  
last_name || ',' ||  
email || ',' ||  
phone_number || ',' ||  
hire_date || ',' ||  
job_id || ',' ||  
salary || ',' ||  
commission_pct || ',' ||  
manager_id || ',' ||  
department_id AS "THE_OUTPUT"  
FROM employees;
```

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **EXERCISE-5**

### **Restricting and Sorting data**

After the completion of this exercise, the students will be able to do the following:

- Limit the rows retrieved by the queries
- Sort the rows retrieved by the queries
- 

#### **Limits the Rows selected**

- ● Using WHERE clause  
Alias cannot be used in WHERE clause

#### **Syntax**

SELECT-----

FROM-----

WHERE condition;

#### **Example:**

---

```
SELECT employee_id, last_name, job_id, department_id FROM employees WHERE
department_id=90;
```

#### **Character strings and Dates**

Character strings and date values are enclosed in single quotation marks.

Character values are case sensitive and date values are format sensitive.

#### **Example:**

```
SELECT employee_id, last_name, job_id, department_id FROM employees
WHERE last_name='WHALEN';
```

#### **Comparison Conditions**

All relational operators can be used. (=, >, >=, <, <=, <>, !=)

#### **Example:**

---

```
SELECT last_name, salary
FROM employees
WHERE salary<=3000;
```

#### **Other comparison conditions**

Operator	Meaning
----------	---------

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

BETWEEN ...AND...	Between two values
IN	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null values

### Example:1

```
SELECT last_name, salary
FROM employees
WHERE salary BETWEEN 2500 AND 3500;
```

### Example:2

```
SELECT employee_id, last_name, salary , manager_id
FROM employees WHERE manager_id IN (101,
100,201);
```

### Example:3

- • Use the LIKE condition to perform wildcard searches of valid string values.
- Two symbols can be used to construct the search string
  - % denotes zero or more characters
  - \_ denotes one character

```
SELECT first_name, salary
FROM employees
WHERE first_name LIKE '%s';
```

### Example:4

```
SELECT last_name, salary
FROM employees
WHERE last_name LIKE '_o%';
```

### Example:5

---

**ESCAPE option**-To have an exact match for the actual % and \_ characters  
To search for the string that contain 'SA\_'

```
SELECT employee_id, first_name, salary, job_id
FROM employees
WHERE job_id LIKE '%sa\_%'ESCAPE'\';
```

**Test for NULL IS NULL operator**

### Example:

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SELECT employee_id, last_name, salary, manager_id  
FROM employees  
WHERE manager_id ISNULL;
```

## Logical Conditions

---

All logical operators can be used. ( AND, OR, NOT)

### Example:1

```
SELECT employee_id, last_name, salary, job_id  
FROM employees  
WHERE salary >= 10000  
AND job_id LIKE '%MAN%';
```

### Example:2

```
SELECT employee_id, last_name, salary, job_id  
FROM employees  
WHERE salary >= 10000  
OR job_id LIKE '%MAN%';
```

### Example:3

```
SELECT employee_id, last_name, salary, job_id  
FROM employees  
WHERE job_id NOT IN ('it_prog', 'st_clerk', 'sa_rep');
```

## Rules of Precedence

---

Order Evaluated	Operator
1	Arithmetic
2	Concatenation
3	Comparison IS [NOT]
4	NULL, LIKE, [NOT] IN [NOT] BETWEEN
5	Logical NOT
6	Logical AND
7	Logical OR
8	

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## **Example:1**

```
SELECT employee_id, last_name, salary , job_id  
FROM employees  
WHERE job_id = 'sa_rep'  
OR job_id='ad_pres'  
AND salary>15000;
```

## **Example:2**

```
SELECT employee_id, last_name, salary , job_id  
FROM employees  
WHERE (job_id='sa_rep'  
OR job_id='ad_pres')  
AND salary>15000;
```

### **Sorting the rows**

Using ORDERBYClause

---

**ASC**-AscendingOrder,Default

**DESC**

-Descendingorder

## **Example:1**

```
SELECT last_name, salary , job_id,department_id,hire_date  
FROM employees  
ORDER BY hire_date;
```

## **Example:2**

```
SELECT last_name, salary , job_id,department_id,hire_date  
FROM employees  
ORDER BY hire_date DESC;
```

## **Example:3**

### **Sorting by column alias**

```
SELECT last_name,salary*12 annsal , job_id,department_id,hire_date  
FROM employees  
ORDER BY annsal;
```

## **Example:4**

### **Sorting by Multiple columns**

---

```
SELECT last_name, salary,job_id,department_id,hire_date  
FROM employees ORDERBY department_id, salary DESC;
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

### **Find the Solution for the following:**

1. Create a query to display the last name and salary of employees earning more than 12000.

```
SELECT last_name, salary  
FROM employees  
WHERE salary > 12000;
```

2. Create a query to display the employee last name and department number for employee number 176.

```
SELECT last_name, department_id  
FROM employees  
WHERE employee_id = 176;
```

3. Create a query to display the last name and salary of employees whose salary is not in the range of 5000 and 12000. (hints: not between )

```
SELECT last_name, salary  
FROM employees  
WHERE salary NOT BETWEEN 5000 AND 12000;
```

4. Display the employee last name, job ID, and start date of employees hired between February 20,1998 and May 1,1998.order the query in ascending order by start date.(hints: between)

```
SELECT last_name, job_id, hire_date  
FROM employees  
WHERE hire_date BETWEEN TO_DATE('20-FEB-1998', 'DD-MON-YYYY')  
                  AND TO_DATE('01-MAY-1998', 'DD-MON-YYYY')  
ORDER BY hire_date ASC;
```

5. Display the last name and department number of all employees in departments 20 and 50 in alphabetical order by name.(hints: in, orderby)

```
SELECT lastname, department_id  
FROM employees  
WHERE department_id IN (20, 50)  
ORDER BY lastname asc;
```

6. Display the last name and salary of all employees who earn between 5000 and 12000 and are in departments 20 and 50 in alphabetical order by name. Label the columns EMPLOYEE, MONTHLY SALARY respectively.(hints: between, in)

```
SELECT last_name AS "EMPLOYEE", salary AS "MONTHLY SALARY"  
FROM employees  
WHERE salary BETWEEN 5000 AND 12000  
AND department_id IN (20, 50) ORDER BY last_name ASC;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

7. Display the last name and hire date of every employee who was hired in 1994.(hints: like)

```
SELECT last_name, hire_date  
FROM employees  
WHERE hire_date LIKE '1994%'; or  
SELECT last_name, hire_date  
FROM employees  
WHERE TO_CHAR(hire_date, 'YYYY') LIKE '1994';
```

8. Display the last name and job title of all employees who do not have a manager.(hints: is null)

```
SELECT last_name, job_title  
FROM employees  
WHERE manager_id IS NULL;
```

9. Display the last name, salary, and commission for all employees who earn commissions. Sort data in descending order of salary and commissions.(hints: is not null,orderby)

```
SELECT last_name, salary, commission_pct  
FROM employees  
WHERE commission_pct IS NOT NULL  
ORDER BY salary DESC, commission_pct DESC;
```

10. Display the last name of all employees where the third letter of the name is a.(hints:like)

```
SELECT last_name  
FROM employees  
WHERE last_name LIKE '__a%';
```

11. Display the last name of all employees who have an a and an e in their last name.(hints: like)

```
SELECT last_name  
FROM employees  
WHERE last_name LIKE '%a%'  
AND last_name LIKE '%e%';
```

12. Display the last name and job and salary for all employees whose job is sales representative or stock clerk and whose salary is not equal to 2500 ,3500 or 7000.(hints:in,not in)

```
SELECT last_name, job_id, salary  
FROM employees  
WHERE job_id IN ('SA_REP', 'ST_CLERK')  
AND salary NOT IN (2500, 3500, 7000);
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

13. Display the last name, salary, and commission for all employees whose commission amount is 20%.(hints:use predicate logic)

SELECT last\_name, salary, commission\_pct  
FROM employees  
WHERE commission\_pct = 0.20;

## EXERCISE-6

### Single Row Functions

#### Objective

After the completion of this exercise, the students will be able to do the following:

- Describe various types of functions available in SQL.
- Use character, number and date functions in SELECT statement.
- Describe the use of conversion functions.

#### Single row functions:

Manipulate data items. Accept arguments and return one value. Act on each row returned. Return one result per row. May modify the datatype. Can be nested. Accept arguments which can be a column or an expression

Syntax Function\_name(arg1,...argn) An argument can be one of the following




User-supplied constant

Variable value

Column name


Expression



# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- Character Functions: Accept character input and can return both character and number values.
- Number functions: Accept numeric input and return numeric values.
- Date Functions: Operate on values of the DATE data type.
- Conversion Functions: Convert a value from one type to another.

## Character Functions



Function	Purpose
lower(column/expr)	Converts alphabetic character values to lowercase
upper(column/expr)	Converts alphabetic character values to uppercase
initcap(column/expr)	Converts alphabetic character values to uppercase for the first letter of each word, all other letters in lowercase Concatenates the first character to the second character
concat(column1/expr1, column2/expr2)	Returns specified characters from character value starting at character position m, n characters long
substr(column/expr, m, n)	Returns the number of characters in the expression Returns the numeric position of a named string
length(column/expr)	Pads the character value right-justified to a total width of n character positions
instr(column/expr, 'string', m, n)	Pads the character value left-justified to a total width of n character positions
lpad(column/expr, n, 'string')	Enables you to trim heading or trailing or both from a character
trim(leading/trailing/both, trim_character FROM trim_source)	

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

replace(text, search_string, replacement_string)	
---	--

**Example:**  
lower('SQL Course')

SsqQl Lco CuOrsUeRSE

upper('SQL Course')

initcap('SQL Course') Sql Course

SELECT 'The job id for'|| upper(last\_name)||'is'||lower(job\_id) AS "EMPLOYEE DETAILS"  
 FROM employees;

SELECT employee\_id, last\_name, department\_id  
 FROM employees  
 WHERE LOWER(last\_name)='higgins';

**Function**

	<b>Result</b>
CONCAT('hello', 'world')	helloworld
Substr('helloworld',1,5)	Hello 10 6
Length('helloworld')	*****24000
Instr('helloworld', 'w')	24000*****
Lpad(salary,10,'*')	elloworld
Rpad(salary,10,'*')	
Trim('h' FROM 'helloworld')	

<b>Command</b>	<b>Query</b>	<b>Output</b>
initcap(char);	select initcap("hello") from dual;	Hello
lower (char); upper (char);	select lower ('HELLO') from dual; select upper ('hello') from dual;	Hello HELLO
ltrim (char,[set]);	select ltrim ('cseit', 'cse') from dual;	IT
rtrim (char,[set]);	select rtrim ('cseit', 'it') from dual;	CSE
replace (char,search string, replace string);	select replace ('jack and jue', 'j', 'bl') from dual;	black and blue
substr (char,m,n);	select substr ('information', 3, 4) from dual;	form

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## Example:

```
SELECT Employee_id, CONCAT(first_name, last_name) NAME, job_id, LENGTH(last_name),  
INSTR(last_name, 'a') "contains'a'?"
```

```
FROM employees WHERE SUBSTR(job_id, 4) = 'ERP';
```

## NUMBER FUNCTIONS

Function	Purpose
round(column/expr,n)	Roundsthe value to specified decimal
trunc(column/expr,n)	Truncates value to specified decimal
mod(m,n)	Returns remainder of division

### Example

Function	Result
round(45.926,2)	45.93
trunc(45.926,2)	45.92
mod(1600,300)	100

```
SELECT ROUND(45.923,2), ROUND(45.923,0), ROUND(45.923,-1) FROM dual;
```

**NOTE:** Dual is a dummy table you can use to view results from functions and calculations.

```
SELECT TRUNC(45.923,2), TRUNC(45.923), TRUNC(45.923,-2) FROM dual;
```

```
SELECT last_name, salary, MOD(salary, 5000) FROM employees WHERE job_id = 'sa_rep';
```

## Working with Dates

The Oracle database stores dates in an internal numeric format: century, year, month, day, hours, minutes, and seconds.

- The default date display format is DD-MON-RR.

– Enables you to store 21st-century dates in the 20th century by specifying only the last

two digits of the year

– Enables you to store 20th-century dates in the 21st century in the same way

### Example

```
SELECT last_name, hire_date FROM employees WHERE hire_date < '01-FEB-88';
```

## Working with Dates

SYSDATE is a function that returns:

- Date
- Time

### Example

Display the current date using the DUAL table.

```
SELECT SYSDATE FROM DUAL;
```

## Arithmetic with Dates

- Add or subtract a number to or from a date for a resultant date value.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- Subtract two dates to find the number of days between those dates.
- Add hours to a date by dividing the number of hours by 24.

### Arithmetic with Dates

Because the database stores dates as numbers, you can perform calculations using arithmetic Operators such as addition and subtraction. You can add and subtract number constants as well as dates.

You can perform the following operations:

Operation	Result	Description
date + number	date	Adds a number of days to a date
date - number	Ddate	Subtracts a number of days from a date
Example	Date	
SELECT last_name, (SYSDATE - hire_date)/7 AS Weeks since one date from another FROM employees WHERE department_id = 90;		Adds a number of hours to a date

### Date Functions

---

---

### Date Functions


Date functions operate on Oracle dates. All date functions return a value of DATE data type except MONTHS\_BETWEEN, which returns a numeric value.

- **MONTHS\_BETWEEN(date1, date2)**::: Finds the number of months between date1 and date2. The result can be positive or negative. If date1 is later than date2, the result is positive; if date1 is earlier than date2, the result is negative. The noninteger part of the result represents a portion of the month.
- **ADD\_MONTHS(date, n)**::: Adds n number of calendar months to date. The value of n must be an integer and can be negative.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- NEXT\_DAY(date, 'char')::: Finds the date of the next specified day of the week ('char') following date. The value of char may be a number representing a day or a character string.
- LAST\_DAY(date)::: Finds the date of the last day of the month that contains date
- ROUND(date[,fmt'])::: Returns date rounded to the unit that is specified by the format model fmt. If the format model fmt is omitted, date is rounded to the nearest day.
- TRUNC(date[,fmt'])::: Returns date with the time portion of the day truncated to the unit that is specified by the format model fmt. If the format model fmt is omitted, date is truncated to the nearest day.

### Using Date Functions



### Example


Display the employee number, hire date, number of months employed, sixmonth review date, first Friday after hire date, and last day of the hire month for all employees who have been employed for fewer than 70 months.

```
SELECT Employee_id, hire_date, MONTHS_BETWEEN (SYSDATE, hire_date)
TENURE, ADD_MONTHS (hire_date, 6) REVIEW, NEXT_DAY (hire_date, 'FRIDAY'),
LAST_DAY(hire_date)
FROM employees
WHERE MONTHS_BETWEEN (SYSDATE, hire_date) < 70;
```

### Conversion Functions

This covers the following topics:

- Writing a query that displays the current date
- Creating queries that require the use of numeric, character, and date functions
- Performing calculations of years and months of service for an employee




# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## Implicit Data Type Conversion


For assignments, the Oracle server can automatically convert the following:

For example, the expression `hire_date > '01-JAN-90'` results in the implicit conversion from the string `'01-JAN-90'` to a date.

For expression evaluation, the Oracle Server can automatically convert the following:



## Explicit Data Type Conversion



SQL provides three functions to convert a value from one data type to another:

### Example:

Using the **TO\_CHAR** Function with Dates

`TO_CHAR(date, 'format_model')`

### **The format model:**


- Must be enclosed by single quotation marks
- Is case-sensitive
- Can include any valid date format element
- Has an `fm` element to remove padded blanks or suppress leading zeros

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- Is separated from the date value by a comma

```
SELECT employee_id, TO_CHAR(hire_date, 'MM/YY') Month_Hired  
FROM employees WHERE last_name = 'Higgins';
```

## Elements of the Date Format Model



### Sample Format Elements of Valid Date

Element	Description
SCC or CC	Century; server prefixes B.C. date with -
Years in dates YYYY or SYYYY	Year; server prefixes B.C. date with -
YYY or YY or Y	Last three, two, or one digits of year
Y,YYY	Year with comma in this position
IYYY, IYY, IY, I	Four-, three-, two-, or one-digit year based on the ISO standard
SYEAR or YEAR	Year spelled out; server prefixes B.C. date with -
BC or AD	Indicates B.C. or A.D. year
B.C. or A.D.	Indicates B.C. or A.D. year using periods
Q	Quarter of year
MM	Month: two-digit value
MONTH	Name of month padded with blanks to length of nine characters
MON	Name of month, three-letter abbreviation
RM	Roman numeral month
WW or W	Week of year or month
DDD or DD or D	Day of year, month, or week
DAY	Name of day padded with blanks to a length of nine characters
DY	Name of day; three-letter abbreviation
J	Julian day; the number of days since December 31, 4713 B.C.

### Date Format Elements: Time Formats

Use the formats that are listed in the following tables to display time information and literals

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

and to change numerals to spelled numbers.

Element	Description
AM or PM	Meridian indicator
A.M. or P.M.	Meridian indicator with periods
HH or HH12 or HH24	Hour of day, or hour (1–12), or hour (0–23)
MI	Minute (0–59)
SS	Second (0–59)
SSSS	Seconds past midnight (0–86399)

## Other Formats

Element	Description
/ . ,	Punctuation is reproduced in the result.
"of the"	Quoted string is reproduced in the result.

## Specifying Suffixes to Influence Number Display

Element	Description
TH	Ordinal number (for example, DDTH for 4TH)
SP	Spelled-out number (for example, DDSP for FOUR)
SPTH or THSP	Spelled-out ordinal numbers (for example, DDSPTH for FOURTH)

## Example

```
SELECT last_name,  
TO_CHAR(hire_date, 'fmDD Month YYYY') AS HIREDATE  
FROM employees;  
Modify example to display the dates in a format that appears as "Seventeenth of June 1987  
12:00:00AM."  
SELECT last_name,  
TO_CHAR (hire_date, 'fmDdspth "of" Month YYYY fmHH:MI:SS AM') HIREDATE
```


```
FROM employees;
```

## Using the TO\_CHAR Function with Numbers

```
TO_CHAR(number, 'format_model')
```

These are some of the format elements that you can use with the TO\_CHAR function to display a number value as a character:

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY



## Number Format Elements

If you are converting a number to the character data type, you can use the following format elements:

Element	Description	Example	Result
9	Numeric position (number of 9s determine display width)	999999	1234
0	Display leading zeros	099999	001234
\$	Floating dollar sign	\$999999	\$1234
L	Floating local currency symbol	L999999	FF1234
D	Returns in the specified position the decimal character. The default is a period (.).	99D99	99.99
.	Decimal point in position specified	999999.99	1234.00
G	Returns the group separator in the specified position. You can specify multiple group separators in a number format model.	9,999	9G999
,	Comma in position specified	999,999	1,234
MI	Minus signs to right (negative values)	999999MI	1234-
PR	Parenthesize negative numbers	999999PR	<1234>
EEEE	Scientific notation (format must specify four Es)	99.999EEEE	1.234E+03
U	Returns in the specified position the "Euro" (or other) dual currency	U9999	€1234
V	Multiply by 10 $n$ times ( $n$ = number of 9s after V)	9999V99	123400
S	Returns the negative or positive value	\$9999	-1234 or +1234
B	Display zero values as blank, not 0	B9999.99	1234.00

```
SELECT TO_CHAR(salary, '$99,999.00') SALARY
FROM employees
WHERE last_name = 'Ernst';
```

## Using the TO\_NUMBER and TO\_DATE Functions

- Convert a character string to a number format using the TO\_NUMBER function:

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

TO\_NUMBER(char[, 'format\_model'])

- Convert a character string to a date format using the TO\_DATE function:

TO\_DATE(char[, 'format\_model'])

- These functions have an fx modifier. This modifier specifies the exact matching for the character

argument and date format model of a TO\_DATE function.

The fx modifier specifies exact matching for the character argument and date format model of a TO\_DATE function:

- Punctuation and quoted text in the character argument must exactly match (except for case) the corresponding parts of the format model.
- The character argument cannot have extra blanks. Without fx, Oracle ignores extra blanks.
- Numeric data in the character argument must have the same number of digits as the corresponding element in the format model. Without fx, numbers in the character argument can omit leading zeros.

```
SELECT last_name, hire_date  
FROM employees  
WHERE hire_date = TO_DATE('May24, 1999', 'fxMonth DD, YYYY');
```

**Find the Solution for the following:**

- 
- Write a query to display the current date. Label the column Date.

**SELECT SYSDATE AS "Date" FROM dual;**

- The HR department needs a report to display the employee number, last name, salary, and increased by 15.5% (expressed as a whole number) for each employee. Label the column New Salary.

**SELECT employee\_id,  
last\_name,  
salary,  
ROUND(salary \* 1.155) AS "New Salary"  
FROM employees;**

- Modify your query lab\_03\_02.sql to add a column that subtracts the old salary from the new salary. Label the column Increase.

**SELECT employee\_id, last\_name, salary,  
ROUND(salary \* 1.155) AS "New Salary",  
ROUND(salary \* 1.155) - salary AS Increase  
FROM employees;**

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

4. Write a query that displays the last name (with the first letter uppercase and all other letters lowercase) and the length of the last name for all employees whose name starts with the letters J, A, or M. Give each column an appropriate label. Sort the results by the employees' last names.

**SELECT**

```
INITCAP(last_name) AS "Last Name",
LENGTH(last_name) AS "Name Length"
FROM employees
WHERE UPPER(SUBSTR(last_name, 1, 1)) IN ('J', 'A', 'M')
ORDER BY last_name;
```

5. Rewrite the query so that the user is prompted to enter a letter that starts the last name. For example, if the user enters H when prompted for a letter, then the output should show all employees whose last name starts with the letter H.

**SELECT last\_name,**

```
LENGTH(last_name) AS "Name Length"
FROM employees
WHERE UPPER(SUBSTR(last_name, 1, 1)) = UPPER('&start_letter')
ORDER BY last_name;
```

6. The HR department wants to find the length of employment for each employee. For each employee, display the last name and calculate the number of months between today and the date on which the employee was hired. Label the column MONTHS\_WORKED. Order your results by the number of months employed. Round the number of months up to the closest whole number.

**Note:** Your results will differ.

```
SELECT last_name,
CEIL(MONTHS_BETWEEN(SYSDATE, hire_date)) AS MONTHS_WORKED
FROM employees
ORDER BY MONTHS_WORKED;
```

7. Create a report that produces the following for each employee:  
<employee last name> earns <salary> monthly but wants <3 times salary>. Label the column Dream Salaries.

```
SELECT last_name || ' earns ' || TO_CHAR(salary) || ' monthlybutwants ' ||
TO_CHAR(salary * 3) AS "Dream Salaries" FROM employees;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

8. Create a query to display the last name and salary for all employees. Format the salary to be 15 characters long, left-padded with the \$ symbol. Label the column SALARY.

```
SELECT last_name,  
       LPAD('$' || TO_CHAR(salary), 15, '$') AS SALARY  
FROM employees;
```

9. Display each employee's last name, hire date, and salary review date, which is the first Monday after six months of service. Label the column REVIEW. Format the dates to appear in the format similar to "Monday, the Thirty-First of July, 2000."

```
SELECT last_name,  
       TO_CHAR(hire_date, 'fmDay, "the" fmDDth "of" Month, YYYY') AS hire_date,  
       TO_CHAR(  
           NEXT_DAY(ADD_MONTHS(hire_date, 6) - 1, 'MONDAY'),  
           'fmDay, "the" fmDDth "of" Month, YYYY'  
) AS REVIEW  
FROM employees;
```

10. Display the last name, hire date, and day of the week on which the employee started. Label the column DAY. Order the results by the day of the week, starting with Monday.

```
SELECT last_name, hire_date,  
       TO_CHAR(hire_date, 'fmDay') AS DAY  
FROM employees ORDER BY  
CASE TO_CHAR(hire_date, 'DY', 'NLS_DATE_LANGUAGE=ENGLISH')  
    WHEN 'MON' THEN 1  
    WHEN 'TUE' THEN 2  
    WHEN 'WED' THEN 3  
    WHEN 'THU' THEN 4  
    WHEN 'FRI' THEN 5  
    WHEN 'SAT' THEN 6  
    WHEN 'SUN' THEN 7  
END;
```

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **EXERCISE-7**

### **Displaying data from multiple tables**

**Objective** After the completion of this exercise, the students will be

- Write SELECT statements to access data from more than one table using equality and nonequality joins
- View data that generally does not meet a join condition by using outer joins
- Join a table to itself by using a self join
- Sometimes you need to use data from more than one table.

#### **Cartesian Products**

- A Cartesian product is formed when:
  - A join condition is omitted – A join condition is invalid – All rows in the first table are joined to all rows in the second table
  - To avoid a Cartesian product, always include a valid join condition in a WHERE clause.A Cartesian product tends to generate a large number of rows, and the result is rarely useful. You should always include a valid join condition in a WHERE clause, unless you have a specific need to combine all rows from all tables. Cartesian products are useful for some tests when you need to generate a large number of rows to simulate a reasonable amount of data.

#### **Example:**

To display employee last name and department name from the EMPLOYEES and DEPARTMENT Stables.

```
SELECT last_name, department_name, dept_name
FROM employees, departments;
```

---

#### **Types of Joins**

- Equijoin
- Non-equijoin
- Outer join
- Self join
- Cross joins
- Natural joins
- Using clause
- Full or two sided outer joins
- Arbitrary join conditions for outer joins

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## Joining Tables Using Oracle Syntax

```
SELECT table1.column, table2.column
```

```
FROM table1, table2
```

```
WHERE table1.column1 = table2.column2;
```

Write the join condition in the WHERE clause.

- Prefix the column name with the table name when the same column name appears in more than one table.

## Guidelines

- When writing a SELECT statement that joins tables, precede the column name with the table name for clarity and to enhance database access.
  - If the same column name appears in more than one table, the column name must be prefixed with the table name.
  - To join n tables together, you need a minimum of n-1 join conditions. For example, to join four tables, a minimum of three joins is required. This rule may not apply if your table has a concatenated primary key, in which case more than one column is required to uniquely identify each row.
- What is an Equijoin?** To determine an employee's department name, you compare the value in the DEPARTMENT\_ID column in the EMPLOYEES table with the DEPARTMENT\_ID values in the DEPARTMENTS table. The relationship between the EMPLOYEES and DEPARTMENTS tables is an equijoin—that is, values in the DEPARTMENT\_ID column on both tables must be equal. Frequently, this type of join involves primary and foreign key complements. Note: Equijoins are also called simple joins or inner joins

```
SELECT employees.employee_id, employees.last_name, employees.department_id,  
departments.department_id, departments.location_id  
FROM employees, departments  
WHERE employees.department_id = departments.department_id;
```

## Additional Search Conditions

### Using the AND Operator

#### Example:

To display employee Matos' department number and department name, you need an additional condition in the WHERE clause.

```
SELECT last_name, employees.department_id,  
department_name
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
FROM employees, departments  
WHERE employees.department_id = departments.department_id AND last_name = 'Matos';
```

## Qualifying Ambiguous

### Column Names

- Use table prefixes to qualify column names that are in multiple tables.
- Improve performance by using table prefixes.
- Distinguish columns that have identical names but reside in different tables by using column aliases.

## Using Table Aliases

- Simplify queries by using table aliases.
- Improve performance by using table prefixes

### Example:

```
SELECT e.employee_id, e.last_name, e.department_id,  
d.department_id, d.location_id  
FROM employees e, departments d  
WHERE e.department_id = d.department_id;
```

## Joining More than Two Tables

To join n tables together, you need a minimum of n-1 join conditions. For example, to join three tables, a minimum of two joins is required.

### Example:

To display the last name, the department name, and the city for each employee, you have to join the EMPLOYEES, DEPARTMENTS, and LOCATIONS tables. SELECT e.last\_name, d.department\_name, l.city FROM employees e, departments d, locations l WHERE e.department\_id = d.department\_id AND d.location\_id = l.location\_id; AND

## Non-Equijoins

A non-equijoin is a join condition containing something other than an equality operator. The relationship between the EMPLOYEES table and the JOB\_GRADES table has an example of a non-equijoin. A relationship between the two tables is that the SALARY column in the EMPLOYEE table must be between the values in the LOWEST\_SALARY and HIGHEST\_SALARY columns of the JOB\_GRADES table. The relationship is obtained using an operator other than equals (=).

### Example:

---

```
SELECT e.last_name, e.salary, j.grade_level  
FROM employees e, job_grades j  
WHERE e.salary
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

BETWEEN j.lowest\_sal AND j.highest\_sal;

## **Outer Joins**

---

### **Syntax**

- You use an outer join to also see rows that do not meet the join condition.
- The Outerjoin operator is the plus sign (+).

SELECT table1.column, table2.column

FROM table1, table2

WHERE table1.column(+) = table2.column;

SELECT table1.column, table2.column

FROM table1, table2

WHERE table1.column = table2.column(+);

The missing rows can be returned if an outer join operator is used in the join condition. The operator

is a plus sign enclosed in parentheses (+), and it is placed on the “side” of the join that is deficient in information. This operator has the effect of creating one or more null rows, to which one or more rows

from the nondeficient table can be joined.

### **Example:**

---

SELECT e.last\_name, e.department\_id, d.department\_name

FROM Employees e, departments d

WHERE e.department\_id(+) = d.department\_id ;

## **Outer Join Restrictions**

- The outerjoin operator can appear on only one side of the expression—the side that has information missing. It returns those rows from one table that have no direct match in the other table.
- A condition involving an outer join cannot use the IN operator or be linked to another condition by the OR operator

## **Self Join**

Sometimes you need to join a table to itself.

### **Example:**

To find the name of each employee's manager, you need to join the EMPLOYEES table to itself, or perform a self join.

SELECT worker.last\_name || ' works for '

|| manager.last\_name

FROM Employees worker, employees manager

WHERE worker.manager\_id = manager.employee\_id ;

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

**Use a join to query data from more than one table.**

```
SELECT table1.column,table2.column  
FROM table1  
[CROSS JOIN table2] |  
[NATURAL JOIN table2] |  
[JOIN table2 USING (column_name)] |  
[JOIN table2  
ON(table1.column_name = table2.column_name)] |  
[LEFT|RIGHT|FULL OUTER JOIN table2  
ON (table1.column_name = table2.column_name)];
```

In the syntax:

table1.column Denotes the table and column from which data is retrieved

CROSS JOIN Returns a Cartesian product from the two tables

NATURAL JOIN Joins two tables based on the same column name

JOIN table USING column\_name Performs an equijoin based on the column name

JOIN table ON table1.column\_name Performs an equijoin based on the condition in the ON clause

=table2.column\_name

### **LEFT/RIGHT/FULL OUTER**

#### **Creating Cross Joins**

- The CROSS JOIN clause produces the crossproduct of two tables.
- This is the same as a Cartesian product between the two tables.

#### **Example:**

```
SELECT last_name, department_name  
FROM Employees  
CROSS JOIN departments ;  
SELECT last_name, department_name  
FROM Employees, departments;
```

#### **Creating Natural Joins**

- 
- The NATURAL JOIN clause is based on all columns in the two tables that have the same name.
  - It selects rows from the two tables that have equal values in all matched columns.
  - If the columns having the same names have different data types, an error is returned.

#### **Example:**

```
SELECT department_id, department_name,  
location_id, city  
FROM departments
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

NATURAL JOIN locations ; LOCATIONS table is joined to the DEPARTMENT table by the LOCATION\_ID column, which is the only column of the same name in both tables. If other common columns were present, the join would have used them all. **Example:** SELECT department\_id, department\_name, location\_id, city FROM departments NATURAL JOIN locations WHERE department\_id IN (20, 50);

### Creating Joins with the USING Clause

---

- If several columns have the same names but the data types do not match, the NATURAL JOIN clause can be modified with the USING clause to specify the columns that should be used for an equijoin.
- Use the USING clause to match only one column when more than one column matches.
- Do not use a table name or alias in the referenced columns.
- The NATURAL JOIN and USING clauses are mutually exclusive.

#### **Example:**

---

```
SELECT l.city, d.department_name
FROM locations l JOIN departments d USING (location_id)
WHERE location_id = 1400;
EXAMPLE:
```

```
SELECT e.employee_id, e.last_name, d.location_id
FROM Employees e JOIN departments d
USING(department_id);
```

### Creating Joins with the ON Clause

- The join condition for the natural join is basically an equijoin of all columns with the same name.
- To specify arbitrary conditions or specify columns to join, the ON clause is used.
- The join condition is separated from other search conditions.
- The ON clause makes code easy to understand.

#### **Example:**

---

```
SELECT e.employee_id, e.last_name, e.department_id,
d.department_id, d.location_id
FROM Employees e JOIN departments d
ON (e.department_id = d.department_id);
EXAMPLE:
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SELECT e.last_name emp, m.last_name mgr
FROM employees e JOIN employees m
ON (e.manager_id = m.employee_id);
INNER Versus OUTER Joins
```

- A join between two tables that returns the results of the inner join as well as unmatched rows left (or right) table is a left (or right) outer join.
- A join between two tables that returns the results of an inner join as well as the results of a left and right join is a full outer join.

### **LEFT OUTER JOIN**

**Example:**

---

---

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e
LEFT OUTER JOIN departments d
ON (e.department_id = d.department_id);
```

Example of LEFT OUTER JOIN

This query retrieves all rows in the EMPLOYEES table, which is the left table even if there is no match in the DEPARTMENTS table.

This query was completed in earlier releases as follows:

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e, departments d
WHERE d.department_id (+) = e.department_id;
```

### **RIGHTOUTER JOIN**

**Example:**

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e
RIGHTOUTER JOIN departments d
ON (e.department_id = d.department_id);
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

This query retrieves all rows in the DEPARTMENTS table, which is the right table even if there is no match in the EMPLOYEES table.

This query was completed in earlier releases as follows:

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e, departments d  
WHERE d.department_id = e.department_id (+);
```

**FULLOUTER JOIN**

**Example:**

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e  
FULLOUTER JOIN departments d  
ON(e.department_id = d.department_id);
```

This query retrieves all rows in the EMPLOYEES table, even if there is no match in the DEPARTMENTS table. It also retrieves all rows in the DEPARTMENTS table, even if there is no match in the EMPLOYEES table.

**Find the Solution for the following:**

---

1. Write a query to display the last name, department number, and department name for all employees.

**SELECT**

```
e.last_name,  
e.department_id,  
d.department_name  
FROM  
employees e  
JOIN  
departments d ON e.department_id = d.department_id;
```

2. Create a unique listing of all jobs that are in department 80. Include the location of the department in the output.

**SELECT DISTINCT**

```
E.job_id, l.location_name FROM employees e  
JOIN  
departments d ON e.department_id = d.department_id  
JOIN  
locations l ON d.location_id = l.location_id WHERE e.department_id = 80;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

3. Write a query to display the employee last name, department name, location ID, and city of all employees who earn a commission

```
SELECT
    e.last_name,
    d.department_name,
    l.location_id,
    l.city
FROM
    employees e
JOIN
    departments d ON e.department_id = d.department_id
JOIN
    locations l ON d.location_id = l.location_id
WHERE
    e.commission_pct IS NOT NULL;
```

4. Display the employee last name and department name for all employees who have an a(lowercase) in their last names. P

```
SELECT
    e.last_name,
    d.department_name
FROM
    employees e
JOIN
    departments d ON e.department_id = d.department_id
WHERE
    e.last_name LIKE '%a%';
```

5. Write a query to display the last name, job, department number, and department name for all employees who work in Toronto.

```
SELECT
    e.last_name, j.job_title, d.department_id, d.department_name
FROM
    employees e
JOIN
    jobs j ON e.job_id = j.job_id
JOIN
    departments d ON e.department_id = d.department_id
JOIN
    locations l ON d.location_id = l.location_id
WHERE
    l.city = 'Toronto';
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

6. Display the employee last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, Respectively

**SELECT**

```
e.last_name AS Employee,  
e.employee_id AS "Emp#",  
m.last_name AS Manager,  
m.employee_id AS "Mgr#"  
FROM  
employees e  
LEFT JOIN  
employees m ON e.manager_id = m.employee_id;
```

7. Modify lab4\_6.sql to display all employees including King, who has no manager. Order the results by the employee number.

**SELECT**

```
e.last_name AS Employee,  
e.employee_id AS "Emp#",  
m.last_name AS Manager,  
m.employee_id AS "Mgr#"  
FROM  
employees e  
LEFT JOIN  
employees m ON e.manager_id = m.employee_id  
ORDER BY  
e.employee_id;
```

8. Create a query that displays employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label

**SELECT**

```
e1.last_name AS "Employee",  
e1.department_id AS "Department Number",  
e2.last_name AS "Colleague"  
FROM  
employees e1  
JOIN  
employees e2 ON e1.department_id = e2.department_id  
ORDER BY  
e1.last_name, e2.last_name;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

9. Show the structure of the JOB\_GRADES table. Create a query that displays the name, job, department name, salary, and grade for all employees

**DESC JOB\_GRADES;**

**SELECT**

```
e.last_name AS "Name",
j.job_title AS "Job",
d.department_name AS "Department Name",
e.salary AS "Salary",
g.grade AS "Grade"
FROM
employees e
JOIN
jobs j ON e.job_id = j.job_id
JOIN
departments d ON e.department_id = d.department_id
JOIN
job_grades g ON e.salary BETWEEN g.low_salary AND g.high_salary;
```

10. Create a query to display the name and hire date of any employee hired after employee Davies.

**SELECT**

```
last_name AS Name,    hire_date AS "Hire Date" FROM    employees
WHERE
hire_date > (
    SELECT hire_date
    FROM employees
    WHERE last_name = 'Davies'
    FETCH FIRST 1 ROW ONLY --it may require if multipl values for davies
);
```

11. Display the names and hire dates for all employees who were hired before their managers, along with their manager's names and hire dates. Label the columns Employee, Emp Hired, Manager, and Mgr Hired, respectively.

**SELECT**

```
e.last_name AS Employee,e.hire_date AS "Emp Hired",
m.last_name AS Manager, m.hire_date AS "Mgr Hired"
FROM    employees e
JOIN
employees m ON e.manager_id = m.employee_id
WHERE
e.hire_date < m.hire_date;
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## EXERCISE-8

### Aggregating Data Using Group Functions

#### Objectives

After the completion of this exercise, the students will be able to do the following:

- Identify the available group functions
- Describe the use of group functions
- Group data by using the GROUP BY clause
- Include or exclude grouped rows by using the HAVING clause

#### What Are Group Functions?

Group functions operate on sets of rows to give one result per group

#### Types of Group Functions

- AVG
- COUNT
- MAX
- MIN
- STDDEV
- SUM
- VARIANCE

Each of the functions accepts an argument. The following table identifies the options that you can use in the syntax:

Function	Description
AVG ( [DISTINCT   ALL] n)	Average value of n, ignoring null values
COUNT ( { *   [DISTINCT   ALL] expr } )	Number of rows, where expr evaluates to something other than null (count all selected rows using *, including duplicates and rows with nulls)
MAX ( [DISTINCT   ALL] expr )	Maximum value of expr, ignoring null values
MIN ( [DISTINCT   ALL] expr )	Minimum value of expr, ignoring null values
STDDEV ( [DISTINCT   ALL] x )	Standard deviation of n, ignoring null values
SUM ( [DISTINCT   ALL] n )	Sum values of n, ignoring null values
VARIANCE ( [DISTINCT   ALL] x )	Variance of n, ignoring null values

#### Group Functions: Syntax

```
SELECT [column,] group_function(column), ...
FROM table
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

[WHERE *condition*]

[GROUP BY *column*]

[ORDER BY *column*];

## Guidelines for Using Group Functions

- DISTINCT makes the function consider only nonduplicate values; ALL makes it consider every value, including duplicates. The default is ALL and therefore does not need to be specified.

- The data types for the functions with an expr argument may be CHAR, VARCHAR2, NUMBER, or DATE.

- All group functions ignore null values.

## **Using the AVG and SUM Functions**

---

You can use AVG and SUM for numeric data.

SELECT AVG(salary), MAX(salary),

MIN(salary), SUM(salary)

FROM employees

WHERE job\_id LIKE '%REP%';

## **Using the MIN and MAX Functions**

You can use MIN and MAX for numeric, character, and date data types.

SELECT MIN(hire\_date), MAX(hire\_date)

FROM employees;

You can use the MAX and MIN functions for numeric, character, and date data types. example displays the most junior and most senior employees.

The following example displays the employee last name that is first and the employee last name that is last in an alphabetized list of all employees:

SELECT MIN(last\_name), MAX(last\_name)

FROM employees;

**Note:** The AVG, SUM, VARIANCE, and STDDEV functions can be used only with numeric data types. MAX and MIN cannot be used with LOB or LONG data types.

## **Using the COUNT Function**

---

---

COUNT(\*) returns the number of rows in a table:

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SELECT COUNT(*)  
FROM employees  
WHERE department_id = 50;
```

COUNT(*expr*) returns the number of rows with nonnull values for the *expr*:

```
SELECT COUNT(commission_pct)  
FROM employees  
WHERE department_id = 80;
```

## Using the DISTINCT Keyword

- COUNT(DISTINCT *expr*) returns the number of distinct non-null values of the *expr*.
- To display the number of distinct department values in the EMPLOYEES table:

```
SELECT COUNT(DISTINCT department_id) FROM employees;  
Use the DISTINCT keyword to suppress the counting of any duplicate values in a column.
```

## **Group Functions and Null Values**

Group functions ignore null values in the column:

```
SELECT AVG(commission_pct)  
FROM employees;
```

The NVL function forces group functions to include null values:

```
SELECT AVG(NVL(commission_pct, 0))  
FROM employees;
```

## **Creating Groups of Data**

To divide the table of information into smaller groups. This can be done by using the GROUP BY clause.

### **GROUP BY Clause Syntax**

---

```
SELECT column, group_function(column)  
FROM table  
[WHERE condition]  
[GROUP BY group_by_expression]  
[ORDER BY column];
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## In the syntax:

*group\_by\_expression* specifies columns whose values determine the basis for grouping rows

## Guidelines

- If you include a group function in a SELECT clause, you cannot select individual results as well, *unless* the individual column appears in the GROUP BY clause. You receive an error message if you fail to include the column list in the GROUP BY clause.
- Using a WHERE clause, you can exclude rows before dividing them into groups.
- You must include the *columns* in the GROUP BY clause.
- You cannot use a column alias in the GROUP BY clause.

## Using the GROUP BY Clause

All columns in the SELECT list that are not in group functions must be in the GROUP BY clause.

```
SELECT department_id, AVG(salary)
```

```
FROM employees
```

```
GROUP BY department_id ;
```

The GROUP BY column does not have to be in the SELECT list.

```
SELECT AVG(salary) FROM employees GROUP BY department_id ;
```

You can use the group function in the ORDER BY clause:

```
SELECT department_id, AVG(salary) FROM employees GROUP BY department_id ORDER  
BY AVG(salary);
```

## Grouping by More Than One Column

```
SELECT department_id, dept_id, job_id, SUM(salary) FROM employees  
GROUP BY department_id, job_id ;
```

## Illegal Queries Using Group Functions

Any column or expression in the SELECT list that is not an aggregate function must be in the GROUP

## BY clause:

---

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

SELECT department\_id, COUNT(last\_name) FROM employees;

You can correct the error by adding the GROUP BY clause:

SELECT department\_id, count(last\_name) FROM employees GROUP BY department\_id;

You cannot use the WHERE clause to restrict groups.

- You use the HAVING clause to restrict groups.
- You cannot use group functions in the WHERE clause.

SELECT department\_id, AVG(salary) FROM employees WHERE AVG(salary) > 8000

GROUP BY department\_id;

You can correct the error in the example by using the HAVING clause to restrict groups:

SELECT department\_id, AVG(salary) FROM employees

HAVING AVG(salary) > 8000 GROUP BY department\_id;

### Restricting Group Results

With the HAVING Clause .When you use the HAVING clause, the Oracle server restricts groups as follows:

1. Rows are grouped.
2. The group function is applied.
3. Groups matching the HAVING clause are displayed.

### Using the HAVING Clause

SELECT department\_id, MAX(salary) FROM employees

GROUP BY department\_idHAVING MAX(salary)>10000 ;

The following example displays the department numbers and average salaries for those departments with a maximum salary that is greater than \$10,000:

SELECT department\_id, AVG(salary) FROM employees GROUP BY department\_id  
HAVING max(salary)>10000;

Example displays the job ID and total monthly salary for each job that has a total payroll exceeding \$13,000. The example excludes sales representatives and sorts the list by the total monthly salary.

SELECT job\_id, SUM(salary) PAYROLL FROM employees WHERE job\_id NOT LIKE  
'%REP%'

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

GROUP BY job\_id HAVING SUM(salary) > 13000 ORDER BY SUM(salary);

## Nesting Group Functions

### **Display themaximumaveragesalary:**

Group functions can be nested to a depth of two. The slide example displays the maximum average salary.

SELECT MAX(AVG(salary)) FROM employees GROUP BY department\_id;

### **Summary**

In this exercise, students should have learned how to:

- Use the group functions COUNT, MAX, MIN, and AVG
- Write queries that use the GROUP BY clause
- Write queries that use the HAVING clause

SELECT *column, group\_function*

FROM *table*

[WHERE *condition*]

[GROUP BY *group\_by\_expression*]

[HAVING *group\_condition*]

[ORDER BY *column*];

### **Find the Solution for the following:**

---

Determine the validity of the following three statements. Circle either True or False.

1. Group functions work across many rows to produce one result per group.

**True/False**

2. Group functions include nulls in calculations.

**True/False**

3. The WHERE clause restricts rows prior to inclusion in a group calculation.

**True/False**

### **The HR department needs the following reports:**

4. Find the highest, lowest, sum, and average salary of all employees. Label the columns Maximum, Minimum, Sum, and Average, respectively. Round your results to the nearest whole number

**SELECT**

**ROUND(MAX(salary)) AS Maximum,  
ROUND(MIN(salary)) AS Minimum,  
ROUND(SUM(salary)) AS Sum,  
ROUND(AVG(salary)) AS Average**

**FROM employees;**

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

5. Modify the above query to display the minimum, maximum, sum, and average salary for each job type.

**SELECT**

```
job_type,  
ROUND(MIN(salary)) AS Minimum,  
ROUND(MAX(salary)) AS Maximum,  
ROUND(SUM(salary)) AS Sum,  
ROUND(AVG(salary)) AS Average  
FROM employees  
GROUP BY job_type;
```

6. Write a query to display the number of people with the same job. Generalize the query so that the user in the HR department is prompted for a job title.

```
SELECT job_type, COUNT(*)AS Number_of_People  
FROM employees  
WHERE job_type = ?  
GROUP BY job_type;
```

7. Determine the number of managers without listing them. Label the column Number of Managers. *Hint: Use the MANAGER\_ID column to determine the number of managers.*

```
SELECT COUNT(DISTINCT MANAGER_ID) AS "Number of Managers"  
FROM employees  
WHERE MANAGER_ID IS NOT NULL;
```

8. Find the difference between the highest and lowest salaries. Label the column DIFFERENCE.

**SELECT**

```
ROUND(MAX(salary) - MIN(salary)) AS DIFFERENCE  
FROM employees;
```

9. Create a report to display the manager number and the salary of the lowest-paid employee for that manager. Exclude anyone whose manager is not known. Exclude any groups where the minimum salary is \$6,000 or less. Sort the output in descending order of salary.

**SELECT**

```
MANAGER_ID AS Manager_Number,  
MIN(salary) AS Lowest_Salary  
FROM employees  
WHERE MANAGER_ID IS NOT NULL  
GROUP BY MANAGER_ID  
HAVING MIN(salary) > 6000  
ORDER BY Lowest_Salary DESC;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

10. Create a query to display the total number of employees and, of that total, the number of employees hired in 1995, 1996, 1997, and 1998. Create appropriate column headings.

```
SELECT  
COUNT(*) AS Total_Employees,  
COUNT(CASE WHEN EXTRACT(YEAR FROM hire_date) = 1995 THEN 1 END) AS Hired_1995,  
COUNT(CASE WHEN EXTRACT(YEAR FROM hire_date) = 1996 THEN 1 END) AS Hired_1996,  
COUNT(CASE WHEN EXTRACT(YEAR FROM hire_date) = 1997 THEN 1 END) AS Hired_1997,  
COUNT(CASE WHEN EXTRACT(YEAR FROM hire_date) = 1998 THEN 1 END) AS Hired_1998  
FROM employees;
```

11. Create a matrix query to display the job, the salary for that job based on department number, and the total salary for that job, for departments 20, 50, 80, and 90, giving each column an appropriate heading.

```
SELECT  
job,  
SUM(CASE WHEN department_id = 20 THEN salary ELSE 0 END) AS Salary_Dept_20,  
SUM(CASE WHEN department_id = 50 THEN salary ELSE 0 END) AS Salary_Dept_50,  
SUM(CASE WHEN department_id = 80 THEN salary ELSE 0 END) AS Salary_Dept_80,  
SUM(CASE WHEN department_id = 90 THEN salary ELSE 0 END) AS Salary_Dept_90,  
SUM(salary) AS Total_Salary  
FROM employees  
WHERE department_id IN (20, 50, 80, 90)  
GROUP BY job  
ORDER BY job;
```

12. Write a query to display each department's name, location, number of employees, and the average salary for all the employees in that department. Label the column name-Location, Number of people, and salary respectively. Round the average salary to two decimal places.

```
SELECT  
d.department_name || '-' || d.location AS "name-Location",  
COUNT(e.employee_id) AS "Number of people",  
ROUND(AVG(e.salary), 2) AS salary  
FROM departments d  
LEFT JOIN employees e ON d.department_id = e.department_id  
GROUP BY d.department_name, d.location  
ORDER BY d.department_name;
```

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **EXERCISE-9**

### **Sub queries**

#### **Objectives**

After completing this lesson, you should be able to do the following:

- Defines subqueries
- Describes the types of problems that subqueries can solve
- Lists the types of subqueries
- Writes single-row and multiple-row subqueries

#### **Using a Subquery to Solve a Problem**

Who has a salary greater than Abel's?

#### **Main query:**

Which employees have salaries greater than Abel's salary?

#### **Subquery:**

What is Abel's salary?

#### **Subquery Syntax**

`SELECT select_list FROM table WHERE expr operator (SELECT select_list FROM table);`

- The subquery (inner query) executes once before the main query (outer query).
- The result of the subquery is used by the main query. A subquery is a SELECT statement that is embedded in a clause of another SELECT statement. You can build powerful statements out of simple ones by using subqueries. They can be very useful when you need to select rows from a table with a condition that depends on the data in the table itself. You can place the subquery in a number of SQL clauses, including the following:
- WHERE clause
- HAVING clause
- FROM clause

#### **In the syntax:**

---

*operator* includes a comparison condition such as `>`, `=`, or `IN`

**Note:** Comparison conditions fall into two classes: single-row operators

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

( $>$ ,  $=$ ,  $\geq$ ,  $<$ ,  $\neq$ ,  $\leq$ ) and multiple-row operators (IN, ANY, ALL). statement. The subquery generally executes first, and its output is used to complete the query condition for the main (or outer) query

## Using a Subquery

```
SELECT last_name FROM employees WHERE salary > (SELECT salary FROM employees WHERE last_name = 'Abel');
```

The inner query determines the salary of employee Abel. The outer query takes the result of the inner query and uses this result to display all the employees who earn more than this amount.

## Guidelines for Using Subqueries

---

- Enclose subqueries in parentheses.
- Place subqueries on the right side of the comparison condition.
- The ORDER BY clause in the subquery is not needed unless you are performing Top-N analysis.
- Use single-row operators with single-row subqueries, and use multiple-row operators with multiple-row subqueries.

## Types of Subqueries


- Single-row subqueries: Queries that return only one row from the inner SELECT statement.
- Multiple-row subqueries: Queries that return more than one row from the inner SELECT statement.

## Single-Row Subqueries

---

- 
- Return only one row
  - Use single-row comparison operators

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY



## **Example**

Display the employees whose job ID is the same as that of employee 141:

```
SELECT last_name, job_id FROM employees WHERE job_id = (SELECT job_id FROM employees WHERE employee_id = 141);
```

Display the employees whose job ID is the same as that of employee 141 and whose salary is greater than that of employee 143.

```
SELECT last_name, job_id, salary FROM employees WHERE job_id = (SELECT job_id FROM employees WHERE employee_id = 141) AND salary > (SELECT salary FROM employees WHERE employee_id = 143);
```

## **Using Group Functions in a Subquery**

Displays the employee last name, job ID, and salary of all employees whose salary is equal to the minimum salary. The MIN group function returns a single value (2500) to the outer query.

```
SELECT last_name, job_id, salary FROM employees WHERE salary = (SELECT MIN(salary) FROM employees);
```

## **The HAVING Clause with Subqueries**

- The Oracle server executes subqueries first.
- The Oracle server returns results into the HAVING clause of the main query.

Displays all the departments that have a minimum salary greater than that of department 50.

```
SELECT department_id, MIN(salary)  
FROM employees
```

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

GROUPBY department\_id HAVINGMIN(salary) > (SELECTMIN(salary) FROM employees WHEREdepartment\_id = 50);

**Example Find the job with the lowest average salary.**

SELECT job\_id, AVG(salary) FROM employees GROUP BY job\_id HAVING AVG(salary) = (SELECT MIN(AVG(salary)) FROM employees GROUP BY job\_id);


**What Is Wrong in this Statements?**

---

SELECT  
= employee\_id, last\_name FROM employees WHERE salary  
(SELECTMIN(salary) FROM employees GROUP BY department\_id); Will This  
Statement ReturnRows? SELECT last\_name, job\_id FROM employees WHERE job\_id =  
(SELECTjob\_id FROM employees WHERE last\_name = 'Haas');

**Multiple-Row Subqueries**

- Return more than one row
- Use multiple-row comparison operators



**Example**

Find theemployees who earn the same salary as the minimum salary for each department.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

SELECT last\_name, salary, department\_id FROM employees WHERE salary IN (SELECT MIN(salary)

FROM employees GROUP BY department\_id);

Using the ANY Operator in Multiple-Row Subqueries

SELECT employee\_id, last\_name, job\_id, salary FROM employees WHERE salary < ANY (SELECT salary FROM employees WHERE job\_id = 'IT\_PROG') AND job\_id > 'IT\_PROG'; Displays employees who are not IT programmers and whose salary is less than that of any IT programmer. The maximum salary that a programmer earns is \$9,000.

<ANY means less than the maximum. >ANY means more than the minimum. =ANY is equivalent to IN.

**Using the ALL Operator in Multiple-Row Subqueries**

---

SELECT employee\_id, last\_name, job\_id, salary  
FROM employees

WHERE salary < ALL (SELECT salary FROM employees WHERE job\_id = 'IT\_PROG')  
AND job\_id > 'IT\_PROG';

Displays employees whose salary is less than the salary of all employees with a job ID of IT\_PROG and whose job is not IT\_PROG.

ALL means more than the maximum, and <ALL means less than the minimum.

The NOT operator can be used with IN, ANY, and ALL operators.

**Null Values in a Subquery**

SELECT emp.last\_name FROM employees emp

WHERE emp.employee\_id NOT IN (SELECT mgr.manager\_id FROM employees mgr);

Notice that the null value as part of the results set of a subquery is not a problem if you use the IN operator. The IN operator is equivalent to =ANY. For example, to display the employees who have subordinates, use the following SQL statement:

SELECT emp.last\_name

FROM employees emp

WHERE emp.employee\_id IN (SELECT mgr.manager\_id FROM employees mgr);

Display all employees who do not have any subordinates:

SELECT last\_name FROM employees

WHERE employee\_id NOT IN (SELECT manager\_id FROM employees WHERE manager\_id IS NOT NULL);

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

### Find the Solution for the following:

1. The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).

```
SELECT last_name, hire_date
FROM employees
WHERE department_id =
    (SELECT department_id
     FROM employees
     WHERE last_name = ?
    )
AND last_name <> ?
ORDER BY last_name;
```

2. Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary.

```
SELECT employee_id, last_name, salary
FROM employees
WHERE salary > (SELECT AVG(salary) FROM employees)
ORDER BY salary ASC;
```

3. Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains a *u*.

```
SELECT employee_id, last_name
FROM employees
WHERE department_id IN (
    SELECT DISTINCT department_id
    FROM employees
    WHERE last_name LIKE '%u%'
)
ORDER BY employee_id;
```

4. The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.

```
SELECT e.last_name, e.department_id, e.job_id
FROM employees e
JOIN departments d ON e.department_id = d.department_id
WHERE d.location_id = 1700
ORDER BY e.last_name;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

5. Create a report for HR that displays the last name and salary of every employee who reports to King.

```
SELECT e.last_name, e.salary  
FROM employees e  
JOIN employees m ON e.manager_id = m.employee_id  
WHERE m.last_name = 'King'  
ORDER BY e.last_name;
```

6. Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

```
SELECT e.department_id, e.last_name, e.job_id  
FROM employees e  
JOIN departments d ON e.department_id = d.department_id  
WHERE d.department_name = 'Executive'  
ORDER BY e.last_name;
```

7. Modify the query 3 to display the employee number, last name, and salary of all employees who earn more than the average salary and who work in a department with any employee whose last name contains a *u*.

```
SELECT employee_id, last_name, salary  
FROM employees  
WHERE salary > (SELECT AVG(salary) FROM employees)  
  
AND department_id IN (  
    SELECT DISTINCT department_id  
    FROM employees  
    WHERE last_name LIKE '%u%'  
)  
ORDER BY salary ASC;
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## EXERCISE-10

### USING THE SET OPERATORS

#### **Objectives**

After the completion of this exercise, the students should be able to do the following:

- Describes set operators
- Use a set operator to combine multiple queries into a single query
- Control the order of rows returned

The set operators combine the results of two or more component queries into one result.

Queries containing set operators are called *compound queries*.

Operator	Returns
UNION	All distinct rows selected by either query
UNION ALL	All rows selected by either query, including all duplicates
INTERSECT	All distinct rows selected by both queries
MINUS	All distinct rows that are selected by the first SELECT statement and not selected in the second SELECT statement

#### **The tables used in this lesson are:**

- EMPLOYEES: Provides details regarding all current employees
- JOB\_HISTORY: Records the details of the start date and end date of the former job, and the job identification number and department when an employee switches jobs

#### **UNION Operator Guidelines**

- The number of columns and the data types of the columns being selected must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- UNION operates over all of the columns being selected. • NULL values are not ignored during duplicate checking.
- The IN operator has a higher precedence than the UNION operator.
- By default, the output is sorted in ascending order of the first column of the SELECT clause.

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## **Example:**

Display the current and previous job details of all employees. Display each employee only once.  
SELECT employee\_id, job\_id FROM employees UNION SELECT employee\_id, job\_id  
FROM job\_history;

## **Example:**

```
SELECT employee_id, job_id, department_id
FROM employees
UNION
SELECT employee_id, job_id, department_id
FROM job_history;
```

## **UNION ALL Operator**

### **Guidelines**

The guidelines for UNION and UNION ALL are the same, with the following two exceptions that pertain to UNION ALL:

- Unlike UNION, duplicate rows are not eliminated and the output is not sorted by default.
- The DISTINCT keyword cannot be used.

## **Example:**

Display the current and previous departments of all employees.

```
SELECT employee_id, job_id, department_id
FROM employees
UNION ALL
SELECT employee_id, job_id, department_id
FROM job_history
ORDER BY employee_id;
```

## **INTERSECT Operator**

### **Guidelines**

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- Reversing the order of the intersected tables does not alter the result.
- INTERSECT does not ignore NULL values.

## **Example:**

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Display the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired (that is, they changed jobs but have now gone back to doing their original job).

```
SELECT employee_id, job_id FROM employees  
INTERSECT  
SELECT employee_id, job_id  
FROM job_history;
```

**Example**

```
SELECT employee_id, job_id, department_id  
FROM employees  
INTERSECT  
SELECT employee_id, job_id, department_id  
FROM job_history;
```

### **MINUS Operator**

#### **Guidelines**

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- All of the columns in the WHERE clause must be in the SELECT clause for the MINUS operator to work.

**Example:**

Display the employee IDs of those employees who have not changed their jobs even once.

```
SELECT employee_id, job_id  
FROM employees  
MINUS  
SELECT employee_id, job_id  
FROM job_history;
```

**Find the Solution for the following:**

---

1. The HR department needs a list of department IDs for departments that do not contain the job ID ST\_CLERK. Use set operators to create this report.
2. The HR department needs a list of countries that have no departments located in them. Display the country ID and the name of the countries. Use set operators to create this report.
3. Produce a list of jobs for departments 10, 50, and 20, in that order. Display job ID and

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

department ID using set operators.

4. Create a report that lists the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired by the company (that is, they changed jobs but have now gone back to doing their original job).
  
5. The HR department needs a report with the following specifications: -Last name and department ID of all the employees from the EMPLOYEES table, regardless of whether or not they belong to a department. -Department ID and department name of all the departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them Write a compound query to accomplish this.

### **EXERCISE-11**

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## CREATING VIEWS

After the completion of this exercise, students will be able to do the following:

- Describe a view
- Create, alter the definition of, and drop a view
- Retrieve data through a view
- Insert, update, and delete data through a view
- Create and use an inline view

### **View**

A view is a logical table based on a table or another view. A view contains no data but is like a window through which data from tables can be viewed or changed. The tables on which a view is based are called base tables.

### **Advantages of Views**

---

- To restrict data access
- To make complex queries easy
- To provide data independence
- To present different views of the same data

### **Classification of views**

1. 2. Simple view  
Complex view

Feature

No. of tables	Simple	Complex
Contains functions	One	One or more
Contains groups of data	No	Yes Yes Not
DML operations on the view	No	always
	Yes	

### **Creating a view**

#### **Syntax**

CREATE OR REPLACE FORCE/NOFORCE VIEW view\_name AS Subquery WITH CHECK OPTION CONSTRAINT constraint WITH READ ONLY CONSTRAINT constraint;

**FORCE** - Creates the view regardless of whether or not the base tables exist.

**NOFORCE** - Creates the view only if the base tables exist.

WITH CHECK OPTION CONSTRAINT-specified that only rows accessible to the view can be inserted or updated.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

WITH READ ONLY CONSTRAINT-ensures that no DML operations can be performed on the view.

**Example:1 (Without using Column aliases)**

Create a viewEMPVU80 that contains details of employees in department80.

**Example 2:**

---

```
CREATE VIEW empvu80 AS SELECT employee_id, last_name, salary FROM employees  
WHERE department_id=80;
```

**Example:1 (Using column aliases)**

CREATE VIEW salvu50

```
AS SELECT employee_id,id_number, last_name NAME, salary *12 ANN_SALARY  
FROM employees  
WHERE department_id=50;
```

### Retrieving data from a view

**Example:**

```
SELECT*from salvu50;
```

### Modifying a view

---

A view can be altered without dropping, re-creating.

**Example:(Simple view)**

Modify the EMPVU80 view by using CREATE OR REPLACE.

```
CREATE OR REPLACE VIEW empvu80 (id_number, name, sal, department_id)
```

```
AS SELECT employee_id,first_name, last_name, salary, department_id  
FROM employees
```

WHERE department\_id=80;

**Example: (complex view)**

CREATE VIEW dept\_sum\_vu (name, minsal, maxsal,avgsal)

```
AS SELECT d.department_name, MIN(e.salary), MAX(e.salary), AVG(e.salary)  
FROM employees e, department d  
WHERE e.department_id=d.department_id  
GROUP BY d.department_name;
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## Rules for performing DML operations on view

- • Can perform operations on simple views
- ... Cannot remove a row if the view contains the following:
  - Group functions
  - Group By clause
  - Distinct keyword
  - Cannot modify data in a view if it contains
    - Group functions
    - Group By clause
    - Distinct keyword
    - Columns contain by expressions
  - Cannot add data through a view if it contains
    - Group functions
    - Group By clause
    - Distinct keyword
    - Columns contain by expressions
  - NOT NULL columns in the base table that are not selected by the view

## Example: (Using the WITH CHECK OPTION clause)

```
CREATE OR REPLACE VIEW empvu20
```

```
SELECT *
FROM employees
WHERE department_id=20
WITH CHECK OPTION CONSTRAINT empvu20_ck;
```

**Note:** Any attempt to change the department number for any row in the view fails because it violates the WITH CHECK OPTION constraint.

## Example – (Execute this and note the error)

```
UPDATE empvu20 SET department_id=10 WHERE employee_id=201;
```

## Denying DML operations

Use of WITH READONLY option.

Any attempt to perform a DML on any row in the view results in an oracle server error.

## Try this code:

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

```
CREATE OR REPLACE VIEW empvu10(employee_number, employee_name, job_title)
AS SELECT employee_id, last_name, job_id
FROM employees
WHERE department_id=10
WITH READ ONLY;
```

### **Find the Solution for the following:**

1. Create a view called EMPLOYEE\_VU based on the employee numbers, employee names and department numbers from the EMPLOYEES table. Change the heading for the employee name to EMPLOYEE.
2. Display the contents of the EMPLOYEES\_VU view.
3. Select the view name and text from the USER\_VIEWS data dictionary views.
4. Using your EMPLOYEES\_VU view, enter a query to display all employees names and department.
5. Create a view named DEPT50 that contains the employee number, employee last names and department numbers for all employees in department 50. Label the view columns EMPNO, EMPLOYEE and DEPTNO. Do not allow an employee to be reassigned to another department through the view.
6. Display the structure and contents of the DEPT50 view.
7. Attempt to reassign Matos to department 80.

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

8. Create a view called SALARY\_VU based on the employee last names, department names, salaries, and salary grades for all employees. Use the Employees, DEPARTMENTS and JOB\_GRADE tables. Label the column Employee, Department, salary, and Grade respectively.

**PL/SQL**

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **Control Structures**

In addition to SQL commands,PL/SQL can also process data usin flow of statements.the flow of control statements are classified into the following categories.

- Conditional control-Branching
- Iterative control-looping
- Sequential control

### **BRANCHING in PL/SQL:**

Sequence of statements canbe executed on satisfying certain condition .

If statements are being usedand different forms of if are:

1.Simple IF

2.ELSIF

3.ELSE IF

#### ***SIMPLE IF:***

---

##### **Syntax:**

IF condition THEN

statement1;

statement2;

END IF;

#### **IF-THEN-ELSE STATEMENT:**

##### **Syntax:**

IF condition THEN

statement1;

ELSE

statement2;

END IF;

#### **ELSIF STATEMENTS:**

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

### Syntax:

```
IF condition1 THEN  
    statement1;  
  
ELSIF condition2 THEN  
    statement2;  
  
ELSIF condition3 THEN  
    statement3;  
  
ELSE  
    statementn;  
  
END IF;
```

### NESTED IF :

### Syntax:

```
IF condition THEN  
    statement1;  
  
ELSE  
    IF condition THEN  
        statement2;  
  
    ELSE  
        statement3;  
  
    END IF;  
  
END IF;  
  
ELSE  
    statement3;  
  
END IF;
```

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **SELECTION IN PL/SQL(Sequential Controls)**

### ***SIMPLE CASE***

---

#### **Syntax:**

CASE SELECTOR

    WHEN Expr1 THEN statement1;

    WHEN Expr2 THEN statement2;

    :

    ELSE

        Statement n;

END CASE;

#### **SEARCHED CASE:**

---

CASE

    WHEN searchcondition1 THEN statement1;

    WHEN searchcondition2 THEN statement2;

    : : ELSE

        statementn;

END CASE;

## **ITERATIONS IN PL/SQL**

Sequence of statements canbe executed any number of times using loop construct.

It is broadly classified into:

- Simple Loop
- For Loop
- While Loop

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## SIMPLE LOOP

Syntax:

LOOP-

```
statement1;  
EXIT [ WHEN Condition];  
END LOOP;
```

## WHILE LOOP

Syntax:

WHILE condition LOOP

```
statement1;  
statement2;  
END LOOP;
```

## FOR LOOP

Syntax:

FOR counter IN [REVERSE]

```
LowerBound..UpperBound  
LOOP  
statement1;  
statement2;END LOOP;
```

---

## EXERCISE-12

---

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## PROCEDURES AND FUNCTIONS

### PROCEDURES

#### DEFINITION

A procedure or function is a logically grouped set of SQL and PL/SQL statements that perform a specific task. They are essentially sub-programs. Procedures and functions are made up of,

- • • Declarative part
- Executable part
- Optional exception handling part

These procedures and functions do not show the errors.

#### KEYWORDS AND THEIR PURPOSES

**REPLACE:** It recreates the procedure if it already exists.

**PROCEDURE:** Argument of the procedure to be created.

~~argument have to be defined in the procedure body. It is not possible to define them outside the procedure body.~~

Specifies that the procedure passes a value for this argument back to its calling environment after execution i.e. used to return values to a caller of the sub-program. **INOUT:** Specifies that a value for the argument must be specified when calling the procedure and that procedure passes a value for this argument back to its calling environment after execution. **RETURN:** It is the datatype of the function's return value because every function must return a value, this clause is required.

### PROCEDURES – SYNTAX

```
create or replace procedure <procedure name> (argument {in,out,inout} datatype ) {is,as}
variable declaration;
constant declaration;
begin
PL/SQL subprogram body;
exception
exception PL/SQL block;
end;
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## FUNCTIONS – SYNTAX

```
create or replace function<function name> (argument in datatype,.....) return datatype {is,as}
variable declaration;
constant declaration;
begin
PL/SQL subprogram body;
exception
exception PL/SQL block;
end;
```

## CREATING THE TABLE ‘ITITEMS’ AND DISPLAYING THE CONTENTS

```
SQL> createtableititems(itemidnumber(3),actualpricenumber(5),ordidnumber(4),prodid
number(4));
Table created.
SQL> insert into ititems values(101, 2000, 500, 201);
1 row created.
SQL> insert into ititems values(102, 3000, 1600, 202);
1 row created.
SQL> insert into ititems values(103, 4000, 600, 202);
1 row created.
SQL> select * from ititems;
ITEMID ACTUALPRICE
```

ORDID PRODID			
101	2000	500	201
102	3000	1600	202
103	4000	600	202

**PROGRAM FOR GENERAL PROCEDURE – SELECTED RECORD’S PRICE IS INCREMENTED BY 500 , EXECUTING THE PROCEDURE CREATED AND DISPLAYING THE UPDATED TABLE to**

```
SQL> create procedure itsum(identity number,
number) is price number;
```

```
2 null_price exception;
3 begin
4 select actualprice into price from ititems where itemid=identity;
5 if price is null then
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
6raisenull_price;
7 else
8updateititems set actualprice=actualprice+total where itemid=identity;
9 endif;
10 exception
11whennull_price then
12dbms_output.put_line('price is null');
13 end;
14/
```

Procedurecreated.

SQL>execitsum(101, 500);

PL/SQLprocedure successfully completed.

SQL>select\*from ititems;

ITEMID	ACTUALPRICE	ORDID	PRODID
101	2500	500	201
102	3000	1600	202
103	4000	600	202

### **PROCEDURE FOR ‘IN’ PARAMETER – CREATION, EXECUTION**

SQL>setserveroutput on;

SQL>createprocedureyyy(a IN number) is price number;

```
2 begin
3selectactualprice into price from ititems where itemid=a;
4dbms_output.put_line('Actual price is ' || price);
5ifpriceisnull then
6dbms_output.put_line('price is null');
7 endif;
8 end;
9/
```

Procedurecreated.

SQL>execyyy(103);

Actualpriceis4000

PL/SQLprocedure successfully completed.

### **PROCEDUREFOR‘OUT’PARAMETER–CREATION, EXECUTION**

SQL> set serveroutput on;

---

SQL> create procedure zzz (a in number, b out number) is identity number;

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
2 begin
3 select ordid into identity from ititems where itemid=a;
4 if identity<1000 then
5 b:=100;
6 end if;
7 end;
8 /
```

Procedure created.

```
SQL> declare
2 a number;
3 b number;
4 begin
5 zzz(101,b);
6 dbms_output.put_line('The value of b is'|| b);
7 end;
8 /
```

The value of b is 100

PL/SQL procedure successfully completed.

### PROCEDUREFOR‘INOUT’PARAMETER–CREATION, EXECUTION

---

```
SQL> create procedure itit ( a in out number) is
2 begin
3 a:=a+1;
4 end;
5 /
Procedure created.
```

```
SQL> declare
2 a number:=7;
3 begin
4 itit(a);
5 dbms_output.put_line('The updated value is '||a);
6 end;
7 /
```

The updated value is 8

PL/SQL procedure successfully completed.

### CREATE THE TABLE ‘ITTRAIN’ TO BE USED FOR FUNCTIONS

---

```
SQL>create table ittrain ( tno number(10), tfare number(10));
```

Table created.

```
SQL>insert into ittrain values (1001, 550);
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
1 row created.  
SQL>insertintoittrainvalues (1002, 600);  
1 row created.  
SQL>select * from ittrain;
```

TNO	TFARE
1001	550
1002	600

### PROGRAMFORFUNCTION AND IT'S EXECUTION

```
SQL>createfunctionaaa(trainnumber number) return number is  
2trainfunctionittrain.tfare % type;  
3 begin  
4 selecttfareintotrainfunction from ittrain where tno=trainnumber;  
5 return(trainfunction);  
6 end;  
7/
```

Function created.

```
SQL> set serveroutput on;  
SQL> declare
```

```
2 total number;  
3 begin  
4 total:=aaa (1001);  
5 dbms_output.put_line('Train fare is Rs. '|total);  
6 end;  
7/
```

Train fare is Rs.550

PL/SQLproceduresuccessfully completed.

### **FACTORIALOFANUMBERUSINGFUNCTION — PROGRAM AND EXECUTION**

---

```
SQL>createfunctionitfact (a number) return number is  
2 factnumber:=1;  
3 bnumber;  
4 begin  
5 b:=a;  
6 whileb>0
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
7 loop  
8 fact:=fact*b;  
9 b:=b-1;  
10 end loop;  
11 return(fact);  
12 end;  
13 /
```

Function created.

```
SQL> set serveroutput on;
```

```
SQL> declare  
2 a number:=7;  
3 f number(10);  
4 begin  
5 f:=itfact(a);  
6 dbms_output.put_line('The factorial of the given number is'||f);  
7 end;  
8 /
```

The factorial of the given number is 5040

PL/SQL procedure successfully completed.

### EXERCISE-13

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **TRIGGER**

### **DEFINITION**

A trigger is a statement that is executed automatically by the system as a side effect of a modification to the database. The parts of a trigger are,

- **Trigger statement:** Specifies the DML statements and fires the trigger body. It also specifies the table to which the trigger is associated.
- **Trigger body or trigger action:** It is a PL/SQL block that is executed when the triggering statement is used.
- **Trigger restriction:** Restrictions on the trigger can be achieved

The different uses of triggers are as follows,

*To generate data automatically*

*To enforce complex integrity constraints*

*To customize complex securing authorizations*

•

*To maintain the replicatable*

• *To audit data modifications*

## **TYPES OF TRIGGERS**

The various types of triggers are as follows,

- **Before:** It fires the trigger before executing the trigger statement.
- **After:** It fires the trigger after executing the trigger statement
- .
- **For each row:** It specifies that the trigger fires once per row
- .
- **For each statement:** This is the default trigger that is invoked. It specifies that the trigger fires once per statement.

## **VARIABLES USED IN TRIGGERS**

- **:new**
- **:old**

These two variables retain the new and old values of the column updated in the database. The values in these variables can be used in the database triggers for data manipulation

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **SYNTAX**

```
create or replace trigger triggername [before/after] {DML statements}  
on [tablename] [foreach row/statement] begin -----  
-----  
-----
```

```
exception  
end;
```

## **USER DEFINED ERROR MESSAGE**

The package “raise\_application\_error” is used to issue the user defined error messages

**Syntax:** raise\_application\_error(error number, ‘error message’);

The error number can lie between -20000 and -20999.

The error message should be a character string.

## **TO CREATE THE TABLE ‘ITEMPLS’**

```
SQL>create table itempls (ename varchar2(10), eid number(5), salary number(10));  
Table created.
```

```
SQL>insert into itempls values('xxx',11,10000);  
1 row created.
```

```
SQL>insert into itempls values('yyy',12,10500);  
1 row created.
```

```
SQL>insert into itempls values('zzz',13,15500);  
1 row created.
```

```
SQL>select * from itempls;
```

ENAME	EID	SALARY
xx	1	10000
x	1	10500
yy	13	15500
y	2	

**TO CREATE A SIMPLE TRIGGER THAT DOES NOT ALLOW INSERT UPDATE AND DELETE OPERATIONS ON THE TABLE**

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> create trigger ittrigg before insert or update or delete on itempls for each row
  2 begin
  3 raise_application_error(-20010,'You cannot do manipulation');
  4 end;
  5
  6 /
```

Trigger created.

```
SQL> insert into itempls values('aaa',14,34000);
insert into itempls values('aaa',14,34000)
```

\*

ERROR at line 1:

```
ORA-20010: You cannot do manipulation
ORA-06512: at "STUDENT.ITTRIGG", line 2
ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'
SQL> delete from itempls where ename='xxx';
delete from itempls where ename='xxx'
```

\*

ERROR at line 1:

```
ORA-20010: You cannot do manipulation
ORA-06512: at "STUDENT.ITTRIGG", line 2
ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'
SQL> update itempls set eid=15 where ename='yyy';
update itempls set eid=15 where ename='yyy'
```

\*

ERROR at line 1:

```
ORA-20010: You cannot do manipulation
ORA-06512: at "STUDENT.ITTRIGG", line 2
ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'
```

### **TO DROP THE CREATED TRIGGER**

---

```
SQL> drop trigger ittrigg;
```

Trigger dropped.

### **TO CREATE A TRIGGER THAT RAISES AN USER DEFINED ERROR MESSAGE ANDDOESNOTALLOW UPDATIONANDINSERTION**

```
SQL> create trigger ittriggs before insert or update of salary onitempls for each row
```

```
2 declare
  3 triggsal itempls.salary%type;
  4 begin
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
5 select salary into triggsal from itempls where eid=12;
6 if(:new.salary>triggsal or :new.salary<triggsal) then
7 raise_application_error(-20100,'Salary has not been changed');
8 end if;
9 end;
10 /
```

Trigger created.

```
SQL> insert into itempls values ('bbb',16,45000);
insert into itempls values ('bbb',16,45000)
```

\*

ERROR at line 1:

```
ORA-04098: trigger 'STUDENT.ITTRIGGS' is invalid and failed re-validation
```

```
SQL> update itempls set eid=18 where ename='zzz';
update itempls set eid=18 where ename='zzz'
```

\*

ERROR at line 1:

```
ORA-04298: trigger 'STUDENT.ITTRIGGS' is invalid and failed re-validation
```

Cursor for loop

Explicit cursor

Implicit cursor

### TOCREATETHETABLE 'SSEMPP'

```
SQL> create table ssempp( eid number(10), ename varchar2(20), job varchar2(20), sal number(10),dnonumber(5));
Table created.
```

```
SQL> insert into ssempp values(1,'nala','lecturer',34000,11);
1 row created.
```

```
SQL> insert into ssempp values(2,'kala',' seniorlecturer',20000,12);
1 row created.
```

```
SQL> insert into ssempp values(5,'ajay','lecturer',30000,11);
1 row created.
```

```
SQL> insert into ssempp values(6,'vijay','lecturer',18000,11);
1 row created.
```

```
SQL> insert into ssempp values(3,'nila','professor',60000,12);
1 row created.
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> select * from ssempp;
```

EID	ENAME	JOB	SAL	DNO
1	nala	lecturer	34000	11
2	kala	seniorlecturer	20000	12
5	ajay	lecturer	30000	11
6	vijay	lecturer	18000	11
3	nila	professor	60000	12

### EXTRA PROGRAMS

**TOWRITE A PL/SQL BLOCK TO DISPLAY THE EMPLOYEE ID AND EMPLOYEE NAME USING CURSOR FOR LOOP**

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 begin
3 for emy in (select eid,ename from ssempp)
4 loop
5 dbms_output.put_line('Employee id and employee name are'|| emy.eid 'and'|| emy.ename);
6 end loop;
7 end;
8 /
```

Employee id and employee name are 1 and nala Employee id and employee name are 2 and kala  
Employee id and employee name are 5 and ajay Employee id and employee name are 6 and vijay  
~~Employee id and employee name are 3 and nila~~  
**EMPLOYEE EXAMPLES**  
**PL/SQL BLOCK TO UPDATE THE SALARY OF ALL EMPLOYEES WHERE DEPARTMENT NO IS 11 BY 5000 USING CURSOR FOR LOOP AND TO DISPLAY THE UPDATED TABLE**

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 cursor cem is select eid,ename,sal,dno from ssempp where dno=11;
3 begin
4 --open cem;
5 for rem in cem
6 loop
7 update ssempp set sal=rem.sal+5000 where eid=rem.eid;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
8 endloop;
9 --closecem;
10 end;
11/
```

PL/SQL procedures successfully completed.

```
SQL> select * from ssempp;
```

EID	ENAME	JOB	SAL	DNO
1	nala	lecturer	39000	11
2	kala	seniorlecturer	20000	12
5	ajay	lecturer	35000	11
6	vijay	lecturer	23000	11
3	nila	professor	60000	12

### **TOWRITEAPL/SQLBLOCK TO DISPLAY THE EMPLOYEE ID AND EMPLOYEE NAME WHERE DEPARTMENT NUMBER IS 11 USING EXPLICIT CURSORS**

```
1 declare
2 cursor cenl is select eid,sal from ssempp where dno=11;
3 ecode ssempp.eid%type;
4 esal empp.sal%type;
5 begin
6 open cenl;
7 loop
8 fetch cenl into ecode,esal;
9 exit when cenl%notfound;
10 dbms_output.put_line(' Employee code and employee salary are' || ecode 'and'|| esal);
11 end loop;
12 close cenl;
13* end;
```

SQL> / Employee code and employee salary are 1 and 39000 Employee code and employee salary are 5 and 35000 Employee code and employee salary are 6 and 23000 PL/SQL procedure  
~~TOCREATEAPL/SQL BLOCK TO UPDATE THE SALARYBY 5000WHERETHEJOBIS LECTURER , TO CHECK IF UPDATES ARE MADEUSING IMPLICIT CURSORS AND TO DISPLAY THE UPDATED TABLE~~

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> declare
  2 countynumber;
  3 begin
  4 updatessempsetsal=sal+10000wherejob='lecturer';
  5 county:=sql%rowcount;
  6 if county > 0 then
  7 dbms_output.put_line('The number of rows are'|| county);
  8 endif;
  9 ifsql%foundthen
10 dbms_output.put_line('Employee record modification successful'); 11
elseifsql%notfoundthen 12 dbms_output.put_line('Employee record is not
found'); 13 end if; 14 end if; 15 end; 16/
```

The number of rows are 3  
Employee record modification successful  
PL/SQL procedure successfully completed.  
SQL> select \* from ssemp;

EIDENAME	JOB	SAL	DNO
nala1	lecturer	44000	11
kala2	seniorlecturer	20000	12
ajay5	lecturer	40000	11
vijay6	lecturer	28000	11
nila 3	professor	60000	12

### PROGRAMS

#### TO DISPLAY HELLO MESSAGE

```
SQL> set serveroutput on;
SQL> declare
  2 a varchar2(20);
  3 begin
  4 a:='Hello';
  5 dbms_output.put_line(a);
  6 end;
  7 /
Hello
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

PL/SQL procedure successfully completed.

### TO INPUT A VALUE FROM THE USER AND DISPLAY IT

SQL> set serveroutput on;

SQL> declare

```
2 a varchar2(20);
3 begin
4 a:=&a;
5 dbms_output.put_line(a);
6 end;
7/
```

Enter value for a: 5

old 4:a:=&a;

new 4:a:=5;

5

PL/SQL procedure successfully completed.

### GREATES OF TWO NUMBERS

SQL> set serveroutput on;

SQL> declare

```
2 a number(7); 3 b number(7); 4 begin 5 a:=&a; 6
b:=&b; 7 if(a>b) then 8 dbms_output.put_line (' The
grerater of the two is'|| a); 9 else
```

```
10 dbms_output.put_line (' The grerater of the two is'|| b);
11 end if;
12 end;
13/
```

Enter value for a: 5

old 5:a:=&a;

new 5:a:=5;

Enter value for b: 9

old 6:b:=&b;

new 6:b:=9;

The grerater of the two is 9

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

PL/SQL procedure successfully completed.

### GREATEST OF THREE NUMBERS

SQL> set serveroutput on;

SQL> declare

```
2 a number(7);
3 b number(7);
4 c number(7);
5 begin
6 a:=&a;
7 b:=&b;
8 c:=&c;
9 if(a>b and a>c) then
10 dbms_output.put_line (' The greatest of the three is ' || a);
11 else if (b>c) then 12 dbms_output.put_line (' The greatest
of the three is ' || b); 13 else 14 dbms_output.put_line (' The
greatest of the three is ' || c); 15 end if; 16 end if; 17 end; 18 /
```

Enter value for a: 5

old 6: a:=&a;

new 6: a:=5;

Enter value for b: 7

old 7: b:=&b;

new 7: b:=7;

Enter value for c: 1

old 8: c:=&c;

new 8: c:=1;

The greatest of the three is 7

PL/SQL procedure successfully completed.

### PRINT NUMBERS FROM 1 TO 5 USING SIMPLE LOOP

SQL> set serveroutput on;

SQL> declare

2 a number:=1;

3 begin

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

```
4 loop
5dbms_output.put_line (a);
6 a:=a+1;
7exitwhen a>5;
8endloop;
9 end;
10/
1 2 3 4 5 PL/SQLprocedure successfully
completed.
```

### **PRINTNUMBERS FROM 1 TO 4 USING WHILE LOOP**

```
SQL>setserveroutput on;
SQL>declare
```

```
2anumber:=1;
3 begin
4while(a<5)
5 loop
6dbms_output.put_line (a);
7 a:=a+1;
8endloop;
9 end;
10/
1 2 3 4 PL/SQLprocedure successfully completed.
```

### **PRINTNUMBERSFROM1TO5USINGFORLOOP**

```
SQL>setserveroutput on; SQL>declare
```

---

```
2anumber:=1;
3 begin
4forain1..5
5 loop
6dbms_output.put_line (a);
7endloop;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
8 end;
```

```
9 /
```

```
1 2 3 4 5 PL/SQL procedure successfully completed. PRINT NUMBERS FROM 1 TO 5 IN REVERSE ORDER USING FOR LOOP SQL> set serveroutput on;  
SQL> declare
```

---

```
2 a number:=1;
```

```
3 begin
```

```
4 for a in reverse 1..5
```

```
5 loop
```

```
6 dbms_output.put_line (a);
```

```
7 end loop;
```

```
8 end;
```

```
9 /
```

```
5 4 3 2 1 PL/SQL procedure successfully completed. TO CALCULATE AREA OF CIRCLE SQL> set serveroutput on; SQL> declare
```

---

```
2 pi constant number(4,2):=3.14;
```

```
3 a number(20);
```

```
4 r number(20);
```

```
5 begin
```

```
6 r:=&r;
```

```
7 a:= pi* power(r,2);
```

```
8 dbms_output.put_line (' The area of circle is ' || a);
```

```
9 end;
```

```
10 /
```

```
Enter value for r: 2
```

```
old 6: r:=&r;
```

```
new 6: r:=2;
```

```
The area of circle is 13
```

```
PL/SQL procedure successfully completed.
```

```
TO CREATE SACCOUNT TABLE
```

```
SQL> create table saccount ( accno number(5), name varchar2(20), bal number(10));
```

```
Table created.
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> insert into saccount values ( 1,'mala',20000);
```

```
1 row created.
```

```
SQL> insert into saccount values (2,'kala',30000);
```

```
1 row created.
```

```
SQL> select * from saccount;
```

ACCNO	NAME	BAL
1	mala	20000
2	kala	30000

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 a_bal number(7);
3 a_no varchar2(20);
4 debit number(7):=2000;
5 minamt number(7):=500;
6 begin
7 a_no:=&a_no;
8 select bal into a_bal from saccount where accno= a_no;
9 a_bal:= a_bal-debit;
10 if (a_bal > minamt) then
11 update saccount set bal=bal-debit where accno=a_no;
12 end if;
13 end;
14
15 /
```

```
Enter value for a_no: 1
```

```
old 7: a_no:=&a_no;
```

```
new 7: a_no:=1;
```

```
PL/SQL procedure successfully completed.
```

```
SQL> select * from saccount;
```

ACCNO	NAME	BAL
1	mala	18000
2	kala	30000

### TO CREATE TABLE SROUTES

```
SQL> create table sroutes ( rno number(5), origin varchar2(20), destination varchar2(20), fare
numbe
```

```
r(10), distance number(10));
```

```
Table created.
```

```
SQL> insert into sroutes values ( 2, 'chennai', 'dindugal', 400,230);
```

```
1 row created.
```

```
SQL> insert into sroutes values ( 3, 'chennai', 'madurai', 250,300);
```

```
1 row created.
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> insertintosroutesvalues(6,'thanjavur','palani', 350,370);
```

```
1 row created.
```

```
SQL> select * from sroutes;
```

RNOORIGIN	DESTINATION	FARE	DISTANCE
2chennai	dindugal	400	230
3chennai	madurai	250	300
6thanjavur	palani	350	370

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 route sroutes.rno % type;
3 fares sroutes.fare % type;
4 dist sroutes.distance % type;
5 begin
6 route:=&route;
7selectfare,distanceintofares,distfromsrouteswhere rno=route;
8 if (dist < 250) then
9 update sroutes set fare=300 where rno=route;
10 else if dist between 250 and 370 then 11
update sroutes set fare=400 where rno=route; 12
13 else if (dist > 400) then
dbms_output.put_line('Sorry'); 14 end if; 15 end
if; 16 end if; 17 end; 18/
```

```
Enter value for route: 3
```

```
old 6:route:=&route;
```

```
new 6: route:=3;
```

```
PL/SQL procedure successfully completed.
```

```
SQL> select * from sroutes;
```

RNOORIGIN	DESTINATION	FARE	DISTANCE
2chennai	dindugal	400	230
3chennai	madurai	400	300
6thanjavur	palani	350	370

**TO CREATE SCALAR CULATE TABLE**

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL>createtables calculate(radiusnumber(3), area number(5,2));
```

Table created.

```
SQL>desc calculate;
```

Null?	Type
	NUMBER(3)
	NUMBER(5,2)

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 pi constant number(4,2):=3.14;
3 radius number(5,2); 4
5 number(3); 6 begin 7 radius:=3; 8
while (radius <=7) 9 loop 9
area:=pi*power(radius,2);
```

```
10 insert into calculate values (radius,area);
```

```
11 radius:=radius+1;
```

```
12 endloop;
```

```
13 end;
```

```
14/
```

PL/SQL procedure successfully completed.

```
SQL> select * from calculate;
```

RADIUS	AREA
3	28.26
4	50.24
5	78.5
6	113.04
7	153.86

### TO CALCULATE FACTORIAL OF A GIVEN NUMBER

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 f number(4):=1;
```

```
3 i number(4);
```

```
4 begin
```

```
5 i:=&i;
```

```
6 while(i>=1)
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

```
7 loop
8   f:=f*i;
9   i:=i-1;
10 end loop;
11 dbms_output.put_line('The value is ' || f);
12 end;
13 /
```

Enter value for i: 5

old 5: i:=&i;

new 5: i:=5;

The value is 120

PL/SQL procedure successfully completed.

### **EXERCISE-14**

#### **OTHER DATABASE OBJECTS**

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY


## **Objectives**

After the completion of this exercise, the students will be able to do the following:

- Create, maintain, and use sequences
- Create and maintain indexes

## **Database Objects**

Many applications require the use of unique numbers as primary key values. You can either build code into the application to handle this requirement or use a sequence to generate unique numbers. If you want to improve the performance of some queries, you should consider creating an index. You can also use indexes to enforce uniqueness on a column or a collection of columns. You can provide alternative names for objects by using synonyms.



## **What Is a Sequence?**

A sequence:

- Automatically generates unique numbers
- Is a sharable object
- Is typically used to create a primary key value
- Replaces application code
- Speeds up the efficiency of accessing sequence values when cached in memory

## **The CREATE SEQUENCE Statement Syntax**

Define a sequence to generate sequential numbers automatically:

```
CREATE SEQUENCE sequence
[INCREMENT BY n]
[START WITH n]
[{MAXVALUE n | NOMAXVALUE}]
[{MINVALUE n | NOMINVALUE}]
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

[{CYCLE | NOCYCLE}]  
[{CACHE *n* | NOCACHE}];

### In the syntax:

*sequence* is the name of the sequence generator

INCREMENT BY *n* specifies the interval between sequence numbers where *n* is an integer (If this clause is omitted, the sequence increments by 1.)

START WITH *n* specifies the first sequence number to be generated (If this clause is omitted, the sequence starts with 1.)

MAXVALUE *n* specifies the maximum value the sequence can generate

NOMAXVALUE specifies a maximum value of  $10^{27}$  for an ascending sequence and -1 for a descending sequence (This is the default option.)

MINVALUE *n* specifies the minimum sequence value

NOMINVALUE specifies a minimum value of 1 for an ascending sequence and -( $10^{26}$ ) for a descending sequence (This is the default option.)

CYCLE | NOCYCLE specifies whether the sequence continues to generate values after reaching its maximum or minimum value (NOCYCLE is the default option.)

CACHE *n* | NOCACHE specifies how many values the Oracle server preallocates and keep in memory (By default, the Oracle server caches 20 values.)

### Creating a Sequence

- Create a sequence named DEPT\_DEPTID\_SEQ to be used for the primary key of the DEPARTMENTS table.
- Do not use the CYCLE option.

### EXAMPLE:

---

```
CREATE SEQUENCE dept_deptid_seq
INCREMENT BY 10
START WITH 120
MAXVALUE 9999
NOCACHE
NOCYCLE;
```

### Confirming Sequences

- Verify your sequence values in the USER\_SEQUENCES data dictionary table.
- The LAST\_NUMBER column displays the next available sequence number if NOCACHE is specified.

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## **EXAMPLE:**

SELECT sequence\_name, min\_value, max\_value, increment\_by, last\_number

## **NEXTVAL and CURRVAL Pseudocolumns**

- NEXTVAL returns the next available sequence value. It returns a unique value every time it is referenced, even for different users.
- CURRVAL obtains the current sequence value.
- NEXTVAL must be issued for that sequence before CURRVAL contains a value.

## **Rules for Using NEXTVAL and CURRVAL**

You can use NEXTVAL and CURRVAL in the following contexts:

- The SELECT list of a SELECT statement that is not part of a subquery
- The SELECT list of a subquery in an INSERT statement
- The VALUES clause of an INSERT statement
- The SET clause of an UPDATE statement

You cannot use NEXTVAL and CURRVAL in the following contexts:

- The SELECT list of a view
- A SELECT statement with the DISTINCT keyword
- A SELECT statement with GROUP BY, HAVING, or ORDER BY clauses
- A subquery in a SELECT, DELETE, or UPDATE statement
- The DEFAULT expression in a CREATE TABLE or ALTER TABLE statement

## **Using a Sequence**

- Insert a new department named “Support” in location ID 2500.
- View the current value for the DEPT\_DEPTID\_SEQ sequence.

## **EXAMPLE:**

```
INSERT INTO departments(department_id, department_name, location_id)
```

```
VALUES (dept_deptid_seq.NEXTVAL, 'Support', 2500);
```

```
SELECT dept_deptid_seq.CURRVAL FROM dual;
```

The example inserts a new department in the DEPARTMENTS table. It uses the DEPT\_DEPTID\_SEQ sequence for generating a new department number as follows:

---

uses the

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

You can view the current value of the sequence:

```
SELECT dept_deptid_seq.CURRVAL FROM dual;
```

## **Removing a Sequence**

- Remove a sequence from the data dictionary by using the DROP SEQUENCE statement.
- Once removed, the sequence can no longer be referenced.

## **EXAMPLE:**

---

```
DROP SEQUENCEdept_deptid_seq;
```

## **What is an Index?**

An index:

- Is a schema object
- Is used by the Oracle server to speedup the retrieval of rows by using a pointer
- Can reduce disk I/O by using a rapidpathaccess method to locate data quickly
- Is independent of the table it indexes
- Is used and maintained automatically by the Oracle server

## **How Are Indexes Created?**

- Automatically: A unique index is created automatically when you define a PRIMARY KEY or UNIQUE constraint in a table definition.
- Manually: Users can create nonunique indexes on columns to speed up access to the rows.

## **Types of Indexes**

Two types of indexes can be created. One type is a unique index: the Oracle server automatically creates this index when you define a column in a table to have a PRIMARY KEY or a UNIQUE key

constraint. The name of the index is the name given to the constraint.

The other type of index is a nonunique index, which a user can create. For example, you can create a

FOREIGN KEY column index for a join in a query to improve retrieval speed.

## **Creating an Index**

- Create an index on one or more columns.
  - Improve the speed of query access to the LAST\_NAME column in the EMPLOYEES table.
- ```
CREATE INDEX index  
ON table (column[, column]...);
```
- 

## **EXAMPLE:**

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
CREATE INDEX emp_last_name_idx  
ON employees(last_name);
```

## In the syntax:

*index* is the name of the index

*table* is the name of the table

*column* is the name of the column in the table to be indexed

## When to Create an Index

You should create an index if:

- A column contains a widerange of values
- A column contains a largenumber of null values
- Oneormorecolumnsarefrequentlyusedtogetherin a WHERE clause or a join condition
- Thetableislargeandmostqueriesareexpectedtoretrieve less than 2 to 4 percent of the rows

## When Not to Create an Index

It is usually not worth creating an index if:

- The table is small
- The columns are not often used as a condition in the query
- Most queries are expected to retrieve more than 2 to 4 percent of the rows in the table
- The table is updated frequently
- The indexed columns are referenced as part of an Expression

## Confirming Indexes

- TheUSER\_INDEXESdata dictionary view contains the name of the index and its uniqueness.
- TheUSER\_IND\_COLUMNSview contains the index name, the table name, and the column name.

## EXAMPLE:

```
SELECT ic.index_name,ic.column_name,ic.column_position col_pos,ix.uniqueness  
FROM user_indexesix,user_ind_columnsic  
WHERE ic.index_name=ix.index_name  
AND ic.table_name='EMPLOYEES';
```

## Removing an Index

- Remove an index from the data dictionary by using the DROP INDEX command.
- Remove the UPPER\_LAST\_NAME\_IDX index from the data dictionary.
- To drop an index, you must be the owner of the index or have the DROP ANY INDEX privilege.

```
DROP INDEX upper_last_name_idx;  
DROP INDEX index;
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

### **Find the Solution for the following:**

1. Create a sequence to be used with the primary key column of the DEPT table. The sequence should start at 200 and have a maximum value of 1000. Have your sequence increment by ten numbers. Name the sequence DEPT\_ID\_SEQ.
2. Write a query in a script to display the following information about your sequences: sequence name, maximum value, increment size, and last number.
3. Write a script to insert two rows into the DEPT table. Name your script lab12\_3.sql. Be sure to use the sequence that you created for the ID column. Add two departments named Education and Administration. Confirm your additions. Run the commands in your script.
4. Create a nonunique index on the foreign key column (DEPT\_ID) in the EMP table.
5. Display the indexes and uniqueness that exist in the data dictionary for the EMP table.

### **EXERCISE-15**


#### **Controlling User Access**

##### **Objectives**

After the completion of this exercise, the students will be able to do the following:

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- Create users
- Create roles to ease setup and maintenance of the security model
- Use the GRANT and REVOKE statements to grant and revoke object privileges
- Create and access database links



### Controlling User Access

In a multiple-user environment, you want to maintain security of the database access and use. With Oracle server database security, you can do the following:

- Control database access
- Give access to specific objects in the database
- Confirm given and received *privileges* with the Oracle data dictionary
- Create synonyms for database objects

### Privileges

---

- Database security:
  - System security
  - Data security
- System privileges: Gaining access to the database
- Object privileges: Manipulating the content of the database objects
- Schemas: Collections of objects, such as tables, views, and sequences

### System Privileges

---

- More than 100 privileges are available.

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- The database administrator has high-level system privileges for tasks such as:
  - Creating new users
  - Removing users
  - Removing tables
  - Backing up tables

## Typical DBA Privileges

| System Privilege | Operations Authorized                                                        |
|------------------|------------------------------------------------------------------------------|
| CREATE USER      | Grantee can create other Oracle users (a privilege required for a DBA role). |
| DROP USER        | Grantee can drop another user.                                               |
| DROP ANY TABLE   | Grantee can drop a table in any schema.                                      |
| BACKUP ANY TABLE | Grantee can back up any table in any schema with the export utility.         |
| SELECT ANY TABLE | Grantee can query tables, views, or snapshots in any schema.                 |
| CREATE ANY TABLE | Grantee can create tables in any schema.                                     |

## Creating Users

The DBA creates users by using the CREATE USER statement.

### **EXAMPLE:**

CREATE USER scott IDENTIFIED BY tiger;

### User System Privileges

- Once a user is created, the DBA can grant specific system privileges to a user.
  - An application developer, for example, may have the following system privileges:
    - CREATE SESSION
    - CREATE TABLE
    - CREATE SEQUENCE
    - CREATE VIEW
    - CREATE PROCEDURE
- GRANT *privilege* [, *privilege*...]  
TO *user* [, *user*|*role*, PUBLIC...];

### Typical User Privileges

| System Privilege | Operations Authorized                                                |
|------------------|----------------------------------------------------------------------|
| CREATE SESSION   | Connect to the database                                              |
| CREATE TABLE     | Create tables in the user's schema                                   |
| CREATE SEQUENCE  | Create a sequence in the user's schema                               |
| CREATE VIEW      | Create a view in the user's schema                                   |
| CREATE PROCEDURE | Create a stored procedure, function, or package in the user's schema |

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## In the syntax:

*privilege* is the system privilege to be granted

*user|role|PUBLIC* is the name of the user, the name of the role, or PUBLIC designates that every user is granted the privilege

**Note:** Current system privileges can be found in the dictionary view SESSION\_PRIVS.

## Granting System Privileges

The DBA can grant a user specific system privileges.

```
GRANT create session, create table, create sequence, create view TO scott;
```

## What is a Role?

A role is a named group of related privileges that can be granted to the user. This method makes it

easier to revoke and maintain privileges.

A user can have access to several roles, and several users can be assigned the same role. Roles are

typically created for a database application.

## **Creating and Assigning a Role**

First, the DBA must create the role. Then the DBA can assign privileges to the role and users to the role.

---

## Syntax

```
CREATEROLE role;
```

In the syntax:

*role* is the name of the role to be created

Now that the role is created, the DBA can use the GRANT statement to assign users to the role as well as

assign privileges to the role.

## **Creating and Granting Privileges to a Role**

```
CREATE ROLE manager;
```

Role created.

```
GRANT create table, create view TO manager;
```

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Grant succeeded.

GRANT manager TO DEHAAN, KOCHHAR;

Grant succeeded.

- Create a role
- Grant privileges to a role
- Grant a role to users

## Changing Your Password

- The DBA creates your user account and initializes your password.
- You can change your password by using the ALTER USER statement.

ALTER USER scott

IDENTIFIED BY lion;

User altered.

## Object Privileges

| Object Privilege | Table | View | Sequence | Procedure |
|------------------|-------|------|----------|-----------|
| ALTER            | ✓     |      | ✓        |           |
| DELETE           | ✓     | ✓    |          |           |
| EXECUTE          |       |      |          | ✓         |
| INDEX            | ✓     |      |          |           |
| INSERT           | ✓     | ✓    |          |           |
| REFERENCES       | ✓     | ✓    |          |           |
| SELECT           | ✓     | ✓    | ✓        |           |
| UPDATE           | ✓     | ✓    |          |           |

## Object Privileges

- Object privileges vary from object to object.
- An owner has all the privileges on the object.
- An owner can give specific privileges on that owner's object.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

GRANT *object\_priv* [(*ON* *columns*)*TO* { *user|role|PUBLIC*} [WITH GRANT OPTION];

**In the syntax:**

*object\_priv* is an object privilege to be granted ALL specifies all object privileges *columns* specifies the column from a table or view on which privileges are granted ON *object* is the object on which the privileges are granted TO identifies to whom the privilege is granted PUBLIC grants object privileges to all users WITH GRANT OPTION allows the grantee to grant the object privileges to other users and roles

### Granting Object Privileges

• Grant query privileges on the EMPLOYEES table. • Grant privileges to update specific columns to users and roles. GRANT select ON employees TO sue, rich; GRANT update (department\_name, location\_id) ON departments TO scott, manager; **Using the WITH GRANT OPTION and PUBLIC Keywords** • Give a user authority to pass along privileges. • Allow all users on the system to query data from Alice's DEPARTMENTS table. GRANT select, insert ON departments TO scott

---

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

WITH GRANT OPTION;

```
GRANT select  
ON alice.departments  
TO PUBLIC;
```

## How to Revoke Object Privileges

- You use the REVOKE statement to revoke privileges granted to other users.
- Privileges granted to others through the WITH GRANT OPTION clause are also revoked.

```
REVOKE {privilege [, privilege...]}|ALL  
ON object  
FROM {user[,user...]|role|PUBLIC}  
[CASCADE CONSTRAINTS];
```

### In the syntax:

CASCADE is

required to remove any referential integrity constraints made to the CONSTRAINTS object by means of the REFERENCES privilege

## Revoking Object Privileges

As user Alice, revoke the SELECT and INSERT privileges given to user Scott on the DEPARTMENTS table.

```
REVOKE select, insert  
ON departments  
FROM scott;
```

### Find the Solution for the following:

- 
1. What privilege should a user be given to log on to the Oracle Server? Is this a system or an object privilege?
- 

2. What privilege should a user be given to create tables?
- 

3. If you create a table, who can pass along privileges to other users on your table?

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

- 
4. You are the DBA. You are creating many users who require the same system privileges. What should you use to make your job easier?
- 
5. What command do you use to change your password?
- 
6. Grant another user access to your DEPARTMENTS table. Have the user grant you query access to his or her DEPARTMENTS table.
7. Query all the rows in your DEPARTMENTS table.
8. Add a new row to your DEPARTMENTS table. Team 1 should add Education as department number 500. Team 2 should add Human Resources department number 510. Query the other team's table.
9. Query the USER\_TABLES data dictionary to see information about the tables that you own.
10. Revoke the SELECT privilege on your table from the other team.
11. Remove the row you inserted into the DEPARTMENTS table in step 8 and save the changes.

**-----END-----**

**[ ANSWERS FOR ABOVE PROBLEMS – STUDENTS WILL NOT TAKE PRINTOUT OF THE BELOW PAGES ]**

**EXNO:**                   **CREATING AND MANAGING TABLES**

**AIM:**

To create tables, to describe the data types that can be used when specifying column definition, to alter table definitions, to drop, rename, and truncate tables.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

### SAMPLE TABLES: EMPLOYEE TABLE:

```
SQL> create table employeetable (employee_id number(6) NOT NULL,first_name  
varchar2(20),last_namevarchar2(25) NOT NULL,email varchar2(25) NOT  
NULL,phone_numbervarchar2(20),hire_date date NOT NULL,job_id varchar2(10) NOT  
NULL,salary number(8,2),commision number(2,2),manager_id number(6),department_id  
number(4)); Table created.
```

```
SQL> desc employeetable;
```

| Name           | Null? | Type                  |
|----------------|-------|-----------------------|
| EMPLOYEE_ID    |       | NOT NULL NUMBER(6)    |
| FIRST_NAME     |       | VARCHAR2(20)          |
| LAST_NAME      |       | VARCHAR2(25) NOT      |
| EMAIL          |       | NOT NULL VARCHAR2(25) |
| PHONE_NUMBER   |       | VARCHAR2(25)          |
| HIRE_DATE      |       | NOT NULL DATE         |
| JOB_ID         |       | NOT NULL VARCHAR2(20) |
| SALARY         |       | NUMBER(8,2)           |
| COMMISSION_PCT |       | NUMBER(2,2)           |
| MANAGER_ID     |       | NUMBER(6)             |
| DEPARTMENT_ID  |       | NUMBER(4)             |

```
SQL>select * from employeetable;
```

| EMPLOYEE_ID | FIRST_NAME | LAST_NAME |
|-------------|------------|-----------|
|-------------|------------|-----------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|
|-------|--------------|-----------|

---

| JOB_ID | SALARY | COMMISSION_PCT | MANAGER_ID | DEPARTMENT_ID |
|--------|--------|----------------|------------|---------------|
|--------|--------|----------------|------------|---------------|

---

|           |              |         |           |  |  |
|-----------|--------------|---------|-----------|--|--|
| sking     | 515.123.4567 |         | 17-JUN-87 |  |  |
| ad_pres   | 24000        |         | 90        |  |  |
| 101 neena |              | kochhar |           |  |  |
| nkochhar  | 515.123.4568 |         | 21-SEP-89 |  |  |
| ad_vp     | 17000        | 100     | 90        |  |  |

| EMPLOYEE_ID | FIRST_NAME | LAST_NAME |
|-------------|------------|-----------|
|-------------|------------|-----------|

---

| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|
|-------|--------------|-----------|

---

| JOB_ID        | SALARY       | COMMISSION_PCT | MANAGER_ID   | DEPARTMENT_ID |  |
|---------------|--------------|----------------|--------------|---------------|--|
| ldehaan       | 515.123.4569 |                | 13-JAN-93    |               |  |
| ad_vp         | 17000        | 100            | 90           |               |  |
| 103 alexandar | hunold       | ahunold        | 590.423.4567 | 03-JAN-93     |  |

| EMPLOYEE_ID | FIRST_NAME | LAST_NAME |
|-------------|------------|-----------|
|-------------|------------|-----------|

---

| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|
|-------|--------------|-----------|

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

| JOB_ID | SALARY | COMMISSION_PCT | MANAGER_ID | DEPARTMENT_ID |
|--------|--------|----------------|------------|---------------|
|--------|--------|----------------|------------|---------------|

---

|           |              |         |           |  |
|-----------|--------------|---------|-----------|--|
| it_prog   | 9000         | 102     | 60        |  |
| 104 bruce |              | ernst   |           |  |
| bernst    | 590.423.4568 |         | 21-MAY-91 |  |
| it_prog   | 6000         | 103     | 60        |  |
| 107 diana |              | lorentz |           |  |

| EMPLOYEE_ID | FIRST_NAME | LAST_NAME |
|-------------|------------|-----------|
|-------------|------------|-----------|

---

|       |              |           |
|-------|--------------|-----------|
| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|

---

| JOB_ID | SALARY | COMMISSION_PCT | MANAGER_ID | DEPARTMENT_ID |
|--------|--------|----------------|------------|---------------|
|--------|--------|----------------|------------|---------------|

---

|           |              |         |           |  |
|-----------|--------------|---------|-----------|--|
| dlorentz  | 590.423.4568 |         | 07-FEB-99 |  |
| it_prog   | 4200         | 103     | 60        |  |
| 124 kevin |              | mourgas |           |  |
| kmourgas  | 650.123.5234 |         | 16-NOV-99 |  |
| st_man    | 5800         | 100     | 50        |  |

| EMPLOYEE_ID | FIRST_NAME | LAST_NAME |
|-------------|------------|-----------|
|-------------|------------|-----------|

---

|       |              |           |
|-------|--------------|-----------|
| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|

---

| JOB_ID | SALARY | COMMISSION_PCT | MANAGER_ID | DEPARTMENT_ID |
|--------|--------|----------------|------------|---------------|
|--------|--------|----------------|------------|---------------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

----- 141 trenna rajs

trajs 650.121.8009 17-OCT-95

st\_clerk 3500 124 50

142 curtis davies

cdavies 650.121.2994 29-JAN-97

st\_clerk 3100 124 50

EMPLOYEE\_ID FIRST\_NAME LAST\_NAME

-----  
EMAIL PHONE\_NUMBER HIRE\_DATE

-----  
JOB\_ID SALARY COMMISSION\_PCT MANAGER\_ID DEPARTMENT\_ID

143 randall matos

rmatos 650.121.2874 15-MAR-98

st\_clerk 2600 124 50 144 peter vargas

pvargas 650.121.2004 09-JUL-98

EMPLOYEE\_ID FIRST\_NAME LAST\_NAME

-----  
EMAIL PHONE\_NUMBER HIRE\_DATE

-----  
JOB\_ID SALARY COMMISSION\_PCT MANAGER\_ID DEPARTMENT\_ID

st\_clerk 2500 124 50

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|           |                    |           |     |         |
|-----------|--------------------|-----------|-----|---------|
|           |                    | 149 eleni |     | zlotkey |
| ezlotkey  | 011.44.1344.429018 | 29-JAN-00 |     |         |
| sa_man    | 10500              | .2        | 100 | 80      |
| 174 ellen | abel               |           |     |         |

| EMPLOYEE_IDFIRST_NAME | LAST_NAME |
|-----------------------|-----------|
|-----------------------|-----------|

---

|       |              |           |
|-------|--------------|-----------|
| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|

---

|        |                                             |
|--------|---------------------------------------------|
| JOB_ID | SALARYCOMMISSION_PCTMANAGER_IDDEPARTMENT_ID |
|--------|---------------------------------------------|

---

|        |                    |           |     |    |
|--------|--------------------|-----------|-----|----|
| eabel  | 011.44.1644.429267 | 11-MAY-96 |     |    |
| sa_rep | 11000              | .3        | 149 | 80 |

|             |        |
|-------------|--------|
| 176jonathan | taylor |
|-------------|--------|

|         |                    |           |
|---------|--------------------|-----------|
| jtaylor | 011.44.1644.429265 | 24-MAR-98 |
|---------|--------------------|-----------|

|        |      |    |     |    |
|--------|------|----|-----|----|
| sa_rep | 8600 | .2 | 149 | 80 |
|--------|------|----|-----|----|

| EMPLOYEE_IDFIRST_NAME | LAST_NAME |
|-----------------------|-----------|
|-----------------------|-----------|

---

|       |              |           |
|-------|--------------|-----------|
| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|

---

|        |                                             |
|--------|---------------------------------------------|
| JOB_ID | SALARYCOMMISSION_PCTMANAGER_IDDEPARTMENT_ID |
|--------|---------------------------------------------|

---

|             |       |
|-------------|-------|
| 178kimberly | grant |
|-------------|-------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

kgrant 011.44.1644.429263 24-MAY-99

sa\_rep 7000 .15 149

200 jennifer] whalen

jwhalen 515.123.4444 17-SEP-87

ad\_asst 4400 101 10

EMPLOYEE\_ID FIRST\_NAME LAST\_NAME

---

EMAIL PHONE\_NUMBER HIRE\_DATE

---

JOB\_ID SALARY COMMISSION\_PCT MANAGER\_ID DEPARTMENT\_ID

---

201micheal hartstein

mhartstein 515.123.5555 17-FEB-96

mk\_man 13000 100 20

202pat fay

pfoy 606.123.6666 17-AUG-97

EMPLOYEE\_ID FIRST\_NAME LAST\_NAME

---

EMAIL PHONE\_NUMBER HIRE\_DATE

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

| JOB_ID | SALARY | COMMISSION_PCT | MANAGER_ID | DEPARTMENT_ID |
|--------|--------|----------------|------------|---------------|
|--------|--------|----------------|------------|---------------|

|             |              |         |           |  |
|-------------|--------------|---------|-----------|--|
| mk_rep      | 6000         | 201     | 20        |  |
| 205 shelley |              | higgins |           |  |
| shiggins    | 515.123.8080 |         | 07-JUN-94 |  |
| ac_mgr      | 12000        | 101     | 110       |  |
| EMPLOYEE_ID | FIRST_NAME   |         | LAST_NAME |  |

| EMAIL | PHONE_NUMBER | HIRE_DATE |
|-------|--------------|-----------|
|-------|--------------|-----------|

| JOB_ID | SALARY | COMMISSION_PCT | MANAGER_ID | DEPARTMENT_ID |
|--------|--------|----------------|------------|---------------|
|--------|--------|----------------|------------|---------------|

|            |              |           |     |  |
|------------|--------------|-----------|-----|--|
| wgeitz     | 515.123.8181 | 07-JUN-94 |     |  |
| ac_account | 8300         | 205       | 110 |  |

20 rows selected.

### DEPARTMENT TABLE:

```
SQL>createtabledepartment(department_id number(6) NOT NULL,dept_name varchar2(20)  
NOTNULL,manager_idnumber(6),location_id number(4));
```

Table created.

```
SQL> desc department
```

| Name          | Null?   | Type         |
|---------------|---------|--------------|
| DEPARTMENT_ID | NOTNULL | NUMBER(6)    |
| DEPT_NAME     | NOTNULL | VARCHAR2(20) |
| MANAGER_ID    |         | NUMBER(6)    |
| LOCATION_ID   |         | NUMBER(4)    |

```
SQL> select * from department;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

| DEPARTMENT_ID | DEPARTMENT_NAME | MANAGER_ID | LOCATION_ID |
|---------------|-----------------|------------|-------------|
| -----         |                 |            |             |
| 10            | administration  | 200        | 1700        |
| 20            | marketing       | 201        | 1800        |
| 50            | shipping        | 124        | 1500        |
| 60            | it              | 103        | 1400        |
| 80            | sales           | 149        | 2500        |
| 90            | executive       | 100        | 1700        |
| 110           | accounting      | 205        | 1700        |
| 190           | contracting     | 0          | 1700        |

8 rows selected.

### JOB\_GRADE TABLE:

SQL> createtable job\_grade(grade\_level varchar2(2), lowest\_sal number, highest\_sal number);  
Table created.

SQL> desc job\_grade

| Name        | Null? | Type        |
|-------------|-------|-------------|
| -----       |       |             |
| GRADE_LEVEL |       | VARCHAR2(2) |
| LOWEST_SAL  |       | NUMBER      |
| HIGHEST_SAL |       | NUMBER      |

SQL> select \* from locations;

| LOCATION_ID | STREET_ADDRESS | POSTAL_CODE |
|-------------|----------------|-------------|
| -----       |                |             |
| CITY        | STATE_PROVINCE | CO          |
| -----       |                |             |

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

|                          |       |    |
|--------------------------|-------|----|
| 1400 2014 jabberwocky rd | 26192 |    |
| southlake                | texas | us |

|                         |            |    |
|-------------------------|------------|----|
| 1500 2011 interior blvd | 99236      |    |
| south san francisco     | california | us |

|                      |            |    |
|----------------------|------------|----|
| 1700 2004 charade rd | 98199      |    |
| seattle              | washington | us |

| LOCATION_ID | STREET_ADDRESS | POSTAL_CODE |
|-------------|----------------|-------------|
|-------------|----------------|-------------|

---

| CITY | STATE_PROVINCE | CO |
|------|----------------|----|
|------|----------------|----|

---

|                   |            |    |
|-------------------|------------|----|
| 1800 460 bloor st | on m5s 1xb |    |
| toronto           | ontario    | ca |

|                                                       |        |    |
|-------------------------------------------------------|--------|----|
| 2500 magdalen centre, the oxford science park on 99zb |        |    |
| oxford                                                | oxford | uk |

### **LOCATION TABLE:**

```
SQL> create table location(location_id number(4) not null,street_address
varchar2(40),postal_code varchar2(12),city varchar2(30) not null,state_province
varchar2(25),country_id char(2));
Table created.
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

SQL> desc location;

| Name           | Null? Type            |
|----------------|-----------------------|
| LOCATION_ID    | NOT NULL NUMBER(4)    |
| STREET_ADDRESS | VARCHAR2(40)          |
| POSTAL_CODE    | VARCHAR2(12)          |
| CITY           | NOT NULL VARCHAR2(30) |
| STATE_PROVINCE | VARCHAR2(25)          |
| COUNTRY_ID     | CHAR(2)               |

SQL>select \* from job\_grades;

GRA LOWEST\_SAL HIGHEST\_SAL

|   | LOWEST_SAL | HIGHEST_SAL |
|---|------------|-------------|
| a | 1000       | 2999        |
| b | 3000       | 5999        |
| c | 6000       | 9999        |
| d | 10000      | 14999       |
| e | 15000      | 24999       |
| f | 25000      | 40000       |

6rowsselected.

SQL>select \* from job\_history;

EMPLOYEE\_ID START\_DATE END\_DATE JOB\_ID DEPARTMENT\_ID

|     |           |           |            |     |
|-----|-----------|-----------|------------|-----|
| 103 | 13-JAN-93 | 24-JUL-98 | it_prog    | 60  |
| 101 | 21-SEP-89 | 27-OCT-93 | ac_account | 110 |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
101 28-OCT-89 15-MAR-97 ac_m gr      110
201 17-FEB-96 19-DEC-99 mk_rep 114    20
24-MAR-98 31-DEC-99 mk_rep 122    50
01-JAN-99 31-DEC-98 st_clerk 200 17-  50
SEP-87 17-JUN-93 ad_asst 176 24-  90
MAR-98 31-DEC-98 sa_rep 176 01-  80
JAN-99 31-DEC-99 sa_man 200 01-  80
JUL-94 31-DEC-98 ac_account          90
```

10rows selected.

```
SQL> spool off;
```

### SOLUTION FOR THE EXERCISES

9. 1. Create the DEPT table based on the following table instance chart. Confirm that the table is created.

| Column name  | ID     | NAME     |
|--------------|--------|----------|
| Key Type     |        |          |
| Nulls/Unique |        |          |
| FK table     |        |          |
| FK column    |        |          |
| Data Type    | Number | Varchar2 |
| Length       | 7      | 25       |

```
create table dept(id number(7),name varchar(25));
```

Table created.

```
SQL> desc dept;
```

| Name | Null? | Type |
|------|-------|------|
|------|-------|------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

---

|      |              |
|------|--------------|
| ID   | NUMBER(7)    |
| NAME | VARCHAR2(25) |

10. Populate the DEPT table with data from the DEPARTMENT table. Include only the columns that are needed.

```
SQL> alter table dept add(manager_id number(10),location_id number(10));
```

Table altered.

```
SQL> desc dept;
```

|             |       |              |
|-------------|-------|--------------|
| Name        | Null? | Type         |
| <hr/>       |       |              |
| ID          | NAME  | NUMBER(7)    |
| MANAGER_ID  |       | VARCHAR2(25) |
| LOCATION_ID |       | NUMBER(10)   |
|             |       | NUMBER(10)   |

11. Create the EMP table based on the following instance chart. Confirm that the table is created.

| Column name  | ID     | LAST NAME | FIRST NAME | DEPT ID |
|--------------|--------|-----------|------------|---------|
| Key Type     |        |           |            |         |
| Nulls/Unique |        |           |            |         |
| FK table     |        |           |            |         |
| FK column    |        |           |            |         |
| Data Type    | Number | Varchar2  | Varchar2   | Number  |
| Length       | 7      | 25        | 25         | 7       |

```
SQL> create table empdb(id number(7),firstname varchar(25),lastname varchar(25),dept_id number(25));
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Table created.

SQL> desc empdb

| Name      | Null? | Type         |
|-----------|-------|--------------|
| ID        |       | NUMBER(7)    |
| FIRSTNAME |       | VARCHAR2(25) |
| LASTNAME  |       | VARCHAR2(25) |
| DEPT_ID   |       | NUMBER(25)   |

12. Modify the EMP table to allow for longer employee last names. Confirm the modification.(Hint: Increase the size to 50)

SQL> alter table empdb modify(lastname varchar(50));

Table altered.

SQL> desc empdb;

| Name      | Null? | Type         |
|-----------|-------|--------------|
| ID        |       | NUMBER(7)    |
| FIRSTNAME |       | VARCHAR2(25) |
| LASTNAME  |       | VARCHAR2(50) |
| DEPT_ID   |       | NUMBER(25)   |

13. Create the EMPLOYEES2 table based on the structure of EMPLOYEES table. Include Only the Employee\_id, First\_name, Last\_name, Salary and Dept\_id coloumns. Name the columns Id, First\_name, Last\_name, salary and Dept\_id respectively.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> create table employee2(id number(10),firstname varchar(10),lastname varchar(10),salary number(8,2),deptid number(10));
```

Table created.

```
SQL> desc employee2;
```

| Name      | Null? | Type         |
|-----------|-------|--------------|
| ID        |       | NUMBER(10)   |
| FIRSTNAME |       | VARCHAR2(10) |
| LASTNAME  |       | VARCHAR2(10) |
| SALARY    |       | NUMBER(8,2)  |
| DEPTID    |       | NUMBER(10)   |

14. Drop the EMP table.

```
SQL> drop table empdb;
```

Table dropped.

15. Rename the EMPLOYEES2 table as EMP.

```
SQL> rename employee2 to employee3;
```

Table renamed.

16. Add a comment on DEPT and EMP tables. Confirm the modification by describing the table.

```
SQL> comment on table dept is'this is department database.';
```

Comment created.

```
SQL> select * from user_tab_comments;
```

| TABLE_NAME | TABLE_TYPE |
|------------|------------|
| COMMENTS   |            |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

STUDENT                    TABLE  
EMPLOYEE                 TABLE  
EMPLOYEE\_DETAIL         TABLE  
TABLE\_NAME                TABLE\_TYPE

---

COMMENTS

-----EMPLOYEES            TABLE

EMP                        TABLE

this is a employee database..

BIN\$JYmxGClpS7KBH/ciI85irw==\\$0 TABLE

TABLE\_NAME                TABLE\_TYPE

---

COMMENTS

---

DEPT                      TABLE

this is department database..

EMPLOYEE3                TABLE

rows selected.

17. Drop the First\_name column from the EMP table and confirm it.  
SQL> alter table employee3 drop column firstname;

Table altered.

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

SQL> desc employee3;

| Name     | Null? | Type         |
|----------|-------|--------------|
| ID       |       | NUMBER(10)   |
| LASTNAME |       | VARCHAR2(10) |
| SALARY   |       | NUMBER(8,2)  |
| DEPTID   |       | NUMBER(10)   |

18. In the DEPT table mark the column Dept\_id as UNUSED and confirm it.  
SQL> alter table employee3 set unused(deptid);

Table altered.

SQL> desc employee3;

| Name     | Null? | Type         |
|----------|-------|--------------|
| ID       |       | NUMBER(10)   |
| LASTNAME |       | VARCHAR2(10) |
| SALARY   |       | NUMBER(8,2)  |

11. Drop all the UNUSED columns from the EMP table and Confirm the modification

SQL> drop table employee3;

Table dropped.

**EXNO:2** **MANIPULATING DATA**

**AIM:**

To describe each DML statement, to insert rows into tables, to update rows into tables, to delete rows from tables, to execute control transactions,

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## SOLUTION FOR THE EXERCISES

10. Create MY\_EMPLOYEE table with the following structure

| NAME       | NULL?    | TYPE        |
|------------|----------|-------------|
| ID         | Not null | Number(4)   |
| Last_name  |          | Varchar(25) |
| First_name |          | Varchar(25) |
| Userid     |          | Varchar(25) |
| Salary     |          | Number(9,2) |

```
create table emp(id number(4) not null, firstname varchar(10), lastname varchar(10), userid number(10), salary number(9,2));
```

Table created.

```
SQL> desc emp;
```

| Name      | Null? Type       |
|-----------|------------------|
| ID        | NOTNULLNUMBER(4) |
| FIRSTNAME | VARCHAR2(10)     |
| LASTNAME  | VARCHAR2(10)     |
| USERID    | NUMBER(10)       |
| SALARY    | NUMBER(9,2)      |

11. Add the first and second rows data to MY\_EMPLOYEE table from the following sample data.

| ID | Last_name | First_name | Userid   | salary |
|----|-----------|------------|----------|--------|
| 1  | Patel     | Ralph      | rpatel   | 895    |
| 2  | Dancs     | Betty      | bdancs   | 860    |
| 3  | Biri      | Ben        | bbiri    | 1100   |
| 4  | Newman    | Chad       | Cnewman  | 750    |
| 5  | Ropebur   | Audrey     | aropebur | 1550   |

```
SQL> insert into my_employee values(1,'patel','ralph','rpatel',895);
```

1 row created.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> insert into my_employee values(2,'dancs','betty','bdancs',860);
```

1 row created.

```
SQL> select * from my_employee
```

| ID | LAST_NAME | FIRST_NAME | USER_ID | SALARY |
|----|-----------|------------|---------|--------|
| 1  | patel     | ralph      | rpatel  | 895    |
| 2  | dancs     | betty      | 2dancs  | 860    |
| 3  | bdancs    |            | bdancs  |        |

12. Display the table with values.

```
SQL> select * from my_employee;
```

| ID | LAST_NAME | FIRST_NAME | USER_ID | SALARY |
|----|-----------|------------|---------|--------|
| 1  | patel     | ralph      | rpatel  | 895    |
| 2  | dancs     | betty      | 2dancs  | 860    |

13. Populate the next two rows of data from the sample data. Concatenate the first letter of the first\_name with the first seven characters of the last\_name to produce Userid.

```
SQL> insert into my_employee  
values(&id,'&last_name','&first_name',lower(substr('&first_name',1,1)||substr('&last_name',1,7))  
,&salary);
```

Enter value for id: 3

Enter value for last\_name: biri

Enter value for first\_name: ben

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Enter value for first\_name: ben Enter value for last\_name: biri Enter value for salary: 1100 old 1:

insert into my\_employee

values(&id,'&last\_name','&first\_name',lower(substr('&first\_name',1,1)||substr('&last\_name',1,7)),&salary) new 1: insert into my\_employee

values(3,'biri','ben',lower(substr('ben',1,1)||substr('biri',1,7)),1100)

1 row created.

SQL> /

Enter value for id: 4

Enter value for last\_name: newman

Enter value for first\_name: chad

Enter value for first\_name: chad

Enter value for last\_name: newman

Enter value for salary: 750

old 1: insert into my\_employee

values(&id,'&last\_name','&first\_name',lower(substr('&first\_name',1,1)||substr('&last\_name',1,7)),&salary) new 1: insert into my\_employee

values(4,'newman','chad',lower(substr('chad',1,1)||substr('newman',1,7)),750)

1 row created.

SQL> select \* from my\_employee;

| ID    | LAST_NAME | FIRST_NAME | USER_ID | SALARY |
|-------|-----------|------------|---------|--------|
| ----- |           |            |         |        |
| ralph | rpatel    | 895        |         | 1patel |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|         |       |        |     |        |     |       |
|---------|-------|--------|-----|--------|-----|-------|
| 2 dancs | betty | bdancs | 860 | 3 biri | ben | bbiri |
| 1100    |       |        |     |        |     |       |

| LAST_NAME | FIRST_NAME | USER_ID | SALARY |
|-----------|------------|---------|--------|
|-----------|------------|---------|--------|

---

|          |      |         |     |
|----------|------|---------|-----|
| 4 newman | chad | cnewman | 750 |
|----------|------|---------|-----|

14. Make the data additions permanent.

SQL> commit;

Commit complete.

Change the last name of employee 3 to Drexler

SQL> update my\_employee set last\_name='drexler'where id=3;

1 row updated.

SQL> select \* from my\_employee;

| ID | LAST_NAME | FIRST_NAME | USER_ID | SALARY |
|----|-----------|------------|---------|--------|
|----|-----------|------------|---------|--------|

---

|         |       |        |     |
|---------|-------|--------|-----|
| 1 patel | ralph | rpatel | 895 |
|---------|-------|--------|-----|

|         |       |        |     |
|---------|-------|--------|-----|
| 2 dancs | betty | bdancs | 860 |
|---------|-------|--------|-----|

|           |     |       |      |
|-----------|-----|-------|------|
| 3 drexler | ben | bbiri | 1100 |
|-----------|-----|-------|------|

| LAST_NAME | FIRST_NAME | USER_ID | SALARY |
|-----------|------------|---------|--------|
|-----------|------------|---------|--------|

---

|          |      |         |     |
|----------|------|---------|-----|
| 4 newman | chad | cnewman | 750 |
|----------|------|---------|-----|

7.Change the salary to 1000 for all the employees with a salary less than 900.

Update my\_employee set salary=1000 where salary<900;

SQL> select \* from my\_employee;

| ID | LAST_NAME | FIRST_NAME | USER_ID | SALARY |
|----|-----------|------------|---------|--------|
|----|-----------|------------|---------|--------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
-----          1 patel      ralph
rpatel 895
3 dredler    ben        bbiri   1000
4 newman     chad      cnewman 750
```

8.Verify the changes to the table

```
SQL> select * from my_employee;
```

```
ID LAST_NAME      FIRST_NAME USER_ID SALARY
```

```
-----  
1 patel      ralph      rpatel    895  
3 dredler    ben        bbiri    1100  
4 newman     chad      cnewman   750
```

```
ID LAST_NAME      FIRST_NAME USER_ID      SALARY
```

```
-----  
5 ropebur    audrey     aropebur   1550
```

9.Delete Betty dances from MY\_EMPLOYEE table.

```
SQL> delete from my_employee where last_name='dances';
```

1 row deleted.

10.Confirm the changes.

```
SQL> select * from my_employee;
```

```
ID LAST_NAME      FIRST_NAME USER_ID      SALARY
```

```
-----  
1 patel      ralph      rpatel    895  
3 dredler    ben        bbiri    1100
```

```
4 newman     chad      cnewman   750
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

Commit the changes. Commit; 12) Populate the last row of sample data as by

```
Q:4 SQL> insert into my_employee  
values(&id,'&last_name','&first_name',lower(substr('&first_name',1,1)||  
substr('&last_name',1,7)),&salary);
```

Enter value for id: 5

Enter value for last\_name: Ropebur

Enter value for first\_name: Audrey

Enter value for first\_name: Audrey

Enter value for last\_name: Ropebur

Enter value for salary: 1550

```
old 1: insert into my_employee  
values(&id,'&last_name','&first_name',lower(substr('&first_name',1,  
new 1: insert into my_employee  
values(5,'Ropebur','Audrey',lower(substr('Audrey',1,1)||substr('Ropebur',1,7)),  
1 row created.
```

13) Confirm the table.

```
SQL> select * from my_employee;
```

| ID | LAST_NAME | FIRST_NAME | USERID   | SALARY |
|----|-----------|------------|----------|--------|
| 1  | Patel     | Ralph      | rpatel   | 1000   |
| 3  | drexler   | Ben        | bbiri    | 1100   |
| 4  | Newman    | Chad       | cnewman  | 1000   |
| 5  | Ropebur   | Audrey     | aropebur | 1550   |

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

14) Mark an intermediate point in the processing of the transaction.

```
SQL> savepoint q14;
```

Savepoint created.

15) Empty the fourth row of the emp table

```
SQL> truncate table my_employee;
```

Table truncated.

16) Confirm the table is empty.

```
SQL> select * from my_employee;
```

no rows selected

17) Discard the most recent DELETE operation without discarding the earlier INSERT operation.

```
Rollback Q14;
```

```
SQL> rollback;
```

18) Confirm that the new row is still intact.

```
SQL> select * from my_employee;
```

| IDLAST_NAME | FIRST_NAME | USERID   | SALARY |
|-------------|------------|----------|--------|
| 1Patel      | Ralph      | rpatel   | 1000   |
| 3drexler    | Ben        | bbiri    | 1100   |
| 4Newman     | Chad       | cnewman  | 1000   |
| 5Ropebur    | Audrey     | aropebur | 1550   |

**EXNO:3**

**INCLUDING CONSTRAINTS**

**AIM:**

To describe the constraints, and to create and maintain constraints

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **SOLUTION FOR THE EXERCISES**

5. Add a table-level PRIMARY KEY constraint to the EMP table on the ID column. The constraint should be named at creation. Name the constraint my\_emp\_id\_pk.

```
SQL> alter table dept add constraint my_dept_id_pk primary key(id);
```

Table altered.

6. Create a PRIMARY KEY constraint to the DEPT table using the ID column. The constraint should be named at creation. Name the constraint my\_dept\_id\_pk.

```
Alter table dept add constraint my_dept_id_pk primary key(id);
```

```
SQL> alter table emp add(dept_id number(7));
```

Table altered.

7. Add a column DEPT\_ID to the EMP table. Add a foreign key reference on the EMP table that ensures that the employee is not assigned to nonexistent department. Name the constraint my\_emp\_dept\_id\_fk.

```
SQL> alter table emp add constraint my_emp_dept_id_fk foreign key(dept_id) references dept(id);
```

Table altered.

8. Modify the EMP table. Add a COMMISSION column of NUMBER data type, precision 2, scale 2. Add a constraint to the commission column that ensures that a commission value is greater than zero.

```
SQL> alter table emp add commission float constraints ck check(commission>=0);
```

Table altered.

5. Confirm that the constraints were added by querying the USER\_CONSTRAINTS view.

```
SQL> select constraint_name,constraint_type from user_constraints where table_name  
in('emp','dept');  
No rows selected.
```

**EXNO:4**

**WRITING BASIC SQL SELECT STATEMENTS**

**AIM:**

To list the capabilities of SQL SELECT statement and to execute a basic SELECT statement.

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## SOLUTIONS FOR THE EXERCISES:

1. Show the structure of departments thetable. Select all the data from it.

SQL> desc department;

| Name | Null? | Type |
|------|-------|------|
|------|-------|------|

|                 |          |              |
|-----------------|----------|--------------|
| DEPARTMENT_ID   | NOT NULL | NUMBER(4)    |
| DEPARTMENT_NAME |          | VARCHAR2(30) |
| MANAGER_ID      |          | NUMBER(6)    |
| LOCATION_ID     |          | NUMBER(4)    |

SQL> select \* from department;

| DEPARTMENT_ID | DEPARTMENT_NAME | MANAGER_ID | LOCATION_ID |
|---------------|-----------------|------------|-------------|
|---------------|-----------------|------------|-------------|

|     |                |     |      |
|-----|----------------|-----|------|
| 10  | administration | 200 | 1700 |
| 20  | marketing      | 201 | 1800 |
| 50  | shipping       | 124 | 1500 |
| 60  | it             | 103 | 1400 |
| 80  | sales          | 149 | 2500 |
| 90  | executive      | 100 | 1700 |
| 110 | accounting     | 205 | 1700 |
| 190 | contracting    | 0   | 1700 |

8 rows selected.

2. Show the structure of the employees the table. Create a query to display the last name, job code, hire date, and employee number for each employee, with employee number appearing first

| DEPARTMENT_ID | DEPARTMENT_NAME | MANAGER_ID | LOCATION_ID |
|---------------|-----------------|------------|-------------|
|---------------|-----------------|------------|-------------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|                     |     |      |
|---------------------|-----|------|
| 10 admin            | 200 | 1700 |
| 20 Marketing        | 201 | 1800 |
| 50 shipping         | 124 | 1500 |
| 60 IT               | 103 | 1400 |
| 80 sales            | 149 | 2500 |
| 90 executive        | 100 | 1700 |
| 110 accounting      | 205 | 1700 |
| 190 contracting     |     | 1700 |
| 70 public relations | 100 | 1700 |
| 70 public relations |     |      |

3. Provide an alias STARTDATE for the hire date

```
SQL> select employee_id ,last_name,job_id,hire_date start_date from employeetable;
```

| EMPLOYEE_ID          | LAST_NAME   | JOB_ID   | START_DATE  |
|----------------------|-------------|----------|-------------|
| 17-JUN-87            | 101 kochhar | ad_vp    | 21-SEP-89   |
| 102 dehaan           |             | ad_vp    | 13-JAN-93   |
| 03-JAN-93<br>it_prog | 104 ernst   | it_prog  | 21-MAY-91   |
|                      | 07-FEB-99   |          | 107 lorentz |
| 124 mourgas          |             | st_man   | 16-NOV-99   |
| 17-OCT-95            |             |          | 141 rajs    |
| 142 davies           |             | st_clerk | 29-JAN-97   |
| 143 matos            |             | st_clerk | 15-MAR-98   |
| 09-JUL-98            |             |          | 144 vargas  |
|                      |             |          | st_clerk    |

| EMPLOYEE_ID | LAST_NAME | JOB_ID    | START_DATE  |
|-------------|-----------|-----------|-------------|
| 29-JAN-00   | 174 abel  | sa_rep    | 149 zlotkey |
|             |           |           | 11-MAY-96   |
| 176 taylor  | sa_rep    | 24-MAR-98 |             |
| 178 grant   | sa_rep    | 24-MAY-99 |             |
| 17-SEP-87   |           |           | 200 whalen  |
|             |           |           | ad_asst     |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|                   |            |           |         |        |
|-------------------|------------|-----------|---------|--------|
| 201 hartstein     | mk_man     | 17-FEB-96 | 202 fay | mk_rep |
| 17-AUG-97         |            |           |         |        |
| 205 higgins       | ac_mgr     | 07-JUN-94 |         |        |
| 206 gietz         | ac_account | 07-JUN-94 |         |        |
| 20 rows selected. |            |           |         |        |

4. Create a query to display unique job codes from the employee table.

SQL> select distinct job\_id from employeetable;

JOB\_ID

-----  
sa\_rep

mk\_rep

ad\_pres

ad\_vp

it\_prog

st\_man

ac\_account

sa\_man

ad\_asst

ac\_mgr

st\_clerk

JOB\_ID

-----  
mk\_man

12 rows selected.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

5. Display the last name concatenated with the job ID , separated by a comma and space, and name the column EMPLOYEE and TITLE.

```
SQL> select last_name||','||job_id"employee and title" from employeetable;  
employee and title
```

```
-----  
king,ad_pres
```

```
kochhar,ad_vp
```

```
dehaan,ad_vp
```

```
hunold,it_prog
```

```
ernst,it_prog
```

```
lorentz,it_prog
```

```
mourgas,st_man
```

```
rajs,st_clerk
```

```
davies,st_clerk
```

```
matos,st_clerk
```

```
vargas,st_clerk
```

```
employee and title
```

```
-----  
zlotkey,sa_man
```

```
abel,sa_rep
```

```
taylor,sa_rep
```

```
grant,sa_rep
```

```
whalen,ad_asst
```

```
hartstein,mk_man
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

fay,mk\_rep

higgins,ac\_mgr

gietz,ac\_account

20 rows selected.

6.Create a query to display all the data from the employees table. Separate each column by a comma. Name the column THE\_OUTPUT.

SQL> select

```
employee_id||','||first_name||','||last_name||','||email||','||phone_number||','||job_id||','||manager_id||','||  
hire_date||','||salary||','||commission_pct||','||department_id the_output from employeetable;
```

THE\_OUTPUT

```
-----100,stevan,king,sking,515.123.4567,ad_pres,,1  
7-JUN-87,24000,,90  
101,neena,kochhar,nkochhar,515.123.4568,ad_vp,100,21-SEP-89,17000,,90  
102,lex,dehaan,ldehaan,515.123.4569,ad_vp,100,13-JAN-93,17000,,90  
103,alexandar,hunold,ahunold,590.423.4567,it_prog,102,03-JAN-93,9000,,60  
104,bruce,ernst,bernst,590.423.4568,it_prog,103,21-MAY-91,6000,,60  
107,diana,lorentz,dlorentz,590.423.4568,it_prog,103,07-FEB-99,4200,,60  
124,kevin,mourgas,kmourgas,650.123.5234,st_man,100,16-NOV-99,5800,,50  
141,trenna,rajs,trajs,650.121.8009,st_clerk,124,17-OCT-95,3500,,50  
142,curtis,davies,cdavies,650.121.2994,st_clerk,124,29-JAN-97,3100,,50  
143,randall,matos,rmatos,650.121.2874,st_clerk,124,15-MAR-98,2600,,50  
144,peter,vargas,pvargas,650.121.2004,st_clerk,124,09-JUL-98,2500,,50
```

THE\_OUTPUT

```
-----149,eleni,zlotkey,ezlotkey,011.44.1344.429018,sa_man,100,29-JAN-00,10500,.2,80
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

174,ellen,abel,eabel,011.44.1644.429267,sa\_rep,149,11-MAY-96,11000,.3,80  
176,jonathan,taylor,jtaylor,011.44.1644.429265,sa\_rep,149,24-MAR-98,8600,.2,80  
178,kimberly,grant,kgrant,011.44.1644.429263,sa\_rep,149,24-MAY-99,7000,.15,  
200,jennifer],whalen,jwhalen,515.123.4444,ad\_asst,101,17-SEP-87,4400,,10  
201,micheal,hartstein,mhartstein,515.123.5555,mk\_man,100,17-FEB-96,13000,,20  
202,pat,fay,pfay,606.123.6666,mk\_rep,201,17-AUG-97,6000,,20  
205,shelley,higgins,shiggins,515.123.8080,ac\_mgr,101,07-JUN-94,12000,,110  
206,william,gietz,wgeitz,515.123.8181,ac\_account,205,07-JUN-94,8300,,110

20 rows selected.

**EXNO:5**

**RESTRICTING AND SORTING DATA**

**AIM:**

To limit the rows retrieved by the queries, and to sort the rows retrieved by the queries.

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

### **SOLUTIONS FOR THE EXERCISES:**

14. Create a query to display the last name and salary of employees earning more than 12000.  
SQL> select last\_name,salary from employeetable where salary>12000;

| LAST_NAME | SALARY |
|-----------|--------|
|-----------|--------|

|           |       |
|-----------|-------|
| king      | 24000 |
| kochhar   | 17000 |
| dehaan    | 17000 |
| hartstein | 13000 |

15. Create a query to display the employee last name and department number for employee number 176.

SQL> select last\_name,department\_id from employeetable where employee\_id=176;

| LAST_NAME | DEPARTMENT_ID |
|-----------|---------------|
|-----------|---------------|

|        |    |
|--------|----|
| taylor | 80 |
|--------|----|

16. Create a query to display the last name and salary of employees whose salary is not in the range of 5000 and 12000. (hints: not between )

SQL> select last\_name,salary from employeetable where salary not between 5000 and 12000;

| LAST_NAME | SALARY |
|-----------|--------|
|-----------|--------|

|         |       |
|---------|-------|
| king    | 24000 |
| kochhar | 17000 |
| dehaan  | 17000 |
| lorentz | 4200  |
| rajs    | 3500  |
| davies  | 3100  |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|           |       |
|-----------|-------|
| matos     | 2600  |
| vargas    | 2500  |
| whalen    | 4400  |
| hartstein | 13000 |

10 rows selected.

17. Display the employee last name, job ID, and start date of employees hired between February 20,1998 and May 1,1998.order the query in ascending order by start date.  
SQL> select last\_name,job\_id,hire\_date from employeetable where hire\_date between '20-feb-98' and '1-may-98';

| LAST_NAME | JOB_ID   | HIRE_DATE |
|-----------|----------|-----------|
| matos     | st_clerk | 15-MAR-98 |
| taylor    | sa_rep   | 24-MAR-98 |

18. Display the last name and department number of all employees in departments 20 and 50 in alphabetical order by name.  
SQL> select last\_name,department\_id from employeetable where department\_id in(20,50) order by last\_name;

| LAST_NAME | DEPARTMENT_ID |
|-----------|---------------|
| davies    | 50            |
| fay       | 20            |
| hartstein | 20            |
| matos     | 50            |

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

mourgas 50

rajs 50

vargas 50

7 rows selected.

19. Display the last name and salary of all employees who earn between 5000 and 12000 and are in departments 20 and 50 in alphabetical order by name. Label the columns EMPLOYEE, MONTHLY SALARY respectively.

SQL> select last\_name,department\_id from employeetable where department\_id in(20,50) order by last\_name;

SQL> select last\_name employee,salary monthly\_salary from employeetable where salary between 5000 and 12000 and department\_id in(20,50) order by last\_name;

EMPLOYEE                   MONTHLY\_SALARY

-----  
fay 6000

mourgas 5800

20. Display the last name and hire date of every employee who was hired in 1994.

SQL> select last\_name,hire\_date from employeetable where hire\_date between '1-jan-94' and '31-dec-94';

LAST\_NAME                   HIRE\_DATE

-----  
higgins 07-JUN-94

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

gietz 07-JUN-94

8.Display the last name and job title of all employees who do not have a manager

SQL> select last\_name,job\_id from employeetable where manager\_id is NULL;

LAST\_NAME JOB\_ID

-----  
king ad\_pres

9.Display the last name, salary, and commission for all employees who earn commissions. Sort data in descending order of salary and commissions.

SQL> select last\_name,salary,commission\_pct from employeetable where commission\_pct is not null;

LAST\_NAME SALARY COMMISSION\_PCT

-----  
zlotkey 10500 .2  
abel 11000 .3  
taylor 8600 .2  
grant 7000 .15

10.Display the last name of all employees where the third letter of the name is *a*.

SQL> select last\_name from employeetable where last\_name like '\_\_a%';

LAST\_NAME

-----  
grant

whalen

11.Display the last name of all employees who have an *a* and an *e* in their last name

SQL> select last\_name from employeetable where last\_name like '%a%e%';

LAST\_NAME

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

-----  
davies

abel

whalen

hartstein

12. Display the last name and job and salary for all employees whose job is sales representative or stock clerk and whose salary is not equal to 2500 ,3500 or 7000

SQL> select last\_name,job\_id,salary from employeetable where job\_id in('sa\_rep','st\_clerk') and salary not in(2500,3500,7000);

| LAST_NAME | JOB_ID   | SALARY |
|-----------|----------|--------|
| davies    | st_clerk | 3100   |
| matos     | st_clerk | 2600   |
| abel      | sa_rep   | 11000  |
| taylor    | sa_rep   | 8600   |

19. Display the last name, salary, and commission for all employees whose commission amount is 20%.

SQL> select last\_name ,salary,commission\_pctfromemployeetablewherecommission\_pct=.2;

| LAST_NAME | SALARY | COMMISSION_PCT |
|-----------|--------|----------------|
| zlotkey   | 10500  | .2             |
| taylor    | 8600   | .2             |

**EXNO:6** **SINGLE ROW FUNCTIONS**

**AIM:**

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

To describe the various types of functions available in SQL, and to use character, number and date functions in SELECT statement and to describe the use of conversion functions.

### SOLUTION FOR THE EXERCISES:

- 1) Write a query to display the current date. Label the column Date.

```
SQL> select sysdate "date" from dual;
```

```
date
```

```
-----
```

```
13-FEB-12
```

```
1 row selected.
```

- 2) The HR department needs a report to display the employee number, last name, salary, and increased by 15.5% (expressed as a whole number) for each employee. Label the column New Salary.

```
SQL> select employee_id,last_name,salary,round(salary*1.15,0)"new salary" from employees;
```

| EMPLOYEE_ID | LAST_NAME | SALARY | new salary |
|-------------|-----------|--------|------------|
|-------------|-----------|--------|------------|

```
-----
```

|         |      |     |       |       |
|---------|------|-----|-------|-------|
| 100     | King | 101 | 24000 | 27600 |
| Kochar  |      | 102 | 17000 | 19550 |
| Dehaan  |      | 103 | 17000 | 19550 |
| Hunold  |      | 104 | 9000  | 10350 |
| Ernst   |      | 107 | 6000  | 6900  |
| Lorentz |      | 124 | 4200  | 4830  |
| Mourgos |      | 141 | 5800  | 6670  |
| Rajs    |      | 142 | 3500  | 4025  |
| Davies  |      | 143 | 3100  | 3565  |
| Matos   |      |     | 2600  | 2990  |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|              |       |       |
|--------------|-------|-------|
| 144 Vargas   | 2500  | 2875  |
| 149 Zlotkey  | 10500 | 12075 |
| 174 Abel     | 11000 | 12650 |
| 176 taylor   | 8600  | 9890  |
| 178 grant    | 7000  | 8050  |
| 200 whalen   | 4400  | 5060  |
| 201 harstein | 13000 | 14950 |
| 202 fay      | 6000  | 6900  |
| 205 higgins  | 12000 | 13800 |
| 206 Gietz    | 8300  | 9545  |
| 113 popp     | 6900  | 7935  |

21 rows selected.

3) Modify your query lab\_03\_02.sql to add a column that subtracts the old salary from the new salary.

Label the column Increase.

```
SQL> select employee_id,last_name,salary,round(salary*1.15,0)"new  
salary",round(salary*1.15,0)-salary "Increase" from employees;
```

| EMPLOYEE_ID | LAST_NAME | SALARY | new salary | Increase |
|-------------|-----------|--------|------------|----------|
|-------------|-----------|--------|------------|----------|

|             |       |       |      |
|-------------|-------|-------|------|
| 100 King    | 24000 | 27600 | 3600 |
| 101 Kochhar | 17000 | 19550 | 2550 |
| 102 Dehaan  | 17000 | 19550 | 2550 |
| 103 Hunold  | 9000  | 10350 | 1350 |
| 104 Ernst   | 6000  | 6900  | 900  |
| 107 Lorentz | 4200  | 4830  | 630  |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|              |       |       |      |
|--------------|-------|-------|------|
| 124 Mourgos  | 5800  | 6670  | 870  |
| 141 Rajs     | 3500  | 4025  | 525  |
| 142 Davies   | 3100  | 3565  | 465  |
| 143 Matos    | 2600  | 2990  | 390  |
| 144 Vargas   | 2500  | 2875  | 375  |
| 149 Zlotkey  | 10500 | 12075 | 1575 |
| 174 Abel     | 11000 | 12650 | 1650 |
| 176 taylor   | 8600  | 9890  | 1290 |
| 178 grant    | 7000  | 8050  | 1050 |
| 200 whalen   | 4400  | 5060  | 660  |
| 201 harstein | 13000 | 14950 | 1950 |
| 202 fay      | 6000  | 6900  | 900  |
| 205 higgins  | 12000 | 13800 | 1800 |
| 206 Gietz    | 8300  | 9545  | 1245 |
| 113 popp     | 6900  | 7935  | 1035 |

21rows selected.

4)Write a query that displays the last name (with the first letter uppercase and all other letters lowercase) and the length of the last name for all employees whose name starts with the letters J, A,orM. Give each column an appropriate label. Sort the results by the employees' last names

SQL>select initcap(last\_name)"Name",length(last\_name)"Length" from employees where last\_name like 'j%' or last\_name like 'M%' or last\_name like 'A%' order by last\_name;

| Name | Length |
|------|--------|
|------|--------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

---

|         |   |
|---------|---|
| Abel    | 4 |
| Matos   | 5 |
| Mourgos | 7 |

3 rows selected.

5)The HR department wants to find the length of employment for each employee. For each employee,display the last name and calculate the number of months between today and the date on which the employee was hired. Label the column MONTHS\_WORKED. Order your results by the number of months employed. Round the number of months up to the closest whole number.

```
SQL> select last_name,round(MONTHS_BETWEEN(SYSDATE,hire_date))  
MONTHS_WORKED from employees order by MONTHS_BETWEEN(SYSDATE,hire_date);
```

| LAST_NAME | MONTHS_WORKED |
|-----------|---------------|
|-----------|---------------|

---

|          |     |
|----------|-----|
| popp     | 0   |
| Zlotkey  | 145 |
| Mourgos  | 147 |
| grant    | 153 |
| Lorentz  | 156 |
| Vargas   | 163 |
| taylor   | 167 |
| Matos    | 167 |
| fay      | 174 |
| Davies   | 181 |
| Abel     | 189 |
| harstein | 192 |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|               |        |     |
|---------------|--------|-----|
| Rajs          | Gietz  | 196 |
| higgins       | Dehaan | 212 |
| Ernst         | Hunold | 212 |
| Kochar        | whalen | 229 |
| King          |        | 249 |
| rowsselected. |        | 265 |
|               |        | 269 |
|               |        | 293 |
|               |        | 296 |

7) Create a query to display the last name and salary for all employees. Format the salary to be 15 characters long, left-padded with the \$ symbol. Label the column SALARY.

```
SQL> select last_name,lpad(salary,15,'$')salary from employees;
```

| LAST_NAME | SALARY                      |
|-----------|-----------------------------|
| King      | \$\$\$\$\$\$\$\$\$\$\$24000 |
| Kochar    | \$\$\$\$\$\$\$\$\$\$\$17000 |
| Dehaan    | \$\$\$\$\$\$\$\$\$\$\$17000 |
| Hunold    | \$\$\$\$\$\$\$\$\$\$\$9000  |
| Ernst     | \$\$\$\$\$\$\$\$\$\$\$6000  |
| Lorentz   | \$\$\$\$\$\$\$\$\$\$\$4200  |
| Mourgos   | \$\$\$\$\$\$\$\$\$\$\$5800  |
| Rajs      | \$\$\$\$\$\$\$\$\$\$\$3500  |
| Davies    | \$\$\$\$\$\$\$\$\$\$\$3100  |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|          |                           |
|----------|---------------------------|
| Matos    | \$\$\$\$\$\$\$\$\$\$2600  |
| Vargas   | \$\$\$\$\$\$\$\$\$\$2500  |
| Zlotkey  | \$\$\$\$\$\$\$\$\$\$10500 |
| Abel     | \$\$\$\$\$\$\$\$\$\$11000 |
| taylor   | \$\$\$\$\$\$\$\$\$\$8600  |
| grant    | \$\$\$\$\$\$\$\$\$\$7000  |
| whalen   | \$\$\$\$\$\$\$\$\$\$4400  |
| harstein | \$\$\$\$\$\$\$\$\$\$13000 |
| fay      | \$\$\$\$\$\$\$\$\$\$6000  |
| higgins  | \$\$\$\$\$\$\$\$\$\$12000 |
| Gietz    | \$\$\$\$\$\$\$\$\$\$8300  |
| popp     | \$\$\$\$\$\$\$\$\$\$6900  |

21 rows selected.

8) Display each employee's last name, hire date, and salary review date, which is the first Monday after six months of service. Label the column REVIEW. Format the dates to appear in the format similar to

```
SQL> select last_name, hire_date, to_char(next_day(add_months(hire_date, 6),  
'monday'), 'fmday"the"ddspth"of" month, YYYY') review from employees;
```

| LAST_NAME | HIRE_DATE | REVIEW |
|-----------|-----------|--------|
|-----------|-----------|--------|

---

|         |           |                                           |
|---------|-----------|-------------------------------------------|
| King    | 17-JUN-87 | monday the twenty-first of december, 1987 |
| Kochhar | 21-SEP-89 | monday the twenty-sixth of march, 1990    |
| Dehaan  | 13-JAN-93 | monday the nineteenth of july, 1993       |
| Hunold  | 03-JAN-90 | monday the ninth of july, 1990            |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|                   |                                                  |
|-------------------|--------------------------------------------------|
| Ernst             | 21-MAY-91 mondaythetwenty-fifthof november,1991  |
| Lorentz           | 07-FEB-99 mondaytheninthof august,1999           |
| Mourgos           | 16-NOV-99 mondaythetwenty-secondof may,2000      |
| Rajs              | 17-OCT-95 mondaythetwenty-secondof april,1996    |
| Davies            | 29-JAN-97 mondaythefourthof august,1997          |
| Matos             | 15-MAR-98 mondaythetwenty-firstof september,1998 |
| Vargas            | 09-JUL-98 mondaytheeleventhof january,1999       |
| Zlotkey           | 29-JAN-00 mondaythethirty-firstof july,2000      |
| 21 rows selected. |                                                  |

9) Display the last name, hire date, and day of the week on which the employee started. Label the column DAY. Order the results by the day of the week, starting with Monday.

```
SQL> select last_name,hire_date,to_char(hire_date,'DAY')DAY from employees order by to_char(hire_date-1,'d');
```

| LAST_NAME | HIRE_DATE DAY     |
|-----------|-------------------|
| grant     | 24-MAY-99 MONDAY  |
| popp      | 30-JAN-12 MONDAY  |
| taylor    | 24-MAR-98 TUESDAY |
| Gietz     | 07-JUN-94 TUESDAY |
| higgins   | 07-JUN-94 TUESDAY |
| Rajs      | 17-OCT-95 TUESDAY |
| Mourgos   | 16-NOV-99 TUESDAY |
| Ernst     | 21-MAY-91 TUESDAY |

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

|          |                     |
|----------|---------------------|
| Davies   | 29-JAN-97 WEDNESDAY |
| Dehaan   | 13-JAN-93 WEDNESDAY |
| King     | 17-JUN-87 WEDNESDAY |
| Hunold   | 03-JAN-90 WEDNESDAY |
| Vargas   | 09-JUL-98 THURSDAY  |
| Kochhar  | 21-SEP-89 THURSDAY  |
| whalen   | 17-SEP-87 THURSDAY  |
| harstein | 17-FEB-96 SATURDAY  |
| Zlotkey  | 29-JAN-00 SATURDAY  |
| Abel     | 11-MAY-96 SATURDAY  |
| Lorentz  | 07-FEB-99 SUNDAY    |
| fay      | 17-AUG-97 SUNDAY    |
| Matos    | 15-MAR-98 SUNDAY    |

21 rows selected.

**EXNO:7**

**DISPLAYING DATA FROM MULTIPLE TABLE**

**AIM:**

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

To write SELECT statement to access data from more than one table using equality and nonequality joins, and to view data that generally does not meet a join condition by using outer joins and to join a table to itself by using a self join.

### **SOLUTIONS FOR THE EXERCISES:**

1. Write a query to display the last name, department number, and department name for all employees.

```
SQL> select e.last_name,e.department_id,d.department_name from employeetable e,department dwhere e.department_id=d.department_id;
```

| LAST_NAME | DEPARTMENT_ID | DEPARTMENT_NAME |
|-----------|---------------|-----------------|
|-----------|---------------|-----------------|

---

|      |    |           |
|------|----|-----------|
| king | 90 | executive |
|------|----|-----------|

|         |    |           |
|---------|----|-----------|
| kochhar | 90 | executive |
|---------|----|-----------|

|        |    |           |
|--------|----|-----------|
| dehaan | 90 | executive |
|--------|----|-----------|

|        |    |    |
|--------|----|----|
| hunold | 60 | it |
|--------|----|----|

|       |    |    |
|-------|----|----|
| ernst | 60 | it |
|-------|----|----|

|         |    |    |
|---------|----|----|
| lorentz | 60 | it |
|---------|----|----|

|         |    |          |
|---------|----|----------|
| mourgas | 50 | shipping |
|---------|----|----------|

|      |    |          |
|------|----|----------|
| rajs | 50 | shipping |
|------|----|----------|

|        |    |          |
|--------|----|----------|
| davies | 50 | shipping |
|--------|----|----------|

|       |    |          |
|-------|----|----------|
| matos | 50 | shipping |
|-------|----|----------|

|        |    |          |
|--------|----|----------|
| vargas | 50 | shipping |
|--------|----|----------|

| LAST_NAME | DEPARTMENT_ID | DEPARTMENT_NAME |
|-----------|---------------|-----------------|
|-----------|---------------|-----------------|

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|           |                   |
|-----------|-------------------|
| zlotkey   | 80 sales          |
| abel      | 80 sales          |
| taylor    | 80 sales          |
| whalen    | 10 administration |
| hartstein | 20 marketing      |
| fay       | 20 marketing      |
| higgins   | 110 accounting    |
| gietz     | 110 accounting    |

19 rows selected.

2. Create a unique listing of all jobs that are in department 80. Include the location of the department in the output

```
SQL> select distinct job_id,location_id from employeetable,department where  
employeetable.department_id=department.department_id and employeetable.department_id=80;
```

| JOB_ID | LOCATION_ID |
|--------|-------------|
|--------|-------------|

```
-----  
sa_man      2500  
sa_rep      2500
```

3. Write a query to display the employee last name, department name, location ID, and city of all employees who earn a commission

```
SQL> select e.last_name,d.department_name ,d.location_id ,l.city from employeetable  
e,department d,locations l where e.department_id=d.department_id and  
d.location_id=l.location_id and e.commission_pct is not null;
```

| LAST_NAME | DEPARTMENT_NAME | LOCATION_ID | CITY |
|-----------|-----------------|-------------|------|
|-----------|-----------------|-------------|------|

```
-----
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|         |       |      |        |
|---------|-------|------|--------|
| lotkey  | sales | 2500 | oxford |
| abel    | sale  | 2500 | oxford |
| toxford | sales | 2500 |        |

4. Display the employee last name and departmentnameforallemployeeswhohavean a(lowercase) in their last names

```
SQL> select last_name,department_name from employeetable,department where employeetable.department_id=department.department_id and last_name like '%a%';
```

| LAST_NAME | DEPARTMENT_NAME |
|-----------|-----------------|
|-----------|-----------------|

|           |                |
|-----------|----------------|
| -----     | -----          |
| whalen    | administration |
| fay       | marketing      |
| hartstein | marketing      |
| vargas    | shipping       |
| matos     | shipping       |
| davies    | shipping       |
| rajs      | shipping       |
| mourgas   | shipping       |
| taylor    | sales          |
| abel      | sales          |
| dehaan    | executive      |
| kochhar   | executive      |

12 rows selected.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

5.rite a query to display the last name, job, department number, and department name for all employees who work in Toronto

no rows selected

6. Display the employee last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, Respectively

```
SQL> select w.last_name "employee",w.employee_id "emp#",m.last_name  
"manager",m.employee_id from employeetable w join employeetable m on  
(w.manager_id=m.employee_id);
```

| emplo     | emp# manager | EMPLOYEE_ID |
|-----------|--------------|-------------|
| hartstein | 201 king     | 100         |
| zlotkey   | 149 king     | 100         |
| mourgas   | 124 king     | 100         |
| dehaan    | 102 king     | 100         |
| kochhar   | 101 king     | 100         |
| higgins   | 205 kochhar  | 101         |
| whalen    | 200 kochhar  | 101         |
| hunold    | 103 dehaan   | 102         |
| lorentz   | 107 hunold   | 103         |
| ernst     | 104 hunold   | 103         |
| vargas    | {44 mourgas  | {24         |
| matos     | {43 mourgas  | {24         |
| davies    |              |             |
| rajs      | 141 mourgas  | {24         |
| grant     | 178 zlotkey  |             |
| employee  | emp# manager | EMPLOYEE_ID |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|        |     |           |     |
|--------|-----|-----------|-----|
| taylor | 176 | zlotkey   | 149 |
| abel   | 174 | zlotkey   | 149 |
| fay    | 202 | hartstein | 201 |
| gietz  | 206 | higgins   | 205 |

19 rows selected.

7. Modify lab4\_6.sql to display all employees including King, who has no manager. Order the results by the employee number.

```
SQL> select w.last_name"employee",w.employee_id"emp#",m.last_name  
"manager",m.employee_id "mgr#" from employeetable w left outer join employeetable m  
on(w.manager_id=m.employee_id);
```

| employee | emp# | manager | mgr# |
|----------|------|---------|------|
|----------|------|---------|------|

|           |     |         |     |
|-----------|-----|---------|-----|
| hartstein | 201 | king    | 100 |
| zlotkey   | 149 | king    | 100 |
| mourgas   | 124 | king    | 100 |
| dehaan    | 102 | king    | 100 |
| kochhar   | 101 | king    | 100 |
| higgins   | 205 | kochhar | 101 |
| whalen    | 200 | kochhar | 101 |
| hunold    | 103 | dehaan  | 102 |
| lorentz   | 107 | hunold  | 103 |
| ernst     | 104 | hunold  | 103 |
| vargas    | 144 | mourgas | 124 |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

| employee | emp# manager  | mgr# |
|----------|---------------|------|
| matos    | 143 mourgas   | 124  |
| davies   | 142 mourgas   | 24   |
| rajs     | 141 mourgas   | 124  |
| grant    | 178 zlotkey   | 149  |
| taylor   | 176 zlotkey   | 149  |
| abel     | 174 zlotkey   | 149  |
| fay      | 202 hartstein | 201  |
| gietz    | 206 higgins   | 205  |
| king     | 100           |      |

20 rows selected.

8. Create a query that displays employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label

```
SQL> select e.department_id department,e.last_name employee,c.last_name colleague from employeetable e join employeetable c on(e.department_id=c.department_id)where e.employee_id<>c.employee_id order by e.department_id ,e.last_name,c.last_name;
```

| DEPARTMENT | EMPLOYEE  | COLLEAGUE |
|------------|-----------|-----------|
| 20         | fay       | hartstein |
| 20         | hartstein | fay       |
| 50         | davies    | matos     |

| DEPARTMENT | EMPLOYEE | COLLEAGUE |
|------------|----------|-----------|
| 50         | davies   | mourgas   |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|        |         |            |
|--------|---------|------------|
| 50     | davies  | rajs       |
| 50     | davies  | vargas     |
| 50     | matos   | davies     |
| 50     | matos   | mourgas    |
| 50     | matos   | rajs       |
| 50     | matos   | vargas     |
| 50     | mourgas | davies     |
| 50     | mourgas | matos      |
| 50     | mourgas | rajs       |
| 50     | mourgas | vargas     |
| 50     | rajs    | 50 davies  |
| rajs   | 50      | rajs matos |
| 50     | rajs    | 50 mourgas |
| vargas | 50      | vargas     |
| vargas | 50      | davies     |
| vargas | 50      | matos      |
| vargas | 60      | mourgas    |
| ernst  | 60      | rajs       |
| ernst  | 60      | hunold     |
| hunold | 60      | lorentz    |
| hunold |         | ernst      |
|        |         | lorentz    |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

DEPARTMENTEMPLOYEE

COLLEAGUE

| -----      |                   |
|------------|-------------------|
| 60lorentz  | ernst             |
| 60lorentz  | hunold            |
| 80abel     | taylor            |
| 80abel     | zlotkey           |
| 80taylor   | abel              |
| 80taylor   | zlotkey           |
| 80zlotkey  | abel              |
| 80zlotkey  | taylor            |
| 90dehaan   | king              |
| 90dehaan   | kochhar           |
| 90king     | dehaan<br>kochhar |
| 90king     |                   |
| 90kochhar  | dehaan<br>king    |
| 90kochhar  | higgins           |
| 110gietz   | gietz             |
| 110higgins |                   |

42 rows selected.

9. Show the structure of the JOB\_GRADE Table. Create a query that displays the name, job, department name, salary, and grade for all employees

SQL> desc job\_grades;

| Name | Null? | Type |
|------|-------|------|
|------|-------|------|

| ----- |  |  |
|-------|--|--|
|-------|--|--|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

GRADE\_LEVEL                    VARCHAR2(3)

LOWEST\_SAL                    NUMBER(10)

HIGHEST\_SAL                    NUMBER

SQL> select \* from job\_grades;

GRA LOWEST\_SAL HIGHEST\_SAL

```
-----  
a      1000    2999  
b      3000    5999  
c      6000    9999  
d     10000   14999  
e     15000   24999  
f     25000   40000
```

6 rows selected.

9. Create a query to display the name and hire date of any employee hired after employee Davies.

SQL> select e.last\_name,e.hire\_date from employeetable e,employeetable davies where davies.last\_name='davies' and davies.hire\_date<e.hire\_date;

LAST\_NAME                    HIRE\_DATE

```
-----  
lorentz                    07-FEB-99  
mourgas                    16-NOV-99  
matos                      15-MAR-98  
vargas                     09-JUL-98  
zlotkey                    29-JAN-00  
taylor                     24-MAR-98
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

grant fay 8 rows s2e4le-cMteAdY. 1-919. Display the names and hire dates for all employees who were hired before their manager's name and hire date. Label the columns Employee, Emp Hired, Manager, and Mgr Hired, respectively.

```
SQL> select w.last_name,w.hire_date,m.last_name,m.hire_date from employeetable  
w,employeetable m where w.manager_id=m.employee_id and w.hire_date < m.hire_date;
```

| LAST_NAME | HIRE_DATE | LAST_NAME | HIRE_DATE |
|-----------|-----------|-----------|-----------|
|-----------|-----------|-----------|-----------|

|        |           |         |           |
|--------|-----------|---------|-----------|
| whalen | 17-SEP-87 | kochhar | 21-SEP-89 |
| hunold | 03-JAN-93 | dahaan  | 13-JAN-93 |
| ernst  | 21-MAY-91 | hunold  | 03-JAN-93 |
| vargas | 09-JUL-98 | mourgas | 16-NOV-99 |
| matos  | 15-MAR-98 | mourgas | 16-NOV-99 |
| davies | 29-JAN-97 | mourgas | 16-NOV-99 |
| rajs   | 17-OCT-95 | mourgas | 16-NOV-99 |
| grant  | 24-MAY-99 | zlotkey | 29-JAN-00 |
| taylor | 24-MAR-98 | zlotkey | 29-JAN-00 |
| abel   | 11-MAY-96 | zlotkey | 29-JAN-00 |

10 rows selected.

**EXNO:8**

**AGGREGATING DATA USING GROUP FUNCTIONS**

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

**AIM:** To identify the available group functions, to describe the use of group functions, to group data by using the GROUP BY clause, to include or exclude grouped rows by using the HAVING clause.

## SOLUTION FOR THE EXERCISE:

1. Find the highest, lowest, sum, and average salary of all employees. Label the columns Maximum, Minimum, Sum, and Average, respectively. Round your results to the nearest whole number

```
SQL> select
round(max(salary),0)"maximum",round(min(salary),0)"minimum",round(sum(salary),0)"sum",ro
und(avg(salary),0)"average" from employeetable;
```

| maximum   | minimum | sum    | average |
|-----------|---------|--------|---------|
| -----     | -----   | -----  | -----   |
| 877254000 | 2500    | 175500 |         |

2. Modify the above query to display the minimum, maximum, sum, and average salary for each job type.

```
SQL>Selectround(max(salary),0)"maximum",round(min(salary),0)
"minimum",round(sum(salary),0)"sum",round(avg(salary),0)"average"    from    employeetable
group by job_id;
```

| maximum | minimum | sum   | average |
|---------|---------|-------|---------|
| -----   | -----   | ----- | -----   |
| 11000   | 7000    | 26600 | 8867    |
| 6000    | 6000    | 6000  | 6000    |
| 24000   | 24000   | 24000 | 24000   |
| 17000   | 17000   | 34000 | 17000   |
| 9000    | 4200    | 19200 | 6400    |
| 5800    | 5800    | 5800  | 5800    |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|         |         |       |         |
|---------|---------|-------|---------|
| 8300    | 8300    | 8300  | 8300    |
| 10500   | 10500   | 10500 | 10500   |
| 4400    | 4400    | 4400  | 4400    |
| maximum | minimum | sum   | average |

---

|       |       |       |       |
|-------|-------|-------|-------|
| 12000 | 12000 | 12000 | 12000 |
| 3500  | 2500  | 11700 | 2925  |
| 13000 | 13000 | 13000 | 13000 |

12 rows selected.

3. Write a query to display the number of people with the same job. Generalize the query so that the user in the HR department is prompted for a job title.

SQL> select job\_id,count(\*) from employeetable group by job\_id;

| JOB_ID | COUNT(*) |
|--------|----------|
|--------|----------|

---

|            |   |
|------------|---|
| sa_rep     | 3 |
| mk_rep     | 1 |
| ad_pres    | 1 |
| ad_vp      | 2 |
| it_prog    | 3 |
| st_man     | 1 |
| ac_account | 1 |
| sa_man     | 1 |
| ad_asst    | 1 |
| ac_mgr     | 1 |
| st_clerk   | 4 |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

mk\_man 1

12 rows selected.

4. Determine the number of managers without listing them. Label the column Number of Managers.

```
SQL> select count(distinct manager_id)"number of managers" from employeetable;  
number of managers
```

-----  
8

5. Find the difference between the highest and lowest salaries. Label the column DIFFERENCE.

```
SQL> select max(salary)-min(salary)"difference" from employeetable;  
difference
```

-----  
21500

6. Create a report to display the manager number and the salary of the lowest-paid employee for that manager. Exclude anyone whose manager is not known. Exclude any groups where the minimum salary is \$6,000 or less. Sort the output in descending order of salary.

```
SQL> select manager_id,min(salary)from employeetable where manager_id is not null group by  
manager_id having min(salary)>6000 order by min(salary)desc;  
MANAGER_ID MIN(SALARY)
```

-----  
9000 102  
1 49  
8300  
7000

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

7. Create a query to display the total number of employees and, of that total, the number of employees hired in 1995, 1996, 1997, and 1998. Create appropriate column headings

SQL> select  
count(\*)"total",sum(decode(to\_char(hire\_date,'YYYY'),1995,1,0))"1995",sum(decode(to\_char(hire\_date,'YYYY'),1996,1,0))"1996",sum(decode(to\_char(hire\_date,'YYYY'),1996,1,0))"1997",sum(decode(to\_char(hire\_date,'YYYY'),1998,1,0))"1998" from employeetable;

| total | 1995 | 1996 | 1997 | 1998 |
|-------|------|------|------|------|
| ----- |      |      |      |      |
| 20    | 1    | 2    | 2    | 3    |

8. Create a matrix query to display the job, the salary for that job based on department number, and the total salary for that job, for departments 20, 50, 80, and 90, giving each column an appropriate heading.

SQL>

Select job\_id"job",sum(decode(department\_id,20,salary))"department20",sum(decode(department\_id,50,salary))"department50",sum(decode(department\_id,80,salary))"department80",sum(decode(department\_id,90,salary))"department90",sum(salary)"total" from employeetable group by job\_id;

job department20 department50 department80 department90 total

|             |       |
|-------------|-------|
| 2s6a6_0re0p | 19600 |
|-------------|-------|

|        |      |      |
|--------|------|------|
| mk_rep | 6000 | 6000 |
|--------|------|------|

|         |       |       |
|---------|-------|-------|
| ad_pres | 24000 | 24000 |
|---------|-------|-------|

|       |       |      |
|-------|-------|------|
| ad_vp | 34000 | 4000 |
|-------|-------|------|

|         |       |
|---------|-------|
| it_prog | 19200 |
|---------|-------|

|        |      |      |
|--------|------|------|
| st_man | 5800 | 5800 |
|--------|------|------|

|            |      |
|------------|------|
| ac_account | 8300 |
|------------|------|

|        |       |       |
|--------|-------|-------|
| sa_man | 10500 | 10500 |
|--------|-------|-------|

|         |      |
|---------|------|
| ad_asst | 4400 |
|---------|------|

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

```
ac_mgr      12000  
st_clerk    11700      11700  
mk_man     13000      13000
```

12 rows selected.

9. Write a query to display each department's name, location, number of employees, and the average salary for all the employees in that department. Label the column name-Location, Number of people, and salary respectively. Round the average salary to two decimal places.

```
SQL> select d.department_name "name" ,d.location_id "location",count(*)"no of  
people",round(avg(salary),2)"salary" from employeetable e,department d where e.department_id  
=d.department_id group by d.department_name,d.location_id;
```

| name           | location | no of people | salary   |
|----------------|----------|--------------|----------|
| it             | 1400     | 3            | 6400     |
| shipping       | 1500     | 5            | 3500     |
| administration | 1700     | 1            | 4400     |
| marketing      | 1800     | 2            | 9500     |
| executive      | 1700     | 3            | 19333.33 |
| sales          | 2500     | 3            | 10033.33 |
| accounting     | 1700     | 2            | 10150    |

7rows selected.

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

## AIM:

To define subqueries, to describe the types of problems that sub queries can solve, to list the types of subqueries, and to write single row and multiple row subqueries.

## SOLUTIONS FOR THE EXERCISES

1. The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).

```
SQL> select last_name, hire_date from employee_table where department_id = (select department_id from employee_table where last_name = 'zlotkey') and last_name <> 'zlotkey';
```

| LAST_NAME | HIRE_DATE |
|-----------|-----------|
|-----------|-----------|

```
-----  
zlotkey      29-JAN-00  
abel          11-MAY-96  
taylor        24-MAR-98
```

2. Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary

```
SQL> select employee_id, last_name, salary from employee_table where salary > (select avg(salary) from employee_table) order by salary;
```

| EMPLOYEE_ID | LAST_NAME | SALARY |
|-------------|-----------|--------|
|-------------|-----------|--------|

```
-----  
103 hunold      9000  
149 zlotkey     10500  
174 abel         11000  
205 higgins     12000
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|               |       |
|---------------|-------|
| 201 hartstein | 13000 |
| 101 kochhar   | 17000 |
| 102 dehaan    | 17000 |
| 100 king      | 24000 |

8 rows selected.

3. Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains a *u*.

```
SQL> select last_name,hire_date from employeetable where department_id in(select department_id from employeetable where last_name like '%ou%');
```

| LAST_NAME | HIRE_DATE |
|-----------|-----------|
| lorentz   | 07-FEB-99 |
| ernst     | 21-MAY-91 |
| hunold    | 03-JAN-93 |
| vargas    | 09-JUL-98 |
| matos     | 15-MAR-98 |
| davies    | 29-JAN-97 |
| rajs      | 17-OCT-95 |
| mourgas   | 16-NOV-99 |

8 rows selected.

4. The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.

```
SQL> select last_name ,department_id,job_id from employeetable where department_id in(select department_id from department where location_id=1700);
```

| LAST_NAME | DEPARTMENT_ID | JOB_ID |
|-----------|---------------|--------|
|-----------|---------------|--------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

whalen dehaan kochhar ki1n0g agdie\_tazs shtiggins 6 rows selected.  
5. Create a report for HR that displays the last name and salary of employee who reports to King.

```
SQL> select last_name,salary from employees where manager_id=(select employee_id from employees where last_name='King');
```

110 ac\_account

110 ac\_mgr

| LAST_NAME | SALARY |
|-----------|--------|
| kochhar   | 17000  |
| dehaan    | 17000  |
| mourgas   | 5800   |
| zlotkey   | 10500  |
| hartstein | 13000  |

|           |       |
|-----------|-------|
| kochhar   | 17000 |
| dehaan    | 17000 |
| mourgas   | 5800  |
| zlotkey   | 10500 |
| hartstein | 13000 |

6. Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

```
SQL> select last_name,department_id,job_id from employees where department_id in(select department_id from departments where department_name='executive');
```

| LAST_NAME | DEPARTMENT_ID | JOB_ID |
|-----------|---------------|--------|
| dehaan    | 90            | ad_vp  |

|        |    |       |
|--------|----|-------|
| dehaan | 90 | ad_vp |
|--------|----|-------|

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

kochhar                    90 ad\_vp

king                      90 ad\_pres

7. Modify the query 3 to display the employee number, last name, and salary of all employees who earn

more than the average salary and who work in a department with any employee whose last name contains a *u*.

```
SQL> select employee_id,last_name,salary from employeetable where department_id in(select department_id from employeetable where last_name like '%u%') and salary >(select avg(salary) from employeetable);
```

| EMPLOYEE_ID | LAST_NAME | SALARY |
|-------------|-----------|--------|
|-------------|-----------|--------|

|     |        |      |
|-----|--------|------|
| 103 | hunold | 9000 |
|-----|--------|------|

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

## **AIM:**

To describe the set operators, to use set operators to combine multiple queries into a single query, and to control the order of rows returned.

## **FIND THE SOLUTIONS:**

1. The HR department needs a list of department IDs for departments that do not contain the job ID ST\_CLERK. Use set operators to create this report.

```
select department_id from department minus select department_id from employee table where job_id='ST_CLERK';
```

DEPARTMENT\_ID

-----

10 20 50 60 80 90

110

190

8 rows selected.

2. The HR department needs a list of countries that have no departments located in them.

Display the country ID and the name of the countries. Use set operators to create this report.

```
SQL> select country_id, country_name from countries minus select l.country_id, c.country_name  
from locations l, countries c where l.country_id = c.country_id;
```

CO COUNTRY\_NAME

-----

de germany

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

3. Produce a list of jobs for departments 10, 50, and 20, in that order. Display job ID and department ID using set operators.

```
SQL> select job_id,department_id from employeetable where department_id=10 union select  
job_id,department_id from employeetable where department_id=50 union select  
job_id,department_id from employeetable where department_id=20;
```

| JOB_ID   | DEPARTMENT_ID |
|----------|---------------|
| ad_asst  | 10            |
| mk_man   | 20            |
| mk_rep   | 20            |
| st_clerk | 50            |
| st_man   | 50            |

```
-----  
ad_asst      10  
mk_man       20  
mk_rep        20  
st_clerk     50  
st_man       50
```

4. Create a report that lists the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired by the company (that is, they changed jobs but have now gone back to doing their original job).

```
SQL> select employee_id,job_id from employeetable intersect select employee_id,job_id from  
job_history;
```

| EMPLOYEE_ID | JOB_ID  |
|-------------|---------|
| 103         | it_prog |
| 176         | sa_rep  |
| 200         | ad_asst |

```
-----  
103 it_prog  
176 sa_rep  
200 ad_asst
```

5. The HR department needs a report with the following specifications:

- Last name and department ID of all the employees from the EMPLOYEES table, regardless of whether or not they belong to a department.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

- Department ID and department name of all the departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them Write a compound query to accomplish this.

```
SQL> select last_name,department_id,to_char(null) from employeetable union select  
to_char(null),department_id,department_name from department;
```

| LAST_NAME | DEPARTMENT_ID TO_CHAR(NULL) |
|-----------|-----------------------------|
|-----------|-----------------------------|

|           |     |
|-----------|-----|
| abel      | 80  |
| davies    | 50  |
| dehaan    | 90  |
| ernst     | 60  |
| fay       | 20  |
| gietz     | 110 |
| grant     |     |
| hartstein | 20  |
| higgins   | 110 |
| hunold    | 60  |
| king      | 90  |
| kochhar   | 90  |
| lorentz   | 60  |
| matos     | 50  |

| LAST_NAME | DEPARTMENT_ID TO_CHAR(NULL) |
|-----------|-----------------------------|
|-----------|-----------------------------|

|        |               |    |
|--------|---------------|----|
|        | ----- mourgas | 50 |
| rajs   | 50            |    |
| taylor | 80            |    |

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

|                |    |
|----------------|----|
| vargas whalen  | 50 |
| zlotkey        | 10 |
| administration | 80 |
|                | 10 |

8 rows selected.

# **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

**EXNO:11**

## **CREATING VIEWS**

### **AIM:**

To describe a view,to create, alter the definition of , and drop a view, to retrieve the data through a view, to insert,update, and delete data through a view, to create and use an inline view.

### **SOLUTIONS:**

- 1) Create a view called EMPLOYEE\_VU based on the employee numbers, employee names and department numbers from the EMPLOYEES table. Change the heading for the employee name to EMPLOYEE.

```
SQL> create view employee_VU as select employee_id, last_name "employee", department_id  
from employees;
```

View created.

- 2) Display the contents of the EMPLOYEES\_VU view.

```
SQL> select * from employee_VU;
```

| EMPLOYEE_ID | EMPLOYEE | DEPARTMENT_ID |
|-------------|----------|---------------|
| -----       |          |               |
| 1           | king     | 90            |
| 101         | kocchar  | 90            |
| 102         | dehaan   | 90            |
| 103         | hunold   | 60            |
| 104         | ernst    | 60            |
| 107         | lorentz  | 4200          |
| 124         | mourgos  | 50            |
| 141         | rajs     | 50            |
| 143         | matos    | 50            |

9 rows selected.

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

3) Select the view name and text from the USER\_VIEWS data dictionary views.

```
SQL> select *from tab; TNAME ----- STUDENT EMP DEPT  
EMPLOYEES   JOB    TDAEBPATYRPTEM ENT CMLYU_SETEMPLOYEEDEPT  
DEPARTMENT1  JOB-_-G--R--ALOCATION  MY_EMPLOYEES    JOBS  
COUNTRIES LOCATIONTAS BELMEP LOYEE_VU 16 rows selected.
```

```
SQL> select view_name, text from uTsAerB_vLiEew s;
```

TABLE

VIEW

| VIEW_NAME | TEXT | EMPLOYEE_VU |
|-----------|------|-------------|
|-----------|------|-------------|

---

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

4) using your EMPLOYEES\_VU view, enter a query to display all employees names and department.

```
SQL> select employee_id,department_id from employee_VU;
```

| EMPLOYEE_ID | DEPARTMENT_ID |
|-------------|---------------|
| 1           | 90            |
| 101         | 90            |
| 102         | 90            |
| 103         | 60            |
| 104         | 60            |
| 107         | 4200          |
| 124         | 50            |
| 141         | 50            |
| 143         | 50            |

9 rows selected.

5) Create a view named DEPT50 that contains the employee number, employee last names and department numbers for all employees in department 50. Label the view columns EMPNO, EMPLOYEE and DEPTNO. Do not allow an employee to be reassigned to another department through the view.

```
SQL> create view dept50 as select  
employee_id"empno",last_name"employees",department_id"deptno" from employees where  
department_id=50 with check option constraints emp_department_50;
```

View created.

6) Display the structure and contents of the DEPT50 view.

```
SQL> desc dept50;
```

| Name | Null? | Type |
|------|-------|------|
|------|-------|------|

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|           |          |              |
|-----------|----------|--------------|
| emp no    | NOT NULL | NUMBER(6)    |
| employees | NOT NULL | VARCHAR2(25) |
| dept no   |          | NUMBER(4)    |

SQL> select \*from dept50;

| emp no | employees | dept no |
|--------|-----------|---------|
| 124    | mourgos   | 50      |
| 141    | rajs      | 50      |
| 143    | matos     | 50      |

7) Attempt to reassign Matos to department 80.

SQL> update dept50 set deptno=80 where employee='matos';

1 row updated.

SQL> select \*from dept50;

| emp no | employees | dept no |
|--------|-----------|---------|
| 124    | mourgos   | 50      |
| 141    | rajs      | 50      |
| 143    | matos     | 80      |

8) Create a view called SALARY\_VU based on the employee last names, department names, salaries, and salary grades for all employees. Use the Employees, DEPARTMENTS and JOB\_GRADE tables. Label the column Employee, Department, salary, and Grade respectively.

SQL> create view salary\_VU as select  
e.last\_name"employee",d.dept\_name"dept",e.salary"salary",j.grade\_level"grades" from  
employees e,department d,job j where e.department\_id=d.dept\_id and e.salarybetween  
j.lowest\_sal and j.highest\_sal;

View created.

# CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

**EXNO:12 AIM:**

## PROCEDURES AND FUNCTIONS

To implement the concept of procedures and functions which is a logically grouped set of SQL and PL/SQL statements.

**PROGRAME FOR GENERATE PROCEDURE –**

**SELECTED RECORD'S PRICE IS INCREMENTED BY 500 , EXECUTING THE PROCEDURE CREATED AND DISPLAYING THE UPDATED TABLE**

SQL> create procedure itsum(identity number, total number) is price number;

2 null\_price exception;

3 begin

4 select actualprice into price from ititems where itemid=identity;

5 if price is null then

6 raise null\_price;

7 else

8 update ititems set actualprice=actualprice+total where itemid=identity;

9 end if;

10 exception

11 when null\_price then

12 dbms\_output.put\_line('price is null');

13 end;

14 /

Procedure created.

SQL> exec itsum(101, 500);

PL/SQL procedure successfully completed.

SQL> select \* from ititems;

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

| ITEMID | ACTUALPRICE | ORDID | PRODID |
|--------|-------------|-------|--------|
| 101    | 2500        | 500   | 201    |
| 102    | 3000        | 1600  | 202    |
| 103    | 4000        | 600   | 202    |

### CREATE THE TABLE ‘ITTRAIN’ TO BE USED FOR FUNCTIONS

```
SQL>create table ittrain (tno number(10), tfare number(10));
```

Table created.

```
SQL>insert into ittrain values (1001, 550);
```

1 row created.

```
SQL>insert into ittrain values (1002, 600);
```

1 row created.

```
SQL>select * from ittrain;
```

| TNO  | TFARE |
|------|-------|
| 1001 | 550   |
| 1002 | 600   |

### PROGRAM FOR FUNCTION AND IT’S EXECUTION

```
SQL> create function aaa (trainnumber number) return number is
```

```
2 trainfunction ittrain.tfare % type;
```

```
3 begin
```

```
4 select tfare into trainfunction from ittrain where tno=trainnumber;
```

```
5 return(trainfunction);
```

```
6 end;
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

7 /

Function created.

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 total number;
```

```
3 begin
```

```
4 total:=aaa (1001);
```

```
5 dbms_output.put_line('Train fare is Rs. '|total);
```

```
6 end;
```

7 /

Train fare is Rs.550

PL/SQL procedure successfully completed.

### **FACTORIAL OF A NUMBER USING FUNCTION — PROGRAM AND EXECUTION**

```
SQL> create function iffact (a number) return number is
```

```
2 fact number:=1;
```

```
3 b number;
```

```
4 begin
```

```
5 b:=a;
```

```
6 while b>0
```

```
7 loop
```

```
8 fact:=fact*b;
```

```
9 b:=b-1;
```

```
10 end loop;
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

```
11 return(fact);
```

```
12 end;
```

```
13 /
```

Function created.

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 a number:=7;
```

```
3 f number(10);
```

```
4 begin
```

```
5 f:=itfact(a);
```

```
6 dbms_output.put_line('The factorial of the given number is'||f);
```

```
7 end;
```

```
8 /
```

The factorial of the given number is 5040

PL/SQL procedure successfully completed.

### **PROGRAMS**

#### **TO DISPLAY HELLO MESSAGE**

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 a varchar2(20);
```

```
3 begin
```

```
4 a:='Hello';
```

```
5 dbms_output.put_line(a);
```

```
6 end;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

7 /

Hello

PL/SQL procedure successfully completed.

### TO INPUT A VALUE FROM THE USER AND DISPLAY IT

SQL> set serveroutput on;

SQL> declare

2 a varchar2(20);

3 begin

4 a:=&a;

5 dbms\_output.put\_line(a);

6 end;

7 /

Enter value for a: 5

old 4: a:=&a;

new 4: a:=5;

5

PL/SQL procedure successfully completed.

### GREATEST OF TWO NUMBERS

SQL> set serveroutput on;

SQL> declare

2 a number(7);

3 b number(7);

4 begin 5

a:=&a;

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
6 b:=&b;  
7 if(a>b) then  
8 dbms_output.put_line (' The grerater of the two is'|| a);  
9 else  
10 dbms_output.put_line (' The grerater of the two is'|| b);  
11 end if;  
12 end;  
13 /
```

Enter value for a: 5

old 5: a:=&a;

new 5: a:=5;

Enter value for b: 9

old 6: b:=&b;

new 6: b:=9;

The grerater of the two is9

PL/SQL procedure successfully completed.

### GREATEST OF THREE NUMBERS

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 a number(7);
```

```
3 b number(7);
```

```
4 c number(7);
```

```
5 begin 6
```

```
a:=&a;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
7 b:=&b;  
8 c:=&c;  
9 if(a>b and a>c) then  
10 dbms_output.put_line (' The greatest of the three is ' || a);  
11 else if (b>c) then 12 dbms_output.put_line (' The greatest  
of the three is ' || b); 13 else 14 dbms_output.put_line (' The  
greatest of the three is ' || c); 15 end if; 16 end if; 17 end; 18 /
```

Enter value for a: 5

old 6: a:=&a;

new 6: a:=5;

Enter value for b: 7

old 7: b:=&b;

new 7: b:=7;

Enter value for c: 1

old 8: c:=&c;

new 8: c:=1;

The greatest of the three is 7

PL/SQL procedure successfully completed.

**PRINT NUMBERS FROM 1 TO 5 USING SIMPLE LOOP**

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

```
SQL> set serveroutput on;  
SQL> declare  
2 a number:=1;  
3 begin  
4 loop  
5 dbms_output.put_line (a);  
6 a:=a+1;  
7 exit when a>5;  
8 end loop;  
9 end;  
10 /  
1 2 3 4 5 PL/SQL procedure successfully  
completed.
```

### **PRINT NUMBERS FROM 1 TO 4 USING WHILE LOOP**

```
SQL> set serveroutput on;  
SQL> declare  
2 a number:=1;  
3 begin  
4 while(a<5)
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
5 loop  
6 dbms_output.put_line (a);  
7 a:=a+1;  
8 end loop;  
9 end;  
10 /
```

1 2 3 4 PL/SQL procedure successfully completed.

### PRINT NUMBERS FROM 1 TO 5 USING FOR LOOP

```
SQL> set serveroutput on;
```

```
SQL> declare  
2 a number:=1;  
3 begin  
4 for a in 1..5  
5 loop  
6 dbms_output.put_line (a);  
7 end loop;  
8 end;  
9 /
```

1

2

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

3 4 5 PL/SQL procedure successfully completed.

### **PRINT NUMBERS FROM 1 TO 5 IN REVERSE ORDER USING FOR LOOP**

SQL> set serveroutput on; SQL> declare

2 a number:=1;

3 begin

4 for a in reverse 1..5

5 loop

6 dbms\_output.put\_line (a);

7 end loop;

8 end;

9 /

5 4 3 2 1 PL/SQL procedure successfully

completed.

### **TO CALCULATE AREA OF CIRCLE**

SQL> set serveroutput on;

SQL> declare

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
2 pi constant number(4,2):=3.14;  
3 a number(20);  
4 r number(20);  
5 begin  
6 r:=&r;  
7 a:= pi* power(r,2);  
8 dbms_output.put_line (' The area of circle is ' || a);  
9 end;  
10 /
```

Enter value for r: 2

old 6: r:=&r;

new 6: r:=2;

The area of circle is 13

PL/SQL procedure successfully completed.

### TO CREATE SACCOUNT TABLE

```
SQL> create table saccount ( accno number(5), name varchar2(20), bal number(10));
```

Table created.

```
SQL> insert into saccount values ( 1,'mala',20000);
```

1 row created.

```
SQL> insert into saccount values ( 2,'kala',30000);
```

1row created.

```
SQL> select * from saccount;
```

| ACCNO | NAME | BAL   |
|-------|------|-------|
| 1     | mala | 20000 |
| 2     | kala | 30000 |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
-----  
1 mala          20000
```

```
2 kala          30000
```

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 a_bal number(7);
```

```
3 a_no varchar2(20);
```

```
4 debit number(7):=2000;
```

```
5 minamt number(7):=500;
```

```
6 begin
```

```
7 a_no:=&a_no;
```

```
8 select bal into a_bal from saccount where accno= a_no;
```

```
9 a_bal:= a_bal-debit;
```

```
10 if (a_bal > minamt) then
```

```
11 update saccount set bal=bal-debit where accno=a_no;
```

```
12 end if;
```

```
13 end;
```

```
14
```

```
15 /
```

```
Enter value for a_no: 1
```

```
old 7: a_no:=&a_no;
```

```
new 7: a_no:=1;
```

```
PL/SQL procedure successfully completed.
```

```
SQL> select * from saccount;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

| ACCNO | NAME | BAL   |
|-------|------|-------|
| 1     | mala | 18000 |
| 2     | kala | 30000 |

### TO CREATE TABLE SROUTES

```
SQL> create table sroutes ( rno number(5), origin varchar2(20), destination varchar2(20), fare number(10), distance number(10));
```

Table created.

```
SQL> insert into sroutes values ( 2, 'chennai', 'dindugal', 400,230);
```

1 row created.

```
SQL> insert into sroutes values ( 3, 'chennai', 'madurai', 250,300);
```

1 row created.

```
SQL> insert into sroutes values ( 6, 'thanjavur', 'palani', 350,370);
```

1 row created.

```
SQL> select * from sroutes;
```

| RNO | ORIGIN    | DESTINATION | FARE | DISTANCE |
|-----|-----------|-------------|------|----------|
| 2   | chennai   | dindugal    | 400  | 230      |
| 3   | chennai   | madurai     | 250  | 300      |
| 6   | thanjavur | palani      | 350  | 370      |

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 route sroutes.rno % type;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
3 fares sroutes.fare % type;  
4 dist sroutes.distance % type;  
5 begin  
6 route:=&route;  
7 select fare, distance into fares , dist from sroutes where rno=route;  
8 if (dist < 250) then  
9 update sroutes set fare=300 where rno=route;  
10 else if dist between 250 and 370 then 11  
update sroutes set fare=400 where rno=route; 12  
else if (dist > 400) then  
dbms_output.put_line('Sorry'); 14 end if; 15 end  
if; 16 end if; 17 end; 18 /
```

Enter value for route: 3

old 6: route:=&route;

new 6: route:=3;

PL/SQL procedure successfully completed.

SQL> select \* from sroutes;

| RNO | ORIGIN | DESTINATION | FARE | DISTANCE |
|-----|--------|-------------|------|----------|
|-----|--------|-------------|------|----------|

-----

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

|   |           |          |     |     |
|---|-----------|----------|-----|-----|
| 2 | chennai   | dindugal | 400 | 230 |
| 3 | chennai   | madurai  | 400 | 300 |
| 6 | thanjavur | palani   | 350 | 370 |

### TO CREATE SCALCULATE TABLE

```
SQL> create table scalculate ( radius number(3), area number(5,2));
```

```
Table created.
```

```
SQL> desc scalculate;
```

| Name   | Type        |
|--------|-------------|
| RADIUS | NUMBER(3)   |
| AREA   | NUMBER(5,2) |

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 pi constant number(4,2):=3.14; 3
```

```
radius number(5,2); 4
```

```
number(3); 5 begin 6 radius:=3; 7
```

```
while (radius <=7) 8 loop 9 area:=
```

```
pi* power(radius,2);
```

```
10 insert into scalculate values (radius,area);
```

```
11 radius:=radius+1;
```

```
12 end loop;
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
13 end;  
14 /
```

PL/SQL procedure successfully completed.

```
SQL> select * from scalculate;
```

| RADIUS | AREA   |
|--------|--------|
| 3      | 28.26  |
| 4      | 50.24  |
| 5      | 78.5   |
| 6      | 113.04 |
| 7      | 153.86 |

### TO CALCULATE FACTORIAL OF A GIVEN NUMBER

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 f number(4):=1;
```

```
3 i number(4); 4
```

```
begin 5 i:=&i; 6
```

```
while(i>=1) 7 loop
```

```
8 f:=f*i; 9 i:=i-1;
```

```
10 end loop;
```

```
11 dbms_output.put_line('The value is ' || f);
```

## **CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY**

12 end;

13 /

Enter value for i: 5

old 5: i:=&i;

new 5: i:=5;

The value is 120

PL/SQL procedure successfully completed.

### **Ex No:13**

#### **TRIGGERS**

##### **TO CREATE THE TABLE ‘ITEMPLS’**

```
SQL> create table itempls (ename varchar2(10), eid number(5), salary number(10));
```

Table created.

```
SQL> insert into itempls values('xxx',11,10000);
```

1 row created.

```
SQL> insert into itempls values('yyy',12,10500);
```

1 row created.

```
SQL> insert into itempls values('zzz',13,15500);
```

1 row created.

```
SQL> select * from itempls;
```

| ENAME | EID | SALARY |
|-------|-----|--------|
| xxx   | 11  | 10000  |

| ENAME | EID | SALARY |
|-------|-----|--------|
| xxx   | 11  | 10000  |

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
yyy      12  10500
```

```
zzz      13  15500
```

### TO CREATE A SIMPLE TRIGGER THAT DOES NOT ALLOW INSERT UPDATE AND DELETE OPERATIONS ON THE TABLE

```
SQL> create trigger ittrigg before insert or update or delete on itempls for each row
```

```
2 begin  
3 raise_application_error(-20010,'You cannot do manipulation');  
4 end;  
5  
6 /
```

```
Trigger created.
```

```
SQL> insert into itempls values('aaa',14,34000);
```

```
insert into itempls values('aaa',14,34000)
```

```
*
```

```
ERROR at line 1:
```

```
ORA-20010: You cannot do manipulation
```

```
ORA-06512: at "STUDENT.ITTRIGG", line 2
```

```
ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'
```

```
SQL> delete from itempls where ename='xxx';
```

```
delete from itempls where ename='xxx'
```

```
*
```

```
ERROR at line 1:
```

```
ORA-20010: You cannot do manipulation
```

```
ORA-06512: at "STUDENT.ITTRIGG", line 2
```

```
ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
SQL> update itempls set eid=15 where ename='yyy';
```

```
update itempls set eid=15 where ename='yyy'
```

```
*
```

ERROR at line 1:

ORA-20010: You cannot do manipulation

ORA-06512: at "STUDENT.ITTRIGG", line 2

ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG' **TO DROP THE  
CREATED TRIGGER**

---

```
SQL> drop trigger ittrigg;
```

Trigger dropped.

**TO CREATE A TRIGGER THAT RAISES AN USER DEFINED ERROR MESSAGE  
AND DOES NOT ALLOW UPDATION AND INSERTION**

```
SQL> create trigger ittriggs before insert or update of salary onitempls for each row
```

2 declare

3 triggsal itempls.salary%type;

4 begin

5 select salary into triggsal from itempls where eid=12;

6 if(:new.salary>triggsal or :new.salary<triggsal) then

7 raise\_application\_error(-20100,'Salary has not been changed');

8 end if;

9 end;

10 /

Trigger created.

```
SQL> insert into itempls values ('bbb',16,45000);
```

```
insert into itempls values ('bbb',16,45000)
```

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

\*

ERROR at line 1:

ORA-04098: trigger 'STUDENT.ITTRIGGS' is invalid and failed re-validation

SQL> update itempls set eid=18 where ename='zzz';

update itempls set eid=18 where ename='zzz'

\*

ERROR at line 1:

ORA-04298: trigger 'STUDENT.ITTRIGGS' is invalid and failed re-validation

### 13/8/2025 Function Example:

DECLARE

a INT;

b FLOAT;

myexp EXCEPTION;

FUNCTION sqroot(x INT)

RETURN FLOAT

AS

answer FLOAT;

BEGIN

IF x < 0 THEN

RAISE myexp;

## CS23332 DATABASE MANAGEMENT SYSTEM LABORATORY

```
ELSE
    answer := SQRT(x);
END IF;
RETURN answer;

EXCEPTION
WHEN myexp THEN
    DBMS_OUTPUT.PUT_LINE('Square root of a negative number is not allowed, so
returning the same number');

    RETURN x;
END;

BEGIN
    b := sqroot(4);
    DBMS_OUTPUT.PUT_LINE('The value is ' || b);
END;
```