Status	Finished
Started	Wednesday, 21 October 2026, 12:41 PM
Completed	Wednesday, 21 October 2026, 12:46 PM
Duration	4 mins 47 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

- a. a list of lines ✓
- b. a list of single characters
- c. a list of integers
- d. str

The correct answer is:
a list of lines

Question **2**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
f = open("data.txt", "a")
f.write("Adding new data\n")
f.close()
```

- a. Raises an error because the file is opened in append mode
- b. Overwrites the file with "Adding new data"
- c. Appends "Adding new data" to the end of the file ✓
- d. Opens the file in read mode

The correct answer is: Appends "Adding new data" to the end of the file

Question **3**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

a. none of the mentioned
b. sets the file's current position within the file
c. sets the file's previous position at the offset
d. sets the file's current position at the offset ✓

The correct answer is:
sets the file's current position at the offset

Question **4**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer to beginning of the file
b. move the file pointer five characters ahead from the current position ✓
c. move the file pointer five characters behind from the current position
d. moves the file pointer to the end of a file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. insert()
b. read()
c. write() ✓
d. append()

The correct answer is: write()

Question **6**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

a. Writes data to the file
b. Deletes the file
c. Reads the file line by line
d. Moves the file cursor to the specified position ✓

The correct answer is: Moves the file cursor to the specified position

Question **7**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. read()
b. readline(size)
c. readlines()
d. readline() ✓

The correct answer is: readline()

Question **8**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

a. To automatically close the file after its suite finishes ✓
b. To read data from a file
c. To delete a file
d. To write data to a file

The correct answer is: To automatically close the file after its suite finishes

Question **9**

Correct

Mark 1.00 out of 1.00

Select the correct method to write a list of lines to a file

a. writelist(list)
b. None of the mentioned
c. write(list)
d. writelines(list) ✓

The correct answer is: writelines(list)

Question **10**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. seek() ✓
b. fseek()
c. ftell()
d. tell()

The correct answer is: seek()

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

a. close() ✓
b. finish()
c. end()
d. terminate()

The correct answer is: close()

Question **12**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

a. Binary
b. Read ✓
c. Append
d. Write

The correct answer is: Read

Question **13**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It raises an error
b. It appends data to the file
c. It clears the old data and starts fresh ✓
d. It does nothing

The correct answer is: It clears the old data and starts fresh

Question **14**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use _____

a. outfile = open(file = “c:\\scores.txt”, “w”)
b. outfile = open(“c:\\scores.txt”, “w”) ✓
c. outfile = open(“c:\scores.txt”, “w”)
d. outfile = open(file = “c:\scores.txt”, “w”)

The correct answer is:
outfile = open(“c:\\scores.txt”, “w”)

Question **15**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. null

b. 2

c. garbage

d. 0 ✓

e. 1

The correct answer is:
0