Experiment 4 - Sets and Dictionaries

Python Lab Manual — Program and Output

EX. NO: 4 — Implementing real-time/technical applications using sets and dictionaries

PROGRAM

```
print("\nSETS:")
cars = {"BMW", "Honda", "Audi", "Mercedes", "Toyota", "Ferrari", "Tesla"}
print("Approach #1 = ", cars)
print("==========")
print("Approach #2")

for car in cars:
    print("Car name = {}".format(car))
    print("==========")

cars.add("Tata")
print("New cars set = {}".format(cars))
cars.discard("Mercedes")
print("discard() method = {}".format(cars))

print("\nDICTIONARY:")
Dict = {}
print("Empty Dictionary:")
print(Dict)

Dict[0] = "BRICKS"
Dict[2] = "CEMENT"
Dict[3] = "BLUE_PRINT"
print("\nDictionary after adding 3 elements:")
print(Dict)

Dict["Value_set"] = (2, 3, 4)
print("\nDictionary after adding values:")
print(Dict)

Dict[2] = "STEEL"
print("\nUpdated key value:")
print(Dict)

Dict[5] = {"Nested": {"1": "LIME", "2": "SAND"}}
print("\nAdding a Nested Key:")
print(Dict)
```

OUTPUT

```
Output order of items in a set may vary.
The program displays the cars set, prints each car, adds Tata, removes Mercedes,
and then displays dictionary creation, added values, an updated value, and a nested dictionary.
```