

# Rajalakshmi Engineering College

Name: srisanjay RD  
Email: 240801332@rajalakshmi.edu.in  
Roll no: 240801332  
Phone: 8667212915  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 6\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Jose has an array of N fractional values, represented as double-point numbers. He needs to sort these fractions in increasing order and seeks your help.

Write a program to help Jose sort the array using the merge sort algorithm.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of fractions to be sorted.

The second line consists of N double-point numbers, separated by spaces, representing the fractions array.

##### ***Output Format***

The output prints N double-point numbers, sorted in increasing order, and rounded to three decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4

0.123 0.543 0.321 0.789

Output: 0.123 0.321 0.543 0.789

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>

// You are using GCC
int compare(double a, double b) {
    if(a<b) return -1;
    else if(a>b) return 1;
    else return 0;
}

void merge(double arr[], int l, int m, int r) {
    int n1=m-l+1;
    int n2=r-m;

    double left[n1],right[n2];
    for(int i=0;i<n1;i++){
        left[i]=arr[l+i];
    }
    for(int j=0;j<n2;j++){
        right[j]=arr[m+1+j];
    }
    int i=0,j=0,k=l;
    while(i<n1&& j<n2){
        if(compare(left[i],right[j])<=0){
            arr[k++]=left[i++];
        }
        else{
            arr[k++]=right[j++];
        }
    }
}
```

```

    }
    while(i<n1){
        arr[k++]=left[i++];
    }
    while(j<n2){
        arr[k++]=right[j++];
    }
}
void mergeSort(double arr[], int l, int r) {
    if(l<r){
        int m=l+(r-l)/2;

        mergeSort(arr,l,m);
        mergeSort(arr,m+1,r);

        merge(arr,l,m,r);
    }
}

int main() {
    int n;
    scanf("%d", &n);
    double fractions[n];
    for (int i = 0; i < n; i++) {
        scanf("%lf", &fractions[i]);
    }
    mergeSort(fractions, 0, n - 1);
    for (int i = 0; i < n; i++) {
        printf("%.3f ", fractions[i]);
    }
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10