FoodLoop | Lean Canvas

SDG 2 - Zero Hunger | Applied AI student project

PROBLEM

- Edible surplus is discarded while nearby people need food.
- Donors lack time to find recipients and coordinate pickups.
- Recipient capacity and pickup windows change quickly.

SOLUTION

- Post surplus with quantity, type, and deadline.
- Rank eligible recipients by fit, distance, capacity, and urgency.
- Send offers; a person confirms every handoff.

UNIQUE VALUE PROPOSITION

- Move safe surplus to a nearby recipient before pickup closes.
- Fast matching with human-confirmed handoff.

UNFAIR ADVANTAGE

- Local partner relationships and reliable capacity data can compound.
- Not yet established; test in a pilot.

CUSTOMER SEGMENTS

- Donors: campus cafeterias, bakeries, grocers.
- Recipients: food banks, shelters, community fridges.

EXISTING ALTERNATIVES

- Manual calls and messages
- End-of-day discounting
- Ad hoc donation

KEY METRICS

- Rescued portions / kg
- Offer acceptance rate
- Median time to match
- Completed pickups

HIGH-LEVEL CONCEPT

- A local food rescue dispatcher: list, match, confirm, learn.

CHANNELS

- Campus and community kitchens
- Food banks and NGOs
- Local volunteer networks

EARLY ADOPTERS

- One campus or neighborhood with repeat donors and a trusted recipient partner.

COST STRUCTURE

- Hosting and messaging
- Partner onboarding and coordination
- Food safety and privacy review

REVENUE STREAMS

- Pilot: grant or institutional sponsorship
- Later hypothesis: donor subscription or partner fee
- Willingness to pay remains untested

Working hypotheses for a student pilot; validate locally before implementation.