

```
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int server_fd, client_fd;
    struct sockaddr_un address;
    char buffer[100];

    // Create socket
    server_fd = socket(AF_UNIX, SOCK_STREAM, 0);

    // Set socket address
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    // Remove old socket
    unlink(SOCKET_PATH);

    // Bind socket to path
    bind(server_fd, (struct sockaddr *)&address, sizeof(address));

    // Wait for client
    listen(server_fd, 5);

    printf("Server waiting...\n");
```

```
    // Accept client
    client_fd = accept(server_fd, NULL, NULL);

    // Receive message
    read(client_fd, buffer, sizeof(buffer));

    printf("Message from client: %s\n", buffer);

    close(client_fd);
    close(server_fd);

    unlink(SOCKET_PATH);

    return 0;
}
```

```
knsat@SRITHIKA: ~/socket_demo X + v
GNU nano 8.7.1 client.c *
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int client_fd;
    struct sockaddr_un address;
    char message[] = "Hello from Socket Client!";

    // Create socket
    client_fd = socket(AF_UNIX, SOCK_STREAM, 0);
    // Set socket address
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    // Connect to the server
    if (connect(client_fd, (struct sockaddr *)&address, sizeof(address)) == -1) {
        perror("Connect failed");
        return 1;
    }
    // Send message
    write(client_fd, message, strlen(message) + 1);
    printf("Message sent to server\n");
    close(client_fd);
    return 0;
}
```

```
knsat@SRITHIKA: ~/socket_demo X + v
knsat@SRITHIKA:~$ cd socket_demo
knsat@SRITHIKA:~/socket_demo$ ./client
Message sent to server
knsat@SRITHIKA:~/socket_demo$
```

```
knsat@SRITHIKA:~$ mkdir socket_demo && cd socket_demo
knsat@SRITHIKA:~/socket_demo$ nano server.c
knsat@SRITHIKA:~/socket_demo$ nano client.c
knsat@SRITHIKA:~/socket_demo$ nano server.c
knsat@SRITHIKA:~/socket_demo$ ^C
knsat@SRITHIKA:~/socket_demo$ nano client.c
knsat@SRITHIKA:~/socket_demo$ nano server.c
knsat@SRITHIKA:~/socket_demo$ gcc server.c -o server
knsat@SRITHIKA:~/socket_demo$ gcc client.c -o client
knsat@SRITHIKA:~/socket_demo$ ./server
Server waiting...
cd socket_demo./clientMessage from client: Hello from Socket Client!
knsat@SRITHIKA:~/socket_demo$ cd socket_demo./client^C
```