

Practical 8A program

```
knsat@SRITHIKA: ~  
GNU nano 8.7.1 practical8.c  
#include <stdio.h>  
#include <stdlib.h>  
  
int main()  
{  
    int *a, *b;  
  
    a = (int *)malloc(5 * sizeof(int));  
    b = (int *)calloc(5, sizeof(int));  
  
    a = (int *)realloc(a, 10 * sizeof(int));  
  
    free(a);  
    free(b);  
  
    return 0;  
}
```

```
knsat@SRITHIKA:~$ nano practical8.c  
knsat@SRITHIKA:~$ gcc practical8.c -o practical8  
knsat@SRITHIKA:~$ ./practical8
```

Practical 8B program

```
knsat@SRITHIKA: ~  
GNU nano 8.7.1 practical8b.c  
#include <stdio.h>  
#include <unistd.h>  
  
int main()  
{  
    int x = 100;  
  
    if (fork() == 0)  
    {  
        printf("Child Before = %d\n", x);  
        x = 500;  
        printf("Child After = %d\n", x);  
    }  
    else  
    {  
        sleep(2);  
        printf("Parent = %d\n", x);  
    }  
  
    return 0;  
}
```

```
knsat@SRITHIKA:~$ nano practical8b.c  
knsat@SRITHIKA:~$ gcc practical8b.c -o practical8b  
knsat@SRITHIKA:~$ ./practical8b  
Child Before = 100  
Child After = 500  
Parent = 100
```