

User Dashboard Implementation Plan

The Petal Pouches E-Commerce Platform

Project: Customer-facing dashboard mirroring admin functionality

Based on: Admin dashboard with TPP theme and component system

Database: Supabase PostgreSQL (25 tables, UUID + JSONB)

Frontend Stack: React 18, Tailwind CSS, Lucide Icons

1. DATABASE SCHEMA ANALYSIS

Core Customer Tables

Table	Purpose	Key Fields
users	Customer accounts	id, name, email, password_hash, created_at
addresses	Delivery addresses	id, user_id, line1-2, city, state, country, zip_code
carts	Shopping carts	id, user_id, session_id, expires_at
cart_items	Cart products	id, cart_id, product_variant_id, quantity
orders	Order records	id, user_id, status, final_total, payment_status
order_items	Order line items	id, order_id, product_variant_id, price, quantity
payments	Payment records	id, order_id, provider (Razorpay/Stripe), status
wishlist	Saved items	id, user_id, product_id
reviews	Product reviews	id, product_id, user_id, rating (1-5), comment
coupons	Discount codes	code, discount_type, discount_value, usage_limit
gift_previews	Personalization	id, user_id, personalization (JSONB)
bundles_custom	User bundles	id, user_id, items, total_price, is_published
bundle_user_public	Shared bundles	id, custom_bundle_id, upvote_count

Key Relationships

- User → Addresses (1:Many)
- User → Orders (1:Many)
- User → Cart (1:1)
- Order → OrderItems → ProductVariants (Many:Many)
- User → Reviews (1:Many)

- User → Wishlist (1:Many)

2. DIRECTORY STRUCTURE

```
frontend/src/
├── pages/customer/
│   ├── Dashboard.jsx      # Home page
│   ├── Profile.jsx        # Account settings
│   ├── Addresses.jsx      # Manage addresses
│   ├── Orders.jsx         # Order history
│   ├── OrderDetails.jsx   # Single order view
│   ├── Wishlist.jsx       # Saved items
│   ├── Cart.jsx           # Shopping cart
│   ├── Checkout.jsx       # Checkout flow
│   └── Settings.jsx       # Security settings
├── components/customer/
│   ├── layout/
│   │   ├── CustomerLayout.jsx
│   │   ├── CustomerSidebar.jsx
│   │   └── CustomerHeader.jsx
│   ├── profile/
│   │   ├── ProfileForm.jsx
│   │   ├── PasswordChange.jsx
│   │   └── AvatarUpload.jsx
│   ├── addresses/
│   │   ├── AddressCard.jsx
│   │   ├── AddressForm.jsx
│   │   ├── AddressList.jsx
│   │   ├── AddressAutocomplete.jsx
│   │   └── AddressMapPicker.jsx
│   ├── orders/
│   │   ├── OrderCard.jsx
│   │   ├── OrderStatusTimeline.jsx
│   │   ├── OrderItems.jsx
│   │   └── TrackingInfo.jsx
│   └── cart/
│       └── CartItem.jsx
```

```
| | | — CartSummary.jsx
| | | — CouponInput.jsx
| | | — PromoCode.jsx
| | | — EmptyCart.jsx
|
| — wishlist/
| | — WishlistCard.jsx
| | — WishlistFilter.jsx
|
| — checkout/
| | — ShippingStep.jsx
| | — PaymentStep.jsx
| | — PersonalizationStep.jsx
| | — ReviewStep.jsx
|
| — reviews/
| | — ReviewForm.jsx
| | — ReviewCard.jsx
| | — RatingStars.jsx
| | — ReviewList.jsx
|
| — services/
| | — authService.js    # Login/Register/Auth
| | — orderService.js   # Order CRUD
| | — addressService.js # Address CRUD
| | — cartService.js    # Cart operations
| | — wishlistService.js # Wishlist operations
| | — reviewService.js  # Review CRUD
| | — paymentService.js # Razorpay/Stripe integration
| | — geocodingService.js # Mapbox + Nominatim
| | — personalizeService.js # Gift personalization
|
| — context/
| | — UserAuthContext.jsx # Auth state
| | — CartContext.jsx     # Cart state
| | — WishlistContext.jsx # Wishlist state
|
| — hooks/
| | — useCustomerAuth.js # Auth logic
| | — useCart.js         # Cart operations
| | — useAddress.js      # Address validation
|
| — utils/
| | — customerHelpers.js # Address formatting, validation
```

└─ paymentHelpers.js # Payment utilities
└─ geocodingHelpers.js # Map utilities

3. BACKEND ENDPOINTS (Express.js)

Authentication

POST /api/auth/register # Email/password registration
POST /api/auth/login # Login
POST /api/auth/logout # Logout
POST /api/auth/refresh # Token refresh
POST /api/auth/verify-email # Email verification
POST /api/auth/forgot-password # Password reset
POST /api/auth/reset-password/:token # Reset token
GET /api/auth/me # Current user profile

User Profile

GET /api/users/profile # Get profile
PUT /api/users/profile # Update profile
POST /api/users/avatar # Upload avatar (Cloudinary)
PUT /api/users/password # Change password
DELETE /api/users/account # Delete account

Addresses

GET /api/addresses # List user addresses
POST /api/addresses # Create address
PUT /api/addresses/:id # Update address
DELETE /api/addresses/:id # Delete address
PATCH /api/addresses/:id/default # Set default
POST /api/addresses/geocode # Nominatim/Mapbox search

Shopping Cart

GET /api/cart # Get user cart
POST /api/cart/items # Add to cart
PATCH /api/cart/items/:id # Update quantity
DELETE /api/cart/items/:id # Remove from cart

DELETE /api/cart # Clear cart
POST /api/cart/apply-coupon # Apply discount code

Orders

GET /api/orders # List user orders
GET /api/orders/:id # Order details
POST /api/orders # Create order
PATCH /api/orders/:id/status # Update status (admin only)
GET /api/orders/:id/tracking # Tracking info
POST /api/orders/:id/cancel # Cancel order

Payments (Razorpay/Stripe)

POST /api/payments/razorpay/create # Create Razorpay order
POST /api/payments/razorpay/verify # Verify payment
POST /api/payments/stripe/intent # Create payment intent
POST /api/payments/stripe/webhook # Stripe webhook

Reviews & Wishlist

POST /api/reviews # Create review
GET /api/reviews/product/:id # Get product reviews
DELETE /api/reviews/:id # Delete review
GET /api/wishlist # List wishlist
POST /api/wishlist # Add to wishlist
DELETE /api/wishlist/:id # Remove from wishlist

4. FILE SPECIFICATIONS

4.1 Authentication Layer

userAuthService.js (60 lines)

- `register(email, password, name)` - Create account, hash password, store in users table
- `login(email, password)` - Verify credentials, generate JWT token
- `logout()` - Clear token from localStorage
- `getCurrentUser()` - Fetch /api/auth/me with token
- `refreshToken()` - Renew expiring tokens

- `requestPasswordReset(email)` - Send reset email
- `resetPassword(token, newPassword)` - Verify token and update

useCustomerAuth.js (80 lines)

- Hook for authentication state
- `isAuthenticated`, `user`, `loading`, `error`
- Persist token to localStorage
- Auto-refresh token on app load
- Logout and clear state

4.2 Address Management

AddressForm.jsx (150 lines)

- Form component for adding/editing addresses
- Fields: line1, line2, city, state, country, zip_code, landmark, phone
- Uses AddressAutocomplete for search suggestions
- Uses AddressMapPicker for map selection

AddressAutocomplete.jsx (120 lines)

- **Nominatim Integration:** Fetch suggestions from OpenStreetMap
- Query: `/nominatim/search.php?q=${query}&format=json&addressdetails=1`
- Debounced input (500ms)
- Display 5 results dropdown
- Return { address, lat, lng }

AddressMapPicker.jsx (200 lines)

- **Mapbox + Leaflet.js combo:**
 - Mapbox as primary (better UX, 50k requests/month free)
 - Fallback to OpenStreetMap with Leaflet
- Embedded map with marker drag
- Click-to-select location
- Reverse geocoding to get full address

addressService.js (60 lines)

- `getAddresses()` - Fetch from `/api/addresses`
- `createAddress(data)` - POST to backend
- `updateAddress(id, data)` - PUT request
- `deleteAddress(id)` - DELETE request
- `setDefault(id)` - PATCH `/api/addresses/:id/default`

4.3 Cart System

cartService.js (80 lines)

- `getCart()` - Fetch user cart with items
- `addToCart(variantId, quantity)` - POST `/api/cart/items`
- `updateQuantity(itemId, quantity)` - PATCH
- `removeItem(itemId)` - DELETE
- `clearCart()` - DELETE `/api/cart`
- `applyCoupon(code)` - POST `/api/cart/apply-coupon`

CartItem.jsx (100 lines)

- Display product image, title, variant details
- Quantity selector with +/- buttons
- Remove button
- Show unit price and item total
- Show discount if applicable

CartSummary.jsx (80 lines)

- Subtotal calculation
- Discount display
- Shipping cost
- Tax calculation
- Final total
- Checkout button (disabled if cart empty)

CouponInput.jsx (60 lines)

- Input for coupon code
- Apply button
- Validation messages
- Show applied coupon and discount amount

4.4 Orders

orderService.js (70 lines)

- `getOrders(filters)` - GET /api/orders with pagination
- `getOrderById(id)` - Fetch single order with items
- `createOrder(cartItems, address, payment)` - POST /api/orders
- `cancelOrder(id)` - PATCH status to cancelled
- `getTracking(id)` - GET tracking info from shipment table

OrderCard.jsx (120 lines)

- Display order ID, date, status badge
- Total amount in TPP pink
- Item count
- Click to expand details
- Show action buttons (Track, Reorder, Return)

OrderStatusTimeline.jsx (100 lines)

- Visual timeline: Pending → Processing → Shipped → Delivered
- Current step highlighted
- Estimated dates
- Tracking number if shipped
- Show delivery date when completed

OrderDetails.jsx (150 lines)

- Full order information
- Order items with images and prices

- Shipping address
- Payment method
- Status timeline
- Download invoice button
- Review products button

4.5 Checkout & Payment

checkoutService.js (100 lines)

- `createRazorpayOrder(amount)` - Create order on Razorpay
- `verifyRazorpayPayment(response)` - Verify payment signature
- `createOrder(cartData, address, payment)` - Create order in DB
- `getCheckoutSummary(cart, address)` - Calculate totals

Checkout.jsx (300 lines)

- Step 1: Review cart
- Step 2: Select/add shipping address
- Step 3: Gift personalization (optional, JSONB)
- Step 4: Payment method (Razorpay/Stripe)
- Step 5: Review & confirm
- Progress indicator
- Persist progress to session storage

PaymentStep.jsx (120 lines)

- Radio buttons: Razorpay, Stripe, COD
- Razorpay:

javascript

```
const options = {  
  key: process.env.RAZORPAY_KEY_ID,  
  amount: total * 100, // in paise  
  currency: 'INR',  
  name: 'The Petal Pouches',  
  handler: verifyPayment,  
  prefill: { email, contact }  
};
```

- Stripe: loadStripe, useElements, useCardElement
- COD: Simple confirmation

PersonalizationStep.jsx (100 lines)

- Gift wrap option (yes/no)
- Gift message (max 500 chars)
- Recipient name & phone
- Store as JSONB in orders.gift_previews
- Preview text overlaid on product image

4.6 Reviews

ReviewForm.jsx (120 lines)

- Star rating selector (1-5)
- Comment textarea (max 1000 chars)
- Upload review images (Cloudinary, max 3)
- Post review to /api/reviews
- Show success/error messages

ReviewCard.jsx (80 lines)

- Customer name, avatar, date
- Star rating display
- Comment text (truncate if long)
- Review images carousel
- Helpful/Unhelpful buttons

RatingStars.jsx (40 lines)

- Reusable star display
- Editable mode: hover to select
- Display mode: show filled stars

4.7 Wishlist

WishlistCard.jsx (100 lines)

- Product image, title, price
- Stock status indicator
- Add to cart button
- Remove from wishlist button
- Show if in stock vs out of stock styling

wishlistService.js (50 lines)

- `getWishlist()` - GET /api/wishlist
- `addToWishlist(productId)` - POST
- `removeFromWishlist(id)` - DELETE
- `addAllToCart()` - Bulk operation

4.8 Layouts & Navigation

CustomerLayout.jsx (80 lines)

- Wrapper with header, sidebar, main content
- Sidebar: Dashboard, Profile, Addresses, Orders, Wishlist, Settings
- Header: User menu, Notifications, Cart icon
- Mobile: Hamburger menu

CustomerSidebar.jsx (120 lines)

- Navigation links with active state
- User profile section (avatar, name, email)
- Logout button
- Settings icon

- Collapsible on mobile

ProtectedCustomerRoute.jsx (60 lines)

- Check if user is authenticated
- Redirect to login if not
- Show loading spinner while checking
- Pass user data to children

4.9 Geocoding Utilities

geocodingService.js (180 lines)

javascript

```

// Mapbox (Primary)
const mapboxSearch = async (query) => {
  const response = await fetch(
    `https://api.mapbox.com/geocoding/v5/mapbox.places/${query}.json?access_token=${MAPBOX_TOKEN}`
  );
  const data = await response.json();
  return data.features.map(f => ({
    address: f.place_name,
    lat: f.geometry.coordinates[1],
    lng: f.geometry.coordinates[0]
  }));
};

// Nominatim (Fallback)
const nominatimSearch = async (query) => {
  const response = await fetch(
    `https://nominatim.openstreetmap.org/search?q=${query}&format=json&addressdetails=1`
  );
  const data = await response.json();
  return data.map(r => ({
    address: r.display_name,
    lat: parseFloat(r.lat),
    lng: parseFloat(r.lon)
  }));
};

// Reverse geocoding
const reverseGeocode = async (lat, lng) => {
  // Try Mapbox first, fallback to Nominatim
};

```

geocodingHelpers.js (100 lines)

- `formatAddress(addressObj)` - Convert DB to display format
- `validateAddressComplete(addressObj)` - Check required fields
- `getDistanceKm(lat1, lng1, lat2, lng2)` - Haversine formula
- `parseAddressComponents(mapResponse)` - Extract city, state, country
- `buildAddressString(line1, line2, city, state, country, zip)` - Format for shipping

4.10 Context & Hooks

UserAuthContext.jsx (100 lines)

- State: user, isAuthenticated, loading, error
- Methods: login, register, logout, updateProfile
- Persist user to localStorage
- Auto-login on app load

CartContext.jsx (150 lines)

- State: items, cart, subtotal, tax, total, coupon
- Methods: addItem, removeItem, updateQuantity, applyCoupon, clearCart
- Sync with API on every change
- Calculate totals automatically

useCart.js (80 lines)

- `useCart()` hook
 - Returns: items, addToCart, removeFromCart, total, etc.
 - Wraps CartContext for easier access
-

5. GEO-MAPPING INTEGRATION

Option 1: Mapbox (RECOMMENDED)

- **Tier:** Free (50,000 monthly requests)
- **Setup:** Get API key from mapbox.com
- **CDN:** `https://api.mapbox.com/...`
- **Features:** Autocomplete, reverse geocoding, interactive maps
- **React:** Use `@react-map-gl/core` or `react-map-gl`

Option 2: OpenStreetMap + Nominatim + Leaflet.js

- **Tier:** Free (1 req/sec rate limit)
- **Setup:** No API key needed
- **CDN:** `https://nominatim.openstreetmap.org/...`

- **Maps:** Leaflet.js with OpenStreetMap tiles

- **React:** Use `react-leaflet`

Implementation Strategy

javascript

// AddressAutocomplete.jsx

```
const [suggestions, setSuggestions] = useState([]);
const searchAddress = debounce(async (query) => {
  try {
    const results = await geocodingService.search(query);
    setSuggestions(results); // Show dropdown
  } catch (err) {
    console.error('Geocoding failed:', err);
  }
}, 500);
```

6. DATABASE OPERATIONS

User Registration

sql

```
INSERT INTO users (id, name, email, password_hash, created_at)
VALUES (gen_random_uuid(), $1, $2, bcrypt($3), now())
```

Add to Cart

sql

```
INSERT INTO cart_items (id, cart_id, product_variant_id, quantity)
VALUES (gen_random_uuid(), $1, $2, $3)
ON CONFLICT (cart_id, product_variant_id)
DO UPDATE SET quantity = quantity + $3
```

Create Order

sql

```
BEGIN;  
INSERT INTO orders (id, user_id, subtotal, final_total, status, payment_status)  
VALUES ($1, $2, $3, $4, 'pending', 'unpaid');  
  
INSERT INTO order_items SELECT gen_random_uuid(), $1, product_variant_id, quantity, price  
FROM cart_items WHERE cart_id = $5;  
  
DELETE FROM cart_items WHERE cart_id = $5;  
COMMIT;
```

7. AUTHENTICATION FLOW

1. User Register → Hash password → Insert into users table
2. User Login → Compare password → Generate JWT token
3. Store token in localStorage
4. Include token in Authorization header: "Bearer {token}"
5. On 401 response → Refresh token or redirect to login
6. Logout → Delete token from localStorage

8. IMPLEMENTATION PRIORITY

Phase 1 (Week 1-2) - Authentication & Core Layout

- User registration/login
- Protected routes
- CustomerLayout, Sidebar, Header
- Basic dashboard home page

Phase 2 (Week 2-3) - Address Management

- Add/edit addresses
- Mapbox + Nominatim integration
- Set default address

Phase 3 (Week 3) - Cart & Checkout

- Add to cart flow

- Cart page & summary
- Basic checkout (non-payment)

Phase 4 (Week 4) - Payments & Orders

- Razorpay integration
- Order creation & confirmation
- Order history view

Phase 5 (Week 5) - Secondary Features

- Reviews & ratings
- Wishlist
- Profile settings
- Order tracking

9. ENVIRONMENT VARIABLES

```
env

# Frontend
VITE_API_BASE_URL=http://localhost:5000
VITE_MAPBOX_TOKEN=pk_live_xxx
VITE_STRIPE_KEY=pk_live_xxx

# Backend
RAZORPAY_KEY_ID=xxx
RAZORPAY_KEY_SECRET=xxx
JWT_SECRET=your-secret-key
```

10. TESTING CHECKLIST

- ☐ User registration with email verification
- ☐ Login/logout functionality
- ☐ Cart add/remove/update operations
- ☐ Address geocoding with both Mapbox & Nominatim
- ☐ Razorpay payment flow
- ☐ Order creation and status updates

- ☐ Wishlist operations
 - ☐ Profile update
 - ☐ Review submission
 - ☐ Mobile responsiveness
-

Document Version: 1.0

Last Updated: November 2025

Theme: TPP Pink ( #EC4899), Slate ( #1E293B), Mint ( #00D9A3)