Experiment 9

CRC and Hamming Code

A. Write a C/C++ program to generate codeword at the sender using CRC method

```
#include<stdio.h>
#include<string.h>
#define N strlen(g)
char t[28],cs[28],g[30];
int a,e,c;
voidexor()
{
        for(c = 1;c < N; c++)
        cs[c] = (( cs[c] == g[c])?'0':'1');
}

voidcrc()
{
        for(e=0;e<N;e++)    cs[e]=t[e];
        do{
                if(cs[0]=='1')  exor();
                for(c=0;c<N-1;c++)
        cs[c]=cs[c+1];
                cs[c]=t[e++];
```

```
        }while(e<=a+N-1);
}

int main()
{
        printf("\nEnter data : ");
        scanf("%s",t);
        printf("\n---------------------------------------");
        printf("\nEnterGenerating polynomial in binary : ");
        scanf("%s",g);
        a=strlen(t);
        for(e=a;e<a+N-1;e++)    t[e]='0';
        printf("\n---------------------------------------");
        printf("\nAugmenteddataword : %s",t);
        printf("\n---------------------------------------");
        crc();
        printf("\nChecksum is : %s",cs);
        for(e=a;e<a+N-1;e++)    t[e]=cs[e-a];
        printf("\n---------------------------------------");
        printf("\nFinalcodeword is : %s",t);
        printf("\n---------------------------------------\n\n");
        return 0;
}
```

B. Write a C/C++ program to generate Hamming code at the sender

```
#include<stdio.h>
#include<stdlib.h>
#include<conio.h>
#include <string.h>
#include <math.h>
#include<iostream>

int main(void)
{
        unsignedint m=0,r=0,l=0,x1=1,x2=1,x0=0;
        char d[1024]= {0};
        int d1[1024],d2[1024];
        printf("Enter the message to be encoded, in binary format: ");
        scanf ("%s",&d);
        //Message Length
         m=strlen(d);

        //Check bits (r)
        for (inti=0; i<20; i++)
        {
                r=i;
                if(m+1+i <= pow(2,i))
```

```
        break;
}

//Codeword length (l)
l =m+r;

//Testing the input in binary
for (inti=0; i<m; i++)
{
        while (!( d[i]=='0' || d[i]=='1'))
        {
        printf("\nPlease enter the input message in binary only.\n");
        exit(0);
        }
}

printf ("\nMessage length (m) = %d\n",m);
printf ("Redundancy bits (r) = %d\n",r);
printf("Codewordlength (l) = %d\n",l);

//Initialization to zero
for (inti=m; i<1024;i++)
        d[i]='0';
for (inti=0; i<1024; i++)
```

```
{   d1[i]=0;    d2[i]=0; }

//Copying string array to intarray, also shifting start index from 0 to 1
for (inti=0; i<m+1; i++)
{
if (d[i]=='1')  d1[i+1]=1;
else            d1[i+1]=0;
}

//Shifting message bits into non parity positions
for (int x2=1; x2<m+r+1; x2++)
{
        float x = (log(x2)/log(2))-(int(log(x2)/log(2)));
        if(x==0 || x==1)
        {   d2[x2]=0; x0=x0+1;  }
        else    d2[x2]=d1[x2-x0];
}

//Finding parity bits
for(int x2=1; x2<m+r+1; x2++)
{
        int x2t=x2;
        for(inti=0; i<r; i++)
        {
```

```
            intipow=pow(2,i);
            if (x2t%2==1)
            d2[ipow]=d2[ipow] ^ d2[x2];
            x2t=x2t/2;
            }
        }

        printf("Code word: ");
        for (intI =1; i<m+r+1; i++)
            printf ("%d",d2[i]);
        printf("\n\n");
}
```

Exercise: Write a C/C++ program to decode the code words at the receiver using CRC and Hamming code.