PROGRAM 5

Write a PL/SQL block to describe the usage of LIKE operator including wildcard characters and escape character.

```
DECLARE
  V.Name employees.last_name%TYPE;
BEGIN
    FOR SAC IN (
      SELECT last.name FROM employees
      WHERE last.name LIKE 'S%' ESCAPE '\'
  ) LOOP
    DBMS-OUTPUT.PUT.LINE('Name starting with S:'||sc.
                                        (c.name);
    END LOOP;
END;
/
```

PROGRAM 6

Write a PL/SQL program to arrange the number of two variable in such a way that the small number will store in num_small variable and large number will store in num_large variable.

```
DECLARE
    num, NUMBER :=40;
    num, NUMBER :=20;
    num . small NUMBER;
    num . large NUMBER .
BEGINS
   IF num, < num 2 THEN
      num -small : = num1;
      num = large : = num2;
   ELSE
      num - small := num 2;
      num : large := num 1;
   END IF;
   DBMS_OUTPUT.PUT-LINE ('Small Number: '||num small);
   DBMS_OUTPUT-LINE ('Large Number :' || num = large);
END;
/
```

Highest_sal		Number

LOCATION TABLE

NAME	NULL?	TYPE
Location_id	Not null	Number(4)
St_addr		Varchar(40)
Postal_code		Varchar(12)
City	Not null	Varchar(30)
State_province		Varchar(25)
Country_id		Char(2)

1. Create the DEPT table based on the DEPARTMENT following the table instance chart below. Confirm that the table is created.

Column name	ID	NAME
Key Type		
Nulls/Unique		
FK table		
FK column		
Data Type	Number	Varchar2
Length	7	25

```
CREATE TABLE dept (
    id number(7)
    name VARCHAR2(25)
);
```

2. Create the EMP table based on the following instance chart. Confirm that the table is created.

Column name	ID	LAST_NAME	FIRST_NAME	DEPT_ID
Key Type				
Nulls/Unique				
FK table				
FK column				
Data Type	Number	Varchar2	Varchar2	Number
Length	7	25	25	7

```
CREATE TABLE emp(
    ~~id number(7)~~
    ID NUMBER(7)
    last_name VARCHAR 2 (25),
    First name VARCHAR 2 (25)
    dept_id NUMBER (7)
);
```

3. Modify the EMP table to allow for longer employee last names. Confirm the modification.(Hint: Increase the size to 50)

```
ALTER TABLE emp
MODIFY (last_name VARCHAR2(50)) ;
```

4. Create the EMPLOYEES2 table based on the structure of EMPLOYEES table. Include Only the Employee_id, First_name, Last_name, Salary and Dept_id coloumns. Name the columns Id, First_name, Last_name, salary and Dept_id respectively.

```
CREATE TABLE EMPLOYEES2 AS
SELECT employee_id AS id , first_name, last_name, salary
, department_id AS dept_id
FROM employees
WHERE 1=2;
```

5. Drop the EMP table.

```
DROP TABLE emp;
```

6. Rename the EMPLOYEES2 table as EMP.

```
RENAME employees2 to emp;
```

7. Add a comment on DEPT and EMP tables. Confirm the modification by describing the table.

```
COMMENT ON TABLE dept IS 'Department information';
COMMENT ON TABLE emp IS 'Employee information';
```

8. Drop the First_name column from the EMP table and confirm it.

```
ALTER TABLE emp
DROP COLUMN first_name;
```

Evaluation Procedure	Marks awarded
Query(5)	5
Execution (5)	5
Viva(5)	5
Total (15)	15
Faculty Signature	