Java Datatypes


by Shafaet

Java has 8 primitive data types; *char, boolean, byte, short, int, long, float, and double*. For this exercise, we'll work with the primitives used to hold integer values (*byte, short, int,* and *long*):

- A *byte* is an 8-bit signed integer.
- A *short* is a 16-bit signed integer.
- An *int* is a 32-bit signed integer.
- A *long* is a 64-bit signed integer.

Given an input integer, you must determine which primitive data types are capable of properly storing that input.

To get you started, a portion of the solution is provided for you in the editor.

Reference: https://docs.oracle.com/javase/tutorial/java/nutsandbolts/datatypes.html

Input Format

The first line contains an integer, T, denoting the number of test cases.
Each test case, T, is comprised of a single line with an integer, n, which can be arbitrarily large or small.

Output Format

For each input variable n and appropriate primitive $dataType$, you must determine if the given primitives are capable of storing it. If yes, then print:

```
n can be fitted in:
* dataType
```

If there is more than one appropriate data type, print each one on its own line and order them by size (i.e.: $byte < short < int < long$).

If the number cannot be stored in one of the four aforementioned primitives, print the line:

```
n can't be fitted anywhere.
```

Sample Input

```
5
-150
150000
1500000000
213333333333333333333333333333333333
-100000000000000
```

Sample Output

```
-150 can be fitted in:
* short
```

```
* int
* long
150000 can be fitted in:
* int
* long
1500000000 can be fitted in:
* int
* long
213333333333333333333333333333333333 can't be fitted anywhere.
-100000000000000 can be fitted in:
* long
```

Explanation

-150 can be stored in a *short*, an *int*, or a *long*.

$213333333333333333333333333333333333$ is very large and is outside of the allowable range of values for the primitive data types discussed in this problem.

Submissions:85024

Max Score:10

Difficulty: Easy

Rate This Challenge:

More

Current Buffer (saved locally, editable)

Java 7

```java
import java.util.*;
import java.io.*;



class Solution{
    public static void main(String []argh)
    {



        Scanner sc = new Scanner(System.in);
        int t=sc.nextInt();

        for(int i=0;i<t;i++)
        {

            try
            {
                long x=sc.nextLong();
                System.out.println(x+" can be fitted in:");
                if(x>=-128 && x<=127)System.out.println("* byte");
                //Complete the code
            }
            catch(Exception e)
            {
                System.out.println(sc.next()+" can't be fitted anywhere.");
            }

        }
    }
}

```

Line: 1 Col: 1

Upload Code as File

Test against custom input

Run Code

Submit Code