

sg13cmos5l_srout_ip_tinyBGR								
						gm/ld		
Process (MOS)	AVDD (V)	Temp (C)	Vref (V)	Tempco (ppm/C)	Iout (uA)	MN1,2	MP1,2	
		-40	1.1804		6.44	29.3	5.6	
TT	3	27	1.1809	3.61	9.65	21.98	3.98	
		125	1.1802		16.08	15.1	2.5	
		-40	1.195		6.755	29.5	5.4	
TT	3.3	27	1.196	3.47	10.001	21.9	3.9	
		125	1.195		16.52	15.5	2.2	
		-40	1.211		7.05			
TT	3.6	27	1.2111	4.1	10.3	21.8	3.85	
		125	1.2103		16.9			
		-40	1.1744		6.32	29	5.5	
SS	3	27	1.1749	5.12	9.51	21.69	3.91	
		125	1.1738		15.8	14.9	2.5	
		-40	1.19		6.63			
SS	3.3	27	1.1903	4.7	9.86	21.6	3.85	
		125	1.1893		16.3			
		-40	1.2051		6.9			
SS	3.6	27	1.2052	5.3	10.2	21.5	3.78	
		125	1.2041		16.7			
		-40	1.1864		6.56			
FF	3	27	1.187	3.146	9.79	22.2	4	
		125	1.1866		16.2			
		-40	1.2019		6.87	29.63	5.57	
FF	3.3	27	1.2023	2.33	10.1	22.2	3.98	
		125	1.2019		16.7	15.3	2.57	
		-40	1.217		7.17			
FF	3.6	27	1.2171	2.96	10.49	22.12	3.91	
		125	1.2165		17.1			
						gm/ld		
Process (MOS)	AVDD (V)	Temp (C)	Vref (V)	Tempco (ppm/C)	Iout (uA)	MN1,2	MP1,2	
MIN			1.1738	2.33	6.32	14.9	2.2	
TYP			1.196	3.47	10.001	21.9	3.9	
MAX			1.2171	5.3	17.1	29.63	5.6	
%VAR								
MIN			1.9%		36.8%	32.0%	43.6%	
MAX			1.8%		71.0%	35.3%	43.6%	

Offset Simulation								
Avt	10 mv-um							
PVT	PDeIVt (mV)	NDeIVt (mV)	Vref (V)	Tempco (ppm/C)	Iout (uA)			
TT	0	1.5	1.205	4.57	10.2			
3.3V	1.5	0	1.201	7.66	10.07			
27C	1.5	1.5	1.21	9.1	10.2			
	0	-1.5	1.187	2.4	9.8			
	-1.5	0	1.191	4.8	9.94			
	-1.5	-1.5	1.182	5.86	9.741			
	-1.5	1.5	1.199	3.92	10.14			
	1.5	-1.5	1.192	6.27	9.86			
3.3V/27C								
TT	4.5	4.5	1.23	23.6	10.7			
SS	4.5	4.5	1.23	24.66	10.6			
FF	4.5	4.5	1.24	22.69	10.9			
Startup Si Vddrise 1ms								
Process	AVDD (V)	Temp (C)	Vref (V)	Tstartup (ms)				
		-40	1.19	7.35				
SS	3.3	27	1.19	1.04				
		125	1.18	0.57				
		-40	1.195	4.3				
TT	3.3	27	1.196	0.89				
		125	1.195	0.56				
		-40	1.201	2.006				
FF	3.3	27	1.202	0.748				
		125	1.201	0.54				
MIN				0.54	FFH			
TYP				0.89	TT27			
MAX				7.35	SSC			
Power Supply Rejection								
Process	AVDD (V)	Temp (C)	100Hz (dB)	10kHz (dB)	100MHz (dB)			
		-40	-25.8	-25.8	-7.6			
SS	3.3	27	-25.9	-25.9	-7.8			
		125	-25.9	-25.9	-8			
		-40	-25.8	-25.8	-7.5			
TT	3.3	27	-25.9	-25.9	-7.7			
		125	-26	-26	-7.9			

		-40		-25.8	-25.8	-7.49		
FF	3.3	27		-26	-26	-7.6		
		125		-26	-26	-7.9		
Noise Simulation								
Process	AVDD (V)	Temp (C)	noise (10-20kHz) (uV)					
		-40	111.6					
SS	3.3	27	130.2					
		125	155.2					
		-40	109.3					
TT	3.3	27	127.6					
		125	152.2					
		-40	106.9					
FF	3.3	27	124.8					
		125	149					