

Exploring the Euclidean Algorithm

Stephen Capps, Sarah Sahibzada, & Taylor Wilson

Texas A&M University

Supervisor: Sara Pollock

July 5, 2015

Overview

Introduction

- Definition

- Examples

Euclidean Algorithm Iterations and Results

- What to explore

- Distribution Results

- Notes

Introduction to Complexity Theory

Euclidean Algorithm Variations

Complexity Results

Introduction to Neural Networks

Attempts at using Neural Networks

Neural Networks Results

- Subsection Example

The Euclidean Algorithm is used to find the Greatest Common Divisor between any pair of whole numbers p, q such that $p > q$. It follows that

$$p = n_1 * q + r_1$$

$$q = n_2 * r_1 + r_2$$

$$\vdots$$
$$\vdots$$
$$\vdots$$

$$r_{k-1} = n_{k+1} * r_k$$

Where

$$r_k = \gcd(p, q).$$

For example, here is the $\text{gcd}(42, 36)$:

$$\text{gcd}(42, 36) = 6 :$$


$$42 = 1 * 36 + 6 \quad (1)$$

$$36 = 6 * 6 + 0 \quad (2)$$


As you can see, it took 2 iterations to complete the algorithm. This is what we will explore. Here are some more gcds and their iterations:

$\text{gcd}(p, q) = d$	Iterations
$\text{gcd}(689, 456) = 1$	6
$\text{gcd}(78, 45) = 3$	5
$\text{gcd}(8394, 238) = 2$	7


Next, we decided to explore the distributions of these iterations:
Do most pairs take many iterations? What is the distribution?
The following graphs are the answer to these questions.



(Figure 1)



(Figure 2)


Iterations Frequency of 50,000 random pairs of the $\gcd(p,q)$ such that $q < p < 10^{10}$ 

(Figure 3)


Euclidean Algorithm

└ Euclidean Algorithm Iterations and Results

└ Distribution Results



(Figure 4)



(Figure 5)

- ▶ in Figure 1, it must be noted that the lack of normality here is due to the lack of available bins. The size of this data set was no more than 4950, and spanned across merely 9 bins. As the number of bins needed increases, the more normal the graph becomes.
- ▶ in Figure 5, the inconsistencies in the normal distribution can be attributed to a too small a sample size. If given the computing power and time, one could compute all pairs less than 10^{1000} . Note the increasing mean iterations as we climb the upper bound.

Verbatim

Example (Theorem Slide Code)

```
\begin{frame}  
\frametitle{Theorem}  
\begin{theorem}[Mass--energy equivalence]  
$E = mc^2$  
\end{theorem}  
\end{frame}
```

References



John Smith (2012)

Title of the publication

Journal Name 12(3), 45 – 678.

The End