EVALUATION OF MEASUREMENT UNCERTAINTY

DATE: 17-02-2024

1. COMPANY NAME: Sri Balaji Castings Pvt. Ltd.

2. DEVICE UNDER CALIBRATION: VVV

Range (min): 96 Resolution (min): 85 Coefficient of Thermal Expansion (DUC)-(αD)(mm/m°C): 0.0047

3. STANDARDS / EQUIPMENT USED FOR CALIBRATION:

Sr.No	Master Name	Range/Size (min) L.C. (min)		Uncertainty (min)	Accuracy (min)	Material
Master 1	Torque Wrench - SBC2/TW/005	10 to 50	63	74	52	Carbide

4. ENVIRONMENTAL PARAMETERS

Start Temp	End Temp	Mean Temp	Ref. Temp	Thermal Expansion of master	Uncertainty of Temperature Indicator		
T1 (°C)	T2 (°C)	(T1+T2)/2)	(TR)	(mm/m°C)(αM)	(mm/m°C)(αD)	(°C) UT (±)	
41	8	24.50	20	0.0047	0.0047	61	

5. REPEATABILITY (min)

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	Standard Deviation	
4	5	7	5	7	1	2	3	4	5	1.9465	10

6. UNCERTAINTY BUDGET

	Source of uncertainty Xi	Estimates (Xi)	Probability Distribution	Туре	Factor (x)	Standard Uncertainty u = (Xi / x)	Sensitivity Coefficient (y)	Uncertainty contribution ui = (x * y)	Degree of freedom vi = (n - 1)
U1	Uncertainty due to Calibration of Master 1 mentioned in the certificate	74.0000	Normal	Туре В	2	37.0000	1	37.0000	∞
U2	Uncertainty due to Calibration of Master 2 mentioned in the certificate		Normal	Туре В	2		1		∞

Combined Uncertainty (Uc): 37.0000 min

Coverge Factor (k): -

Degree of freedom (veff): -

Expanded Uncertainty (U): ± 0.0000 min

Metric Metric Prepared By