

EVALUATION OF MEASUREMENT UNCERTAINTY

1. COMPANY NAME : Sri Balaji Castings Pvt. Ltd.

DATE : 17-02-2024

2. DEVICE UNDER CALIBRATION : nal

Range (mm) : 21	Resolution (mm) : 68	Coefficient of Thermal Expansion (DUC)-(αD)(mm/m°C) : 0.0047
------------------------	-----------------------------	---------------------------------------------------------------------------------------

3. STANDARDS / EQUIPMENT USED FOR CALIBRATION :

Sr.No	Master Name	Range/Size (mm)	L.C. (mm)	Uncertainty (mm)	Accuracy (mm)	Material
Master 1	Cast Iron Weights - SBC2/WCI/001	20	52	41	2	Carbide

4. ENVIRONMENTAL PARAMETERS

Start Temp T1 (°C)	End Temp T2 (°C)	Mean Temp (TA= (T1+T2)/2)	Ref. Temp (TR)	Thermal Expansion of master (mm/m°C) (αM)	Thermal Expansion of DUC (mm/m°C) (αD)	Uncertainty of Temperature Indicator (°C) UT (±)
52	41	46.50	20	0.0047	0.0047	2

5. REPEATABILITY (mm)

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	Standard Deviation	n
3	6	5	2	5	4	1	5	6	5	1.6865	10

6. UNCERTAINTY BUDGET

Source of uncertainty Xi		Estimates (Xi)	Probability Distribution	Type	Factor (x)	Standard Uncertainty $u = (Xi / x)$	Sensitivity Coefficient (y)	Uncertainty contribution $ui = (x * y)$	Degree of freedom $vi = (n - 1)$
U1	Uncertainty due to Calibration of Master 1 mentioned in the certificate	41.0000	Normal	Type B	2	20.5000	1	20.5000	∞
U2	Uncertainty due to Calibration of Master 2 mentioned in the certificate		Normal	Type B	2		1		∞
U3	Uncertainty due to Calibration of Master 3 mentioned in the certificate		Rect	Type B	$\sqrt{3}$		1		∞
U4	Uncertainty due to accuracy of Master 1	2.0000	Rect	Type B	$\sqrt{3}$	1.1547	1	1.1547	∞

Combined Uncertainty (Uc) : 20.5325 -

Coverge Factor (k) : -

Degree of freedom (v_{eff}): -

Expanded Uncertainty (U): ± 0.0000 -

Metric Metric

Prepared By