

EVALUATION OF MEASUREMENT UNCERTAINTY

1. COMPANY NAME : Super Auto Forge Private Limited DATE : 21-02-2024

2. DEVICE UNDER CALIBRATION : dd

Range/Size (mm) : 52	Least Count (mm) : 52
----------------------	-----------------------

3. STANDARDS / EQUIPMENT USED FOR CALIBRATION :

Sr.No	Master Name	Range/Size (mm)	L.C. (mm)	Uncertainty (mm)	Accuracy (mm)	Material
Master 1	2D Height Gauge - UM-700-YE-112	0-700	1	52	36	Carbide

4. ENVIRONMENTAL PARAMETERS

Start Temp T1 (°C)	End Temp T2 (°C)	Mean Temp (TA= (T1+T2)/2)	Ref. Temp (TR)	Thermal Expansion of master (mm/m°C)(αM)	Thermal Expansion of DUC (mm/m°C)(αD)	Uncertainty of Temperature Indicator (°C) UT (±)
41	52	46.50	20	0.0047	0.0047	63

5. REPEATABILITY (mm)

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	Standard Deviation	n
2	35	6	5	25	6	6	2	5	4	11.1076	10

6. UNCERTAINTY BUDGET

Source of uncertainty Xi		Estimates (xi)	Probability Distribution	Type	Factor (x)	Standard Uncertainty u = (xi / x)	Sensitivity Coefficient (y)	Uncertainty contribution ui = (x * y)	Degree of freedom vi = (n - 1)
U1	Uncertainty due to Calibration of Master 1 mentioned in the certificate	52.0000	Normal	Type B	2	26.0000	1	26.0000	∞
U2	Uncertainty due to Calibration of Master 2 mentioned in the certificate		Normal	Type B	2		1		∞
U3	Uncertainty due to Calibration of Master 3 mentioned in the certificate		Rect	Type B	√3		1		∞
U4	Uncertainty due to accuracy of Master 1	36.0000	Rect	Type B	√3	20.7846	1	20.7846	∞

Combined Uncertainty (Uc) : 33.2866 mm

Coverge Factor (k) : -

Degree of freedom (veff): -

Expanded Uncertainty (U): ± 0.0000 mm

Metric Metric
Prepared By