1. Write a C program to simulate dining philosopher problem

```
#include <stdio.h>

#include <stdlib.h>

#include <pthread.h>

#include <semaphore.h>

#include <unistd.h>


#define N 5


sem_t chopstick[N];

pthread_mutex_t mutex;


void *philosopher(void *num) {

    int id = *(int *)num;


    while (1) {

        pthread_mutex_lock(&mutex);

        printf("Philosopher %d status: THINKING\n", id);

        pthread_mutex_unlock(&mutex);


        sleep(1);


        pthread_mutex_lock(&mutex);

        printf("Philosopher %d status: WAITING\n", id);

        pthread_mutex_unlock(&mutex);


        sem_wait(&chopstick[id]);

        sem_wait(&chopstick[(id + 1) % N]);


        pthread_mutex_lock(&mutex);

        printf("Philosopher %d status: EATING\n", id);
```

```
        pthread_mutex_unlock(&mutex);

        sleep(2);

        sem_post(&chopstick[id]);
        sem_post(&chopstick[(id + 1) % N]);
    }
}

int main() {
    pthread_t tid[N];
    int i, ids[N];

    pthread_mutex_init(&mutex, NULL);

    for (i = 0; i < N; i++)
        sem_init(&chopstick[i], 0, 1);

    for (i = 0; i < N; i++) {
        ids[i] = i;
        pthread_create(&tid[i], NULL, philosopher, &ids[i]);
    }

    for (i = 0; i < N; i++)
        pthread_join(tid[i], NULL);

    return 0;
}
```

OUTPUT:

```
Philosopher 0 status: THINKING
Philosopher 2 status: THINKING
Philosopher 1 status: THINKING
Philosopher 3 status: THINKING
Philosopher 4 status: THINKING
Philosopher 2 status: WAITING
Philosopher 4 status: WAITING
Philosopher 4 status: EATING
Philosopher 1 status: WAITING
Philosopher 0 status: WAITING
Philosopher 2 status: EATING
Philosopher 3 status: WAITING
Philosopher 4 status: THINKING
Philosopher 1 status: EATING
Philosopher 2 status: THINKING
Philosopher 3 status: EATING
Philosopher 4 status: WAITING
Philosopher 2 status: WAITING
Philosopher 3 status: THINKING
Philosopher 0 status: EATING
Philosopher 1 status: THINKING
Philosopher 2 status: EATING
Philosopher 3 status: WAITING
Philosopher 1 status: WAITING
Philosopher 0 status: THINKING
Philosopher 4 status: EATING
Philosopher 2 status: THINKING
Philosopher 1 status: EATING
Philosopher 0 status: WAITING
Philosopher 2 status: WAITING
Philosopher 1 status: THINKING
Philosopher 4 status: THINKING
Philosopher 0 status: EATING
```

2. Write a C program to simulate deadlock detection algorithm. Use the examples solved in the class to verify your output.

```
#include <stdio.h>

#include <stdbool.h>


#define P 10

#define R 10


int allocation[P][R], request[P][R], available[R];

int n, m;


void detectDeadlock() {

   bool finish[P];

   int work[R];

   for (int i = 0; i < n; i++) finish[i] = false;

   for (int i = 0; i < m; i++) work[i] = available[i];


   bool deadlock = false;


   for (int count = 0; count < n; count++) {

      bool found = false;

      for (int p = 0; p < n; p++) {

         if (!finish[p]) {

            bool canProceed = true;

            for (int r = 0; r < m; r++) {

               if (request[p][r] > work[r]) {

                  canProceed = false;

                  break;

               }

            }

            if (canProceed) {
```

```
                for (int r = 0; r < m; r++)
                    work[r] += allocation[p][r];
                finish[p] = true;
                found = true;
            }
        }
    }
    if (!found) break;
  }

  for (int p = 0; p < n; p++) {
    if (!finish[p]) {
        deadlock = true;
        printf("Process %d is in deadlock.\n", p);
    }
  }

  if (!deadlock)
    printf("No deadlock detected.\n");
}

int main() {
  printf("Enter number of processes: ");
  scanf("%d", &n);
  printf("Enter number of resources: ");
  scanf("%d", &m);

  printf("Enter Allocation Matrix (%d x %d):\n", n, m);
  for (int i = 0; i < n; i++)
    for (int j = 0; j < m; j++)
        scanf("%d", &allocation[i][j]);
```

```
    printf("Enter Request Matrix (%d x %d):\n", n, m);
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            scanf("%d", &request[i][j]);

    printf("Enter Available Resources (%d):\n", m);
    for (int i = 0; i < m; i++)
        scanf("%d", &available[i]);

    detectDeadlock();
    return 0;
}
```

0UTPUT:

```
Enter number of processes: 3
Enter number of resources: 3
Enter Allocation Matrix (3 x 3):
0 1 0
2 0 0
3 0 3
Enter Request Matrix (3 x 3):
0 0 1
0 2 0
0 0 2
Enter Available Resources (3):
0 0 0
Process 0 is in deadlock.
Process 1 is in deadlock.
Process 2 is in deadlock.

Process returned 0 (0x0)   execution time : 91.342 s
Press any key to continue.
```