

ScanPulse Report

1. Introduction

Date of Report: May 14, 2026
Target IP: 192.xxx.x.x
Target Hostname: REDACTED
Scan Performed By: ScanPulse - Automated Detection and Security Assessment tool
Purpose: Identify vulnerabilities and security issues in the target environment.

2. Scan Summary

2.1 Nmap Scan Summary

Scan Start Time: May 14, 2026 17:01:36
Scan End Time: May 14, 2026 17:01:52
Total Ports Scanned: 3
Open Ports:


Port Id	Service Name
53	domain
80	http
443	http

3. Vulnerability Assessment

3.1 Open Ports and Services

- Port 53 (domain):**
Recommendation: No specific recommendation available – please review the service configuration.
- Port 80 (http):**
Recommendation: Ensure that the HTTP service is secure and consider using HTTPS for encrypted communication.
- Port 443 (http):**
Recommendation: Ensure HTTPS configuration uses strong encryption standards and secure certificates.

4. Vulnerability Risk & Remediation Metrics



CVE-2023-28450

- Base Score: 7.5
- Severity: HIGH
- Attack Vector: NETWORK
- Privileges Required: NONE
- Confidentiality Impact: NONE
- Integrity Impact: NONE
- Description: An issue was discovered in Dnsmasq before 2.90. The default maximum EDNS.0 UDP packet size was set to 4096 but should be 1232 because of DNS Flag Day 2020.
- Remediation: Vendor Remediation: Update to the latest version as per vendor advisory.

CVE-2022-41556

- Base Score: 7.5
- Severity: HIGH
- Attack Vector: NETWORK
- Privileges Required: NONE
- Confidentiality Impact: NONE
- Integrity Impact: NONE
- Description: A resource leak in gw_backend.c in lighttpd 1.4.56 through 1.4.66 could lead to a denial of service (connection-slot exhaustion) after a large amount of anomalous TCP behavior by clients. It is related to RDHUP mishandling in certain HTTP/1.1 chunked situations. Use of mod_fastcgi is, for example, affected. This is fixed in 1.4.67.
- Remediation: Vendor Remediation: Update to the latest version as per vendor advisory.

CVE-2023-50387

- Base Score: 7.5
- Severity: HIGH

- Attack Vector: NETWORK
- Privileges Required: NONE
- Confidentiality Impact: NONE
- Integrity Impact: NONE
- Description: Certain DNSSEC aspects of the DNS protocol (in RFC 4033, 4034, 4035, 6840, and related RFCs) allow remote attackers to cause a denial of service (CPU consumption) via one or more DNSSEC responses, aka the "KeyTrap" issue. One of the concerns is that, when there is a zone with many DNSKEY and RRSIG records, the protocol specification implies that an algorithm must evaluate all combinations of DNSKEY and RRSIG records.
- Remediation: <https://msrc.microsoft.com/update-guide/vulnerability/CVE-2023-50387>;
<https://msrc.microsoft.com/update-guide/vulnerability/CVE-2023-50387>

CVE-2022-22707

- Base Score: 5.9
- Severity: MEDIUM
- Attack Vector: NETWORK
- Privileges Required: NONE
- Confidentiality Impact: NONE
- Integrity Impact: NONE
- Description: In lighttpd 1.4.46 through 1.4.63, the mod_extforward_Forwarded function of the mod_extforward plugin has a stack-based buffer overflow (4 bytes representing -1), as demonstrated by remote denial of service (daemon crash) in a non-default configuration. The non-default configuration requires handling of the Forwarded header in a somewhat unusual manner. Also, a 32-bit system is much more likely to be affected than a 64-bit system.
- Remediation: Vendor Remediation: Update to the latest version as per vendor advisory.

5. Conclusion

This assessment highlights the key areas where the target system can be improved. Addressing the identified issues will enhance the security posture and reduce potential risks. Regular security assessments and best practices should be followed to maintain a secure environment.

6. Appendices

6.1 Tools Used

- Nmap: Network scanner for identifying open ports and services.

6.2 References

- Nmap Documentation: <https://nmap.org/docs.html>
- NVD: <https://nvd.nist.gov/>