Has a developer you know lost their peace? Is that developer you? Find a more peaceful way.

honest-gratitude / production

31 Agent

@workspace/api-server
app.snapserve.ai
Online

Postgres
Online
postgres-volume

@workspace/gender-s...
Online

@workspace/api-server

Deployments Variables Metrics Console Settings

Filter Settings... /

Source

Source Repo

srundme/voiceorch Disconnect

Root Directory

Configure where we should look for your code. Docs

/

Branch connected to production

Changes made to this GitHub branch will be automatically pushed to this environment.

GitHub Repo not found

Wait for CI

Trigger deployments after all GitHub actions have completed successfully.

Wait for CI

Networking

Public Networking

Access your application over HTTP with the following domains

workspaceapi-server-production-99ef.up.railway.app
→ Port 8888

app.snapserve.ai
→ Port 8888 · DNS records

+ Custom Domain + TCP Proxy

Private Networking

Communicate with this service from within the Railway network.

workspaceapi-server.railway.internal IPv4 & IPv6
Ready to talk privately · You can also simply call me workspaceapi-server

Static Outbound IPs

This will assign a permanent IP address which your service will use for outbound traffic, however it cannot be used for inbound traffic.

Enable Static IPs

Outbound IPv6

Enable your service to make outbound connections to IPv6 destinations.

Enable Outbound IPv6

Edge

Under Attack Mode

Being DDoSed? One click puts a browser check in front of your domains, shedding bot floods at the edge. Real visitors solve it once and browse normally.

Until turned off Activate

Takes effect across the globe in ~20 seconds.

CDN Caching

Cache static assets and optionally HTML at the edge. Reduces latency and origin load for your service's domains.

Enable CDN Caching

Scale

Regions & Replicas

Deploy replicas per region for horizontal scaling.

Southeast Asia (Singapore, Singapore) 1 Replica

+ Add Region

Replica Limits

Allocate a maximum vCPU and Memory for each replica.

CPU: **24 vCPU** Plan limit: 24 vCPU

Memory: **24 GB** Plan limit: 24 GB

Upgrade for higher limits

Build

Builder

The value is set in `/artifacts/api-server/railway.json` Open file

Dockerfile Dockerfile
Build with a Dockerfile using BuildKit. Docs

Watch Paths

Gitignore-style rules to trigger a new deployment based on what file paths have changed. Docs

The value is set in `/artifacts/api-server/railway.json` Open file

artifacts/api-server/**
artifacts/dashboard/**
artifacts/admin/**
artifacts/snapserve-book/**

Source
Networking
Edge
Scale
Build
Deploy
Config-as-code
Feature-flags
Danger

lib/**

pnpm-lock.yaml

pnpm-workspace.yaml

Dockerfile

Deploy

Custom Start Command

Command that will be run to start new deployments. Docs ↗

+ Start Command

+ Add pre-deploy step (Docs ↗)

Teardown

Configure old deployment termination when a new one is started. Docs ↗

Enable Teardown

Cron Schedule

Run the service according to the specified cron schedule.

+ Add Schedule

Healthcheck Path

Endpoint to be called before a deploy completes to ensure the new deployment is live. Docs ↗

The value is set in `/artifacts/api-server/railway.json` Open file ↗

/api/healthz

Healthcheck Timeout

Number of seconds we will wait for the healthcheck to complete. Docs ↗

The value is set in `/artifacts/api-server/railway.json` Open file ↗

60

Serverless

Containers will scale down to zero and then scale up based on traffic. Requests while the container is sleeping will be queued and served when the container wakes up. Docs ↗

Enable Serverless

Restart Policy

Configure what to do when the process exits. Docs ↗

The value is set in `/artifacts/api-server/railway.json` Open file ↗

On Failure

Restart the container if it exits with a non-zero exit code.

Number of times to try and restart the service if it stopped due to an error.

The value is set in `/artifacts/api-server/railway.json` Open file ↗

10

Config-as-code

Railway Config File

Manage your build and deployment settings through a config file. Docs ↗

artifacts/api-server/railway.json

Feature-flags

Skipped Builds

Skips the build step when the same source code was already built in a previous deployment. GitHub only. Learn more ↗

Delete Service

Deleting this service will **permanently delete** all its deployments and remove it from **this environment**. This cannot be undone.

Delete service