Assignment 06 CODE -

SERVER -

%%writefileserver.cpp

```
#include<iostream>
#include<cstring>
#include<cctype>
#include<algorithm>
#include<sys/socket.h>
#include<netinet/in.h>
#include<unistd.h>

#definePORT8080
#defineMAXLINE 1024

//Datastructureto hold menu choice and message payload
struct Packet {
    int choice;
    chartext[MAXLINE];
};

//Functiontochange case (Uppercase <-> Lowercase)
std::stringchangeCase(std::string str) {
    for(char&c:str) {
        if(std::isupper(c)) c = std::tolower(c);
        elseif(std::islower(c)) c = std::toupper(c);
    }
    return str;
}

//Functiontoreverse the string
std::stringreverseString(std::string str) {
    std::reverse(str.begin(), str.end());
    return str;
}

int main() {
    int sockfd;
    structsockaddr_in servaddr, cliaddr;

    if((sockfd=socket(AF_INET, SOCK_DGRAM, 0)) < 0) {
        perror("Socket creation failed");
        return -1;
    }
```

```
 memset(&servaddr, 0, sizeof(servaddr));
   memset(&cliaddr, 0, sizeof(cliaddr));

   servaddr.sin_family = AF_INET;
   servaddr.sin_addr.s_addr = INADDR_ANY;
   servaddr.sin_port = htons(PORT);

   if (bind(sockfd, (const struct sockaddr *)&servaddr, sizeof(servaddr)) < 0) {
      perror("Bind failed");
      return -1;
   }

   std::cout << "[SERVER] UDP Server running on port " << PORT << "...\n";

   while (true) {
      Packet pkt;
      socklen_t len = sizeof(cliaddr);

      int n = recvfrom(sockfd, &pkt, sizeof(pkt), MSG_WAITALL, (struct sockaddr *)&cliaddr,
&len);
      if (n <= 0) continue;

      if (pkt.choice == 3) {
         std::cout << "[SERVER] Client requested exit. Closing connection.\n";
         std::string exitMsg = "Session ended by server.";
         sendto(sockfd, exitMsg.c_str(), exitMsg.length(), MSG_CONFIRM, (const struct
sockaddr *)&cliaddr, len);
         break;
      }

      std::cout << "[SERVER] Choice Received: " << pkt.choice << " | Input Text: \"" <<
pkt.text << "\"\n";

      std::string result;
      if (pkt.choice == 1) {
         result = changeCase(pkt.text);
      } else if (pkt.choice == 2) {
         result = reverseString(pkt.text);
      } else {
         result = "Invalid Option";
      }

      sendto(sockfd, result.c_str(), result.length(), MSG_CONFIRM, (const struct sockaddr
*)&cliaddr, len);
   }

   close(sockfd);
   return 0;
```

```
}
```

CLIENT -

```
%%writefile client.cpp

#include <iostream>
#include <cstring>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <unistd.h>

#define PORT 8080
#define MAXLINE 1024

struct Packet {
    int choice;
    char text[MAXLINE];
};

int main() {
    int sockfd;
    structsockaddr_inservaddr;

    if((sockfd=socket(AF_INET, SOCK_DGRAM, 0)) < 0) {
        perror("Socketcreation failed");
        return -1;
    }

    memset(&servaddr,0,sizeof(servaddr));
    servaddr.sin_family=AF_INET;
    servaddr.sin_port=htons(PORT);
    servaddr.sin_addr.s_addr = inet_addr("127.0.0.1");

    while (true) {
        std::cout<<"\nMENU\n";
        std::cout<<"1.Change Case\n";
        std::cout<<"2.Reverse String\n";
        std::cout<<"3.Exit\n";
        std::cout<<"Enteryour choice (1-3): ";

        Packet pkt;
        if(!(std::cin>>pkt.choice)) break;
        std::cin.ignore();//Flush newline character from buffer
```

```
        if (pkt.choice == 3) {
            memset(pkt.text,0,sizeof(pkt.text));
            sendto(sockfd,&pkt,sizeof(pkt),MSG_CONFIRM, (const struct sockaddr
*)&servaddr, sizeof(servaddr));
            std::cout<<"[CLIENT]Exitingclient application.\n";
            break;
        }

        if(pkt.choice!=1&&pkt.choice!=2) {
            std::cout<<"Invalidselection!Please choose 1, 2, or 3.\n";
            continue;
        }

        std::cout << "Enter string: ";
        std::string inputStr;
        std::getline(std::cin, inputStr);

        strncpy(pkt.text,inputStr.c_str(),sizeof(pkt.text) - 1);
        pkt.text[sizeof(pkt.text) - 1] = '\0';


        sendto(sockfd,&pkt,sizeof(pkt),MSG_CONFIRM, (const struct sockaddr *)&servaddr,
sizeof(servaddr));

        char buffer[MAXLINE];
        socklen_t len = sizeof(servaddr);
        intn=recvfrom(sockfd,buffer,MAXLINE - 1, MSG_WAITALL, (struct sockaddr
*)&servaddr, &len);
        buffer[n] = '\0';

        std::cout<<"[CLIENT]ServerResult: " << buffer << "\n";
    }

    close(sockfd);
    return 0;
}
```

OUTPUT -



GITHUB LINK-

https://github.com/srushtijayaraman/CN-Lab