# **React.js Component Creation**

Name : MUPPARAJU ANURADHA

Email :chowdaryanuradha55@gmail.com


Phone no : 6302366735

Roll NO : 20HU1A0408

sCollege Name: Chebrolu engineering college

# **Source Code:**


### **CARD COMPONENT:**



#### **BUTTON COMPONENT:**

```
■ button.css ×
C
                                                                                                                       card > src > components > button > ₹ button.css > ६ button
     V INTERSHIP
                                         1 import React from 'react'
2 import './button.css'
      ∨ 📹 card
                                                                                                                               outline:none;
border:none;
       > node_modules
        > 🗱 public
H
                                                                                                                               width:90%;
padding: 10px 5px;
background: aqua;
border-radius: 5px;
font-weight: bold;
         ∨ 📹 button
          button.css
Button.jsx
                                                                                                                                 margin-inline: auto;
                                                                                                                       11 }
12
13 button:hover{
14 opacity:.6;
15 }
          card.css
         ∨ 📹 images
            image1.jpeg
            image2.jpeg
            image3.jpeg
            image4.jpeg
            image5.jpeg
           image6.jpeg
           ☐ App.css
           index.css
           JS index.js
          .gitignore
          package-lock.json
package.json
          README.md
> OUTLINE > TIMELINE
```

#### **APP COMPONENT:**




## Approach:

1. initially taking an array of objects like below


```
const cards = [
   url:image1,
   title: "Audi R8",
   description: "The definition of a supercar describes an expensive car that's flashy,"
   url:image2,
   title: "Maserati MC20",
   description: "The definition of a supercar describes an expensive car that's flashy"
   url:image3,
   title: "Porsche 911 GT3 RS",
   description: "The definition of a supercar describes an expensive car that's flashy"
   url:image4,
   title: "Lamborghini Huracan Tecnica",
   description: "The definition of a supercar describes an expensive car that's flashy"
   url:image5,
   title: "Rimac Nevera",
   description: "The definition of a supercar describes an expensive car that's flashy"
   url:image6,
   title: "ferrari F9",
   description: "The definition of a supercar describes an expensive car that's flashy"
```


- Passing this card array to child (card component) of App component by using props;
- 3 . getting data as argument like {card} in card component.
- 4 . in card component i use one state [show, set Show] to get extra info as description.
- 5. When we click the button then show becomes true by assigning set Show (! show).

#### **OUTPUT:**



#### **AFTER BUTTON CLICKS:**





#### GitHub link:

https://github.com/4727yesuraju/card live

demo: <a href="https://yesucard.netlify.app">https://yesucard.netlify.app</a>