EXPERIMENT - 10

Aim: To simulate routing information Protocol (RIP) using Cisco Packet Tracer.

IP Configuration:

Device	Interface	IP Address
PC0	Fast Ethernet	10.0.0.2/8
Router 0	f0/0	10.0.0.1/8
Router 0	S0/0/1	192.168.1.254/30
Router 1	S0/0/1	192.168.1.253/30
Router 1	S0/0/0	192.168.1.246/30
Router 2	S0/0/0	192.168.1.254/30
Router 2	S0/0/1	192.168.1.253/30
PC1	Fast Ethernet	20.0.0.2/8

Procedure:-

* Create the topology with 3 routers and 2 PCs
* Connect the routers using serial cables and connects PCs to routers
* Assign IP
* Enable router interfaces
* Configure Remaining interfaces

* Enable RIP on router 0 and configure RIP on router 1 and 2.

* From PC0, use ping 20.0.0.2 to verify connection.

* Use tracer to observe the route taken by packet.

* Disconnect the direct Router 0 and Router 2 link and Observe.

```
Router(config-if)#ip address 10.0.0.1
255.0.0.0 Router(config-if)#no shutdown
Router(config-if)#exit
Router(config)#
Router#show controllers serial 0/0/0
Interface Serial0/0/0
Hardware is PowerQUICC MPC860
DCE V.35, clock rate 2000000
[Output omitted]


Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface serial 0/0/0
Router(config-if)#ip address 192.168.1.249 255.255.255.252
Router(config-if)#clock rate 64000
Router(config-if)#bandwidth 64
Router(config-if)#no shutdown
Router(config-if)#exit
Router(config)#interface serial 0/0/1
Router(config-if)#ip address 192.168.1.254 255.255.255.252
Router(config-if)#clock rate 64000
Router(config-if)#bandwidth
64 Router(config-if)#no
shutdown Router(config-
```

Router1

```
Router>enable
Router#configure
terminal
Enter configuration commands, one per line. End with CNTL/Z.
```

Result:

Thus RIP was successfully simulated in Cisco Packet tracer.