

# Rajalakshmi Engineering College

Name: Sruthi Dinesh  
Email: 240701536@rajalakshmi.edu.in  
Roll no: 240701536  
Phone: 7845725087  
Branch: REC  
Department: CSE - Section 7  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : COD

##### 1. Problem Statement

Tony is an e-learning platform administrator, he oversees the user ratings for various online courses offered in the platform.

To enhance user experience, you should assist him in utilizing a HashMap to store course ratings given by learners. Regularly, he analyzes this data to identify the highest and lowest-rated courses, enabling targeted improvements and ensuring the quality of the educational content. This process assists in maintaining a competitive and engaging online learning environment for the users.

##### ***Input Format***

The input consists of a string representing the course name followed by a double value representing the course's rating, in separate lines.

The input is terminated by entering "done".

### **Output Format**

The first line of output prints the string "Highest Rated Course: " followed by the highest-rated course.

The second line prints the string "Lowest Rated Course: " followed by the lowest-rated courses.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: DSA

4.0

OOPS

4.2

C

3.2

done

Output: Highest Rated Course: OOPS

Lowest Rated Course: C

### **Answer**

```
import java.util.HashMap;
import java.util.Map;
import java.util.Scanner;

class CourseAnalyzer {
    public Map<String, String>
    identifyHighestAndLowestRatedCourses(Map<String, Double> courseRatings) {
        double highestRating = Double.MIN_VALUE;
        double lowestRating = Double.MAX_VALUE;
        String highestRatedCourse = "";
        String lowestRatedCourse = "";

        for (Map.Entry<String, Double> entry : courseRatings.entrySet()) {
            String course = entry.getKey();
            double rating = entry.getValue();
```

```

        if (rating > highestRating) {
            highestRating = rating;
            highestRatedCourse = course;
        }
        if (rating < lowestRating) {
            lowestRating = rating;
            lowestRatedCourse = course;
        }
    }

    Map<String, String> result = new HashMap<>();
    result.put("highest", highestRatedCourse);
    result.put("lowest", lowestRatedCourse);
    return result;
}
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Map<String, Double> courseRatings = new HashMap<>();

        while (true) {
            String courseName = scanner.nextLine();
            if (courseName.equalsIgnoreCase("done")) {
                break;
            }
            double rating = Double.parseDouble(scanner.nextLine().trim());
            courseRatings.put(courseName, rating);
        }

        CourseAnalyzer analyzer = new CourseAnalyzer();
        Map<String, String> result =
        analyzer.identifyHighestAndLowestRatedCourses(courseRatings);

        System.out.printf("Highest Rated Course: %s\n", result.get("highest"));
        System.out.printf("Lowest Rated Course: %s", result.get("lowest"));

        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

## 2. Problem Statement

The city library maintains a record of books available for lending. Each book is uniquely identified by its ISBN number, along with its title and author. The librarian wants to efficiently store and manage these records, ensuring books can be listed in the order they were added.

Your task is to implement a Library Management System using HashSet where:

The librarian adds books with ISBN, title, and author. The librarian can remove books by providing an ISBN. Finally, the librarian displays the available books in the order they were added.

Implement a class Library that will handle these operations. The main function should manage user input and interact with the Library class accordingly.

### **Input Format**

The first line contains an integer  $n$  – the number of books to be added.

The next  $n$  lines contain three values: ISBN (integer), Title (string without spaces), and Author (string without spaces).

1. An integer employee\_id
2. A string title
3. A string author name

The next line contains an integer  $m$  – the number of books to be removed.

The next  $m$  lines follow, each contains an ISBN number to remove.

### **Output Format**

The output prints a list of books available in the library after performing all operations in the format:

"ISBN: <isbn>, Title: <title>, Author: <author>"

If no books remain, print: "No books available"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

1234 JavaCompleteGuide JohnDoe

5678 PythonBasics JaneDoe

9012 DataStructures AliceSmith

1

5679

Output: ISBN: 1234, Title: JavaCompleteGuide, Author: JohnDoe

ISBN: 9012, Title: DataStructures, Author: AliceSmith

ISBN: 5678, Title: PythonBasics, Author: JaneDoe

### **Answer**

```
import java.util.*;
```

```
class Book {
    int isbn;
    String title, author;

    public Book(int isbn, String title, String author) {
        this.isbn = isbn;
        this.title = title;
        this.author = author;
    }

    public boolean equals(Object obj) {
        if (this == obj) return true;
        if (obj == null || getClass() != obj.getClass()) return false;
        Book book = (Book) obj;
        return isbn == book.isbn;
    }

    public int hashCode() {
        return Objects.hash(isbn);
    }
}
```

```

    }
}

class Library {
    HashSet<Book> books = new HashSet<>();

    void addBook(int isbn, String title, String author) {
        books.add(new Book(isbn, title, author));
    }

    void removeBook(int isbn) {
        books.removeIf(book -> book.isbn == isbn);
    }

    void displayBooks() {
        if (books.isEmpty()) {
            System.out.println("No books available");
        } else {
            for (Book book : books) {
                System.out.println("ISBN: " + book.isbn + ", Title: " + book.title + ",
Author: " + book.author);
            }
        }
    }
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        Library library = new Library();
        int n = sc.nextInt();
        for (int i = 0; i < n; i++) {
            int isbn = sc.nextInt();
            String title = sc.next();
            String author = sc.next();
            library.addBook(isbn, title, author);
        }
        int m = sc.nextInt();
        for (int i = 0; i < m; i++) {
            int isbn = sc.nextInt();
            library.removeBook(isbn);
        }
        library.displayBooks();
    }
}

```

```
        sc.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

A linguist named Meera is classifying a list of words based on their first character. She wants to store words grouped by their starting letter using a `TreeMap` so that the groups appear in sorted order of characters (i.e., 'a' to 'z'). For each letter, all words starting with that letter should be stored in the order they appear.

Implement the logic inside a class named `WordClassifier` using the `TreeMap<Character, List<String>>` collection.

#### **Input Format**

The first line of the input contains an integer `n`, representing the number of words.

The next `n` lines each contain a word.

#### **Output Format**

The first line of the output prints: "Grouped Words by Starting Letter:"

The next lines print each character key and its list of words in the format:

"letter: word1 word2 word3..."

..."

Refer to the sample output for formatting specifications.

#### **Sample Test Case**

Input: 5

dog  
deer  
cat  
cow  
camel

Output: Grouped Words by Starting Letter:

c: cat cow camel

d: dog deer

### **Answer**

```
import java.util.*;

class WordClassifier {
    public void classifyWords(List<String> words) {
        TreeMap<Character, List<String>> map = new TreeMap<>();

        for (String word : words) {
            char initial = word.charAt(0);
            if (!map.containsKey(initial)) {
                map.put(initial, new ArrayList<>());
            }
            map.get(initial).add(word);
        }

        System.out.println("Grouped Words by Starting Letter:");
        for (Map.Entry<Character, List<String>> entry : map.entrySet()) {
            System.out.print(entry.getKey() + ": ");
            for (String word : entry.getValue()) {
                System.out.print(word + " ");
            }
            System.out.println();
        }
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        List<String> words = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            words.add(sc.nextLine());
        }
    }
}
```



```
}  
    WordClassifier classifier = new WordClassifier(),  
    classifier.classifyWords(words);  
}  
}
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Arjun is working on a program that checks if one set of numbers is a subset of another. If Set B is a subset of Set A, the program should print "YES" followed by the sorted elements of Set B. If Set B is not a subset of Set A, the program should print "NO" followed by the average of all elements from both sets combined, rounded to two decimal places.

Implement a class Solution with the required method to perform the subset check using TreeSet in Java.

##### **Input Format**

The first line contains an integer n - the number of elements in Set A.

The second line contains n space-separated integers - the elements of Set A.

The third line contains an integer m - the number of elements in Set B.

The fourth line contains m space-separated integers - the elements of Set B.

##### **Output Format**

If Set B is a subset of Set A, print "YES" followed by the sorted values of Set B.

Otherwise, print "NO" followed by the average of all numbers in both sets (rounded to two decimal places).

Refer to the sample output for formatting specifications.

### Sample Test Case

Input: 5

1 2 3 4 5

3

2 3 5

Output: YES 2 3 5

### Answer

```
import java.util.*;
```

```
class Solution {  
    public static void checkSubset(TreeSet<Integer> setA, TreeSet<Integer> setB,  
int totalElements, double sum) {  
        if (setA.containsAll(setB)) {  
            System.out.print("YES ");  
            for (int num : setB) {  
                System.out.print(num + " ");  
            }  
            System.out.println();  
        } else {  
            double average = sum / totalElements;  
            System.out.printf("NO %.2f%n", average);  
        }  
    }  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        TreeSet<Integer> setA = new TreeSet<>();  
        long sum = 0;  
        for (int i = 0; i < n; i++) {  
            int num = sc.nextInt();  
            setA.add(num);  
            sum += num;  
        }  
        int m = sc.nextInt();  
        TreeSet<Integer> setB = new TreeSet<>();  
        for (int i = 0; i < m; i++) {  
            int num = sc.nextInt();  
            setB.add(num);  
        }  
    }  
}
```

```
        sum += num;
    }
    Solution.checkSubset(setA, setB, n + m, sum);
    sc.close();
}
}
```

**Status :** Correct

**Marks :** 10/10