

A grammar of graphics framework for generalized parallel coordinate plots

AUTHOR 1^{1*} AUTHOR 2² AUTHOR 3³

¹ University 1; ² University 2; ³ University 3

August 18, 2021

Abstract

Parallel coordinate plots (PCP) are a useful tool in exploratory data analysis of high-dimensional numerical data. The use of PCPs is limited when working with categorical variables or a mix of categorical and continuous variables. In this paper, we propose generalized parallel coordinate plots (GPCP) to extend the ability of PCPs from just numeric variables to dealing seamlessly with a mix of categorical and numeric variables in a single plot. In this process we find that existing solutions for categorical values only, such as hammock plots or parsets become edge cases in the new framework. By focusing on individual observations rather than a marginal frequency we gain additional flexibility. The resulting approach is implemented in the R package ggpcp.

1 Introduction

Few approaches in data visualization exist that are truly high-dimensional. Most visualizations are projections of data into two or three dimensions enhanced by additional mappings to plot aesthetics, such as point size and color, or facetting. Parallel coordinate plots are one of the exceptions: in parallel coordinate plots we can actually visualize an arbitrary many number of variables to get a visual summary of a high-dimensional data set. In a parallel coordinate plot each variable takes the role of a vertical (or parallel) axis; giving the visualization its name. Multivariate observations are then plotted by connecting their respective values on each axis across all axes using polylines (cf. Figure 1). For just two variables this switch from orthogonal axes to parallel axes is equivalent to a switch from the familiar Euclidean geometry to the Projective Space. In the projective space, points take the role of lines, while lines are replaced by points, i.e. points falling on a line in the Euclidean space correspond to lines crossing in a single point in the Projective Space. This duality provides a good basis for interpreting geometric features observed in a parallel coordinate plot [Inselberg, 1985].

The origins of parallel coordinate plots date back to the 19th century and are, depending on the source, either attributed to d'Ocagne [1885] or Gannett [1880]. Modern era parallel coordinate plots go back to Inselberg [1985] and Wegman [1990]. Parallel coordinate plots are used in an exploratory setting as a way to get a high-level overview of the marginal distributions involved, to identify outliers in the data and to find potential clusters of points. In the absence of those, Parallel Coordinate Plots are often criticized for the amount of clutter they produce, resembling a game of mikado rather than organized data. This clutter is sometimes combatted by the use of α -blending [Miller and Wegman, 1991], density estimation [Heinrich and Weiskopf, 2009], or edge-bundling parallel coordinate plots [McDonnell and Mueller, 2008]. For a detailed overview of these and other techniques see Heinrich and Weiskopf [2013].

However, parallel coordinate plots have some shortcomings. **XXXX after bashing clutter in pcps, 'some shortcomings' feels like rubbing it in :)** The biggest challenge comes when working with categorical

*Corresponding author: xxx




Figure 1: Sketch of a parallel coordinate plot of two observations in four dimensions. Each dimension is shown as a vertical axis, observations are connected by polylines from one axis to the next.

variables. In current solutions, levels of categorical variables are transformed to numbers and variables are then used as if they were numeric. This introduces a lot of ties into the data, and the resulting parallel coordinate plot becomes uninformative, as it only shows lines from each level of one variable to all levels of the next variable. Some versions of parallel coordinate plots have been specifically developed to deal with categorical data, e.g. parallel set plots [Kosara et al., 2006], Hammock plots [Schonlau, 2003], and common angle plots [Hofmann and Vendettuoli, 2013]. These solutions all have in common that they work with tabularized data and show bands of observations from one categorical variable to the next. Hammock plots and common angle plots provide solutions to mitigate the sine-illusion’s effects [Day and Stecher, 1991, VanderPlas and Hofmann, 2015] on parallel sets plots. An attempt to combine categorical and numeric variables in a parallel coordinate plot is introduced in the categorical parallel coordinate plots of Pilhöfer and Unwin [2013]. These plots provide an extension to parallel sets that allows numeric variables to be included in the plot. Similar to parallel sets, this approach is also based on marginal frequencies for the categorical variables. Categorical parallel coordinate plots are the closest of these variations to our solution, but they are not implemented in the ggplot2 framework and can therefore not be further extended.

Various packages in R [R Core Team, 2019] exist that contain an implementation of one of the parallel coordinate plots. The function "parcoord" in the MASS package [Venables and Ripley, 2002] makes use of the base plot system of R to draw parallel coordinate plots. The function "cpcp" in package iplots implements the parallel coordinate plot [Pilhöfer and Unwin, 2013]. Developments based on the grammar of graphics [Wilkinson, 2005] and the ggplot2 [Wickham, 2016] framework are, e.g. the function 'ggparcoord' in GGally [Schloerke et al., 2018] or ggparallel [Hofmann and Vendettuoli, 2016] which provide an implementation of Hammock and common-angle plots.

Those packages based on ggplot2 make use of ggplot2, but are actually wrapper of existing functions for highly specialized plots with tens of parameters, which do not allow the full flexibility of ggplot2 and do not make use of ggplot2’s layer framework.

The remainder of the paper is organized as follows: section 2 describes the data processing for parallel coordinate plots.

2 Data management

The idea behind this re-implementation of parallel coordinate plots is to expose parallel coordinate plots at a functional level. Rather than using a single function with parameters controlling every aspect, we separate the data management from the visual rendering.

One of the biggest strengths of the Grammar of Graphics is its mapping between data variables and

visual aesthetics. In standard plots any mapping is a function between one aesthetic and one data variable. In a parallel coordinate plot, this one-to-one mapping between data and plot aesthetics is seemingly turned into a one-to-many mapping between arbitrarily many data variables to the x axis. However, by transforming the wide form of the data set into a long form [Wickham, 2007, Wickham et al., 2021, Wickham, 2014, 2021], we get to a form of the dataset in which we achieve a one-to-one mapping to a now discrete x axis consisting of the (names of the) original data variables.

2.1 Variable selection and data wrangling

`pcp_select(data, ...)` allows a selection of variables to be included in the parallel coordinate plot. Variables can be specified by

- position, e.g. 1:4, 7, 5, 4,
- name, e.g. `class`, `age`, `sex`, `aede1:aede3` or
- using pattern selectors, e.g. `starts_with("aede")`, see `?tidyselect::select_helpers`

or any combination thereof. Variables can be selected multiple times and will then be included in the data and the resulting plot multiple times. The order in which variables are selected determines the order in which the corresponding axis is drawn in the parallel coordinate plots. `pcp_select` transforms the selected variables to long form and embellishes the data set with a number of additional variables. All of the newly created and added variables start with the prefix `pcp_`:

- `pcp_x`: discrete variable consisting of the names of the selected variables in the order that they were selected - this is the order in which the variables will be included in the plot.
- `pcp_y`: numeric variable containing the values of all of the selected variables. In case a selected variable is not numeric, it is converted to a factor variable and the (numeric) factor levels are saved in `pcp_y`.
- `pcp_level`: character variable containing the factor levels of selected data variables. In case of numeric variables, the data values are stored (in textual form).
- `pcp_class`: character variable containing the class information of a selected variable.
- `pcp_id`: integer variable identifying each observation in the original dataset. This variable will be used as grouping variable to identify which values should be connected by a line segment in the parallel coordinate plot.

XXX reordering variables in the parallel coordinate plot could be done before the selection by `pcp_select` or after it by re-ordering the levels in the `pcp_x` variable. We should probably include an example.

XXX univariate transformations, such as reversing an axis for a variable can be done using a `mutate` statement before the variable selection. example? changing order of levels on a categorical variable or a log transform or square root transformation work the same.

2.2 Scaling

`pcp_scale(data, method)` scales the values on each axis and determines the relative relationship of the axes to each other.

`method` is a character string specifying the method to be used when transforming the values of each variable into a common y axis. By default, the method `uniminmax` is chosen, which univariately scales each variable into a range of [0,1] with a minimum at 0 and the maximum at 1. `globalminmax` maps the values across all axes into a an interval of [0,1]. The method `raw` leaves all values unscaled. Both of these methods should only be used if the values across all variables are comparable. The method `robust` normalizes values univariately by mapping the median value to 0.5 and a robust 95% confidence interval (based on the median absolute deviation) to an interval of 0 to 1.

Figure 2 shows two of the scaling methods at the example of the olive oil data [Cook and Swayne, 2007, Wickham et al., 2011, Forina et al., 1983]: measurements of fatty acids in 572 olive oils from three different

regions in Italy are visualized as parallel coordinate plots. Similar to the findings in Cook and Swayne [2007], we see that eicosenoic acid is only found in increased quantities in olive oils from Southern Italy. Quantities of oleic and linoleic acids allow a separation between olive oils from Sardinia and Northern Italy. Both scaling methods enable us to find these conclusions.

2.3 Breaking ties on categorical axes

`pcp_arrange(data, method, space)` provides a rescaling of values on categorical axes to break ties. `method` is a parameter specifying which variables to use to break ties. The two implemented methods are "from-left" and "from-right", meaning that ties are broken using a hierarchical ordering using variables' values from the left or the right, respectively. The parameter `scale` specifies the amount of the 'y' axis to use for space between levels of categorical variables. By default, 5% of the axis is used for spacing.

Figure 3 shows several approaches of dealing with categorical variables in parallel coordinate plots. The left-most panel shows two categorical variables and the typical net of lines that forms between them in an original parallel coordinate plot. The other three panels show three different approaches of breaking the ties resulting from the categorical variables, with our favored solution shown on the right: all observations are spaced out evenly. This results in a natural visualization of the marginal frequencies along each axis (additionally enhanced by the lightly greyed boxes grouping observations in the same category). The ordering of the observations within the level is such that a minimal number of line crossings occurs between the axes. This method of dealing with categorical variables is the one we propose in the generalized parallel coordinate plot. While it is aesthetically pleasing, it also allows us in the spirit of the original parallel coordinate plots to follow an individual observation from left to right through the plot even for categorical variables. The other two solutions in the middle panels of Figure 3 show two intermediary solutions of breaking ties in categorical variables: jittering and equi-spaced (unordered) values.

3 The Generalized Parallel Coordinate Plot

XXX We need to include some code somewhere to also show the 'how'.

Figure 4 shows a first generalized parallel coordinate plot of the Palmer penguins data [Horst et al., 2020]. The data consists of body measurements, such as weight, flipper length, bill length, and depth, of three species of penguins. What can be seen is that Adelie penguins generally have smaller bill lengths than the other two species, while Gentoo penguins can be distinguished from the other two species by their relatively larger flipper lengths. The lines in Figure 4 are colored by sex of penguins. What can be seen is that within each species, the males tend to be larger in size and heavier than the females. For several of the penguins, sex could not be determined because either the sexing primer did not amplify or no blood sample was obtained [penguins2]. These penguins are represented by black lines. Based on these penguins' body measurements within the context of the other penguins, we can make some suggestions regarding their sex. Figure 5 shows body measurements of penguins in generalized parallel coordinate plots faceted by species. Chinstrap penguins are excluded because all of their individuals in the data have a gender assigned. The general pattern of measurements of the Gentoo penguins suggests that all four individuals with missing sex information are female (for further evidence, we find from the original data that their nest partners are all sexed as male). For Adelie penguins the situation is not quite as clear-cut, but based on body weight and bill length measurements the three lightest penguins might be female, while the heaviest one could be male. The fifth penguin walks the line between typical male and typical female measurements.




Figure 2: Two scaling methods showing fatty acid compositions of olive oils from different regions in Italy. The scaling methods roughly allow the same conclusions.




Figure 3: Four different approaches of dealing with categorical variables: the panel on the left shows the typical net of lines resulting from categorical variables in regular parallel coordinate plots. In the other three panels ties in categorical levels are broken using different approaches: from left to right, jittering, equi-spaced line segments and ordered equi-spaced line segments are shown.

4 Results

5 Discussion

References

- D. Cook and D. F. Swayne. *Interactive and Dynamic Graphics for Data Analysis With R and GGobi*. Springer Publishing Company, Incorporated, 1st edition, 2007. ISBN 0387717617.
- R. H. Day and E. J. Stecher. Sine of an illusion. *Perception*, 20:49–55, 1991.
- M. d’Ocagne. Coordonnées parallèles et axiales : Méthode de transformation géométrique et procédé nouveau de calcul graphique déduits de la considération des coordonnées parallèles. *Gauthier-Villars*, page 112, 1885. URL <https://archive.org/details/coordonnesparal00ocaggoog/page/n10>.
- M. Forina, C. Armanino, and S. Lanteri. Classification of olive oils from their fatty acid composition. *Food Research and Data Analysis*, pages 189–214, 01 1983.
- H. Gannett. General summary showing the rank of states by ratios 1880, plate 71. In *Scribner’s statistical atlas of the United States, showing by graphic methods their present condition and their political, social and industrial development*. Charles Scribner’s Sons, New York, 1880.
- J. Heinrich and D. Weiskopf. Continuous Parallel Coordinates. *IEEE Transactions on Visualization and Computer Graphics*, 15(6):1531–1538, 2009. doi: 10.1109/TVCG.2009.131. URL <http://ieeexplore.ieee.org/document/5290770/>.
- J. Heinrich and D. Weiskopf. State of the Art of Parallel Coordinates. In M. Sbert and L. Szirmay-Kalos, editors, *Eurographics 2013 - State of the Art Reports*. The Eurographics Association, 2013. doi: 10.2312/conf/EG2013/stars/095-116.




Figure 4: Generalized Parallel Coordinate Plot of the Palmer penguins data.




Figure 5: Closer investigation of non-sexed Adelie and Gentoo penguins. The `group_by` call before `pcp_scale` is responsible for scaling by species.

- H. Hofmann and M. Vendettuoli. Common Angle Plots as Perception-True Visualizations of Categorical Associations. *IEEE Transactions on Visualization and Computer Graphics*, 19(12):2297–2305, Dec. 2013. doi: 10.1109/TVCG.2013.140. URL <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=6634157>.
- H. Hofmann and M. Vendettuoli. *ggparallel: Variations of Parallel Coordinate Plots for Categorical Data*, 2016. URL <https://cran.r-project.org/package=ggparallel>. R package version 0.2.0.
- A. M. Horst, A. P. Hill, and K. B. Gorman. *palmerpenguins: Palmer Archipelago (Antarctica) penguin data*, 2020. URL <https://allisonhorst.github.io/palmerpenguins/>. R package version 0.1.0.
- A. Inselberg. The plane with parallel coordinates. *The Visual Computer*, 1(2):69–91, Aug. 1985. doi: 10.1007/BF01898350. URL <http://link.springer.com/10.1007/BF01898350>.
- R. Kosara, F. Bendix, and H. Hauser. Parallel Sets: interactive exploration and visual analysis of categorical data. *IEEE Transactions on Visualization and Computer Graphics*, 12(4):558–568, 2006. doi: 10.1109/TVCG.2006.76. URL <http://ieeexplore.ieee.org/document/1634321/>.
- K. T. McDonnell and K. Mueller. Illustrative Parallel Coordinates. *Computer Graphics Forum*, 27(3): 1031–1038, May 2008. doi: 10.1111/j.1467-8659.2008.01239.x. URL <http://doi.wiley.com/10.1111/j.1467-8659.2008.01239.x>.
- J. J. Miller and E. J. Wegman. Computing and graphics in statistics. chapter Construction of Line Densities for Parallel Coordinate Plots, pages 107–123. Springer-Verlag New York, Inc., New York, NY, USA, 1991. ISBN 0-387-97633-7. URL <http://dl.acm.org/citation.cfm?id=140806.140816>.
- A. Pilhöfer and A. Unwin. New Approaches in Visualization of Categorical Data: R Package extracat. *Journal of Statistical Software*, 53(7), 2013. doi: 10.18637/jss.v053.i07. URL <http://www.jstatsoft.org/v53/i07/>.
- R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2019. URL <https://www.R-project.org/>.
- B. Schloerke, J. Crowley, D. Cook, F. Briatte, M. Marbach, E. Thoen, A. Elberg, and J. Larmarange. *GGally: Extension to 'ggplot2'*, 2018. URL <https://CRAN.R-project.org/package=GGally>. R package version 1.4.0.
- M. Schonlau. Visualizing Categorical Data Arising in the Health Sciences Using Hammock Plots. In *Proceedings of the Section on Statistical Graphics, American Statistical Association*, 2003.
- S. VanderPlas and H. Hofmann. Signs of the sine illusion—why we need to care. *Journal of Computational and Graphical Statistics*, 24(4):1170–1190, 2015. doi: 10.1080/10618600.2014.951547. URL <https://doi.org/10.1080/10618600.2014.951547>.
- W. N. Venables and B. D. Ripley. *Modern Applied Statistics with S*. Springer, 4 edition, 2002. ISBN 0-387-95457-0. URL <http://www.stats.ox.ac.uk/pub/MASS4/>.
- E. J. Wegman. Hyperdimensional data analysis using parallel coordinates. *Journal of the American Statistical Association*, 85:664–675, 1990.
- H. Wickham. Reshaping data with the reshape package. *Journal of Statistical Software*, 21(12), 2007. URL <http://www.jstatsoft.org/v21/i12/paper>.
- H. Wickham. Tidy data. *Journal of Statistical Software, Articles*, 59(10):1–23, 2014. ISSN 1548-7660. doi: 10.18637/jss.v059.i10. URL <https://www.jstatsoft.org/v059/i10>.
- H. Wickham. *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York, 2 edition, 2016. ISBN 978-3-319-24277-4. URL <https://ggplot2.tidyverse.org>.

- H. Wickham. *tidyr: Tidy Messy Data*, 2021. URL <https://CRAN.R-project.org/package=tidyr>. R package version 1.1.3.
- H. Wickham, D. Cook, H. Hofmann, and A. Buja. *tourr: An r package for exploring multivariate data with projections*. *Journal of Statistical Software, Articles*, 40(2):1–18, 2011. ISSN 1548-7660. doi: 10.18637/jss.v040.i02. URL <https://www.jstatsoft.org/v040/i02>.
- H. Wickham, R. François, L. Henry, and K. Müller. *dplyr: A Grammar of Data Manipulation*, 2021. URL <https://CRAN.R-project.org/package=dplyr>. R package version 1.0.7.
- L. Wilkinson. *The Grammar of Graphics*. NY: Springer, New York, 2 edition, 2005.