



Vishal S R 250701844-2025-CSE ▾

V2**Started on** Sunday, 30 August 2026, 12:43 AM**State** Finished**Completed on** Sunday, 30 August 2026, 12:45 AM**Time taken** 1 min 40 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int compareAsc(const void *a, const void *b)
5  {
6      return (*(int *)a - *(int *)b);
7  }
8
9  int compareDesc(const void *a, const void *b)
10 {
11     return (*(int *)b - *(int *)a);
12 }
13
14 int main()
15 {
16     int n;
17     scanf("%d", &n);
18
19     int A[n], B[n];
20
21     for (int i = 0; i < n; i++)
22     {
23         scanf("%d", &A[i]);
24     }
25
26     for (int i = 0; i < n; i++)
27     {
28         scanf("%d", &B[i]);
29     }
30
31
32     qsort(A, n, sizeof(int), compareAsc);
33
34
35     qsort(B, n, sizeof(int), compareDesc);
36
37     long long sum = 0;
38
39     for (int i = 0; i < n; i++)
40     {
41         sum += (long long)A[i] * B[i];
42     }
43
44     printf("%lld", sum);
45
46     return 0;
47 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)