

CS383 Part#4 theory

Shivansh Suhane

Winter 2020

1. $X_1, X_2 \rightarrow Y$

a. The entropy formula is given in homework 1:

$$E(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

$$H = -(12/21) * \log_2 (12/21) - 9/21 * \log_2 (9/21)$$

$$H = 0.5239 + 0.4613$$

$$H = 0.9852$$

b. In this question, we first classify the observations per feature based on the True or false. +T is for example, the count of Trues matching a + on Y.

For feature 1,

$$+T = 7 \quad 4+3$$

$$-T = 1 \quad 1$$

$$+F = 5 \quad 4+1$$

$$-F = 8 \quad 5+3$$

For feature 2,

$$+T = 7 \quad 4+3$$

$$-T = 3 \quad 3$$

$$+F = 5 \quad 5$$

$$-F = 6 \quad 5+1$$

Now we use the formula,

$$E(S) = \sum_{i=1}^c -p_i \log_2 p_i$$


$$R = (8/21 * (-7/8 \log_2 (7/8) + -1/8(\log_2(1/8))) + (13/21 * (-5/13 * (-5/13 \log_2 (5/13) + -8/13 \log_2(8/13))))$$

$$= \underline{\underline{0.8021}}$$

$$R = (10/21 * (-7/10 \log_2(7/10) -3/10 \log_2(3/10))) + (11/21 * (-5/21 * (-5/11 \log_2(5/11) -6/11 \log_2(6/11))))$$

$$= \underline{\underline{0.9403}}$$

c. Here's the decision tree



2. Character count questions:

a. The priors are:

$$P(A) = 3/5$$

$$P(!A) = 2/5$$

b. In this question, we try to find the statistics to perform a naïve Bayes classification. We firstly standardize the data for each feature, then find out the parameters for Gaussian for each feature: Mean for num of Chars for YES and NO, Mean of Avg. Word length for YES and NO, Standard Deviation of No. of Chars for YES and NO, and Standard Deviation of Avg. Word Length for YES and NO.

Standardized Data for Number of Chars:

Formulas:

Standardization:

$$z = \frac{x - \mu}{\sigma}$$

with mean:

$$\mu = \frac{1}{N} \sum_{i=1}^N (x_i)$$

and standard deviation:

$$\sigma = \sqrt{\frac{1}{N} \sum_{i=1}^N (x_i - \mu)^2}$$

$$Z(\#) = X - \text{mean} / \text{Dev}$$

X=[216,
69,
302,
60,
393]

mean = 208

dev = $\sqrt{0.25(5.68-4.026)^2 * (4.78-4.026)^2 * \dots * (4.2-4.026)^2}$

$Z(\text{char_count}) = [0.055,$
 -0.957,
 0.647,
 -1.019,
 1.273]

This is the standardized feature.

Standardized Data for Avg. word length:

$Z(\text{avg_WL}) = X - \text{mean} / \text{Dev}$

Dev = $\sqrt{(1/N-1) \text{ summation: } 1 \rightarrow N (X_i - X)^2}$

mean = 4.026

$Z(\text{char_avg}) = [1.247,$
 0.567,
 -1.294,
 -0.653,
 0.131]

This is the standardized feature 2.

Mean for number of Chars:

Mean(A=yes) = $1/3 \text{ sum}(0.055, -0.957, -1.019) = -0.06404$

Mean(A=no) = $1/2 \text{ sum}(0.6473+1.2739) = 0.9606$

Mean for word length:

Mean(A=yes) = $1/3 \text{ sum}(1.247+ 0.568+-0.653) = 0.3877$

Mean(A=no) = $1/2 \text{ sum}(-1.294+0.131) = -0.5816$

Standard Deviation for number of Chars:

Mean(A=yes) = $\sqrt{(1/N-1) \text{ summation: } 1 \rightarrow N (X_i - X)^2} = 0.6031$

Mean(A=no) = $\sqrt{(1/N-1) \text{ summation: } 1 \rightarrow N (X_i - X)^2} = 0.4431$

Standard Deviation for Avg. word length:

Mean(A=yes) = $\sqrt{(1/N-1) \text{ summation: } 1 \rightarrow N (X_i - X)^2} = 0.9633$

Mean(A=no) = $\sqrt{(1/N-1) \text{ summation: } 1 \rightarrow N (X_i - X)^2} = 1.0081$

- c. We need to find gaussian with standardized data.

$$P(x_k|y) \propto \frac{1}{\sigma_k \sqrt{2\pi}} e^{-\frac{(x_k - \mu_k)^2}{2\sigma_k^2}}$$

Passed Feature values =[242, 4.56]

We standardize these values to get [0.234,0.403]

Then, we find probability for A=yes and A=no

Y = Yes

Mean = -0.640, dev = 0.603, G = gaussian function F1

Mean = 0.3877, dev = 0.9633, G = gaussian function F2

$P(Y=A) = P(A=YES) * G(0.234, -0.640, 0.603) * G(0.403, 0.3877, 0.9633)$
 $= 0.6 * 0.2312 * 0.4142 = 0.057441$

Y = No

Mean = 0.961, dev = 0.4431, G = gaussian function F1

Mean = -0.582, dev = 1.0081, G = gaussian function F2

$P(Y \neq A) = P(A=No)G(0.234, 0.9612, 0.4431)G(0.403, -0.582, 1.0081)$
 $P = 0.4 * 0.234 * 0.245 = 0.022932$

Since the probability of $Y = A$ is greater than $Y \neq A$, the student gets an A.

Coding assignments statistics:

3. Run statistics for Naïve Bayes Classifier:

Run Statistics:

- Accuracy :0.8044328552803129**
- Recall: 0.9633333333333334**
- Precision: 0.6752336448598131**
- f-measure: 0.7939560439560439**

4. Run statistics for Logistic Regression Classifier:

Run Statistics:

- Accuracy :0.923728813559322**
- Recall: 0.8675496688741722**
- Precision: 0.9340463458110517**
- f-measure: 0.8995708154506438**

