Software Requirements Specification

Sift

Baseline requirements for the hiring workspace: policy-aware jobs, checklist screening, a live interview, and a cited assessment.

This document specifies the product as it is required to behave. Workflow diagrams kept beside it show step order. Where they disagree, this document is corrected first and the diagram is updated to match.

The outline is the usual four-part requirements specification. Every actor, limit, and identifier below belongs to Sift.

Version ID: 1.0

Date: 27/10/2026

Document ID: SWD/SIFT-SRS

Revision History

Doc. Ver.	Date	Author	Reviewer	Description of Revision
1.0	27/10/2026	Sift baseline		Baseline requirements for Sift, arranged in this template. No requirement, limit, identifier, or release membership removed.

Contents

1. Introduction 4
1.1 Purpose 4
1.2 Scope 4
1.3 Intended Stakeholder 5
1.4 References 5
1.5 Definitions, Acronyms, and Abbreviations 5
2. Overall Description 7
2.1 Overview 7
2.1.1 Product perspective 7
2.1.2 Product functions 7
2.1.3 User characteristics 8
2.1.4 Constraints 8
2.1.5 Assumptions and dependencies 8
2.1.6 Apportioning of requirements 8
2.2 Technical platform 9
2.2.1 Software interfaces 9
2.2.2 Communications interfaces 10
3. Functional Requirements 11
3.1 Overview 11
3.1.1 Open, refuse, and leave the workspace 12
3.1.2 Policy documents 12
3.1.3 Job brief and draft checklist 13
3.1.4 Lock, post, and the next version 14
3.1.5 Desk copilot 15
3.1.6 Mailbox intake and CV upload 16
3.1.7 Read, screen, and redact a CV 17
3.1.8 Rank, notify, and compare 18
3.1.9 Interview slot and invitation 19
3.1.10 Interview list and practice 19
3.1.11 Face check and admission 20
3.1.12 Live room, speech, and transcript 20
3.1.13 In-call copilot 21
3.1.14 Quiz paper 22
3.1.15 Reports and the consolidated assessment 22
3.1.16 Desk and progress 24
3.1.17 Candidate interview 25
4. User Interface 27
5. Non-Functional Requirements 28
5.1 Performance Requirements 28
5.2 Safety Requirements 29
5.3 Security Requirements 30
6. Design Constraints 32

7. Software Quality Attributes 33
7.1 Reliability 33
7.2 Availability 33
7.3 Security 33
7.4 Maintainability 33
7.5 Portability 33
8. User Interface 35
9. Other Requirements 36
9.1 Logical data 36
9.2 Prioritization and release plan 36
9.2.1 Release A — complete a hire 36
9.2.2 Release B — operate and explain 37
9.2.3 Release C — channels with a fallback 37
9.2.4 What a slip means 37
9.3 Failures the product must show 37
9.4 State of a role, a file, and a call 38
9.4.1 Job version 38
9.4.2 CV parse 39
9.4.3 Query status 39
9.4.4 Interview session 39
9.4.5 Claim and suitability 39
9.5 One complete hiring pass 39
9.5.1 Empty workspace 39
9.5.2 Policy 39
9.5.3 Brief and draft 39
9.5.4 Approval and post 40
9.5.5 Two CVs and one bad file 40
9.5.6 Invitation 40
9.5.7 Candidate entry 40
9.5.8 The call 40
9.5.9 Reports 40
9.5.10 What this pass does not prove 40
9.6 Appendices 41
9.6.1 Appendix A — Architecture 41
9.6.2 Appendix B — Workflows 41
9.6.3 Appendix C — Identifier index 41
9.6.4 Appendix D — Requirement titles 41

1. Introduction

This specification says what Sift must do, for whom, and which limits those behaviors must respect. It is the document a reviewer can grade against and a developer can implement against. It is not an operator manual and it is not a model prompt.

The baseline contents are kept in full and presented in this template's section order:

- Introduction
- Overall description
- Specific requirements
- Prioritization and release plan
- Appendices
- One complete hiring pass
- Failures the product must show
- State of a role, a file, and a call

1.1 Purpose

The purpose is to freeze the hiring loop so that later changes are visible as changes to a numbered requirement. A requirement is met only when the named person can produce the named outcome under the named conditions. Internal step names are mentioned only where the order itself is required, because the diagrams and the tests treat that order as part of the product.

The readers are the people building Sift, the people demonstrating it, and the people assessing the project. They are expected to know what a CV, an interview, and a checklist are. They are not expected to know vendor APIs.

1.2 Scope

Sift is a workspace in which one organization hires for a role.

- The recruiter stores policy documents and creates a job. The job's description and its ten checklist queries are drafted from that brief and from the stored policies.
- The recruiter edits the draft, then approves it. Approval locks the checklist and can post the role, telling applicants to email a CV.
- CVs arrive by email or by upload. Each readable CV is scored against the locked checklist. Unreadable files are kept apart from the ranking.
- The recruiter compares people and invites the ones they choose. Sift finds a free time and sends the link. Sift does not invite anyone by itself.
- The candidate opens the link, consents to a face check, and waits to be admitted. The recruiter admits them.
- The admitted candidate, an interviewer agent, and a transcriber agent share a live room. A ten-question quiz may run in the same session.
- After the call, Sift writes a transcript analysis, a claim check, an interview score that ignores the CV number, a process review that does not affect suitability, and a consolidated assessment with a fixed mix of weights.

In scope for the interfaces around that loop: the browser workspace, the HTTP API, the mailbox, outbound invitation mail, an optional calendar, a posting tool aimed at a Telegram channel, LiveKit for media, and the model and embedding services named later.

Out of scope: payroll, contracts of employment, offer letters, onboarding, background-check vendors, multi-organization tenancy, and a public careers site beyond the posted announcement. A practice call is in scope. It must not create an applicant.

1.3 Intended Stakeholder

The readers are the people building Sift, the people demonstrating it, and the people assessing the project. They are expected to know what a CV, an interview, and a checklist are. They are not expected to know vendor APIs.

The people whose work this specification describes are the recruiter and the candidate. There is no third human class. Agents that speak or transcribe are parts of the system, not users. Section 2.1 gives the characteristics of the two human classes.

1.4 References

Reference	Location
Sift system architecture	File 07-system-architecture.pdf, stored with the project diagrams. Appendix A in section 9.6 is the reading note for that figure.
Workflow diagram 01	01-langgraph-job-creation.pdf. Required order for FR-R07. Appendix B.
Workflow diagram 02	02-langgraph-cv-screening.pdf. Required order for FR-R22. Appendix B.
Workflow diagram 03	03-langgraph-qa-analysis.pdf. Required order for FR-R40. Appendix B.
Workflow diagram 04	04-langgraph-master-assessment.pdf. Required order for FR-R45. Appendix B.
IEEE Std 830	Recommended practice for software requirements specifications, used as a document outline only.

No requirement in this document is taken from another product’s specification. Neighboring systems are named only where Sift calls them.

- Sift system architecture, file 07-system-architecture.pdf, stored with the project diagrams.
- Workflow diagrams 01 through 04 for job creation, CV screening, question-and-answer analysis, and the master assessment.
- IEEE Std 830, recommended practice for software requirements specifications, used as a document outline only.

1.5 Definitions, Acronyms, and Abbreviations

The following terms are used with these meanings. They are the terms a reader needs for the requirements below.

Term	Meaning in Sift
Recruiter	The person who signs in with the workspace password and owns jobs, invitations, and admission.
Candidate	A person created from a CV, who may later receive one interview link.
Job	A role with one or more versions.
Version	A draft or locked snapshot: description, weights, contract, category, and checklist.
Locked checklist	Queries Q1–Q10 frozen at approval. Screening and the interview use this set.
Must-have	A query whose type is required. Ranking reports the share of these that were met.
Preferred	A query that counts in the weighted total and is not part of the must-have ratio.
Query status	One of met, partially met, unmet, or insufficient evidence.
CV screening	The workflow that assigns a status to every locked query for one file.
Invite	The email, the calendar attachment, and the private link for one candidate.
Session token	A signed token carrying role, candidate, job, and session.
Workspace JWT	The recruiter token issued at sign-in. It is not a session token.
Fallback chain	Claude, then Gemini, then local Ollama, for ordinary completions.
Local recheck	The Ollama-only pass that may raise an unmet skill and must not lower one.

Term	Meaning in Sift
MCP	The tool server whose post_job action publishes an approved role. The default deployment posts to Telegram.
Live room	The LiveKit session shared by the candidate, the interviewer agent, and the transcriber agent.
Packet	The PDF assembled from the stored interview record.
Suitability	The label Strong Fit, Moderate Fit, Unsuited, or Insufficient evidence.

2. Overall Description

This section describes the general factors that affect Sift and its requirements. It does not replace the numbered requirements in section 3, the interfaces in sections 4 and 8, or the checks in sections 5 and 7. It is the background that makes those requirements easier to understand: product perspective, product functions, user characteristics, constraints, and assumptions and dependencies.

Section 2 places Sift among the browser, the workers, and the outside services, and it says what each human can do. Section 3 specifies one requirement per behavior. Sections 4 and 8 specify the interfaces. Sections 5 and 7 are the measurable checks. Section 9 assigns every identifier to a release, lists the stored records, the failures the product must show, the states, and one complete hiring pass, and points at the diagrams.

2.1 Overview

2.1.1 Product perspective

Sift is one browser application and a set of server processes. Recruiters and candidates never share an account. They share a database.

The browser is a Next.js application on port 3000. Recruiter pages are Home, Policies, Jobs, Candidates, Interviews, Practice, and the sign-in page. Candidate pages are the invite link, the face lobby, and the interview room. A copilot panel sits on the recruiter desk. Every page that needs data calls the HTTP API under /api/v1 on port 8000.

The processes, storage, and outside services that sit beside that browser are specified in section 2.2.

2.1.2 Product functions

For the recruiter

- Sign in, sign out, and land on a desk that shows roles, people waiting, and upcoming calls.
- Upload policies and read a short summary of each.
- Create a role from a form or from the copilot, then correct the draft.
- Approve the draft, which locks it and posts it.
- Open a later draft without moving old applicants onto the new questions.
- Pull CVs from the mailbox or upload one, and watch scanning and scoring progress.
- Read a ranking, compare two people, and invite the people they pick.
- Watch the face-check result and admit the candidate.
- Use a practice room, and during a real call ask the in-call copilot about that candidate only.
- Read claim follow-ups, the interview score, the process review, the HTML assessment, and the PDF packet.

For the candidate

- Open the link from the invitation and see only that interview.
- Consent to the camera or refuse it.
- Wait until the recruiter admits them, then join the room and speak.
- Submit the quiz once if it is offered.

For the system, without a human request on that step

- Poll the mailbox on an interval.
- Speak checklist questions and store the transcript during an admitted call.
- After the call, run analysis, claims, interview score, quality, and assessment in that order.

2.1.3 User characteristics

Recruiter. They know the role well enough to accept or edit a checklist. They can read a ranking and decide whom to invite. They are not expected to write prompts, SQL, or room tokens. One workspace password is enough. They may use the copilot in everyday language. They must still press approve, still choose who is invited, and still admit the face. Several recruiters are not modeled as separate accounts in this baseline. The token represents the workspace.

Candidate. They can read email, open a link, and use a camera and microphone in a browser. They do not learn a password. They do not see scores during the call. They may refuse the camera and then cannot be admitted. They are not expected to understand weights or model tiers.

2.1.4 Constraints

These limits bind the behaviors in section 3. The mandated design decisions are in section 6.

- Recruiter routes listed in QR-02 require a workspace JWT. Interview tokens are a different credential.
- A locked checklist is immutable. A new draft is a new version.
- Descriptions used for posting and for screening are at least 100 characters. Titles are 2 to 255 characters. Minimum years are 0 to 50.
- CVs are PDF or DOCX, at most 8 MB.
- Ordinary completions use Claude, then Gemini, then Ollama. The spoken line uses Gemini only. The skill recheck uses Ollama only.
- When CV, quiz, and interview question-and-answer scores all exist, suitability uses 30, 20, and 50 percent. Otherwise it abstains.
- Interview performance does not read the CV aggregate. Interview quality does not feed suitability. Claim flags do not feed the percentage.
- Face confirmation is cosine similarity 0.42. A possible match starts at 0.32.
- The quiz clock is 600 seconds with 15 seconds of grace, one submit.
- Policy embeddings are 384 dimensions.

2.1.5 Assumptions and dependencies

- Secrets arrive through the environment: recruiter password, JWT secret, model keys, mailbox password, LiveKit keys, and the optional calendar refresh token. The repository does not contain a production secret.
- If IMAP is not configured, the local mail catcher is the apply mailbox. Invitation mail then goes to that catcher as well, which is acceptable for a demonstration and must be replaced for a real candidate.
- If the posting-tool URL is set, approval uses it. Direct Telegram and the third-party board are reached only when that URL is empty.
- Local speech models are present on the interviewer volume. If they are missing, the room cannot speak and the failure must be visible rather than silent.
- Optical character recognition depends on the recognizer being installed where the API or worker runs. If it is missing, the parse records that pass as unavailable and the CV follows the unreadable path when earlier passes also failed.
- The organization name shown in invitations is configuration. It defaults to Sift. Nothing in scoring depends on that string.

2.1.6 Apportioning of requirements

Release A is the loop from sign-in through a cited assessment. Release B is how a recruiter operates and explains that loop: copilot drafting, comparison, practice, claims, the separate interview score, process quality, and progress. Release C is a channel that already has a fallback: Google Calendar, a job board other than the posting tool, and any use of Redis. Section 9.2 names every identifier. If the schedule slips, Release C is dropped first.

2.2 Technical platform

The technical platform is the browser, the server processes, the database and volumes, and the outside services named here. Development and demonstration run from one composition file.

Beside the API, four processes do work the request cannot finish inside one click:

- The inbox worker polls the apply mailbox and starts CV screening.
- The interviewer agent joins a LiveKit room, listens, and speaks.
- The transcriber agent joins the same room and writes the transcript. It does not speak.
- The posting tool exposes a single post_job action on port 8080. The API calls it when a version is approved.

Data sits in Postgres 16 with the vector type. Policy chunks store 384-dimension embeddings. Original policy files live on a policy volume. CV bytes live on a CV volume, separated into received, processed, and failed. Speech models live on a volume mounted by the interviewer.

Outside the compose file, Sift calls Claude and Gemini when keys are present, a LiveKit deployment for the room, Gmail over IMAP when mailbox credentials exist, and Telegram through the posting tool. Ollama, a local mail catcher, and a TURN server are part of the compose file so a demonstration can run without those remote services. Google Calendar is consulted only when its three credentials are set.

Redis is started by the same file and the API is given its address. No current requirement reads or writes Redis. Release A must not depend on it.

Figure reference: the one-page architecture diagram shows this split. This section is the requirement; the figure is the map.

2.2.1 Software interfaces

System	Direction	Required behavior
Postgres 16 with pgvector	Read and write	Jobs, people, sessions, transcripts, scores, assessments, and 384-dimension policy chunks survive a process restart.
Policy volume and CV volume	Write, then read	The original bytes remain at the stored path. Failed CVs are not mixed into the processed folder.
Claude and Gemini	Request text	A completion or a failure the fallback logic can see. Keys come from the environment.
Ollama	Request text	Local completions for the last tier and for the skill recheck. The interviewer container may be given an Ollama address, but the spoken line must not call it.
MiniLM	Text in, vectors out	384-dimension embeddings for policy chunks and for CV-to-query similarity. A hashing embedder may be used only when MiniLM is explicitly turned off.
InsightFace buffalo_l	Image in, vector out	Embeddings comparable by cosine similarity with the thresholds in FR-R32.
LiveKit	Tokens and media	A room the three participants can join. The API mints the token. The agents join with the server credentials.
coturn and public STUN	Media path	Relay when a direct path is blocked. The browser is told the STUN and TURN addresses.
AssemblyAI via the transcriber	Audio in, text out	Lines the transcriber can attribute and store. The transcriber’s instructions are to transcribe and not to speak.
Gmail IMAP or the local mail catcher	Read attachments	Summaries, message bodies, and attachment bytes. Listing is read-only.
SMTP	Send invitation	A message plus an interview.ics part with method REQUEST.
Google Calendar	Free/busy and create	Used only when client id, secret, and refresh token are all set. Otherwise the interface is skipped.
Posting tool and Telegram	Approved job out	post_job accepts the title, description, apply instructions, contract, category, company, seniority, and skills, and returns a result the version stores.

2.2.2 Communications interfaces

- Browser to API: HTTP under /api/v1. Recruiter calls send the workspace JWT. Interview calls send the session token or the invite token, depending on whether the session exists yet.
- Browser to LiveKit: WebRTC after the token is issued. Signaling is LiveKit's. Media may pass through coturn.
- API to posting tool: HTTP to the configured MCP address, defaulting to the compose service.
- Worker to mailbox: IMAP to the configured host when credentials exist, otherwise HTTP to the local mail catcher.
- API to models: the vendor HTTPS APIs for Claude and Gemini, and HTTP to Ollama.
- The API does not expose a public unauthenticated list of candidates. Health may be unauthenticated. Auth, invites, interview sessions, and quizzes are the routes a candidate or a signing-in recruiter can reach without already holding a workspace JWT, and each of those still checks its own token or password.

3. Functional Requirements

This section is the testable part of the specification. Interfaces say what crosses the boundary. Functional requirements say what each person can complete. Quality requirements say how those behaviors are checked.

Each requirement has an identifier, a title, the behavior, why it exists, and what it depends on. User class 1 is the recruiter. User class 2 is the candidate. There is no third human class. Agents that speak or transcribe are parts of the system, not users.

Test case identifiers of the form HP-9.5.n point at the matching step in section 9.5. QR-nn points at that quality requirement. Diagram 01 through Diagram 04 point at Appendix B in section 9.6.

3.1 Overview

The table sums up the main functionalities of Sift. Each row is specified in the subsection of the same name, with the actors who use it. The required step order inside job creation, CV screening, question-and-answer analysis, and the master assessment is the set of workflow diagrams in section 9.6, not a separate use-case drawing.

Serial No	Main Features	Description
1	Open, refuse, and leave the workspace	The recruiter opens the workspace with one password, stays on the sign-in page when that password is wrong or unset, and can discard the desk session.
2	Policy documents	The recruiter stores the organization’s own rules and can see which documents are available before trusting a draft.
3	Job brief and draft checklist	The recruiter captures an explicit brief. Sift drafts a description and ten queries, refuses a draft the schema cannot accept, and lets the recruiter edit the draft before it is locked.
4	Lock, post, and the next version	Approval locks the checklist and posts the role. A later draft is a new version. People already scored stay on the version they were scored against.
5	Desk copilot	The copilot can draft a role through the same brief path, and it can look at stored records and move around the desk. It cannot approve a version or poll the mailbox.
6	Mailbox intake and CV upload	CVs arrive by email or by upload. The wrong type and an oversized file are rejected. Listing mail does not mark messages read.
7	Read, screen, and redact a CV	A readable CV is parsed, screened against the locked checklist in a fixed order, and redacted. An unreadable file and a duplicate file stay out of the ranking.
8	Rank, notify, and compare	Applicants are ordered, the recruiter is told when a batch finishes, and two named people can be compared. Sift does not invite anyone by itself.
9	Interview slot and invitation	Sift finds a free time and sends the link and a calendar file. A missing calendar does not block the mail. A message that was not handed to the mail server is not an invitation.
10	Interview list and practice	Interviews lists calls. Practice uses the interview path and must not create an applicant or an assessment.
11	Face check and admission	After consent, frames are compared with the enrolled face at the published thresholds. The room stays closed until the recruiter admits the candidate.
12	Live room, speech, and transcript	One LiveKit room carries the call. The interviewer speaks from the checklist. The transcriber stores speaker-labelled lines and does not speak.
13	In-call copilot	The answer may use only this candidate’s CV, the locked checklist, and the transcript so far.
14	Quiz paper	One ten-question quiz may run in the same session. A failed generation does not invent a paper.
15	Reports and the consolidated assessment	Analysis, claims, interview score, process quality, and the consolidated assessment run in that order. The published mix is used only when all three scores exist.
16	Desk and progress	Home shows roles, people waiting, and upcoming calls. Long work exposes a status the page can show.
17	Candidate interview	The mail link is the whole of the candidate’s access. They consent or refuse, wait to be admitted, join the room, and submit the quiz once if it is offered.

User class 1 — Recruiter

User class 1 is the recruiter. System steps the recruiter relies on are included in this class. There is no third human class.

3.1.1 Open, refuse, and leave the workspace

The recruiter opens the workspace with one password, stays on the sign-in page when that password is wrong or unset, and can discard the desk session.

Actors. Recruiter.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R01	Open the workspace with the recruiter password **Description.** The sign-in page accepts one password. When it matches the configured recruiter password, Sift returns a JWT whose role is recruiter and whose scope is the workspace, then opens Jobs unless a safe in-app return path was requested. The token lifetime defaults to 240 minutes. **Rationale.** Hiring records must not be readable by anyone who walks up to the browser. **Depends on.** None.	**Description.** The sign-in page accepts one password. When it matches the configured recruiter password, Sift returns a JWT whose role is recruiter and whose scope is the workspace, then opens Jobs unless a safe in-app return path was requested. The token lifetime defaults to 240 minutes.	Token lifetime defaults to 240 minutes. Success opens Jobs unless a safe in-app return path was requested.	HP-9.5.1; QR-01
FR-R02	Refuse a bad or unconfigured sign-in **Description.** A wrong password produces no token and leaves the recruiter on the sign-in page with a visible failure. If no recruiter password is configured at all, sign-in is refused rather than falling open. **Rationale.** An empty secret must not become a back door. **Depends on.** FR-R01.	**Description.** A wrong password produces no token and leaves the recruiter on the sign-in page with a visible failure. If no recruiter password is configured at all, sign-in is refused rather than falling open.	If no recruiter password is configured, sign-in is refused rather than falling open. A wrong password produces no token.	HP-9.5.1; QR-01
FR-R03	Sign out **Description.** Sign-out discards the token held in the browser and returns to the sign-in page. A later call to a recruiter route without a valid JWT is rejected. An interview session token must not be accepted in place of the workspace JWT. **Rationale.** A shared computer has to be able to end the desk session, and a candidate credential must not open the desk. **Depends on.** FR-R01.	**Description.** Sign-out discards the token held in the browser and returns to the sign-in page. A later call to a recruiter route without a valid JWT is rejected. An interview session token must not be accepted in place of the workspace JWT.	An interview session token must not be accepted in place of the workspace JWT.	QR-02

3.1.2 Policy documents

The recruiter stores the organization’s own rules and can see which documents are available before trusting a draft.

Actors. Recruiter.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R04	Upload a policy document **Description.** From Policies, the recruiter uploads a PDF or DOCX. Sift extracts the text, splits it into chunks, embeds each chunk as a 384-dimension vector, stores the vectors with the chunk text, and writes the original file under the policy storage directory. **Rationale.** Later job drafts need the organization's own rules, not a generic template. **Depends on.** FR-R01.	**Description.** From Policies, the recruiter uploads a PDF or DOCX. Sift extracts the text, splits it into chunks, embeds each chunk as a 384-dimension vector, stores the vectors with the chunk text, and writes the original file under the policy storage directory.	PDF or DOCX. Each chunk is a 384-dimension vector. The original file is kept under the policy storage directory.	HP-9.5.2
FR-R05	List policies and open a summary **Description.** Policies lists every stored document with its filename and kind. Opening one document shows a short summary. The list is empty, with no error, when nothing has been uploaded yet. **Rationale.** The recruiter has to see which rules are available before trusting a draft. **Depends on.** FR-R04.	**Description.** Policies lists every stored document with its filename and kind. Opening one document shows a short summary. The list is empty, with no error, when nothing has been uploaded yet.	The list is empty, with no error, when nothing has been uploaded. There is no editor for the chunk text on this page.	HP-9.5.2

3.1.3 Job brief and draft checklist

The recruiter captures an explicit brief. Sift drafts a description and ten queries, refuses a draft the schema cannot accept, and lets the recruiter edit the draft before it is locked.

Actors. Recruiter.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R06	Capture a job brief **Description.** Create a role collects title (2 to 255 characters), seniority (Junior, Mid-Level, Senior, or Not specified), contract (Full Time, Part Time, Freelance, or Internship), a supported category defaulting to Information Technology, at least one required skill, optional preferred skills, qualifications, minimum years from 0 to 50, and technical, experience, and qualification weights. The weights must sum to 1 within a tolerance of 0.001. Defaults are Mid-Level, Full Time, 0.5, 0.3, and 0.2 when the recruiter does not change them. **Rationale.** The draft has to start from an explicit brief so the checklist can be checked against it. **Depends on.** FR-R01.	**Description.** Create a role collects title (2 to 255 characters), seniority (Junior, Mid-Level, Senior, or Not specified), contract (Full Time, Part Time, Freelance, or Internship), a supported category defaulting to Information Technology, at least one required skill, optional preferred skills, qualifications, minimum years from 0 to 50, and technical, experience, and qualification weights. The weights must sum to 1 within a tolerance of 0.001. Defaults are Mid-Level, Full Time, 0.5, 0.3, and 0.2 when the recruiter does not change them.	Title 2 to 255 characters. Minimum years 0 to 50. Weights sum to 1 within 0.001. Seniority, contract, and category must be one of the enumerated values. Defaults are Mid-Level, Full Time, 0.5, 0.3, and 0.2.	HP-9.5.3
FR-R07	Draft the description and the ten queries **Description.** Submitting the brief runs the job workflow in this order: retrieve policy excerpts similar to the title, seniority, skills, and qualifications; write a description of at least 100 characters that respects those excerpts when they constrain pay, location, or hiring rules; propose queries Q1 through Q10; validate the set. Each query has one question, a dimension of technical, experience, or qualification, a type of must-have or preferred, a positive weight,	**Description.** Submitting the brief runs the job workflow in this order: retrieve policy excerpts similar to the title, seniority, skills, and qualifications; write a description of at least 100 characters that respects those excerpts when they constrain pay, location, or hiring rules; propose queries Q1 through Q10; validate the set. Each query has one question, a dimension of technical, experience, or qualification, a type of must-have or preferred, a positive weight, evidence hints, and one rubric string. The ten	Description at least 100 characters. Query ids Q1 through Q10, each once. Ten weights normalize to 1. A draft is still produced when no policy exists. Stored as version 1 in draft.	HP-9.5.3; QR-03; Diagram 01

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	evidence hints, and one rubric string. The ten weights are normalized so they sum to 1. The new job is stored as version 1 in draft, together with the excerpts used, the model tier, and whether a fallback tier was used. **Rationale.** Every later score cites this checklist, so the checklist has to exist before any CV is read. **Depends on.** FR-R06. Policy excerpts are included when policies exist. A draft is still produced when none exist.	weights are normalized so they sum to 1. The new job is stored as version 1 in draft, together with the excerpts used, the model tier, and whether a fallback tier was used.		
FR-R08	Reject a draft the schema cannot accept **Description.** If the model returns a description under 100 characters, omits the queries array, repeats a query id, or breaks the checklist schema, the draft is not stored. The recruiter sees a failure they can correct by submitting again. Partial checklist rows must not be committed. **Rationale.** A broken checklist would make ranking incomparable. **Depends on.** FR-R07.	**Description.** If the model returns a description under 100 characters, omits the queries array, repeats a query id, or breaks the checklist schema, the draft is not stored. The recruiter sees a failure they can correct by submitting again. Partial checklist rows must not be committed.	Partial checklist rows must not be committed. A short description, a missing queries array, a repeated query id, or a broken schema means the draft is not stored.	HP-9.5.3; QR-03
FR-R09	Edit a draft checklist and description **Description.** On the Brief tab of a draft, the recruiter can replace the description and the ten queries. A replacement description must still be at least 100 characters. Query ids remain Q1 through Q10, each once. Locked versions reject the edit. **Rationale.** The recruiter has to be able to correct a draft before it becomes the scoring contract. **Depends on.** FR-R07.	**Description.** On the Brief tab of a draft, the recruiter can replace the description and the ten queries. A replacement description must still be at least 100 characters. Query ids remain Q1 through Q10, each once. Locked versions reject the edit.	Locked versions reject the edit. A replacement description must still be at least 100 characters. Query ids remain Q1 through Q10, each once.	HP-9.5.3

3.1.4 Lock, post, and the next version

Approval locks the checklist and posts the role. A later draft is a new version. People already scored stay on the version they were scored against.

Actors. Recruiter. The posting tool publishes the approved role.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R10	Approve and lock a version **Description.** Approval sets the version status to locked and records the lock time. The locked checklist is the only checklist used for CVs and interviews on that version. The Brief tab no longer accepts edits. **Rationale.** Scores are only comparable while the questions stay still. **Depends on.** FR-R07.	**Description.** Approval sets the version status to locked and records the lock time. The locked checklist is the only checklist used for CVs and interviews on that version. The Brief tab no longer accepts edits.	The locked checklist is immutable. The Brief tab no longer accepts edits. A new draft is a new version.	HP-9.5.4
FR-R11	Post the approved role **Description.** On approval, Sift builds an apply instruction that asks for a PDF or DOCX CV by email, using the job's mail subject. If the posting-tool address is set, the post goes through that tool and the result is stored on the version. The tool's default action is a Telegram channel post. If the tool address is empty, Sift tries a direct Telegram post when	**Description.** On approval, Sift builds an apply instruction that asks for a PDF or DOCX CV by email, using the job's mail subject. If the posting-tool address is set, the post goes through that tool and the result is stored on the version. The tool's default action is a Telegram channel post. If the tool address is empty, Sift tries a direct Telegram post when a bot token and chat id exist, and otherwise	A description shorter than 100 characters is not posted. A posting failure is stored and does not unlock the version. Direct Telegram and a third-party board are reached only when	HP-9.5.4

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	a bot token and chat id exist, and otherwise a third-party board only when that key exists. A description shorter than 100 characters is not posted. A posting failure is stored on the version and does not unlock it. **Rationale.** Applicants need a public instruction that lands in the mailbox the screener reads, and a failed post must not pretend the version is still a draft. **Depends on.** FR-R10.	a third-party board only when that key exists. A description shorter than 100 characters is not posted. A posting failure is stored on the version and does not unlock it.	the posting-tool URL is empty.	
FR-R12	Open the next version without rewriting history **Description.** From a locked version the recruiter can open version N+1 as a draft that copies seniority, skills, qualifications, years, weights, contract, category, description, policy excerpts, and the ten queries. People already scored stay attached to the version they were scored against. **Rationale.** A role can change without moving old scores onto new questions. **Depends on.** FR-R10.	**Description.** From a locked version the recruiter can open version N+1 as a draft that copies seniority, skills, qualifications, years, weights, contract, category, description, policy excerpts, and the ten queries. People already scored stay attached to the version they were scored against.	People already scored stay attached to the version they were scored against. Moving the role to a new version must not retarget that row.	HP-9.5.10

3.1.5 Desk copilot

The copilot can draft a role through the same brief path, and it can look at stored records and move around the desk. It cannot approve a version or poll the mailbox.

Actors. Recruiter.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R13	Ask the copilot to draft a role **Description.** If the recruiter asks for a new role and the conversation already contains a title and at least one required skill, the copilot submits the same brief path as FR-R07. Seniority, contract, category, years, qualifications, and weights fall back to the documented defaults only when the recruiter did not state them. If the title or a required skill is missing, the copilot asks for the missing piece and creates nothing. **Rationale.** The copilot is a faster way into the same draft, not a second, looser draft. **Depends on.** FR-R07.	**Description.** If the recruiter asks for a new role and the conversation already contains a title and at least one required skill, the copilot submits the same brief path as FR-R07. Seniority, contract, category, years, qualifications, and weights fall back to the documented defaults only when the recruiter did not state them. If the title or a required skill is missing, the copilot asks for the missing piece and creates nothing.	If the title or a required skill is missing, nothing is created. Unstated seniority, contract, category, years, qualifications, and weights use the documented defaults only.	HP-9.5.10; QR-13
FR-R14	Let the copilot look and navigate, not decide **Description.** The copilot may list stored jobs, list policies, open a ranking, open a named person, compare two named people, explain a pipeline that is stuck or empty, open a draft, open an assessment report, and jump to a known place: home, policies, jobs, create, a job's brief or applicants, candidates, interviews, or practice. It must refuse to approve a version and must refuse to poll the mailbox. It must not invent stored people, scores, or jobs. **Rationale.** Approval and intake are the recruiter's decisions. A chat reply must not	**Description.** The copilot may list stored jobs, list policies, open a ranking, open a named person, compare two named people, explain a pipeline that is stuck or empty, open a draft, open an assessment report, and jump to a known place: home, policies, jobs, create, a job's brief or applicants, candidates, interviews, or practice. It must refuse to approve a version and must refuse to poll the mailbox. It must not invent stored people, scores, or jobs.	Must refuse to approve a version and must refuse to poll the mailbox. Must not invent stored people, scores, or jobs.	HP-9.5.10; QR-13

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	take them. **Depends on.** FR-R01.			

3.1.6 Mailbox intake and CV upload

CVs arrive by email or by upload. The wrong type and an oversized file are rejected. Listing mail does not mark messages read.

Actors. Recruiter and the inbox worker. The worker runs without a click. The recruiter can also start a pass or upload a file.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R15	Poll the apply mailbox on a cycle **Description.** The inbox worker lists the mailbox, downloads CV attachments that match an open job, and starts screening. The cycle repeats every configured interval, default 20 seconds. An error in one cycle is logged and the next cycle still runs. Listing mail must not mark the messages as read. **Rationale.** Applications should show up without a person living in the inbox, and reading the list must not hide mail from the recruiter's own client. **Depends on.** FR-R11.	**Description.** The inbox worker lists the mailbox, downloads CV attachments that match an open job, and starts screening. The cycle repeats every configured interval, default 20 seconds. An error in one cycle is logged and the next cycle still runs. Listing mail must not mark the messages as read.	Default cycle 20 seconds. An error in one cycle must not stop the next. Listing mail must not mark messages read.	HP-9.5.5; QR-06
FR-R16	Let the recruiter start a poll **Description.** From the workspace the recruiter can request an inbox pass. That pass uses the same intake as the worker. The job shows that a scan is underway. **Rationale.** A demonstration or a burst of mail should not have to wait for the next interval. **Depends on.** FR-R15.	**Description.** From the workspace the recruiter can request an inbox pass. That pass uses the same intake as the worker. The job shows that a scan is underway.	The manual pass uses the same intake as the worker.	HP-9.5.5
FR-R17	Upload a CV onto a job **Description.** On a job, the recruiter can upload a PDF or DOCX. The file is stored and screened with the same rules as a mailed attachment, against that job's locked checklist. **Rationale.** Referrals and live demonstrations do not always arrive as email. **Depends on.** FR-R10.	**Description.** On a job, the recruiter can upload a PDF or DOCX. The file is stored and screened with the same rules as a mailed attachment, against that job's locked checklist.	PDF or DOCX only, screened against that job's locked checklist, with the same rules as a mailed attachment.	HP-9.5.5
FR-R18	Reject a CV that is the wrong type or too large **Description.** A file that is not a PDF beginning with the PDF signature, or a DOCX beginning as a zip package, is rejected. A file over 8 MB is rejected. The rejection names the rule. No checklist score is created. **Rationale.** Random attachments must not enter the ranking. **Depends on.** FR-R15 or FR-R17.	**Description.** A file that is not a PDF beginning with the PDF signature, or a DOCX beginning as a zip package, is rejected. A file over 8 MB is rejected. The rejection names the rule. No checklist score is created.	Not a PDF beginning with the PDF signature, or not a DOCX beginning as a zip package, is rejected. Over 8 MB is rejected. No checklist score is created.	HP-9.5.5; QR-07

3.1.7 Read, screen, and redact a CV

A readable CV is parsed, screened against the locked checklist in a fixed order, and redacted. An unreadable file and a duplicate file stay out of the ranking.

Actors. The system, after a file has been accepted. The recruiter reads the result.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R19	Read CV text in three passes **Description.** For an accepted file, Sift tries native text first. If the text is too sparse and the file is a PDF, it tries spatial reading order. If that is still too sparse, it renders pages and runs optical character recognition. The stored parse records which pass succeeded and a confidence. Native success is recorded at 0.92 and spatial success at 0.78. **Rationale.** Scanned CVs are common, and the method used should be visible when a score looks odd. **Depends on.** FR-R18.	**Description.** For an accepted file, Sift tries native text first. If the text is too sparse and the file is a PDF, it tries spatial reading order. If that is still too sparse, it renders pages and runs optical character recognition. The stored parse records which pass succeeded and a confidence. Native success is recorded at 0.92 and spatial success at 0.78.	Native success is recorded at 0.92 and spatial success at 0.78. Spatial reading is tried when the text is too sparse and the file is a PDF. OCR runs when that is still too sparse.	HP-9.5.5
FR-R20	Keep an unreadable CV out of the ranking **Description.** When every pass yields too little text, the file is copied to the failed area, a failed parse is stored, and the candidate is not given checklist statuses. The batch notice counts these files separately from scored CVs. **Rationale.** An empty file must not look like a weak applicant. **Depends on.** FR-R19.	**Description.** When every pass yields too little text, the file is copied to the failed area, a failed parse is stored, and the candidate is not given checklist statuses. The batch notice counts these files separately from scored CVs.	The candidate is not given checklist statuses. The batch notice counts these files separately from scored CVs. If OCR is missing and earlier passes failed, the CV follows this path.	HP-9.5.5; QR-07; QR-14
FR-R21	Enrol a face from the CV **Description.** When a readable CV contains a usable face image, Sift stores an embedding for that candidate. A CV with no usable face still scores. The missing face is reported so the later lobby can say identification has nothing to compare. **Rationale.** The interview check needs a reference picture, but a missing picture must not block screening. **Depends on.** FR-R19.	**Description.** When a readable CV contains a usable face image, Sift stores an embedding for that candidate. A CV with no usable face still scores. The missing face is reported so the later lobby can say identification has nothing to compare.	A CV with no usable face still scores. The missing face is reported so the lobby can say identification has nothing to compare.	HP-9.5.5
FR-R22	Run CV screening in a fixed order **Description.** A readable CV is processed as: parse and normalize; extract attributes including name, contact, and experience; load the locked checklist; compute a semantic similarity for each query; evaluate every query; recheck only the items that are not met, using the local model; flag and redact protected phrases; write one justification line per query. The recruiter-facing score includes the aggregate, the must-have ratio, and the technical, experience, and qualification subtotals. **Rationale.** Two CVs are comparable only when they walk the same steps against the same questions. **Depends on.** FR-R10, FR-R19.	**Description.** A readable CV is processed as: parse and normalize; extract attributes including name, contact, and experience; load the locked checklist; compute a semantic similarity for each query; evaluate every query; recheck only the items that are not met, using the local model; flag and redact protected phrases; write one justification line per query. The recruiter-facing score includes the aggregate, the must-have ratio, and the technical, experience, and qualification subtotals.	The order is fixed: parse and normalize; attributes; locked checklist; semantic similarity; evaluation; local recheck of items that are not met; flag and redact; one justification line per query.	HP-9.5.5; Diagram 02
FR-R23	Allow the local recheck to raise a skill, never to lower one **Description.** The local model may move an	**Description.** The local model may move an open item to met or partially met when the CV shows the requirement or a related	Must not lower any item, must not judge years of experience, and must	HP-9.5.5; QR-04

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	open item to met or partially met when the CV shows the requirement or a related tool, and the evidence must be a short quote from the CV. It must not lower any item, must not judge years of experience, and must omit an item it would not raise. If the local model fails, the earlier evaluation stands. **Rationale.** A second pass can catch implied skills such as a framework implying its language. It must not quietly punish the candidate. **Depends on.** FR-R22.	tool, and the evidence must be a short quote from the CV. It must not lower any item, must not judge years of experience, and must omit an item it would not raise. If the local model fails, the earlier evaluation stands.	omit an item it would not raise. Evidence must be a short quote from the CV. If the local model fails, the earlier evaluation stands.	
FR-R24	Redact protected phrases before the recruiter reads them **Description.** Gender, religion, ethnicity, disability, and an explicit age in years found in the CV text are flagged. Those phrases are removed from extracted attributes and from justification lines. Checklist status is not a field for storing those phrases. **Rationale.** A hiring note must not repeat protected attributes as if they were evidence. **Depends on.** FR-R22.	**Description.** Gender, religion, ethnicity, disability, and an explicit age in years found in the CV text are flagged. Those phrases are removed from extracted attributes and from justification lines. Checklist status is not a field for storing those phrases.	Gender, religion, ethnicity, disability, and an explicit age in years. Checklist status is not a field for storing those phrases.	HP-9.5.5; QR-08
FR-R25	Ignore a duplicate file **Description.** A CV whose content hash was already stored for that intake is not screened again and does not create a second candidate from the same bytes. **Rationale.** A mailbox retry must not double a person's rank. **Depends on.** FR-R15.	**Description.** A CV whose content hash was already stored for that intake is not screened again and does not create a second candidate from the same bytes.	The same content hash for that intake is not screened again and does not create a second candidate from the same bytes.	HP-9.5.5; QR-07

3.1.8 Rank, notify, and compare

Applicants are ordered, the recruiter is told when a batch finishes, and two named people can be compared. Sift does not invite anyone by itself.

Actors. Recruiter.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R26	Rank a job's applicants **Description.** Applicants on a version are ordered by the weighted checklist result and the must-have ratio. Status points are 1 for met, 0.5 for partially met, and 0 for unmet or insufficient evidence. The Candidates page and the job's Applicants tab show this order, including people who could not be scored. **Rationale.** The desk needs one order, and the recruiter still chooses who is invited. **Depends on.** FR-R22.	**Description.** Applicants on a version are ordered by the weighted checklist result and the must-have ratio. Status points are 1 for met, 0.5 for partially met, and 0 for unmet or insufficient evidence. The Candidates page and the job's Applicants tab show this order, including people who could not be scored.	Status points are 1 for met, 0.5 for partially met, and 0 for unmet or insufficient evidence. People who could not be scored are still shown. The recruiter still chooses who is invited.	HP-9.5.5
FR-R27	Tell the recruiter when a batch finishes **Description.** After a mailbox batch, Sift records a notice with how many CVs were scored, how many could not be read, and the instruction to review the ranking before inviting anyone. The recruiter can	**Description.** After a mailbox batch, Sift records a notice with how many CVs were scored, how many could not be read, and the instruction to review the ranking before inviting anyone. The recruiter can mark a notice read.	The notice counts scored CVs and unreadable CVs and says to review the ranking before inviting anyone. The recruiter can mark a notice read.	HP-9.5.5

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	mark a notice read. **Rationale.** Scoring can finish while the recruiter is on another page. **Depends on.** FR-R26.			
FR-R28	Compare two named candidates **Description.** The recruiter can open two people side by side. The comparison uses checklist standing and, when present, interview and assessment material. The copilot can open the same comparison when the recruiter names both people. It must not invent a reason that is not on the record. **Rationale.** Close ranks need the evidence next to each other. **Depends on.** FR-R26.	**Description.** The recruiter can open two people side by side. The comparison uses checklist standing and, when present, interview and assessment material. The copilot can open the same comparison when the recruiter names both people. It must not invent a reason that is not on the record.	The copilot must not invent a reason that is not on the record. Comparison uses checklist standing and, when present, interview and assessment material.	HP-9.5.10

3.1.9 Interview slot and invitation

Sift finds a free time and sends the link and a calendar file. A missing calendar does not block the mail. A message that was not handed to the mail server is not an invitation.

Actors. Recruiter. The candidate receives the mail.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R29	Choose a free interview slot **Description.** An invitation looks for a window that does not overlap another Sift call. The default length is 45 minutes, inside the configured weekday hours, and not sooner than the configured lead time. When Google Calendar credentials exist, that calendar's busy windows are included. When they do not, Sift's own calls are still avoided. **Rationale.** Two candidates must not be booked into the same slot, and a missing calendar must not block every invite. **Depends on.** FR-R26.	**Description.** An invitation looks for a window that does not overlap another Sift call. The default length is 45 minutes, inside the configured weekday hours, and not sooner than the configured lead time. When Google Calendar credentials exist, that calendar's busy windows are included. When they do not, Sift's own calls are still avoided.	Default length 45 minutes, inside the configured weekday hours, and not sooner than the configured lead time. Google Calendar is included only when client id, secret, and refresh token are all set.	HP-9.5.6
FR-R30	Email the invitation and a calendar file **Description.** Each selected person receives mail that names them when a name is known, names the role and company, states the time, and includes a link that opens only their interview. An interview.ics attachment is included so they can accept the time. Failure to send is visible. Sift does not mark them invited if the message was not handed to the mail server. **Rationale.** The link is the candidate's credential, and the time has to be on their calendar. **Depends on.** FR-R29.	**Description.** Each selected person receives mail that names them when a name is known, names the role and company, states the time, and includes a link that opens only their interview. An interview.ics attachment is included so they can accept the time. Failure to send is visible. Sift does not mark them invited if the message was not handed to the mail server.	Sift does not mark the person invited if the message was not handed to the mail server. The link opens only their interview. An interview.ics attachment uses method REQUEST.	HP-9.5.6

3.1.10 Interview list and practice

Interviews lists calls. Practice uses the interview path and must not create an applicant or an assessment.

Actors. Recruiter.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R31	List calls and open a practice room **Description.** Interviews lists calls by role. Practice starts a recruiter-only room that uses the interview path without creating an application or an invite. Ending practice does not write a candidate assessment. **Rationale.** The recruiter should rehearse the room, and that rehearsal must not pollute a ranking. **Depends on.** FR-R01.	**Description.** Interviews lists calls by role. Practice starts a recruiter-only room that uses the interview path without creating an application or an invite. Ending practice does not write a candidate assessment.	Practice must not create an application or an invite. Ending practice does not write a candidate assessment.	HP-9.5.10

3.1.11 Face check and admission

After consent, frames are compared with the enrolled face at the published thresholds. The room stays closed until the recruiter admits the candidate.

Actors. Candidate, for consent and the camera. Recruiter, who is the only one who can admit.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R32	Compare the live face with the enrolled face **Description.** After the candidate consents, camera frames are embedded and compared with the invited candidate first, then the rest of the gallery. Cosine similarity at or above 0.42 confirms the invited person. From 0.32 up to but not including 0.42 the match is only possible. Below 0.32 the frame does not identify them. Frames with no face are counted and cannot vote. The recruiter sees the result and is the only one who can admit. **Rationale.** A forwarded link should be hard to use as someone else, and a weak similarity must not become a name. **Depends on.** FR-R21, FR-R30.	**Description.** After the candidate consents, camera frames are embedded and compared with the invited candidate first, then the rest of the gallery. Cosine similarity at or above 0.42 confirms the invited person. From 0.32 up to but not including 0.42 the match is only possible. Below 0.32 the frame does not identify them. Frames with no face are counted and cannot vote. The recruiter sees the result and is the only one who can admit.	Confirm at or above cosine similarity 0.42. Possible from 0.32 up to but not including 0.42. Below 0.32 the frame does not identify them. Frames with no face cannot vote. Only the recruiter can admit.	HP-9.5.7; QR-12
FR-R33	Hold the room until admission **Description.** Before admission the candidate can see that identification is in progress. They cannot start the scored conversation. After the recruiter admits them, the session can connect to the room. **Rationale.** Scoring should not begin on an unidentified visitor. **Depends on.** FR-R32.	**Description.** Before admission the candidate can see that identification is in progress. They cannot start the scored conversation. After the recruiter admits them, the session can connect to the room.	They cannot start the scored conversation before admission.	HP-9.5.7

3.1.12 Live room, speech, and transcript

One LiveKit room carries the call. The interviewer speaks from the checklist. The transcriber stores speaker-labelled lines and does not speak.

Actors. The admitted candidate, the interviewer agent, and the transcriber agent. The agents are parts of the system, not users.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R34	Run the live room with three participants **Description.** The admitted candidate, the interviewer agent, and the transcriber	**Description.** The admitted candidate, the interviewer agent, and the transcriber agent share one LiveKit room. The browser	The browser receives a URL and a token for that room only. coturn	HP-9.5.7; QR-16

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	agent share one LiveKit room. The browser receives a URL and a token for that room only. coturn provides TURN, with public STUN as fallback for the path. Disconnecting the candidate ends their media. The interviewer and transcriber keep writing only for that session. **Rationale.** The conversation, the voice, and the transcript have to be the same call. **Depends on.** FR-R33.	receives a URL and a token for that room only. coturn provides TURN, with public STUN as fallback for the path. Disconnecting the candidate ends their media. The interviewer and transcriber keep writing only for that session.	provides TURN, with public STUN as fallback. The interviewer and transcriber write only for that session.	
FR-R35	Speak the interview from the checklist **Description.** The interviewer listens with local speech recognition, asks Gemini for the next spoken line, and speaks it with the configured local voice, Kokoro unless Piper is selected. The line is a short turn. If Gemini does not answer inside its short budget, the room gets a filler, a nudge, or a close, and does not wait on Claude or Ollama. Questions prefer checklist items the CV did not fully meet. The opening, the quiz handoff, and the close are fixed spoken moments, not free-form monologues. **Rationale.** The call should probe gaps, and a live turn cannot stall on the full model chain. **Depends on.** FR-R34, FR-R22.	**Description.** The interviewer listens with local speech recognition, asks Gemini for the next spoken line, and speaks it with the configured local voice, Kokoro unless Piper is selected. The line is a short turn. If Gemini does not answer inside its short budget, the room gets a filler, a nudge, or a close, and does not wait on Claude or Ollama. Questions prefer checklist items the CV did not fully meet. The opening, the quiz handoff, and the close are fixed spoken moments, not free-form monologues.	The spoken line uses Gemini only, with Kokoro unless Piper is selected. If Gemini does not answer inside its short budget, about five seconds, the room gets a filler, a nudge, or a close, and does not wait on Claude or Ollama.	HP-9.5.8; QR-05
FR-R36	Store a speaker-labelled transcript **Description.** The transcriber listens in the same room and stores lines with the speaker and whether the line is final. It does not speak. Lines that are only noise or an echo of the prompt are not treated as answers. The stored wording is the wording that was recognized. A cleaned view may be used for scoring, but it must not overwrite the stored lines. **Rationale.** Reports have to cite what was said, including a messy answer. **Depends on.** FR-R34.	**Description.** The transcriber listens in the same room and stores lines with the speaker and whether the line is final. It does not speak. Lines that are only noise or an echo of the prompt are not treated as answers. The stored wording is the wording that was recognized. A cleaned view may be used for scoring, but it must not overwrite the stored lines.	The transcriber does not speak. A cleaned view may be used for scoring but must not overwrite the stored lines. Noise or an echo of the prompt is not treated as an answer.	HP-9.5.8

3.1.13 In-call copilot

The answer may use only this candidate's CV, the locked checklist, and the transcript so far.

Actors. Recruiter, during a call they are observing.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R37	Answer the recruiter from this call only **Description.** During the call the recruiter can ask the in-call copilot a question. The answer may use that candidate's CV text, the locked checklist, and the transcript so far. It must not use another candidate's record and must not invent a quote. **Rationale.** The person running the call needs a reminder of the file in front of them, not a new source of facts. **Depends on.** FR-R36.	**Description.** During the call the recruiter can ask the in-call copilot a question. The answer may use that candidate's CV text, the locked checklist, and the transcript so far. It must not use another candidate's record and must not invent a quote.	Must not use another candidate's record and must not invent a quote.	HP-9.5.8

3.1.14 Quiz paper

One ten-question quiz may run in the same session. A failed generation does not invent a paper.

Actors. The system offers the paper. The candidate sits it. The recruiter can open it afterward.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R38	Offer one ten-question quiz **Description.** The session can present ten multiple-choice questions generated from the CV. Each is worth 10 points, so the paper is out of 100. The candidate has 600 seconds from the start, and a submit up to 15 seconds after that may still count. A second submit must not replace the score. The recruiter can open the paper afterward. If generation fails, the interview can continue without a fabricated paper. **Rationale.** The quiz is a third evidence source and it has to be the same length for everyone. **Depends on.** FR-R34.	**Description.** The session can present ten multiple-choice questions generated from the CV. Each is worth 10 points, so the paper is out of 100. The candidate has 600 seconds from the start, and a submit up to 15 seconds after that may still count. A second submit must not replace the score. The recruiter can open the paper afterward. If generation fails, the interview can continue without a fabricated paper.	Ten questions, 10 points each, out of 100. 600 seconds from the start, and a submit up to 15 seconds after that may still count. A second submit must not replace the score. No fabricated paper if generation fails.	HP-9.5.8; QR-11

3.1.15 Reports and the consolidated assessment

Analysis, claims, interview score, process quality, and the consolidated assessment run in that order. The published mix is used only when all three scores exist.

Actors. The system writes the reports after the call. The recruiter reads and downloads them.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R39	Close the call and start the report sequence **Description.** Ending the session marks it ended and starts report work in this order: question-and-answer analysis, claim check, interview score, interview quality, then the consolidated assessment. Progress shows which of those steps is running. A step that has no input records the gap and does not block the later steps that can still run. **Rationale.** The recruiter should see that the call is over and which report is still working. **Depends on.** FR-R36.	**Description.** Ending the session marks it ended and starts report work in this order: question-and-answer analysis, claim check, interview score, interview quality, then the consolidated assessment. Progress shows which of those steps is running. A step that has no input records the gap and does not block the later steps that can still run.	Order: question-and-answer analysis, claim check, interview score, interview quality, then the consolidated assessment. A step with no input records the gap and does not block later steps that can still run.	HP-9.5.9; QR-17
FR-R40	Pair and score the transcript **Description.** Question-and-answer analysis loads the turns, pairs each question with the following answer, classifies intent as technical, experience, qualification, clarification, or other, then scores relevance, technical accuracy, completeness, and articulation side by side. Those four scores join before queries are mapped, coverage gaps are listed, and justifications are written with citations. The stored analysis keeps the mean of each dimension, the model tier, and whether a fallback was used. **Rationale.** A single blended impression is not enough. The four readings have to be	**Description.** Question-and-answer analysis loads the turns, pairs each question with the following answer, classifies intent as technical, experience, qualification, clarification, or other, then scores relevance, technical accuracy, completeness, and articulation side by side. Those four scores join before queries are mapped, coverage gaps are listed, and justifications are written with citations. The stored analysis keeps the mean of each dimension, the model tier, and whether a fallback was used.	Four scores stay separable: relevance, technical accuracy, completeness, and articulation. The stored analysis keeps the mean of each dimension, the model tier, and whether a fallback was used.	HP-9.5.9; Diagram 03

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	separable and cited. **Depends on.** FR-R39.			
FR-R41	Say so when nobody spoke **Description.** If the transcript has no usable text, the analysis stores that no speech was captured, leaves the pairs empty, and does not invent questions or scores. The assessment may then report insufficient interview evidence. **Rationale.** A dropped call must not read as a poor answer. **Depends on.** FR-R40.	**Description.** If the transcript has no usable text, the analysis stores that no speech was captured, leaves the pairs empty, and does not invent questions or scores. The assessment may then report insufficient interview evidence.	No usable text means no invented questions or scores. Pairs stay empty. The assessment may then report insufficient interview evidence.	HP-9.5.9; QR-14
FR-R42	Check CV claims against spoken words **Description.** Claims taken from the CV are kept only when their wording can be found in the CV. After the interview they are marked supported, contradicted, or unverified. A faulting status requires a quote whose words appear in order in the transcript. Supported claims stay on the ledger and off the follow-up list. The others are shown to the recruiter as follow-up questions. This ledger is not an input to the suitability percentage. **Rationale.** A dispute about a CV line should point at words in the CV and words in the call. **Depends on.** FR-R22, FR-R40.	**Description.** Claims taken from the CV are kept only when their wording can be found in the CV. After the interview they are marked supported, contradicted, or unverified. A faulting status requires a quote whose words appear in order in the transcript. Supported claims stay on the ledger and off the follow-up list. The others are shown to the recruiter as follow-up questions. This ledger is not an input to the suitability percentage.	A faulting status requires a quote whose words appear in order in the transcript. Claims are kept only when their wording can be found in the CV. This ledger is not an input to the suitability percentage.	HP-9.5.9; QR-15
FR-R43	Score the interview on six spoken dimensions **Description.** The interview performance score uses only the spoken record. The weights are technical competency 24 percent, alignment with the job 22 percent, depth of experience 18 percent, communication 14 percent, relevance of responses 12 percent, and problem-solving approach 10 percent. The CV aggregate must not be added in, subtracted, or used as a ceiling. **Rationale.** The call has to be able to disagree with the paper screen. **Depends on.** FR-R40.	**Description.** The interview performance score uses only the spoken record. The weights are technical competency 24 percent, alignment with the job 22 percent, depth of experience 18 percent, communication 14 percent, relevance of responses 12 percent, and problem-solving approach 10 percent. The CV aggregate must not be added in, subtracted, or used as a ceiling.	Weights: technical competency 24 percent, alignment with the job 22 percent, depth of experience 18 percent, communication 14 percent, relevance of responses 12 percent, and problem-solving approach 10 percent. The CV aggregate must not be added, subtracted, or used as a ceiling.	HP-9.5.9; QR-09
FR-R44	Review the interview process separately **Description.** A second review covers question effectiveness, competency coverage, consistency across candidates, and interaction quality, and it may recommend a change for the next call. Those findings must not be added into the suitability score. **Rationale.** A badly run interview and a weak answer are different problems. **Depends on.** FR-R39.	**Description.** A second review covers question effectiveness, competency coverage, consistency across candidates, and interaction quality, and it may recommend a change for the next call. Those findings must not be added into the suitability score.	Question effectiveness, competency coverage, consistency across candidates, and interaction quality must not be added into the suitability score.	HP-9.5.9
FR-R45	Build the consolidated assessment **Description.** When the recruiter requests it, or when the report sequence reaches it, Sift loads the candidate, the CV screening snapshot, the quiz score, and the question-and-answer analysis, in that order. Strengths and weaknesses must	**Description.** When the recruiter requests it, or when the report sequence reaches it, Sift loads the candidate, the CV screening snapshot, the quiz score, and the question-and-answer analysis, in that order. Strengths and weaknesses must cite the CV or a transcript span. Evidence	When CV, quiz, and interview question-and-answer scores all exist: 30 percent, 20 percent, and 50 percent, rounded to one decimal. Strong Fit at or above 75. Moderate Fit at or above 50	HP-9.5.9; QR-10; Diagram 04

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	cite the CV or a transcript span. Evidence gaps are listed. Component scores are stored. When the CV score, the quiz score, and the interview question-and-answer score all exist, the overall is 30 percent CV, 20 percent quiz, and 50 percent interview, rounded to one decimal. At or above 75 the label is Strong Fit. At or above 50 and below 75 it is Moderate Fit. Below 50 it is Unsuited. If any of the three is missing, the overall is empty and the label is Insufficient evidence. The narrative must keep the source references and is capped at 4000 characters. **Rationale.** The final reading has to show its arithmetic and its citations, and it must not pretend a missing paper is a zero unless the product is explicitly changed to say so. **Depends on.** FR-R22, FR-R38, FR-R40.	gaps are listed. Component scores are stored. When the CV score, the quiz score, and the interview question-and-answer score all exist, the overall is 30 percent CV, 20 percent quiz, and 50 percent interview, rounded to one decimal. At or above 75 the label is Strong Fit. At or above 50 and below 75 it is Moderate Fit. Below 50 it is Unsuited. If any of the three is missing, the overall is empty and the label is Insufficient evidence. The narrative must keep the source references and is capped at 4000 characters.	and below 75. Unsuited below 50. If any of the three is missing, the overall is empty and the label is Insufficient evidence. Narrative cap 4000 characters. Load order is candidate, CV screening snapshot, quiz score, then question-and-answer analysis.	
FR-R46	Publish the assessment and the interview packet **Description.** The recruiter can open the assessment as an HTML report listing the component scores, the suitability label, strengths, weaknesses, and the time it was generated. The interview packet, including the transcript view and the analysis, can be downloaded as a PDF. Both documents are produced from stored rows, not from a fresh undocumented model pass. **Rationale.** A result that cannot be handed to a colleague is not finished. **Depends on.** FR-R45.	**Description.** The recruiter can open the assessment as an HTML report listing the component scores, the suitability label, strengths, weaknesses, and the time it was generated. The interview packet, including the transcript view and the analysis, can be downloaded as a PDF. Both documents are produced from stored rows, not from a fresh undocumented model pass.	Both documents are produced from stored rows, not from a fresh undocumented model pass. The HTML assessment and the PDF packet must not be the only copy of the score.	HP-9.5.9

3.1.16 Desk and progress

Home shows roles, people waiting, and upcoming calls. Long work exposes a status the page can show.

Actors. Recruiter.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-R47	Show the desk, the pipeline, and report progress **Description.** Home shows open roles, people waiting for a look, and upcoming interviews, and it links into the role or the person. A role with nobody yet tells the recruiter to create or open a job. Per-role progress distinguishes waiting on the mailbox, scanning, and scoring. After a call, report progress follows question-and-answer, claims, score, quality, and assessment. **Rationale.** The recruiter should see what is stuck without reading logs. **Depends on.** FR-R15, FR-R39.	**Description.** Home shows open roles, people waiting for a look, and upcoming interviews, and it links into the role or the person. A role with nobody yet tells the recruiter to create or open a job. Per-role progress distinguishes waiting on the mailbox, scanning, and scoring. After a call, report progress follows question-and-answer, claims, score, quality, and assessment.	Per-role progress distinguishes waiting on the mailbox, scanning, and scoring. After a call, report progress follows question-and-answer, claims, score, quality, and assessment.	HP-9.5.9; QR-17

User class 2 — Candidate

User class 2 is the candidate.

3.1.17 Candidate interview

The mail link is the whole of the candidate's access. They consent or refuse, wait to be admitted, join the room, and submit the quiz once if it is offered.

Actors. Candidate.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
FR-C01	Open only the invited interview **Description.** The link in the invitation resolves to that candidate and that job. The page shows the role they were invited for. It does not list other applicants, other roles, or recruiter controls. **Rationale.** The mail link is the whole of the candidate's access. **Depends on.** FR-R30.	**Description.** The link in the invitation resolves to that candidate and that job. The page shows the role they were invited for. It does not list other applicants, other roles, or recruiter controls.	The page does not list other applicants, other roles, or recruiter controls.	HP-9.5.7
FR-C02	Reject a bad invite or session token **Description.** A token that is missing, expired, signed with another secret, or bound to a different session does not open materials. The page explains that the link cannot be used. It does not fall through to another person's room. **Rationale.** A forwarded or edited link must fail closed. **Depends on.** FR-C01.	**Description.** A token that is missing, expired, signed with another secret, or bound to a different session does not open materials. The page explains that the link cannot be used. It does not fall through to another person's room.	A token that is missing, expired, signed with another secret, or bound to a different session does not open materials and does not fall through to another person's room.	HP-9.5.7
FR-C03	Ask for consent before the camera **Description.** The lobby explains the face check and waits for consent. No frame is sent until the candidate agrees. Refusing consent leaves them out of the room rather than sending a silent capture. **Rationale.** The camera is optional until the person agrees. **Depends on.** FR-C01.	**Description.** The lobby explains the face check and waits for consent. No frame is sent until the candidate agrees. Refusing consent leaves them out of the room rather than sending a silent capture.	No frame is sent until the candidate agrees. Refusing consent leaves them out of the room rather than sending a silent capture.	HP-9.5.7
FR-C04	Wait for the recruiter to admit them **Description.** After consent, the candidate sees that frames are being checked. They have no admit control. They enter the room only after FR-R33 succeeds. **Rationale.** Identification is not the same as permission to start. **Depends on.** FR-C03, FR-R33.	**Description.** After consent, the candidate sees that frames are being checked. They have no admit control. They enter the room only after FR-R33 succeeds.	The candidate has no admit control. Entry happens only after FR-R33 succeeds.	HP-9.5.7
FR-C05	Join the room and speak **Description.** After admission the browser connects to LiveKit with the session token. The candidate hears the interviewer and can speak. The token's claims are that candidate, that job, and that session. Leaving the room stops their media. Ending the session prevents another join with the same token. **Rationale.** The conversation is live, and the credential dies with the session. **Depends on.** FR-C04, FR-R34.	**Description.** After admission the browser connects to LiveKit with the session token. The candidate hears the interviewer and can speak. The token's claims are that candidate, that job, and that session. Leaving the room stops their media. Ending the session prevents another join with the same token.	The token's claims are that candidate, that job, and that session. Ending the session prevents another join with the same token.	HP-9.5.7
FR-C06	Sit the quiz once **Description.** When the quiz is offered, the candidate sees ten questions and the	**Description.** When the quiz is offered, the candidate sees ten questions and the remaining time. They select one option	One option per question and one submit. After a successful submit the	HP-9.5.8; QR-11

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	remaining time. They select one option per question and submit once. After a successful submit, the answers stay and cannot be replaced. When the quiz is not offered, the spoken interview still stands. **Rationale.** One attempt keeps the score meaningful. **Depends on.** FR-C05, FR-R38.	per question and submit once. After a successful submit, the answers stay and cannot be replaced. When the quiz is not offered, the spoken interview still stands.	answers stay and cannot be replaced. When the quiz is not offered, the spoken interview still stands.	

4. User Interface

Each row is a screen the baseline requires. The description is the screen behavior. Hardware the screen depends on is in section 8.

UI No.	UI Name	Related Function Req ID	Description	Test case Identifier
UI-01	Sign-in	FR-R01, FR-R02, FR-R03	Sign-in. A person who is not signed in and who opens a recruiter page is shown the sign-in form. The form has one password field and a submit action. Failure text stays on that page. Success opens Jobs, or the in-app path they were trying to reach if that path is a local Sift path.	HP-9.5.1; QR-01
UI-02	Home	FR-R47, FR-R01	Home. After sign-in, Home greets the recruiter and shows three kinds of cards: roles that need a next step, people waiting for review, and upcoming interviews. Each card links to the role or the person. If the desk cannot load, the page says so and offers a link to Jobs. If no role exists, the empty state points at creating one.	HP-9.5.1; QR-16
UI-03	Policies	FR-R04, FR-R05	Policies. The page lists documents and accepts an upload. Choosing a document shows its summary. The filename's extension is shown as PDF, DOCX, or FILE. There is no editor for the chunk text on this page.	HP-9.5.2
UI-04	Jobs	FR-R06, FR-R07, FR-R09, FR-R10, FR-R11, FR-R16, FR-R17, FR-R26, FR-R30	Jobs. Two tabs: Existing roles, and Create a role. Create a role is the brief in FR-R06. Existing roles show draft or locked. Opening a role splits into Brief and Applicants. Brief shows the description and the ten queries and, while the version is a draft, accepts edits and approval. Applicants shows scoring progress, the ranked people, CV upload, and invite. A locked pill is visually distinct from a draft pill.	HP-9.5.3; HP-9.5.4; HP-9.5.5
UI-05	Candidates	FR-R26, FR-R28, FR-R42, FR-R43, FR-R44, FR-R45, FR-R46	Candidates. Roles are listed with their people. Opening a person shows their rank, name, screening standing, and the later reports when those exist: claims, interview score, quality, assessment, and the packet. Comparison is a separate view of two people.	HP-9.5.5; HP-9.5.9; HP-9.5.10
UI-06	Interviews and Practice	FR-R31	Interviews and Practice. Interviews lists calls. Practice starts a room for the recruiter only.	HP-9.5.10
UI-07	Copilot	FR-R13, FR-R14, FR-R37	Copilot. A panel on the recruiter shell accepts a message and can reply with navigation. It does not look like the approve or invite buttons. Those remain on the job page.	HP-9.5.10; QR-13
UI-08	Invite and lobby	FR-C01, FR-C02, FR-C03, FR-C04, FR-R32, FR-R33	Invite and lobby. The candidate sees the role, a consent choice for the camera, and then a waiting state. There is no password field and no list of other people.	HP-9.5.7
UI-09	Interview room	FR-C05, FR-C06, FR-R34, FR-R35, FR-R37, FR-R38	Interview room. After admission the page connects to the room and shows the call. The quiz, when present, is a ten-question form with one submit. The recruiter can open an identity and CV panel beside a call they are observing. The candidate does not see the ranking.	HP-9.5.8

5. Non-Functional Requirements

These requirements are checks on the functional ones. Where a number appears, it is the number implemented for Sift, not a copied target from another product. The meter is an automated test or a single described trial.

For each quality requirement below, the description holds the gist and the scale, the completion criterion holds the must-statement, and the test case identifier holds the meter. Nothing in those four fields is omitted.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
Performance	QR-05, QR-06, QR-11, QR-16, QR-17. Response time, degradation, and the clocks the baseline actually states.	Specified in section 5.1.	No transactions-per-second figure is stated.	Section 5.1
Safety	QR-08, QR-12, QR-14. Harm from a camera, a weak face match, a protected phrase, or invented evidence.	Specified in section 5.2.	No safety certification is named.	Section 5.2
Security	QR-01, QR-02, QR-13, QR-18, with FR-C02 and FR-C05.	Specified in section 5.3.	One workspace password. No separate anonymous public API for candidate records.	Section 5.3
Software quality attributes	QR-03, QR-04, QR-07, QR-09, QR-10, QR-15, QR-19, QR-20, and the reliability, availability, security, maintainability, and portability readings.	Specified in section 7.	No numeric uptime percentage is promised.	Section 7

5.1 Performance Requirements

The performance characteristics below are the ones the baseline states. Where the baseline gives no number, this section does not invent one. Related behaviors are named by requirement identifier.

Response time. The spoken interviewer line waits on Gemini only, inside a short live budget of about five seconds, and then speaks a filler, a nudge, or a close (QR-05, FR-R35). The workspace JWT lifetime defaults to 240 minutes (FR-R01); that is a credential lifetime, not a transaction time. The quiz accepts a submit inside 600 seconds and up to 15 seconds after that (QR-11, FR-R38). The inbox worker repeats every configured interval, default 20 seconds (QR-06, FR-R15).

Throughput. The baseline states no transactions-per-second figure, and none is added here. The intake requirement is that a failed poll does not stop the next cycle, and that listing mail does not mark messages read (QR-06).

Capacity. A CV is at most 8 MB, and that limit is per file, not a quota on the volume (FR-R18). A checklist is exactly ten queries (QR-03). A quiz is ten questions (FR-R38). An assessment narrative is capped at 4000 characters (FR-R45). Policy embeddings are 384 dimensions (FR-R04).

Degradation modes. Ordinary completions fall through Claude, then Gemini, then Ollama, and the stored row names the tier that answered (QR-04, section 7). A mailbox exception is logged and the next cycle still runs (QR-06). A textless CV or a speechless transcript stays a recorded gap (QR-14, section 5.2). Home, Jobs, and Candidates load when LiveKit is unreachable; starting a room may fail and must say so (QR-16). A spoken line that misses its budget does not retry Claude or Ollama (QR-05).

Resource utilization. The interviewer process needs CPU capacity for local recognition and local synthesis. No GPU is required. Disk is required for policy files, CV files, speech models, and the Postgres volume. Memory, disk, and communications are otherwise not given numeric budgets.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
QR-05	The spoken turn gives up quickly **Gist.** The room does not freeze while models are retried. **Scale.** Time the interviewer will wait on Gemini before speaking a filler, a nudge, or a close.	**Must.** The wait stays inside the short live budget, about five seconds, and Claude and Ollama are not tried for that line.	**Scale.** Time the interviewer will wait on Gemini before speaking a filler, a nudge, or a close.	**Meter.** A call in which the Gemini request is forced to fail.
QR-06	Mailbox failures do not stop the loop **Gist.** Intake survives a bad poll. **Scale.** Whether the worker sleeps and polls again after an exception, and whether listing mail marks messages read.	**Must.** The next cycle still runs. Listing does not mark messages read. The default sleep is 20 seconds.	**Scale.** Whether the worker sleeps and polls again after an exception, and whether listing mail marks messages read.	**Meter.** A poll against a mailbox that errors once, and a mailbox client observed after a list.
QR-11	Quiz timing is the same for every attempt **Gist.** The clock does not depend on who is sitting. **Scale.** Seconds from start until a submit is accepted.	**Must.** The first two can count. The third cannot change the stored score. A second submit cannot replace the first.	**Scale.** Seconds from start until a submit is accepted.	**Meter.** An attempt submitted inside 600 seconds, one submitted at 610 seconds, and one submitted later.
QR-16	The desk stays usable when the room is down **Gist.** Listing jobs and candidates does not require LiveKit. **Scale.** Whether Home, Jobs, and Candidates load when the room service is unreachable.	**Must.** The pages load and show the last stored records. Starting a room may fail and must say so.	**Scale.** Whether Home, Jobs, and Candidates load when the room service is unreachable.	**Meter.** Those pages requested while LiveKit is unset.
QR-17	Progress is visible for long work **Gist.** Scanning, scoring, and report steps change a status the page can show. **Scale.** Distinct states for waiting on mail, scanning, scoring, and each report step.	**Must.** The state changes at the start and at the end of each of those activities. Report order matches FR-R39.	**Scale.** Distinct states for waiting on mail, scanning, scoring, and each report step.	**Meter.** One uploaded CV and one ended interview, watching the progress fields.

5.2 Safety Requirements

This section specifies those requirements that are concerned with possible loss, damage, or harm that could result from the use of Sift. It defines the safeguards the baseline requires and the actions that must be prevented. The baseline names no safety certification and no external safety regulation.

The safeguards are the ones already required of the product. The camera is optional until the person agrees, and refusing it sends no frame (FR-C03). A face similarity below 0.32 does not identify the person, a frame with no face does not vote, and only the recruiter can admit (FR-R32, QR-12). Gender, religion, ethnicity, disability, and an explicit age are removed from the text the recruiter reads as a reason (FR-R24, QR-08). Missing CV text or missing speech is a recorded gap, not an invented answer (FR-R20, FR-R41, QR-14).

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
QR-08	Protected phrases do not appear as reasons **Gist.** The justification text the recruiter reads has those phrases removed. **Scale.** Presence of gender, religion, ethnicity, disability, and explicit age phrases in stored	**Must.** Each matching phrase is flagged and replaced in the recruiter-facing text.	**Scale.** Presence of gender, religion, ethnicity, disability, and explicit age phrases in stored justifications and extracted attributes after screening.	**Meter.** A CV fixture that contains each class of phrase, then the stored justification lines.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	justifications and extracted attributes after screening.			
QR-12	Face decisions use the two thresholds **Gist.** Similarity becomes a decision only at the published cuts. **Scale.** Confirm, possible, and no-match outcomes.	**Must.** Confirm at or above 0.42, possible down to 0.32, and no identification below that. A faceless frame does not vote.	**Scale.** Confirm, possible, and no-match outcomes.	**Meter.** Face-identity tests at 0.42, just below 0.42, at 0.32, and below 0.32, plus a frame with no face.
QR-14	Empty evidence stays empty **Gist.** Missing text is a recorded gap. **Scale.** Analyses and assessments produced from a textless CV or a speechless transcript.	**Must.** No invented pairs, quotes, or checklist statuses. The report says the evidence is missing.	**Scale.** Analyses and assessments produced from a textless CV or a speechless transcript.	**Meter.** The empty-transcript and failed-parse tests.

5.3 Security Requirements

The factors that protect Sift from accidental or malicious access, use, modification, destruction, or disclosure are the workspace password, the session token, the face thresholds, the redaction list, and the copilot's refusals. There is no separate anonymous public API for candidate records.

- Cryptographic techniques. The workspace credential is a JWT whose role is recruiter and whose scope is the workspace (FR-R01). An invite or session token signed with another secret does not open materials (FR-C02). Secrets arrive through the environment and the repository does not contain a production secret.
- Log and history data. A posting failure is stored on the version and secret material in that error is redacted (FR-R11, QR-18). A mailbox error is logged and the next cycle still runs (QR-06). A CV parse records which pass succeeded and a confidence (FR-R19). Suitability labels are stored, not inferred later by the page.
- Functions assigned to different modules. The API, inbox worker, interviewer, transcriber, and posting tool are separate processes so a long poll or a live call does not live inside the web request (section 6).
- Restricted communications. Recruiter routes require a workspace JWT. An interview session token must not open them (QR-02, FR-R03). The API does not expose a public unauthenticated list of candidates. Health may be unauthenticated. Auth, invites, interview sessions, and quizzes still check their own token or password.
- Data integrity. A strength, weakness, or claim quote has to be a real span of the CV or the transcript (QR-15). A duplicate file hash does not create a second scored candidate (FR-R25). The copilot must not invent stored people, scores, jobs, or quotes (FR-R14, FR-R37, QR-13).

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
QR-01	Sign-in either opens the desk or it does not **Gist.** Password checking is deterministic. **Scale.** Share of attempts with the configured password that receive a workspace JWT, and share of wrong passwords that receive none.	**Must.** Every correct configured password succeeds. Every wrong password fails. Zero tokens when the password is not configured.	**Scale.** Share of attempts with the configured password that receive a workspace JWT, and share of wrong passwords that receive none.	**Meter.** The authentication tests, plus a manual wrong-password try on the sign-in page.
QR-02	Recruiter routes reject the wrong credential **Gist.** Hiring routes stay closed. **Scale.** Share of calls to policies, jobs, copilot, screening, progress, interviews, notices, assessments, claims, and interview reports that	**Must.** None of those calls succeed.	**Scale.** Share of calls to policies, jobs, copilot, screening, progress, interviews, notices, assessments, claims, and interview reports that succeed without a valid recruiter JWT.	**Meter.** Requests with no header, with an expired token, and with an interview session token.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
	succeed without a valid recruiter JWT.			
QR-13	The copilot cannot take the two guarded actions **Gist.** Chat is not an approval button. **Scale.** Copilot turns that approve a version or poll the mailbox by themselves.	**Must.** Zero such turns perform the action. The recruiter is asked to do it, or the turn only navigates.	**Scale.** Copilot turns that approve a version or poll the mailbox by themselves.	**Meter.** Prompts that ask the copilot to approve and to check the inbox.
QR-18	Secrets are not in the product responses **Gist.** Configuration secrets stay on the server. **Scale.** API responses and stored posting errors that contain the JWT secret, a model key, a mailbox password, or the Telegram bot token.	**Must.** None of those values appear. Posting errors that might echo a token are redacted.	**Scale.** API responses and stored posting errors that contain the JWT secret, a model key, a mailbox password, or the Telegram bot token.	**Meter.** A failed post and an ordinary candidate read, searched for those values.

6. Design Constraints

Design constraints are decisions the baseline already mandates. Behavioral limits that sit on top of these decisions are in section 2.1.

- The workspace and the candidate pages are a browser application. Native mobile clients are not required.
- The API, inbox worker, interviewer, transcriber, and posting tool are separate operating-system processes so a long poll or a live call does not live inside the web request.
- Persistent structured data is Postgres. Files that are originals, not scores, stay on volumes.
- Checklist identifiers are the strings Q1 through Q10.
- Job categories must be one of the supported set used by the brief form, including Information Technology, Engineering, Operations, Human Resources, Research, and None, among the wider list stored with the schema. An unknown category is rejected.
- Seniority and contract must be one of the enumerated values in FR-R06.
- The interviewer and the transcriber are LiveKit agents. They are not pages.
- Report documents are rendered from stored rows. The HTML assessment and the PDF packet must not be the only copy of the score.

7. Software Quality Attributes

The numbered checks in sections 5 and 7 are the attributes. They are grouped here so a reader can see which quality each serves.

7.1 Reliability

QR-04, QR-06, QR-07, and QR-14. A failed provider, a failed poll, a bad file, or a silent call must degrade into a stored outcome. They must not leave a half-written checklist or a fabricated answer.

7.2 Availability

QR-16 and QR-17. The desk and the room fail separately. Long jobs expose progress. This specification does not promise a numeric uptime percentage, because none has been measured for this deployment.

7.3 Security

QR-01, QR-02, QR-08, QR-12, QR-13, and QR-18, together with FR-C02 and FR-C05. The workspace password, the session token, the face thresholds, the redaction list, and the copilot's refusals are the security behavior. There is no separate anonymous public API for candidate records.

7.4 Maintainability

QR-19. The four workflows return state to the service that called them, and that service commits the rows. Tests cover the workflow order and the numeric rules. A page change is not required to change a weight, and a weight change is a change to this specification as well as to the code.

7.5 Portability

QR-20. The supported shape is the compose file on a machine that can run those containers and a current browser. iOS and Android applications are not a requirement. A browser on a phone is enough for the candidate only if it can open the link, the camera, and the microphone. The specification does not promise a layout unique to a store app.

The quality requirements that carry these attributes, and that are not already tabulated under performance, safety, or security, are the following.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
QR-03	A checklist is exactly ten queries **Gist.** The scoring contract has a fixed shape. **Scale.** Stored draft and locked versions whose query ids are Q1 through Q10 once each, with weights summing to 1.	**Must.** Every stored checklist meets the rule. A model reply that does not is discarded.	**Scale.** Stored draft and locked versions whose query ids are Q1 through Q10 once each, with weights summing to 1.	**Meter.** Job-creation tests and one created role inspected on the Brief tab.
QR-04	Ordinary model calls fall through three tiers **Gist.** One provider outage does not end a draft or a screen. **Scale.** Order of providers tried, and whether the stored row names the tier that answered.	**Must.** The order is Claude, then Gemini, then Ollama. The spoken interviewer line and the CV skill recheck are the exceptions named in FR-R35 and FR-R23.	**Scale.** Order of providers tried, and whether the stored row names the tier that answered.	**Meter.** Tests that fail the first provider and expect the next, plus the tier field on a stored job version.
QR-07	Unreadable and duplicate CVs stay out of the score **Gist.** The ranking counts real screens only. **Scale.** Files over 8 MB, non-PDF and non-DOCX files, textless files, and byte-identical repeats.	**Must.** Wrong type and oversize are rejected. Textless files are stored as failed and unscored. A repeated hash does not create a second scored candidate.	**Scale.** Files over 8 MB, non-PDF and non-DOCX files, textless files, and byte-identical repeats.	**Meter.** One file of each kind submitted to intake.

REQUIREMENT ID	Requirement Description	Acceptability / Completion Criteria	Limitations / Constraints	Test case Identifier
QR-09	The interview score ignores the CV number **Gist.** Spoken performance is independent. **Scale.** Whether the six weights sum to 1 and whether the CV aggregate is read while computing them.	**Must.** Weights are 0.24, 0.22, 0.18, 0.14, 0.12, and 0.10 in the order in FR-R43. Changing the CV score alone does not change this result.	**Scale.** Whether the six weights sum to 1 and whether the CV aggregate is read while computing them.	**Meter.** The interview-score tests, and a candidate whose CV score and interview score differ.
QR-10	Suitability uses the published mix or it abstains **Gist.** The headline number is either the stated mix or it is absent. **Scale.** Overall score and label against the three inputs.	**Must.** With all three present, the mix is 0.30, 0.20, and 0.50. Labels break at 75 and 50 as in FR-R45. With any input missing, the label is Insufficient evidence and the overall is empty.	**Scale.** Overall score and label against the three inputs.	**Meter.** Assessment tests with all three inputs, and with one input removed.
QR-15	Citations are real spans **Gist.** A strength, weakness, or claim quote points at source text. **Scale.** Share of stored claims whose source reference is a CV excerpt or a transcript span that contains the quoted words in order.	**Must.** A quote that is not in the source is not stored as support or as a contradiction.	**Scale.** Share of stored claims whose source reference is a CV excerpt or a transcript span that contains the quoted words in order.	**Meter.** Assessment and claim tests that reject a quote not present in the source.
QR-19	Workflow steps are covered by tests **Gist.** The four workflows and the rules around them can be run without the live room. **Scale.** Presence of automated tests for job creation, CV screening, question-and-answer analysis, the master assessment, invites, face decisions, and quiz timing.	**Must.** Each of those areas has tests that fail if the order, the weights, or the rejection rules change by accident.	**Scale.** Presence of automated tests for job creation, CV screening, question-and-answer analysis, the master assessment, invites, face decisions, and quiz timing.	**Meter.** The test suite in the backend test folder.
QR-20	The stack starts from one composition **Gist.** The processes named in this specification are the ones an operator starts together. **Scale.** Whether the database, API, frontend, inbox worker, interviewer, transcriber, posting tool, local model host, mail catcher, and TURN are defined in the composition file.	**Must.** All of those services are defined. Redis may be defined and must not be required for Release A.	**Scale.** Whether the database, API, frontend, inbox worker, interviewer, transcriber, posting tool, local model host, mail catcher, and TURN are defined in the composition file.	**Meter.** The composition file and a start on a clean machine with secrets supplied in the environment.

8. User Interface

Section 4 names the screens. This section names the hardware those screens depend on, in the same kind of interface record. The notes are the limits already stated on each device.

UI No.	UI Name	Related Info No.	Description	Notes	Test case Identifier
HW-01	Camera and microphone	FR-C03, FR-R41	The candidate browser needs permission for microphone and camera. Refusing the camera is FR-C03. Refusing the microphone ends the useful interview and is recorded as little or no speech under FR-R41.	Refusing the camera sends no frame. Refusing the microphone ends the useful interview and is recorded as little or no speech.	HP-9.5.7; HP-9.5.9
HW-02	Interviewer processor	FR-R35	The interviewer process needs CPU capacity for local recognition and local synthesis. No GPU is required by this specification.	No GPU is required by this specification.	QR-05; HP-9.5.8
HW-03	Disk	FR-R04, FR-R18, FR-R20	Disk is required for policy files, CV files, speech models, and the Postgres volume. The 8 MB CV limit is per file, not a quota on the volume.	The 8 MB CV limit is per file, not a quota on the volume. Failed CVs are not mixed into the processed folder.	HP-9.5.5; QR-07

9. Other Requirements

This section defines the baseline requirements that are not a screen, a functional row, a quality row, or a design constraint. The template allows database requirements, schedule requirements, and any further sections the project needs. No budget requirement, internationalization requirement, or legal requirement is stated in the baseline, so none is added.

The subsections keep the baseline's release plan, stored records, failure conditions, states, hiring pass, and appendices. A few sentences that named a section number in the earlier outline now name the section in this template. The obligations in those sentences are the same.

9.1 Logical data

The following groups must remain consistent with the requirements above. Names are the stored concepts, not a promise that a column cannot be renamed if the behavior stays.

Group	Keeps	Written when
Policy	Original file, chunks, 384-dimension embeddings	FR-R04
Job	Job, version, ten queries, posting result, scoring progress	FR-R07 through FR-R12, FR-R16
Candidate intake	Candidate, document, parse result, profile, face, query evaluations, claims, notices	FR-R19 through FR-R27
Interview	Session, invite link, face checks, transcript lines, quiz attempt	FR-R30 through FR-R38
Reports	Question-and-answer analysis, claim flags, interview performance, interview quality, consolidated assessment, strengths, weaknesses, evidence links, component scores	FR-R40 through FR-R46

A candidate row points at the job version it was scored against. Moving the role to a new version must not retarget that row.

9.2 Prioritization and release plan

The release numbers 9.2.1 to 9.2.4 below are the baseline release plan.

The order is by dependency. A behavior that another required behavior cannot start without is Release A. A behavior that explains or operates that loop is Release B. A behavior that already has a working substitute is Release C. No stakeholder ballot and no cost-value chart is claimed. The tables are the whole of the method.

9.2.1 Release A — complete a hire

The demonstration is incomplete until every row here works on one role, from an empty database through an assessment.

IDs	Reason this cannot wait
FR-R01, FR-R02, FR-R03, QR-01, QR-02, QR-18	The desk is either closed correctly or it is not a desk.
FR-R04, FR-R05, FR-R06, FR-R07, FR-R08, FR-R09, FR-R10, QR-03	There is no honest score without a policy-aware locked checklist.
FR-R11	Applicants need a posted instruction. A failed post is still recorded.
FR-R15, FR-R16, FR-R17, FR-R18, FR-R19, FR-R20, FR-R21, FR-R22, FR-R23, FR-R24, FR-R25, FR-R26, FR-R27, QR-06, QR-07, QR-08, QR-14	Intake through ranking is the first half of the loop.

IDs	Reason this cannot wait
FR-R29, FR-R30, FR-C01, FR-C02, FR-C03, FR-C04, FR-R32, FR-R33, QR-12	The invitation and the face gate are one path.
FR-R34, FR-R35, FR-R36, FR-C05, QR-05, QR-16	The room has to speak, listen, and store lines.
FR-R38, FR-C06, QR-11	The assessment's quiz term needs a real attempt.
FR-R39, FR-R40, FR-R41, FR-R45, FR-R46, QR-04, QR-10, QR-15	The loop ends at a cited document, including the empty-speech case.

9.2.2 Release B — operate and explain

Release A can be demonstrated without these. They are still required for the workspace the recruiter uses day to day, and they are part of this baseline rather than ideas for a future product.

IDs	Reason it can follow the loop
FR-R12	History is safe only because the locked version already exists.
FR-R13, FR-R14, QR-13	The copilot calls the same draft and must keep the same refusals. The form already creates jobs.
FR-R28	Comparison reads scores that ranking already stored.
FR-R31	Practice reuses the room and must not write an applicant.
FR-R37	The in-call copilot reads a transcript the room already stores.
FR-R42, FR-R43, FR-R44, QR-09	Claims, the six-dimension score, and the process review explain a result. Suitability already has a rule for missing pieces.
FR-R47, QR-17	Progress makes the loop observable. The loop runs without the Home cards.
QR-19, QR-20	Tests and the compose file keep the requirements from drifting. They are not a hiring step.

9.2.3 Release C — channels with a fallback

- Google Calendar busy time and event creation. FR-R29 and FR-R30 already send mail and an ics file.
- Direct Telegram or a third-party board when the posting-tool URL is empty. FR-R11 already prefers the tool.
- Any product use of Redis. None is specified. Adding one is a revision of this document, not a silent dependency.

9.2.4 What a slip means

If time is lost, drop Release C first. Do not drop a Release A row in order to polish a Release B report. Do not change a weight, a threshold, or a checklist size in code without changing the matching requirement in sections 3, 5, and 7.

9.3 Failures the product must show

Each row is a condition, the required visible or stored result, and the requirement that owns it. A stack trace in the browser is never the required result.

Condition	Required result	Owner
Wrong workspace password	Stay on sign-in. No token.	FR-R02
Recruiter password not configured	Sign-in refused.	FR-R02
Recruiter route with an interview token	Rejected.	FR-R03, QR-02
Expired workspace JWT	Rejected. The browser returns to sign-in on the next guarded load.	FR-R01
Weights do not sum to 1	Brief is not submitted.	FR-R06
Unknown category or seniority	Brief is rejected.	FR-R06
Model returns an invalid checklist	No version is stored.	FR-R08

Condition	Required result	Owner
Edit after lock	Change is rejected. Locked rows stay.	FR-R09
Description under 100 characters at post	Version may lock only through the approve path that already required a valid draft. Posting is skipped and the skip is stored.	FR-R11
Posting tool returns an error	Version stays locked. Posting status is failed. Secret material is redacted.	FR-R11, QR-18
CV over 8 MB or wrong type	Rejected. No score.	FR-R18
CV with no extractable text	Failed parse stored. Counted as unreadable, not as a low score.	FR-R20
Same CV bytes again	No second scored candidate.	FR-R25
Local skill recheck fails	Earlier query statuses remain.	FR-R23
All three model tiers fail a draft or a screen	The action fails visibly. No partial checklist is presented as final.	QR-04
Gemini misses the spoken-line budget	Filler, nudge, or close. No wait for the other tiers.	FR-R35
Mailbox poll throws	Error is logged. Next interval still runs.	QR-06
Invite mail is refused	The person is not treated as successfully invited.	FR-R30
Calendar is not configured	Invite email still sends. No calendar error is shown as a crash.	FR-R29
Bad or expired invite token	No room and no other candidate's data.	FR-C02
Camera consent refused	No frames sent. No admission.	FR-C03
Similarity below 0.32	Not identified. Recruiter can see that. Candidate is not auto-admitted.	FR-R32
Frame with no face	Counted, not used as a match.	FR-R32
LiveKit unreachable	Desk pages still load. Joining the room fails with an explanation.	QR-16
No speech in the room	Analysis records the gap. No invented answers.	FR-R41
Quiz submit after the grace period	Stored score unchanged.	QR-11
Second quiz submit	Rejected or ignored. First score remains.	FR-C06
Quiz could not be generated	Interview continues. No fake paper.	FR-R38
Assessment requested with a missing component	Label is Insufficient evidence. Overall is empty.	FR-R45
Copilot asked to approve or to poll mail	The action is not performed.	FR-R14
Copilot asked for a person who is not stored	It says so. It does not create a person.	FR-R14
OCR program missing and earlier reads failed	CV follows the unreadable path.	FR-R20

9.4 State of a role, a file, and a call

The state numbers 9.4.1 to 9.4.5 below are the baseline state description.

9.4.1 Job version

A version is a draft or it is locked. A draft accepts description and checklist edits and can be approved. A locked version accepts neither edits nor a second approval. The next number is a new draft. Posting status is a separate field: it may be skipped, failed, not configured, or the success value returned by the tool. Posting status must not be used as a substitute for locked versus draft.

9.4.2 CV parse

A file is rejected before storage as a candidate document when the type or size rule fails. Otherwise it is stored and the parse is either a success with a method of native, layout, or optical recognition, or a failure. Only a success enters FR-R22. Scoring progress on the job moves among waiting for mail, scanning, and scoring, and returns to a settled state when the batch finishes.

9.4.3 Query status

Each of the ten queries ends as met, partially met, unmet, or insufficient evidence. Points are 1, 0.5, 0, and 0. The local recheck may move an item toward met or partially met. Nothing in screening may move an item toward unmet once a higher status was stored in that pass. Protected-attribute flags are a list beside the score, not a sixth status.

9.4.4 Interview session

A session is created from an invite, or from practice. An invited session waits on consent and admission before media starts. It then runs, and it ends. Practice never creates a candidate. A session token stops authorizing joins after the end. Transcript lines accumulate only while the transcriber is in that room. Report progress is empty before the end and then advances through question-and-answer, claims, interview score, interview quality, and assessment.

9.4.5 Claim and suitability

A claim is supported, contradicted, or unverified. Only supported claims leave the follow-up list. Suitability is Strong Fit at 75 or above, Moderate Fit from 50 up to but not including 75, Unsuited below 50, and Insufficient evidence when the overall cannot be computed. These labels are stored, not inferred later by the page.

9.5 One complete hiring pass

The step numbers 9.5.1 through 9.5.10 are the baseline hiring pass. Test case identifiers HP-9.5.n refer to these steps.

This section is not a new set of requirements. It is the order in which Release A is exercised so a reviewer can see that the identifiers fit together. The names are examples.

9.5.1 Empty workspace

The operator starts the composition file with a recruiter password, a JWT secret, and model settings. Postgres is empty. The recruiter opens the browser and is shown sign-in, because no workspace token exists. FR-R02 is satisfied if a wrong password stays on that page. FR-R01 is satisfied when the right password opens the desk. Home may be empty. The empty state must point at Jobs rather than invent a sample role. QR-16 is satisfied if this page loads before LiveKit is configured.

9.5.2 Policy

The recruiter opens Policies and uploads a PDF that states, among other rules, a constraint the draft should respect, such as a location or a hiring rule. FR-R04 is satisfied when the file is stored, the text is chunked, and each chunk has a 384-dimension vector. FR-R05 is satisfied when the document appears in the list and a summary can be opened. A second upload of a different file adds a row. It must not replace the first file’s chunks.

9.5.3 Brief and draft

On Create a role the recruiter enters a title, leaves seniority at Mid-Level, leaves the weights at 0.5, 0.3, and 0.2, and types at least one required skill. FR-R06 rejects the form if the weights are changed so they no longer sum to 1, or if the required-skill field is blank. A valid submit runs FR-R07. The Brief tab then shows a description of at least 100 characters and queries Q1 through Q10. If the policy text constrained the role, the description should reflect that constraint. The version is a draft. The model tier is stored. QR-03 is checked by counting the query ids.

The recruiter changes one query's question and saves. FR-R09 allows that. They then try the same save after approval and it must fail.

9.5.4 Approval and post

Approval runs FR-R10 and FR-R11. The pill becomes locked. The posting result is stored. In the default composition the posting tool is reached and Telegram receives the role, including the instruction to email a PDF or DOCX with the job's subject. If the tool is down, the version stays locked and the posting row records the failure. The recruiter must not have to recreate the checklist to retry a post, and this specification does not require a second button beyond what the product already uses to record that failure.

9.5.5 Two CVs and one bad file

The reviewer emails two real CVs and one text file renamed to look like a document, using the posted subject. FR-R15 picks them up within one poll interval after the worker is running, or immediately if the recruiter starts FR-R16. The text file fails FR-R18 or FR-R20 and is counted as unreadable in the notice from FR-R27. Each real CV gets attributes, a face when one exists, ten statuses, and justifications. FR-R24 is checked by including a protected phrase in a fixture CV and reading the justification. FR-R25 is checked by delivering the same bytes twice and confirming a single scored candidate. FR-R26 shows an order. The recruiter does not receive automatic invites.

9.5.6 Invitation

The recruiter selects one person. FR-R29 finds a slot that does not collide with another Sift call. FR-R30 sends mail with the time, the link, and interview.ics. The other person remains uninvited. That is the requirement, not an omission.

9.5.7 Candidate entry

Opening the link satisfies FR-C01. Editing the token satisfies FR-C02. The lobby waits for consent, satisfying FR-C03. Frames are compared under FR-R32. The candidate cannot click admit, satisfying FR-C04 and FR-R33. The recruiter admits them. The browser joins the room under FR-C05 and FR-R34.

9.5.8 The call

The interviewer speaks from the checklist, preferring gaps, under FR-R35. The transcriber stores lines under FR-R36. If the reviewer asks the in-call copilot what the CV said about a skill, FR-R37 answers from that file and the lines so far. The quiz, if generated, is one submit under FR-R38 and FR-C06. Ending the call starts FR-R39.

9.5.9 Reports

FR-R40 produces four dimension means and citations. If the microphone was refused and no text exists, FR-R41 applies instead and the later assessment uses Insufficient evidence rather than a harsh invented score. FR-R42 lists follow-ups only for claims that are not supported. FR-R43 produces a spoken score that does not equal the CV aggregate merely because the CV aggregate is high. FR-R44 produces a process note that is absent from the suitability arithmetic. FR-R45 writes the mix when all three numbers exist, and FR-R46 renders HTML and a PDF from those rows. FR-R47 shows the report steps moving in the required order.

9.5.10 What this pass does not prove

It does not prove Google Calendar, a third-party job board, or Redis. Those are Release C. It does not prove the copilot, comparison, practice, or a successor version. Those are Release B and should be tried in a second pass: ask the copilot to draft a role with a missing skill and confirm it refuses, compare the two candidates, start practice and confirm no new applicant, and open version 2 and confirm version 1's scores stay put.

9.6 Appendices

9.6.1 Appendix A — Architecture

07-system-architecture.pdf is the map for sections 2.1, 2.2, 4, and 8. It shows the recruiter and the candidate, the browser, the five processes, the three stages of the loop, the shared model and speech services, the external mailbox, Telegram, LiveKit, mail, and calendar, and the four storage groups.

9.6.2 Appendix B — Workflows

Diagram	Requirement	Required order
01-langgraph-job-creation.pdf	FR-R07	Policy retrieval, description, ten queries, schema check.
02-langgraph-cv-screening.pdf	FR-R22	Parse, attributes, locked checklist, semantic match, evaluation, local recheck, fairness, justifications.
03-langgraph-qa-analysis.pdf	FR-R40	Load, pair, classify, four parallel scores, map, gaps, justifications, means.
04-langgraph-master-assessment.pdf	FR-R45	Candidate, CV snapshot, quiz, question-and-answer, strengths, gaps, suitability, narrative, tier.

The diagrams may show state fields that this specification does not repeat. They may not add a step, drop a step, or run a step early. The database write sits in the service that called the workflow, after it returns.

9.6.3 Appendix C — Identifier index

FR-R01 through FR-R47 are recruiter and system behaviors the recruiter relies on. FR-C01 through FR-C06 are candidate behaviors. QR-01 through QR-20 are the checks. Section 9.2 is the membership list. No identifier in this document is reserved or unused.

9.6.4 Appendix D — Requirement titles

ID	Title
FR-R01	Open the workspace with the recruiter password
FR-R02	Refuse a bad or unconfigured sign-in
FR-R03	Sign out
FR-R04	Upload a policy document
FR-R05	List policies and open a summary
FR-R06	Capture a job brief
FR-R07	Draft the description and the ten queries
FR-R08	Reject a draft the schema cannot accept
FR-R09	Edit a draft checklist and description
FR-R10	Approve and lock a version
FR-R11	Post the approved role
FR-R12	Open the next version without rewriting history
FR-R13	Ask the copilot to draft a role
FR-R14	Let the copilot look and navigate, not decide
FR-R15	Poll the apply mailbox on a cycle
FR-R16	Let the recruiter start a poll
FR-R17	Upload a CV onto a job

ID	Title
FR-R18	Reject a CV that is the wrong type or too large
FR-R19	Read CV text in three passes
FR-R20	Keep an unreadable CV out of the ranking
FR-R21	Enrol a face from the CV
FR-R22	Run CV screening in a fixed order
FR-R23	Allow the local recheck to raise a skill, never to lower one
FR-R24	Redact protected phrases before the recruiter reads them
FR-R25	Ignore a duplicate file
FR-R26	Rank a job's applicants
FR-R27	Tell the recruiter when a batch finishes
FR-R28	Compare two named candidates
FR-R29	Choose a free interview slot
FR-R30	Email the invitation and a calendar file
FR-R31	List calls and open a practice room
FR-R32	Compare the live face with the enrolled face
FR-R33	Hold the room until admission
FR-R34	Run the live room with three participants
FR-R35	Speak the interview from the checklist
FR-R36	Store a speaker-labelled transcript
FR-R37	Answer the recruiter from this call only
FR-R38	Offer one ten-question quiz
FR-R39	Close the call and start the report sequence
FR-R40	Pair and score the transcript
FR-R41	Say so when nobody spoke
FR-R42	Check CV claims against spoken words
FR-R43	Score the interview on six spoken dimensions
FR-R44	Review the interview process separately
FR-R45	Build the consolidated assessment
FR-R46	Publish the assessment and the interview packet
FR-R47	Show the desk, the pipeline, and report progress
FR-C01	Open only the invited interview
FR-C02	Reject a bad invite or session token
FR-C03	Ask for consent before the camera
FR-C04	Wait for the recruiter to admit them
FR-C05	Join the room and speak
FR-C06	Sit the quiz once
QR-01	Sign-in either opens the desk or it does not
QR-02	Recruiter routes reject the wrong credential
QR-03	A checklist is exactly ten queries

ID	Title
QR-04	Ordinary model calls fall through three tiers
QR-05	The spoken turn gives up quickly
QR-06	Mailbox failures do not stop the loop
QR-07	Unreadable and duplicate CVs stay out of the score
QR-08	Protected phrases do not appear as reasons
QR-09	The interview score ignores the CV number
QR-10	Suitability uses the published mix or it abstains
QR-11	Quiz timing is the same for every attempt
QR-12	Face decisions use the two thresholds
QR-13	The copilot cannot take the two guarded actions
QR-14	Empty evidence stays empty
QR-15	Citations are real spans
QR-16	The desk stays usable when the room is down
QR-17	Progress is visible for long work
QR-18	Secrets are not in the product responses
QR-19	Workflow steps are covered by tests
QR-20	The stack starts from one composition