# What's New in Apple Push Notification Service

Session 724

Mayur Mahajan Apple Push Notification Service Engineer

#### Review

HTTP/2 provider API

Instant feedback

Larger payload

Simplified certificate handling


Sending notifications


**APNs** 


Provider





Client App

















### Simplified Certificate Handling

Application push

VoIP push

Complication push

Development and production environment



Simplified provider authentication when connecting to APNs

Secure

Easy to generate

No more expired certificates!


Connecting to APNs with client certificate

APNs


Provider

Account

Connecting to APNs with client certificate




Connecting to APNs with client certificate



Account

Connecting to APNs with client certificate



Account


Connecting to APNS with Token Authentication

APNs Provider Account


Connecting to APNS with Token Authentication

APNs Provider Account


Connecting to APNS with Token Authentication





Connecting to APNS with Token Authentication





Connecting to APNS with Token Authentication











## Token Authentication Details

#### Provision signing key via Developer Account

- App Store and Ad Hoc
   Sign your iOS app for submission to the App Store or for Ad Hoc distribution.
- Apple Push Notification Service Key (Sandbox & Production)
  Generate an authentication key that can be used to sign your push notification requests.
- Apple Push Notification service SSL (Sandbox & Production)
  Establish connectivity between your notification server, the Apple Push Notification service sandbox, and production environments to deliver remote notifications to your app. When utilizing HTTP/2, the same certificate can be used to deliver app notifications, update ClockKit complication data, and alert background VoIP apps of incoming activity. A separate certificate is required for each app you distribute.

## Token Authentication Details

#### Provision signing key via Developer Account

- App Store and Ad Hoc
   Sign your iOS app for submission to the App Store or for Ad Hoc distribution.
- Apple Push Notification Service Key (Sandbox & Production)
  Generate an authentication key that can be used to sign your push notification requests.
- Apple Push Notification service SSL (Sandbox & Production)
  Establish connectivity between your notification server, the Apple Push Notification service sandbox, and production environments to deliver remote notifications to your app. When utilizing HTTP/2, the same certificate can be used to deliver app notifications, update ClockKit complication data, and alert background VoIP apps of incoming activity. A separate certificate is required for each app you distribute.

#### Details

Provision signing key via Developer Account

Construct the token

Sign token using ES256 (ECDSA using P256 curve, SHA256 hash)

```
// Token Authentication
// JSON Web Tokens
eyJhbGciOiJFUzI1NiIsImtpZCI6IkFCQ0RFRkdISUoifQ.eyJpc3MiOiIxMjM0NTY30DkwIiwiaWF0Ijoi
MTQ2Mzk3NTIzMyJ9.aBup1REyXE9Po8ekWJ3ifUly67NlPyTlcgfSwy...
Header
  "alg": "ES256",
  "kid": "ABCDEFGHIJ"
Claims
  "iss": "QRSTUVWXYZ",
  "iat": "1463975233"
Signature
```

```
// Token Authentication
// JSON Web Tokens
```

eyJhbGciOiJFUzI1NiIsImtpZCI6IkFCQ0RFRkdISUoifQ.eyJpc3MiOiIxMjM0NTY30DkwIiwiaWF0Ijoi
MTQ2Mzk3NTIzMyJ9.aBup1REyXE9Po8ekWJ3ifUly67NlPyTlcgfSwy...

```
Header
{
    "alg": "ES256",
    "kid": "ABCDEFGHIJ"
}
Claims
{
    "iss": "QRSTUVWXYZ",
    "iat": "1463975233"
}
Signature
```

```
// Token Authentication
// JSON Web Tokens
eyJhbGciOiJFUzI1NiIsImtpZCI6IkFCQ0RFRkdISUoifQ.eyJpc3MiOiIxMjM0NTY30DkwIiwiaWF0Ijoi
MTQ2Mzk3NTIzMyJ9.aBup1REyXE9Po8ekWJ3ifUly67NlPyTlcgfSwy...
Header
  "alg": "ES256",
  "kid": "ABCDEFGHIJ"
Claims
  "iss": "QRSTUVWXYZ",
```

"iat": "1463975233"

Signature

```
// Token Authentication
// JSON Web Tokens
eyJhbGciOiJFUzI1NiIsImtpZCI6IkFCQ0RFRkdISUoifQ.eyJpc3MiOiIxMjM0NTY30DkwIiwiaWF0Ijoi
MTQ2Mzk3NTIzMyJ9.aBup1REyXE9Po8ekWJ3ifUly67NlPyTlcgfSwy...
Header
  "alg": "ES256",
  "kid": "ABCDEFGHIJ"
Claims
  "iss": "QRSTUVWXYZ",
  "iat": "1463975233"
```

Signature

```
// Token Authentication
// JSON Web Tokens
eyJhbGciOiJFUzI1NiIsImtpZCI6IkFCQ0RFRkdISUoifQ.eyJpc3MiOiIxMjM0NTY30DkwIiwiaWF0Ijoi
MTQ2Mzk3NTIzMyJ9.aBup1REyXE9Po8ekWJ3ifUly67NlPyTlcgfSwy...
Header
  "alg": "ES256",
  "kid": "ABCDEFGHIJ"
Claims
  "iss": "QRSTUVWXYZ",
  "iat": "1463975233"
Signature
```

```
// Token Authentication
// JSON Web Tokens
eyJhbGciOiJFUzI1NiIsImtpZCI6IkFCQ0RFRkdISUoifQ.eyJpc3MiOiIxMjM0NTY30DkwIiwiaWF0Ijoi
MTQ2Mzk3NTIzMyJ9.aBup1REyXE9Po8ekWJ3ifUly67NlPyTlcgfSwy...
Header
  "alg": "ES256",
  "kid": "ABCDEFGHIJ"
Claims
  "iss": "QRSTUVWXYZ",
  "iat": "1463975233"
Signature
```

```
// Token Authentication
// JSON Web Tokens
eyJhbGciOiJFUzI1NiIsImtpZCI6IkFCQ0RFRkdISUoifQ.eyJpc3MiOiIxMjM0NTY30DkwIiwiaWF0Ijoi
MTQ2Mzk3NTIzMyJ9.aBup1REyXE9Po8ekWJ3ifUly67NlPyTlcgfSwy...
Header
  "alg": "ES256",
  "kid": "ABCDEFGHIJ"
Claims
  "iss": "QRSTUVWXYZ",
  "iat": "1463975233"
Signature
```

```
// Token Authentication
// Request example
HEADERS
– END_STREAM
+ END_HEADERS
:authority = api.push.apple.com
:method = POST
:path = /3/device/ad2bcd38f6773cdad050411...
authorization = bearer eyJhbGciOiJFUzI1N...
apns-topic = com.foo.tokenauth
DATA
+ END_STREAM
```

{ "aps" : { "alert" : "Hello Token Authentication" } }

```
// Token Authentication
// Request example
HEADERS
– END_STREAM
+ END_HEADERS
:authority = api.push.apple.com
:method = POST
:path = /3/device/ad2bcd38f6773cdad050411...
authorization = bearer eyJhbGciOiJFUzI1N...
apns-topic = com.foo.tokenauth
DATA
+ END_STREAM
```

{ "aps" : { "alert" : "Hello Token Authentication" } }

```
// Token Authentication
// Response example
```

#### HEADERS

- + END\_STREAM
- + END\_HEADERS
- :status = 200

```
// Token Authentication
// Response example

HEADERS
- END_STREAM
+ END_HEADERS
:status = 403
content-type = application/json
DATA
+ END_STREAM
```

{ "reason": "InvalidProviderToken" }

```
// Token Authentication
// Response example

HEADERS
- END_STREAM
+ END_HEADERS
:status = 403
content-type = application/json
DATA
+ END_STREAM
```

{ "reason": "ExpiredProviderToken" }

#### Details

Signed tokens need to be generated periodically

Signing key does not expire

Signing key can be revoked through your Account

## Coming later this year...

More Information

https://developer.apple.com/wwdc16/724

### Related Sessions

Introduction to Notifications	Pacific Heights	Wednesday 9:00AM
Advanced Notifications	Pacific Heights	Wednesday 10:00AM

## Labs

Notifications Lab	Frameworks Lab C	Wednesday 11:00AM
Notifications Lab	Graphics, Games & Media Lab B	Friday 9:00AM

# W W D C 16