

Menus, Dialogs and Fragments

CE881: Mobile and Social Application Programming

Simon Lucas & Spyros Samothrakis

February 03, 2015

1 / 36

- 1 Interesting Cultural Artefacts
- 2 Menus
- 3 Fragments

2 / 36

Theme: "Social apps"

- The social network (movie)

3 / 36

Apps


- Facebook
- Twitter
- Pinterest
- OkCupid
- Instagram

Where's the value?

4 / 36

IDE Tips

- Ctrl+Shift+A
- Ctrl+B
- Ctrl+U
- Ctrl+J

A screenshot of the IntelliJ IDEA keyboard shortcuts window, which has an orange background. It lists various IDE actions and their corresponding keyboard shortcuts.

Comment/Uncomment block	CTRL+SHIFT+//
Quick switch scheme	CTRL+BackQuote
Quick Definition lookup	CTRL+SHIFT+J
Smart type completion	CTRL+SHIFT+SPACE
Surround with statement	CTRL+ALT+T
Surround with Live Template	CTRL+ALT+J
Go to Implementation	CTRL+ALT+B
File structure popup	CTRL+F12
View Recent changes	ALT+SHIFT+C
Browse external javadoc	SHIFT+F1
Complete Statement	CTRL+SHIFT+Enter

<http://stackoverflow.com/questions/294167/what-are-the-most-useful-intellij-idea-keyboard-shortcuts>

5 / 36

Progress Test

- Next week
- Sample progress test online
- 20 Questions
- 30 Minutes

6 / 36

Types of Menu

- Options Menu
 - Will pop up when the menu “button” is pressed on an app
 - The location of the “button” will depend on the device: on modern nexus devices it appears as a column of dots in the ActionBar
- Popup Menu
 - Appears when an item within a view is clicked, where the item handles the relevant event
- Context Menu
 - Appears on items that handle a long-click event
 - Menus can be declared in XML or in Java

7 / 36

Menus: all about selection

- A menu presents one or more items for a user to select
- When the item is selected an action should be taken
- Menus are added to parent views
 - Write a method to handle the appropriate event
 - It is common for the same method to handle many menu item selections
 - Then use a switch statement to detect which item was selected

8 / 36

Creating a Menu in XML

```
MyActivity.java x AndroidManifest.xml x strings.xml x menu1.xml x
<?xml version="1.0" encoding="utf-8"?>
<menu xmlns:android="http://schemas.android.com/apk/res/android">
  <item android:id="@+id/search"
        android:icon="@android:drawable/ic_menu_search"
        android:title="@string/search"
        />
  <item android:id="@+id/help"
        android:showAsAction="ifRoom"
        android:icon="@drawable/ic_launcher"
        android:title="@string/help"/>
  <item android:id="@+id/quit"
        android:icon="@android:drawable/ic_menu_add"
        android:showAsAction="ifRoom"
        android:title="@string/waah"/>
/>
</menu>
```

9 / 36

Questions

android:id="@id/help" vs android:id="@+id/help"

10 / 36

Then loading it in Java

- Override the `onCreateOptionsMenu` method
- Use a `MenuInflater` to build the menu
- Note: `menu1` matches the name of the xml file (`menu1.xml`) in the folder `res/menu/`

```
public boolean onCreateOptionsMenu(Menu menu) {
    MenuInflater inflater = getMenuInflater();
    inflater.inflate(R.menu.menu1, menu);
    return true;
}
```

11 / 36


Creating a Menu in Java

- Override the **`onCreateOptionsMenu`** method
- Add the menu item and assign the return value to a reference variable of type `MenuItem`
- Call methods of the `MenuItem` object to modify its appearance or where it appears

12 / 36

Java Code

- In addition to adding a menu item labelled "Test" we also add an Icon to it




```
public boolean onCreateOptionsMenu(Menu menu) {
    MenuItem test = menu.add("Test");
    test.setIcon(R.drawable.ic_launcher);
    return true;
}
```

13 / 36

Frustrating Differences

- The exact appearance of a menu differs with version of Android OS (or variations in UI added by manufacturer)
- E.g. the above Java code running on S4 (above) versus on a Nexus 7 emulator (below)



14 / 36

Adding Custom Menu Icons

- Normal practice is to either:
 - Use Android Platform Icons
 - Add your own in the drawable folder
 - Ideally there should be separate versions for each resolution
 - The IDE may do this for you
- Somehow you need to do it automatically for your sanity
- But it's also possible to draw your own at Runtime...

15 / 36

Dynamic Menu Icon Creation

- When setting up the menu icon:
 - setIcon() can take a Drawable (Drawable is an Abstract Class)
- So do this:
 - **class MyIcon extends Drawable**
 - Then implement the draw(Canvas c) method
 - Doing this felt a bit "off" - it might be useful - and was an interesting exercise, but use with some caution

16 / 36

Dialogs (1)

- Dialogs can be built very easily using the AlertDialog builder.
- The following code assumes this is being called from a method of an Activity
 - (note the “this” object being passed to the AlertDialog.Builder(this) constructor)
- The rest of the code:
- Sets the title and message strings
- Sets handlers for the onClick events for each button
- Shows the Dialog

17 / 36

Dialogs (2)

```

@Override
public boolean onKeyDown(int keyCode, KeyEvent event)
{
    if (keyCode == KeyEvent.KEYCODE_BACK && event.getRepeatCount() == 0)
    {
        AlertDialog alertDialog =
            new AlertDialog.Builder(this).create();
        alertDialog.setTitle("I see you're trying to leave.");
        alertDialog.setMessage("Are you sure?");

        alertDialog.setButton(DialogInterface.BUTTON_POSITIVE,
            "Yes", new DialogInterface.OnClickListener()
            {
                @Override
                public void onClick(DialogInterface dialog, int which)
                {
                    finish();
                }
            });

        alertDialog.setButton(DialogInterface.BUTTON_NEGATIVE,
            "No", new DialogInterface.OnClickListener()
            {
                @Override
                public void onClick(DialogInterface dialog, int which)
                {
                    // do nothing dialog will dismiss
                }
            });

        alertDialog.show();
        return true; //meaning you've dealt with the keyevent
    }
    return super.onKeyDown(keyCode, event);
}

```

18 / 36

Custom Dialogs

- Main idea:
 - Your custom Dialog class will extend DialogFragment
 - Use the AlertDialog.Builder as before
 - Override the onCreateDialog method within the subclass
 - Then create a new instance of your class and call its show method to show it

19 / 36

Example

see: <http://developer.android.com/guide/topics/ui/dialogs.html>

```

public class FireMissilesDialogFragment extends DialogFragment {
    @Override
    public Dialog onCreateDialog(Bundle savedInstanceState) {
        // Use the Builder class for convenient dialog construction
        AlertDialog.Builder builder = new AlertDialog.Builder(getActivity());
        builder.setMessage(R.string.dialog_fire_missiles)
            .setPositiveButton(R.string.fire, new DialogInterface.OnClickListener() {
                public void onClick(DialogInterface dialog, int id) {
                    // FIRE ZE MISSILES!
                }
            })
            .setNegativeButton(R.string.cancel, new DialogInterface.OnClickListener() {
                public void onClick(DialogInterface dialog, int id) {
                    // User cancelled the dialog
                }
            });
        // Create the AlertDialog object and return it
        return builder.create();
    }
}

```

20 / 36

Specifying a Custom Layout

- Within the builder we can call `setView` to set a custom view
- Can use Views specified in XML or created dynamically in Java
- This is equivalent to the `setContentView` we've used in the `onCreate` method of an Activity
- The relevant line on the next slide (copied from the Android developer guide) is below
- Note that the code looks more complex than necessary due to method call chaining

```
public void onCreate(Bundle savedInstanceState)
{
    builder.setView(inflater.inflate(
        R.layout.dialog_signin, null)
    );
}
```

21 / 36

Code

```
@Override
public Dialog onCreateDialog(Bundle savedInstanceState) {
    AlertDialog.Builder builder = new AlertDialog.Builder(getActivity());
    // Get the layout inflater
    LayoutInflater inflater = getActivity().getLayoutInflater();

    // Inflate and set the layout for the dialog
    // Pass null as the parent view because its going in the dialog layout
    builder.setView(inflater.inflate(R.layout.dialog_signin, null))
    // Add action buttons
    .setPositiveButton(R.string.signin, new DialogInterface.OnClickListener() {
        @Override
        public void onClick(DialogInterface dialog, int id) {
            // sign in the user ...
        }
    })
    .setNegativeButton(R.string.cancel, new DialogInterface.OnClickListener() {
        public void onClick(DialogInterface dialog, int id) {
            LoginDialogFragment.this.getDialog().cancel();
        }
    });
    return builder.create();
}
```

22 / 36

Fragments

- Fragments offer a powerful way to compose Apps in a highly modular way
- Choice of Layout can easily depend on screen size
- Each Fragment has it's own lifecycle, tied to its parent activity's cycle
 - Composing an Activity from several fragments offers flexibility
 - The overhead is additional coding
 - These notes summarise the main points:
- See examples and lab exercise for more detail

23 / 36


Fragments and Android API Versions

- Fragments have native support from API 11 (Honeycomb, 3.0) onwards
 - If compatibility with earlier versions is required then the Android Support Library must be used
 - This also leads to some differences in the code
 - Fragments always belong to an Activity
- i.e. an Activity hosts a Fragment
 - From API 11 onwards, any Activity can host a Fragment
 - With earlier APIs and the Support Library, a `FragmentActivity` is needed (or a sub-class of this)

24 / 36

Example

<http://developer.android.com/training/basics/fragments/fragment-ui.html>



25 / 36


Defining Fragment GUIs

- Like other layouts, can be done in XML or in Java code
- XML trick:
 - Define two layouts, one for small screen, one for tablet (large screen)
 - The one for the tablet must be in a directory with the "large" qualifier e.g. two layouts could be:
 - `res/layout/news_articles.xml`
 - `res/layout-large/news_articles.xml`
 - When the layout is inflated the correct one will be chosen
- Following shows FragmentBasics example on Nexus One and Nexus 7 emulators

26 / 36

FragmentBasics Example

Note the different layouts



27 / 36

Fragments in Java Code

- When Fragments are added to XML layouts they cannot be removed in code
- Alternative: Fragments can be added or removed with the appropriate Java
 - This enables dynamic construction of GUIs
 - BUT NOTE: all additions and removals of Fragments MUST be done within a Fragment Transaction
 - Discussion: why is this so?

28 / 36

Implementing Fragments

- Similar to defining an Activity
- Except main override for Activity is onCreate()
- For Fragment use:

```
onCreateView()  
    // check the savedInstanceState  
    // inflate the layout  
onStart()  
    // can now update view components  
    // since layout is ready for use  
    // perform any initialisation  
    // and restoration of state
```

29 / 36

Managing Fragments

- The host activity is responsible for:
- Creating, adding and removing fragments
- Note:
 - To be visible each Fragment must be added to a View
 - Within the Fragment code, Save any state by overriding onPause() or onSaveInstanceState()

30 / 36

Programming with Fragments

- Note: communication between sibling fragments is not allowed
- Instead communicate via parent activity
- Also, see examples here:
 - <http://developer.android.com/training/basics/fragments/fragment-ui.html>
 - <http://developer.android.com/training/animation/cardflip.html>
- Discussion question: there is nothing to stop you trying this, but why do you think it is “not allowed”
- Do you need more than one activities in your app? Why not just stick to fragments?

31 / 36

XML Fragments - loading

```
<?xml version="1.0" encoding="utf-8"?>  
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"  
    android:orientation="horizontal"  
    android:layout_width="match_parent"  
    android:layout_height="match_parent">  
    <fragment android:name="com.example.news.ArticleListFragment"  
        android:id="@+id/list"  
        android:layout_weight="1"  
        android:layout_width="0dp"  
        android:layout_height="match_parent" />  
    <fragment android:name="com.example.news.ArticleReaderFragment"  
        android:id="@+id/viewer"  
        android:layout_weight="2"  
        android:layout_width="0dp"  
        android:layout_height="match_parent" />  
</LinearLayout>
```

32 / 36

XML Fragments - loading

```
public static class ExampleFragment extends Fragment {  
    @Override  
    public View onCreateView(LayoutInflater inflater, ViewGroup container,  
        Bundle savedInstanceState) {  
        // Inflate the layout for this fragment  
        return inflater.inflate(R.layout.example_fragment, container, false);  
    }  
}
```

33 / 36

Programmatically

```
FragmentManager fragmentManager = getFragmentManager()  
FragmentTransaction fragmentTransaction = fragmentManager.beginTransaction();  
ExampleFragment fragment = new ExampleFragment();  
fragmentTransaction.add(R.id.fragment_container, fragment);  
fragmentTransaction.commit();
```

34 / 36

Fragment Transactions

- Why transactions?

35 / 36

Summary

- With these Menus and Dialogs you can build sophisticated custom-designed User Interfaces for your apps
- Practice these ideas in the lab
- Use fragments
- Fragments are recommended for building apps in a scalable and flexible way
- Especially good for coping with different screen sizes
- They are reusable modules that always belong to a parent (host) Activity
- But are responsible for managing some lifecycle callbacks to initialise, save, and restore their state

36 / 36