

#PROGRAM1

```
class Student:
def display(self):
print("Welcome Student")

s1 = Student()
s1.display()
```

OUTPUT

Welcome Student

#PROGRAM2

```
class Student:
def display_details(self):
print("Name:", self.name)
print("Age:", self.age)
print("Marks:", self.marks)

student1 = Student()

student1.name = "SARUBALA"
student1.age = 20
student1.marks = 85.5

student1.display_details()
```

OUTPUT

Name: SARUBALA
Age: 20
Marks: 85.5

#PROGRAM4

```
class Student:
def __init__(self, name, age, marks):
self.name = name
self.age = age
self.marks = marks

def display_details(self):
print("Name:", self.name)
print("Age:", self.age)
print("Marks:", self.marks)

student1 = Student("SARUBALA", 20, 85.5)
student2 = Student("Kavin", 21, 90.0)

student1.display_details()
print()

student2.display_details()
```

OUTPUT

Name: SARUBALA
Age: 20
Marks: 85.5

Name: Kavin
Age: 21

Marks: 90.0

#PROGRAM5

```
class Calculations:
def __init__(self, n1, n2):
self.n1 = n1
self.n2 = n2

def addition(self):
return self.n1 + self.n2

def subtraction(self):
return self.n1 - self.n2

obj = Calculations(200, 100)

print("Object Instantiated")
print("Addition Working")
print("Subtraction Working")

print("Sum:", obj.addition())
print("Difference:", obj.subtraction())
```

OUTPUT

```
Object Instantiated
Addition Working
Subtraction Working
Sum: 300
Difference: 100
```

#PROGRAM6

```
class Student:
def display_details(self):
print("Name:", self.name)
print("Age:", self.age)
print("Marks:", self.marks)

student1 = Student()

student1.name = "SARUBALA"
student1.age = 20
student1.marks = 85.5

student1.display_details()
```

OUTPUT

```
Name: SARUBALA
Age: 20
Marks: 85.5
```

#PROGRAM7

```
class MyClass:
variable = "blah"

def function(self):
print("This is a message inside the class.")

myobjectx = MyClass()
myobjecty = MyClass()
```

```
myobjecty.variable = "yackity"
print(myobjectx.variable)
print(myobjecty.variable)
myobjectx.function()
myobjecty.function()
```

OUTPUT

```
blah
yackity
This is a message inside the class.
This is a message inside the class.
```

#PROGRAM8

```
class MyClass:
a = 10
b = 20

def add(self):
sum = self.a + self.b
print(sum)

ob = MyClass()

print(ob.a)
print(ob.b)
ob.add()
```

OUTPUT

```
10
20
30
```

#PROGRAM9

```
class DemoClass:
def __init__(self):
print("Calling Default Constructor")

x = DemoClass()
```

OUTPUT

```
Calling Default Constructor
```

#PROGRAM10

```
class DemoClass:
a = 20

def __init__(self):
print("Calling Default Constructor")
print(self.a)

x = DemoClass()
```

OUTPUT

```
Calling Default Constructor
20
```

#PROGRAM11

```
class DemoClass:
```

```
num = 101

def __init__(self, data):
    self.num = data

def read_number(self):
    print(self.num)

obj = DemoClass(55)
obj.read_number()

obj2 = DemoClass(66)
obj2.read_number()
```

OUTPUT

55

66