



FARRELL ANCHORING CEMENT

Product Data Sheet

Quick Setting & Non-Shrinking Anchoring Cement

DESCRIPTION:

FARRELL ANCHORING CEMENT is a quick setting and non-shrinking anchoring cement which gives a rock hard anchor for any items needing anchoring. As it hardens it expands to fill all voids and locks itself securely in place. Sets up hard in 15 minutes and will be stronger than concrete in one hour.

USES:

Anchors bolts, lamp posts, signs, hand railings, fence and mail box posts, etc. Can be used both interior and exterior.

ADVANTAGES:

1. Quick setting
2. Non-shrinking
3. Rock hard
4. Self locking
5. Stronger than concrete
6. Easy to use

TECHNICAL DATA

Compression 4700 P.S.I.

PACKAGING: 50 lb. Plastic Pail

INSTALLATION:

MIXING

Pourable Consistency: Approximately 6 quarts clean water per 50-lbs. of Anchoring Cement.

Putty Consistency: Approximately 5 quarts clean water per 50-lbs. of Anchoring Cement.

MIX ONLY WHAT CAN BE USED IN 10 MINUTES.

Mix for only 1-2 minutes. Excess water may result in failure to attain proper strength. For cold weather application, warm product to over 50° F and use warm water for mixing. Pre-heat hole before application.

Anchoring In Vertical Surfaces (Putty Consistency)

Fill hole with putty like cement first. Then temp bolt or rod into place. Let stand a few minutes before smoothing out the surface with a putty knife. Let harden for 30 minutes; then sprinkle with water. For best results allow anchor to sit overnight before weight is applied.

Anchoring in Horizontal Surfaces (Pourable Consistency)
Drill or chisel hole in concrete, brick or stone at least 3" deep. Hole should not be tapered. Blow out all dust and loose material and flood hole with water. Scrub side and bottom with stiff brush and remove excess water. Provide washers on anchor bolts before placing in hole. Place bolt in hole and fill with Anchoring Cement. Be sure to taper Anchoring Cement up and around bolt or rod about 1/4" above surface to avoid a trap where water and dirt may accumulate.

NOTE:

Anchoring Cement may weaken and erode if continuously exposed to running or still water. Where these conditions exist, the product should be tapered and coated with a good quality concrete sealer or waterproof paint. Anchor Cement is a hole filler only, not a surface patch because it expands when setting.

WARRANTY:

All products are made with the finest quality raw material under exacting care. We fully guarantee all products when applied according to manufacturer's instructions. Improper mixing, applications and other factors beyond our control

 **MADE IN USA**

Farrell Equipment & Supply Co., Inc.

EAU CLAIRE

715-835-4334
800-533-0909
1510 N. Hastings Way
Eau Claire, WI 54703

LA CROSSE

608-796-9300
888-533-0909
508 Monitor Street
La Crosse, WI 54603

MADISON

608-222-5372
888-533-7909
2300 Kilgust Road
Monona, WI 53713

ROCHESTER

507-252-0234
888-533-8909
1635 3rd Avenue S.E.
Rochester, MN 55904

WAUSAU

715-355-8300
800-933-5939
7405 Commerce Drive
Weston, WI 54476