

Advanced Shell Scripting for Bioinformatics

Stephen A. Sefick

2017-02-23



Outline

- 1 Introduction
- 2 Bash Scripting Example
- 3 Exercise
- 4 Reproducible Research

- 1 Introduction
- 2 Bash Scripting Example
- 3 Exercise
- 4 Reproducible Research

Motivation: why write a bash script?

Motivation: why write a bash script?

1 Reusable

Motivation: why write a bash script?

1 Reusable

- Do something once; do it a thousand times

Motivation: why write a bash script?

❶ Reusable

- Do something once; do it a thousand times

❷ Remember what you did

Motivation: why write a bash script?

① Reusable

- Do something once; do it a thousand times

② Remember what you did

- analysis documentation

Motivation: why write a bash script?

① Reusable

- Do something once; do it a thousand times

② Remember what you did

- analysis documentation
- reproducible research

Motivation: why write a bash script?

① Reusable

- Do something once; do it a thousand times

② Remember what you did

- analysis documentation
- reproducible research
- literate programming

Motivation: why write a bash script?

- ❶ Reusable
 - Do something once; do it a thousand times
- ❷ Remember what you did
 - analysis documentation
 - reproducible research
 - literate programming
- ❸ Deploy-able on desktop or supercomputer

Motivation: why write a bash script?

- 1 Reusable
 - Do something once; do it a thousand times
- 2 Remember what you did
 - analysis documentation
 - reproducible research
 - literate programming
- 3 Deploy-able on desktop or supercomputer
- 4 Computer Programming is JUST DARN FUN!!!

Basic Bash Scripting

Basic Bash Scripting

- 1 What is a script?

Basic Bash Scripting

- 1 What is a script?
 - a "recipe" for the computer

Basic Bash Scripting

- 1 What is a script?
 - a "recipe" for the computer
- 2 A collection of instructions in an **interpreted language**

Basic Bash Scripting

- 1 What is a script?
 - a "recipe" for the computer
- 2 A collection of instructions in an **interpreted language**
 - Bash, R, Python, Perl, etc.

Basic Bash Scripting

- ❶ What is a script?
 - a "recipe" for the computer

- ❷ A collection of instructions in an **interpreted language**
 - Bash, R, Python, Perl, etc.
 - Instructions executed at run-time

Basic Bash Scripting

- 1 What is a script?
 - a "recipe" for the computer
- 2 A collection of instructions in an **interpreted language**
 - Bash, R, Python, Perl, etc.
 - Instructions executed at run-time
 - with language specified in the shebang line

Basic Bash Scripting

- ❶ What is a script?
 - a "recipe" for the computer
- ❷ A collection of instructions in an **interpreted language**
 - Bash, R, Python, Perl, etc.
 - Instructions executed at run-time
 - with language specified in the shebang line
- ❸ Human-readable (next step literate programming)

Basic Bash Scripting

- ❶ What is a script?
 - a "recipe" for the computer
- ❷ A collection of instructions in an **interpreted language**
 - Bash, R, Python, Perl, etc.
 - Instructions executed at run-time
 - with language specified in the shebang line
- ❸ Human-readable (next step literate programming)
 - comment, comment, comment!!!

Basic Bash Scripting

- ❶ What is a script?
 - a "recipe" for the computer

- ❷ A collection of instructions in an **interpreted language**
 - Bash, R, Python, Perl, etc.
 - Instructions executed at run-time
 - with language specified in the shebang line

- ❸ Human-readable (next step literate programming)
 - comment, comment, comment!!!
 - worst enemy in 6 months?

Basic Bash Scripting


- ❶ What is a script?
 - a "recipe" for the computer

- ❷ A collection of instructions in an **interpreted language**
 - Bash, R, Python, Perl, etc.
 - Instructions executed at run-time
 - with language specified in the shebang line

- ❸ Human-readable (next step literate programming)
 - comment, comment, comment!!!
 - worst enemy in 6 months?
 - YOU ARE!!!!

Anatomy of a script

Anatomy of a script



Anatomy of a script

```
1 #!/usr/bin/env sh
```

“she-bang” line:

Absolute path to the interpreted
language binary

Anatomy of a script

1 `#!/usr/bin/env sh`

2 `Module block`

Modules

Load modules next



Anatomy of a script

1 `#!/usr/bin/env sh`

2 `Module block`

3 `Variable block`

Variables

Define variables next

Anatomy of a script

1 `#!/usr/bin/env sh`

2 `Module block`

3 `Variable block`

4 `Commands`

Commands

What the script will do

What are variables?

1 Environmental variables

What are variables?

- 1 Environmental variables
 - used by 1 or more applications

What are variables?

- ① Environmental variables
 - used by 1 or more applications
 - \$HOME, \$PATH, \$SHELL, etc.

What are variables?

- ❶ Environmental variables
 - used by 1 or more applications
 - \$HOME, \$PATH, \$SHELL, etc.
- ❷ User defined variables

What are variables?

① Environmental variables

- used by 1 or more applications
- \$HOME, \$PATH, \$SHELL, etc.

② User defined variables

- can be anything (assume env variable names are **reserved**)

What are variables?

① Environmental variables

- used by 1 or more applications
- \$HOME, \$PATH, \$SHELL, etc.

② User defined variables

- can be anything (assume env variable names are **reserved**)
- best practice

What are variables?

1 Environmental variables

- used by 1 or more applications
- \$HOME, \$PATH, \$SHELL, etc.

2 User defined variables

- can be anything (assume env variable names are **reserved**)
- best practice
 - indicative of what it stores

What are variables?

1 Environmental variables

- used by 1 or more applications
- \$HOME, \$PATH, \$SHELL, etc.

2 User defined variables

- can be anything (assume env variable names are **reserved**)
- best practice
 - indicative of what it stores
 - contains no special characters (i.e., \$)

What are variables?

1 Environmental variables

- used by 1 or more applications
- \$HOME, \$PATH, \$SHELL, etc.

2 User defined variables

- can be anything (assume env variable names are **reserved**)
- best practice
 - indicative of what it stores
 - contains no special characters (i.e., \$)
 - separated by underscores raw_counts

Why are variables important?

Why are variables important?

- 1 tidy code

Why are variables important?

- 1 tidy code
- 2 easily readable

Why are variables important?

- 1 tidy code
- 2 easily readable
- 3 less mistakes

Why are variables important?

- 1 tidy code
- 2 easily readable
- 3 less mistakes
 - type once use multiple times

Variable creation

1 directly

```
wd=${HOME}/analysis_directory  
echo ${wd}
```

```
/home/ssefick/analysis_directory
```

Variable creation

1 directly

```
wd=${HOME}/analysis_directory
echo ${wd}
```

```
/home/ssefick/analysis_directory
```

2 dynamically

```
##direct
input_dir=input
##dynamic
files=('ls ${input_dir} | grep sh$')
echo ${files[@]}
```

```
awesome_script1.sh awesome_script2.sh awesome_script3.sh
```

- 1 Introduction
- 2 Bash Scripting Example
- 3 Exercise
- 4 Reproducible Research

An example: work smarter not harder

- 1 I accidentally named files with `.sh` and not `.pl`

An example: work smarter not harder

- 1 I accidentally named files with `.sh` and not `.pl`
- 2 What we know about the problem

An example: work smarter not harder

- 1 I accidentally named files with `.sh` and not `.pl`
- 2 What we know about the problem
 - more than 1 mislabeled file

An example: work smarter not harder

- ❶ I accidentally named files with `.sh` and not `.pl`
- ❷ What we know about the problem
 - more than 1 mislabeled file
 - Contained in a folder called input

An example: work smarter not harder

- ❶ I accidentally named files with `.sh` and not `.pl`
- ❷ What we know about the problem
 - more than 1 mislabeled file
 - Contained in a folder called `input`
- ❸ What is a sensible way to go about this?

An example: work smarter not harder

- ❶ I accidentally named files with `.sh` and not `.pl`
- ❷ What we know about the problem
 - more than 1 mislabeled file
 - Contained in a folder called `input`
- ❸ What is a sensible way to go about this?
- ❹ Let's write a little script to fix it

Let's build a script interactively

Parts of a script

- 1 Shebang -language specific

Let's build a script interactively

Parts of a script

- 1 Shebang -language specific
- 2 Module block

Let's build a script interactively

Parts of a script

- 1 Shebang -language specific
- 2 Module block
 - all HPC modules (e.g., module load)

Let's build a script interactively

Parts of a script

- ❶ Shebang -language specific
- ❷ Module block
 - all HPC modules (e.g., module load)
- ❸ Variable block

Let's build a script interactively

Parts of a script

- 1 Shebang -language specific
- 2 Module block
 - all HPC modules (e.g., module load)
- 3 Variable block
 - all variables

Let's build a script interactively

Parts of a script

- ❶ Shebang -language specific
- ❷ Module block
 - all HPC modules (e.g., module load)
- ❸ Variable block
 - all variables
- ❹ Commands

Let's build a script interactively

Parts of a script

- ❶ Shebang -language specific
- ❷ Module block
 - all HPC modules (e.g., module load)
- ❸ Variable block
 - all variables
- ❹ Commands
 - instruction set

input

- 1 I think the files are in "input"

Let's check

```
#####  
wd='ls input | grep sh$'  
echo ${wd}
```

```
awesome_script1.sh awesome_script2.sh awesome_script3.sh
```

Shebang and module block

shebang

1 top of file

```
#####  
#!/usr/bin/env sh  
#####
```

Shebang and module block

shebang

- 1 top of file

```
#####  
#!/usr/bin/env sh  
#####
```

module block

- 1 Load all modules here
- 2 Easily find/remember what modules loaded
- 3 No modules to load because I built this presentation on a PC

```
#####  
##Modules  
##module load something  
#####
```

Variable Block

- 1 Easily find input/output directories
- 2 Tidy programming

variable block

```
#####  
##Variables  
input_dir=input  
out_dir=output  
##input/output files arrays  
files=('ls ${input_dir} | grep sh$')  
out_files=('echo ${files[@]} | sed s/sh/pl/g')  
  
##parameter expansion  
##parameter/patten/string  
input_with_path=( "${files[@]}/#/${input_dir}/" )  
output_with_path=( "${out_files[@]}/#/${out_dir}/" )  
#####
```

For loop

```
#####  
##commands  
##make the output dir  
mkdir -p ${out_dir}  
  
##for loop  
##use length to iterate in order to index input output arrays  
for ((i=0; i<${#input_with_path[@]}; i++)); do  
  
    echo ${i}  
  
    echo cp ${input_with_path[${i}]} ${output_with_path[${i}]}  
  
done  
#####
```


Understanding the script

```
files=('ls ${input_dir} | grep sh$')
```

```
awesome_script1.sh  
awesome_script2.sh  
awesome_script3.sh
```

```
out_files=('echo ${files[@]} | sed s/  
sh/pl/g')
```

```
awesome_script1.pl  
awesome_script2.pl  
awesome_script3.pl
```

```
input_with_path=( "${files[@]}/#/${  
input_dir}/}" )
```

```
input/awesome_script1.sh  
input/awesome_script2.sh  
input/awesome_script3.sh
```

```
output_with_path=( "${out_files[@]}/#/${  
out_dir}/}" )
```

```
output/awesome_script1.pl  
output/awesome_script2.pl  
output/awesome_script3.pl
```

Understanding the for loop

```
for ((i=0; i<${#input_with_path[@]}; i++)); do  
    ${i}  
    cp ${input_with_path[${i}]} ${output_with_path[${i}]}  
  
done  
  
echo ${i}
```

0
1
2

```
cp ${input_with_path[${i}]} ${output_with_path[${i}]}
```

```
cp  input/awesome_script1.sh  output/awesome_script1.pl  
cp  input/awesome_script2.sh  output/awesome_script2.pl  
cp  input/awesome_script3.sh  output/awesome_script3.pl
```

- 1 Introduction
- 2 Bash Scripting Example
- 3 Exercise
- 4 Reproducible Research

History to script

- 1 blast history to script from last class

History to script

- 1 blast history to script from last class
- 2 Use some information from today

History to script

- 1 blast history to script from last class
- 2 Use some information from today
- 3 Why in the world would we want to redo an analysis?

History to script

- 1 blast history to script from last class
- 2 Use some information from today
- 3 Why in the world would we want to redo an analysis?
 - reproducible research artifact

History to script

- 1 blast history to script from last class
- 2 Use some information from today
- 3 Why in the world would we want to redo an analysis?
 - reproducible research artifact
- 4 ~20 min

History to script

- ❶ blast history to script from last class
- ❷ Use some information from today
- ❸ Why in the world would we want to redo an analysis?
 - reproducible research artifact
- ❹ ~20 min
 - HW5

- 1 Introduction
- 2 Bash Scripting Example
- 3 Exercise
- 4 Reproducible Research


"Let us change our traditional attitude to the construction of programs: Instead of imagining that our main task is to instruct a computer what to do, let us concentrate rather on explaining to human beings what we want a computer to do."

-Knuth

Some Tools



L^AT_EX



10 suggestions from the paper

- 1 For every result, keep track of how it was produced
- 2 Avoid manual data manipulation steps
- 3 Archive the exact versions of all external programs used
- 4 Version control all custom scripts
- 5 Record all intermediate results, when possible in standardized formats
- 6 For analyses that include randomness, note underlying random seeds
- 7 Always store raw data behind plots
- 8 Generate hierarchical analysis output, allowing layers of increasing detail to be inspected
- 9 Connect textual statements to underlying results
- 10 Provide public access to scripts, runs, and results