

SPECIFICATION SHEET

DNC EROSION CONTROL BLANKET

DNC is manufactured using 100% mattress grade coir matrix that is mechanically bonded between 2 layers of HD UV stabilized netting.

PROPERTY	TEST METHOD	TYPICAL ENGLISH	TYPICAL METRIC
Wide Width Tensile	ASTM D6818	250.8 x 180 lbs/ft	3.66 x 2.63 kN/m
Mass/Unit Area	ASTM D6475	11.44 oz/yd ²	387.82 g/m ²
Thickness	ASTM D6525	264 mils	6.71 mm
Ground Cover	ASTM D6567	92%	92%
Light Penetration	ASTM D6467	7.2%	7.2%
Water Absorption	ASTM D1117	254%	254%
Stitching		2 in centers	5.08 cm centers
Netting		3/4 in x 3/4 in	1.9 cm x 1.9 cm

PROPERTY	TEST METHOD	TYPICAL ENGLISH	TYPICAL METRIC
Roll Dimensions	Measured	7.5 ft x 120 ft 15 ft x 120 ft	2.3 m x 36.6 m 4.6 m x 36.6 m
Roll Area	Measured	100 yd ² 200 yd ²	83.61 m ² 167.22 m ²

The information provided is for reference purposes only and is not intended as a warranty or guarantee whether implied or inferred. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The property values listed above are subject to change without notice. BW Geotextiles assumes no liability in connection with the use of this information and product.

1239 Notre Dame Drive, Box 178
Petersburg, ON N0B 2H0
Phone: (519)778-1953 Toll Free: 1-844-778-1953
www.bwgeotextiles.com

02/11/2020