

2025 USA-NA-AIO Round 1, Problem 2, Part 13

Topics

More

CATEGORIES

General

Site Feedback

All categories

USAAIO 

Mar 2025

Part 13 (15 points, coding task)

In this part, we use the training dataset constructed in Part 12 to train a model defined in Part 11.

- Use mean-squared error (MSE) as the loss function.
- Use Adam as the optimization algorithm.
- Do whole-batch training in each epoch.
- After every 10 epochs, print the following sentence:

Epoch: XXX. Loss: XXX.

The loss value should be with 4 decimal places.

- Generate an epoch-MSE loss plot after completing the training. Set the x-label as epoch and the y-label as MSE loss .

USAAIO 

Mar 2025

```
# HYPERPARAMETERS
''' DO NOT CHANGE ANYTHING IN THIS CODE CELL '''
```

```
hidden_features1 = 32
hidden_features2 = 16
```

```
num_epochs = 500
```

Skip to main content

```
learning_rate = 1e-3

### WRITE YOUR SOLUTION HERE ###

my_mlp_model = My_MLP_Model(1, hidden_features1, hidden_features2, 1)
optimizer = torch.optim.Adam(my_mlp_model.parameters(), lr = learning_rate)
loss_fn = torch.nn.MSELoss()

loss_list_plot = []

for epoch in range(num_epochs):
    optimizer.zero_grad()
    y_pred = my_mlp_model(x_train.reshape(-1,1))
    loss = loss_fn(y_pred, y_train.reshape(-1,1))
    loss.backward()
    optimizer.step()

    if epoch % 10 == 0:
        print(f"Epoch: {epoch}. Loss: {loss.item():.4f}")
        loss_list_plot.append(loss.item())

plt.plot(loss_list_plot)
plt.xlabel("epoch")
plt.ylabel("MSE loss")
plt.show()
""" END OF THIS PART """
```

[Skip to main content](#)

◆ Related topics

Topic	Replies	Activity
2025 USA-NA-AIO Round 2, Problem 3, Part 16	1	May 2025
2025 USA-NA-AIO Round 2, Problem 1, Part 10	1	May 2025
2025 USA-NA-AIO Round 2, Problem 3, Part 14	1	May 2025

[Skip to main content](#)

Topic	Replies	Activity
2025 USA-NA-AIO Round 2, Problem 1, Part 8	1	May 2025
2025 USA-NA-AIO Round 1, Problem 3, Part 17	1	Mar 2025

 Powered by Discourse