

 Topics My posts More

▼ CATEGORIES

General

Site Feedback

 All categories[Skip to main content](#)

2025 USA-NA-AIO Round 2, Problem 1, Part 2

USAAIO 

May 2025

The high level idea of PINN is as follows:

- (Neural network)** We design a neural network (functional mapping) $U(\cdot, \cdot \mid \theta) : [0,1]^2 \rightarrow \mathbb{R}$, such that
 - θ : learnable parameters in U .
 - Inputs are time t and position x .
 - Output is the predicted temperature.
- (Training data)** To train U (equivalently, to learn θ), we use the following three groups of temporal-spatial data (t, x) :
 - (Training data for PDE)** (t, x) are randomly sampled from $[0,1]^2$.
Denote by \mathcal{D}_{PDE} the set of these data points.
 - (Training data for IC)** $(0, x)$ with x that are evenly distributed on $[0, 1]$.
Denote by \mathcal{D}_{IC} the set of these data points.
 - (Training data for BC)** $(t, 0)$ and $(t, 1)$ with t that are evenly distributed on $[0, 1]$.
Denote by \mathcal{D}_{BC} the set of these data points.

3. **(Loss function in training)**

$$L_{total} = L_{PDE} + L_{IC} + L_{BC},$$

where

- Residual loss in PDE:

$$L_{PDE} = \frac{1}{|\mathcal{D}_{PDE}|} \sum_{(t,x) \in \mathcal{D}_{PDE}} \left(\frac{\partial U(t,x|\theta)}{\partial t} - \alpha \frac{\partial^2 U(t,x|\theta)}{\partial x^2} \right)^2.$$

- IC loss:

$$L_{IC} = \frac{1}{|\mathcal{D}_{IC}|} \sum_{(t,x) \in \mathcal{D}_{IC}} (U(t,x|\theta) - u(t,x))^2.$$

- BC loss:

$$L_{BC} = \frac{1}{|\mathcal{D}_{BC}|} \sum_{(t,x) \in \mathcal{D}_{BC}} (U(t,x|\theta) - u(t,x))^2.$$

Part 2 (10 points, coding task)

In this part, you are asked to build a deep neural network that is used to output PDE solutions.

1. The class name is `HeatPINN`.

It subclasses `nn.Module`.

2. The model consists of the following layers that are sequentially connected:

[Skip to main content](#)

(1) Fully connected layer with `out_features = 64` (you need to determine `in_features` taken from the input).

(2) Activation layer with `tanh` function.

(3) Fully connected layer with `in_features = 64` and `out_features = 64`.

(4) Activation layer with `tanh` function.

(5) Fully connected layer with `in_features = 64` (you need to determine `out_features` as the output of the entire model).

3. Construct a model who is an object of this class and is called as `model`.

USAAIO **May 2025**

WRITE YOUR SOLUTION HERE

```
class HeatPINN(nn.Module):
    def __init__(self):
        super().__init__()
        self.net = nn.Sequential(
            nn.Linear(2, 64),
            nn.Tanh(),
            nn.Linear(64, 64),
            nn.Tanh(),
            nn.Linear(64, 1)
        )

    def forward(self, x):
        return self.net(x)
```

```
model = HeatPINN()
```

```
""" END OF THIS PART """
```

[Skip to main content](#)

✦ **Related topics**

Topic	Replies	Activity
2025 USA-NA-AIO Round 2, Problem 1, Part 1	1	May 2025

[Skip to main content](#)

Topic	Replies	Activity
2025 USA-NA-AIO Round 2, Problem 1, Part 10	1	May 2025
2025 USA-NA-AIO Round 2, Problem 1, Part 12	1	May 2025
2025 USA-NA-AIO Round 2, Problem 1, Part 6	1	May 2025
2025 USA-NA-AIO Round 1, Problem 2, Part 5	1	Mar 2025

 Powered by Discourse