FONDAY MOISTURE CONTROL · ACTIVATED ALUMINA

Rechargeable Desiccant Beads

Activated alumina in refill buckets from 2 to 32 lb, with free mesh bags included. The beads pull moisture out of enclosed spaces, are checked by weight, and recharge for repeated reuse in the oven only (never in a microwave).



Activated Alumina

More powerful · Check by weight, recharge in the oven

3–5 mm
Industry standard bead size across every jug and bucket

Up to 35%
Of its own dry weight in moisture absorbed at full saturation

2–32 lb
Six pack sizes across the alumina range

1 way
Recharges in the oven only — never in a microwave

More powerful than silica gel

No colour change — check by weight

Oven recharge only

Free mesh bags included

Reusable many times

Beads 3–5 mm

Not for food, drugs or supplements

THE RANGE

Activated alumina

Activated alumina uses the same 3–5 mm industry standard bead and the same rigid refill buckets with a pour-friendly neck. Sizes run from 2 to 32 lb, all in buckets with free mesh bags included, and every pack recharges in the oven only.



MORE POWERFUL

Activated Alumina

- White beads that do not change colour — saturation is checked by weight.
- Sizes: 2, 4, 6, 8, 12 and 32 lb, all in buckets.
- Free mesh bags included: 2 lb gets 5, 4/6/8 lb get 10, 12 lb gets 20 and 32 lb gets 40.
- Oven recharge only — never place activated alumina in a microwave.

SIZE	NET WEIGHT	PACKAGING	INCLUDED MESH BAGS	FORMULA
2 lb	32 oz · 907 g	Bucket	5 (alumina)	Activated alumina
4 lb	64 oz · 1.81 kg	Bucket	10 (alumina)	Activated alumina
6 lb	96 oz · 2.72 kg	Bucket	10 (alumina)	Activated alumina
8 lb	128 oz · 3.63 kg	Bucket	10 (alumina)	Activated alumina
12 lb	192 oz · 5.44 kg	Bucket ×2 (2 × 6 lb)	20 (alumina)	Activated alumina
32 lb	512 oz · 14.5 kg	Bucket ×4 (4 × 8 lb)	40 (alumina)	Activated alumina

Bulk packs: the 12 lb pack contains two 6 lb buckets and the 32 lb pack contains four 8 lb buckets, so you can rotate one bucket in service while the others recharge. Every bead in this guide measures 3–5 mm and can be poured straight into the included mesh bags or any breathable container of your own.

HOW TO USE

Place, watch, recharge

Fonday beads work in any enclosed space. Put them in, let them pull the moisture out, and weigh them to know exactly when it is time for a recharge.

Place the beads 01

Set a bucket inside the space, or pour beads into the included mesh bags and tuck them next to what you are protecting. Keep the space closed.

Let them work 02

The beads absorb moisture from the air and from the items around them. Drying takes from a few hours to several days depending on how damp the space is.

Check the level 03

Weigh the beads. The guide below shows exactly what each stage means.

Recharge & reuse 04


When the beads are saturated, dry them in the oven only, never in a microwave (page 4). Once cool, they are ready to go back to work.

READING THE BEADS

What the weight is telling you

Activated alumina

No colour change — check by weight



Activated alumina stays white, so it is checked on a scale instead. Weigh the beads when dry, then recharge in the oven (never in a microwave) once they reach their maximum saturation moisture content of about 30–35% of that dry weight (see page 4).

COMMON USES

Anywhere trapped moisture causes trouble

3D printer filament

Keep spools bone dry in dry boxes and storage cabinets to stop brittle prints and stringing.

Camera & optics

Protect lenses, bodies and sensor bags from fungus and fogging in cases and cabinets.

Safes & tool boxes

Stop rust on firearms, tools and dies inside gun safes, cabinets and drawers.

Electronics & parts

Dry components, boards, seeds and powders in storage bins and component drawers.

Closets & storage

Fight musty smells and damp patches in wardrobes, suitcases and storage totes.

Boats, RVs & gear

Control moisture in cabins, campers, tackle boxes and camping gear between trips.

This product is not for use with food, drugs, or dietary supplements. Keep the beads and buckets out of reach of children and pets, and wash your hands after handling.

RECHARGE & CARE

Bring the beads back to life

Heating drives the absorbed moisture back out of the beads. Activated alumina recharges in the oven only and is timed by weight — it must never be placed in a microwave.

Oven

ACTIVATED ALUMINA

1. **Preheat** to 400–480 °F (204–249 °C).
2. **Spread the beads** no thicker than about 2 cm on a baking tray — never place the bucket in the oven.
3. **Heat** for 2–2.5 hours.
4. **Cool completely**, then store in an airtight container until the beads go back to work.

ACTIVATED ALUMINA

Recharge by weight

Because the beads never change colour, a simple kitchen scale is your indicator.

1. **Weigh the beads when they are dry**, before first use, and write the value on the bucket or in a note.
2. **Re-weigh every few weeks.** The extra weight is the moisture the beads have absorbed.
3. **Recharge in the oven only** (never in a microwave) once the beads reach their maximum saturation moisture content of about 30–35%, then note the new dry weight.

WHERE TO BUY

Find Fonday on Amazon

Activated Alumina
ASIN X004U7JIS5
www.amazon.com/dp/X004U7JIS5

Available sizes vary by marketplace and pack. Please check the listing in your store before ordering.

Safety when recharging: beads and trays stay hot long after heating — let them cool before handling. Never overheat, never add water to hot beads, and never place activated alumina in the microwave. This product is not for use with food, drugs, or dietary supplements.

CERTIFICATES

Tested, reported, certified

Independent documentation for activated alumina. Certificate numbers are quoted below and can be verified with the issuing bodies.

CERTIFICATE	ACTIVATED ALUMINA
Safety Data Sheet (SDS) SGS-CSTC Standards Technical Services (Qingdao) Co., Ltd. Issued 12 February 2026 · SGS job no. SZP26-006039 Prepared to Annex II of REACH (1907/2006) — Regulation 2020/878	**EECSSDS2602032001** Fonday Filament Drying Desiccant
EU REACH · SVHC screening SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch Issued 10 February 2026 · SGS job no. SZP26-005851 253 Candidate List substances per Regulation (EC) No. 1907/2006	**CANEC26003121705** All screened SVHC ≤ 0.1% (w/w) — Pass
Product carbon footprint ClimatePartner LLC, Boston, Massachusetts, USA Inventory date 3 February 2026 · GHG Protocol Product Standard Report: Barrel Silica Gel Desiccant (Version 1), cradle-to-grave	**35.78 kg CO_2e** Per 6.37 kg bottle of silica gel, retail packaging included

QUICK REFERENCE

How much do I need?

TYPICAL SPACE	GETTING STARTED	BEST PICK
Safes, tool boxes, camera cases, filament dry boxes	1 × 2 lb bucket, or beads in the included mesh bags	Weigh the beads to check saturation
Closets, wardrobes, storage totes, small rooms	1 × 4 lb or 6 lb bucket	Weigh every few weeks to track moisture
Walk-in closets, basements, RV and boat cabins	1 × 8 lb or 12 lb pack	12 lb bulk pack lets you rotate buckets
Large rooms, garages and bulk storage	1 × 32 lb pack of activated alumina	Alumina with its 40 included mesh bags

Activated alumina CAS No. 1344-28-1. Applicant: SHENZHEN SHI FANGDEJIANGXIN E-COMMERCE CO., LTD. This guide applies to Fonday activated alumina beads in 3–5 mm, in 2 to 32 lb packs. It does not cover Fonday orange or blue indicating silica gel, flower drying crystals or 1–500 g sachet products, which have their own guides. Full SDS, REACH and carbon footprint documents are available at **www.fondayair.com** or on request from Fonday customer support. This product is not for use with food, drugs, or dietary supplements.