

Remote controlled phantom for dynamic tomography

Tommi Heikkilä

tommi.heikkila@helsinki.fi

December 15, 2022



UNIVERSITY OF HELSINKI
DEPARTMENT OF MATHEMATICS
AND STATISTICS

Overview


1 Inverse problems and real data

2 Dynamic tomography

3 STEMPO


4 Use and Examples

Combining theory and practice




XKCD#435 by Randall Munroe

Combining theory and practice




Combining theory and practice

Example: X-ray tomography



Combining theory and practice

Example: X-ray tomography




No plan of operations extends with any certainty beyond the first encounter with the main enemy forces.

– Helmuth von Moltke (1871), Prussian field marshall

Combining theory and practice

Example: X-ray tomography




No plan of operations extends with any certainty beyond the first encounter with the main enemy forces realistic setting and data.

– Helmuth von Moltke (1871), Prussian field-marshall inversionist*

[citation needed]

Tomographic data

- Finnish Inverse Problems Society:
fips.fi/dataset.php




X-ray data of a walnut

*K. Hämäläinen, L. Harhanen, A. Kallonen,
A. Kujanpää, E. Niemi & S. Siltanen*

Tomographic data

- Finnish Inverse Problems Society:
fips.fi/dataset.php
- Validation in Medical Image Processing:
www.vmip.org/7.html




X-ray data of a walnut

*K. Hämäläinen, L. Harhanen, A. Kallonen,
A. Kujanpää, E. Niemi & S. Siltanen*

Tomographic data

- Finnish Inverse Problems Society:
fips.fi/dataset.php
- Validation in Medical Image Processing:
www.vmip.org/7.html
- Variety of formats, methods and sources




X-ray data of a walnut

*K. Hämäläinen, L. Harhanen, A. Kallonen,
A. Kujanpää, E. Niemi & S. Siltanen*

Tomographic data


- Finnish Inverse Problems Society:
fips.fi/dataset.php
- Validation in Medical Image Processing:
www.vmip.org/7.html
- Variety of formats, methods and sources
- New data is always welcome!



X-ray data of a walnut

*K. Hämäläinen, L. Harhanen, A. Kallonen,
A. Kujanpää, E. Niemi & S. Siltanen*

Movement = trouble




Radon transform

$$\mathcal{R} f(x) \longmapsto p(r, \theta) = \int_{\{x \cdot \theta = r\}} f(x) dx$$

- Projections (information) of the target from multiple directions.

Movement = trouble



$t = 1$

Radon transform

$$\mathcal{R} f(x) \longmapsto p(r, \theta) = \int_{\{x \cdot \theta = r\}} f(x) dx$$

- Projections (information) of the target from multiple directions.

Movement = trouble




$t = 180$

Radon transform

$$\mathcal{R} f(x) \longmapsto p(r, \theta) = \int_{\{x \cdot \theta = r\}} f(x) dx$$

- Projections (information) of the target from multiple directions.
- Measurements are not instant!

Movement = trouble




Radon transform

$$\mathcal{R} f(x) \longmapsto p(r, \theta) = \int_{\{x \cdot \theta = r\}} f(x) dx$$

- Projections (information) of the target from multiple directions.
- Measurements are not instant!

Movement = trouble




FBP reconstruction

Radon transform

$$\mathcal{R} f(x) \longmapsto p(r, \theta) = \int_{\{x \cdot \theta = r\}} f(x) dx$$

- Projections (information) of the target from multiple directions.
- Measurements are not instant!
- Special methods are required

Movement = trouble



FBP reconstruction

Radon transform

$$\mathcal{R} f(x) \longmapsto p(r, \theta) = \int_{\{x \cdot \theta = r\}} f(x) dx$$

- Projections (information) of the target from multiple directions.
- Measurements are not instant!
- Special methods are required
- ...and equally special data

Dynamic data examples



Emoji phantom

A. Meaney, Z. Purisha & S. Siltanen

- Some options are available

Dynamic data examples

- Some options are available



Emoji phantom

A. Meaney, Z. Purisha & S. Siltanen



Gel phantom

TH, H. Help & A. Meaney

Dynamic data examples

- Some options are available
- Limited temporal resolution



Emoji phantom

A. Meaney, Z. Purisha & S. Siltanen



Gel phantom

TH, H. Help & A. Meaney

Dynamic data examples

- Some options are available
- Limited temporal resolution
- Hard or impossible to repeat



Emoji phantom

A. Meaney, Z. Purisha & S. Siltanen



Gel phantom

TH, H. Help & A. Meaney

Dynamic data examples

- Some options are available
- Limited temporal resolution
- Hard or impossible to repeat
- What if you need special measurement setup?



Emoji phantom

A. Meaney, Z. Purisha & S. Siltanen




Gel phantom

TH, H. Help & A. Meaney


Spatio-TEmporal Motor PPowered phantom

STEMPO





Spatio-TEmporal Motor PPowered phantom

STEMPO



Spatio-TEmporal Motor PPowered phantom

STEMPO



STEMPO data: 10.5281/zenodo.7081688

- Static measurement using 360 projections
stempo_static_*d_b*.mat

STEMPO data: 10.5281/zenodo.7081688

- Static measurement using 360 projections
`stempo_static_*d_b*.mat`
- Two differently sampled dynamic measurements
`stempo_cont360_*d_b*.mat` → 360 projections with 1° spacing
`stempo_seq8x45_*d_b*.mat` → 8 × 45 projections with 8° spacing

STEMPO data: 10.5281/zenodo.7081688

- Static measurement using 360 projections
`stempo_static_*d_b*.mat`
- Two differently sampled dynamic measurements
`stempo_cont360_*d_b*.mat` → 360 projections with 1° spacing
`stempo_seq8x45_*d_b*.mat` → 8×45 projections with 8° spacing
- Both 2D and 3D geometry, multiple resolution levels



3D FDK recon.

STEMPO data: 10.5281/zenodo.7081688

- Static measurement using 360 projections
`stempo_static_*d_b*.mat`
- Two differently sampled dynamic measurements
`stempo_cont360_*d_b*.mat` → 360 projections with 1° spacing
`stempo_seq8x45_*d_b*.mat` → 8×45 projections with 8° spacing
- Both 2D and 3D geometry, multiple resolution levels
- Interpolated approximation of the movement, but no $\Phi(x, t)$ or $\nu(t)$



3D FDK recon.

STEMPO data: 10.5281/zenodo.7081688

- Static measurement using 360 projections
`stempo_static_*d_b*.mat`
- Two differently sampled dynamic measurements
`stempo_cont360_*d_b*.mat` → 360 projections with 1° spacing
`stempo_seq8x45_*d_b*.mat` → 8×45 projections with 8° spacing
- Both 2D and 3D geometry, multiple resolution levels
- Interpolated approximation of the movement, but no $\Phi(x, t)$ or $\nu(t)$



3D FDK recon.

Recommended:

- ASTRA toolbox
- Spot operators
- HelTomo Toolbox
- CUDA GPU*

Example 1: 2D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| Wf \|_1$$

Example 1: 2D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| Wf \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 16$, each with 23 projections.

Example 1: 2D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| Wf \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 16$, each with 23 projections.
- Minimize with primal-dual fixed point algorithm and 3D Haar wavelets

Example 1: 2D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| Wf \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 16$, each with 23 projections.
- Minimize with primal-dual fixed point algorithm and 3D Haar wavelets



$t = 1$

Example 1: 2D + time wavelet regularization


Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| Wf \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 16$, each with 23 projections.
- Minimize with primal-dual fixed point algorithm and 3D Haar wavelets



$t = 1$



$t = 6$

Example 1: 2D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| Wf \|_1$$


- `stempo_seq8x45_2d_b8.mat` data, $T = 16$, each with 23 projections.
- Minimize with primal-dual fixed point algorithm and 3D Haar wavelets



$t = 1$



$t = 6$



$t = 11$

Example 1: 2D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| Wf \|_1$$


- `stempo_seq8x45_2d_b8.mat` data, $T = 16$, each with 23 projections.
- Minimize with primal-dual fixed point algorithm and 3D Haar wavelets




$t = 1$



$t = 6$



$t = 11$



$t = 16$

Bonus: 3D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| \mathcal{C} f \|_1$$

- `stempo_seq8x45_3d_b8.mat` data, $T = 16$, each with 23 projections.
- Minimize with primal-dual fixed point algorithm and 4D complex wavelets ["4D Dual-Tree Complex Wavelets for Time-Dependent Data"]

Bonus: 3D + time wavelet regularization

Minimize functional J_w :

$$J_w(f) = \sum_{t=1}^T \frac{1}{2} \| \mathcal{R} f_t - m_t^\eta \|_2^2 + \lambda \| \mathcal{C} f \|_1$$

- `stempo_seq8x45_3d_b8.mat` data, $T = 16$, each with 23 projections.
- Minimize with primal-dual fixed point algorithm and 4D complex wavelets ["4D Dual-Tree Complex Wavelets for Time-Dependent Data"]

Example 2: Low-rank + sparse decomposition

Minimize functional J_{L+S} :

$$J_{L+S}(L, S) = \frac{1}{2} \| \mathcal{R}(L+S) - m^\eta \|_2^2 + \mu_L \| L \|_* + \mu_S \| \tilde{W}S \|_1$$

Example 2: Low-rank + sparse decomposition

Minimize functional J_{L+S} :

$$J_{L+S}(L, S) = \frac{1}{2} \| \mathcal{R}(L+S) - m^\eta \|_2^2 + \mu_L \| L \|_* + \mu_S \| \tilde{W}S \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 85$, each with 24 projections.

Example 2: Low-rank + sparse decomposition

Minimize functional J_{L+S} :

$$J_{L+S}(L, S) = \frac{1}{2} \| \mathcal{R}(L+S) - m^\eta \|_2^2 + \mu_L \| L \|_* + \mu_S \| \tilde{W}S \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 85$, each with 24 projections.




Example 2: Low-rank + sparse decomposition

Minimize functional J_{L+S} :

$$J_{L+S}(L, S) = \frac{1}{2} \| \mathcal{R}(L+S) - m^\eta \|_2^2 + \mu_L \| L \|_* + \mu_S \| \tilde{W}S \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 85$, each with 24 projections.




Example 2: Low-rank + sparse decomposition

Minimize functional J_{L+S} :

$$J_{L+S}(L, S) = \frac{1}{2} \| \mathcal{R}(L+S) - m^\eta \|_2^2 + \mu_L \| L \|_* + \mu_S \| \tilde{W}S \|_1$$

- stempo_seq8x45_2d_b8.mat data, $T = 85$, each with 24 projections.




Example 2: Low-rank + sparse decomposition

Minimize functional J_{L+S} :

$$J_{L+S}(L, S) = \frac{1}{2} \| \mathcal{R}(L+S) - m^\eta \|_2^2 + \mu_L \| L \|_* + \mu_S \| \tilde{W}S \|_1$$

- `stempo_seq8x45_2d_b8.mat` data, $T = 85$, each with 24 projections.




Example 2: Low-rank + sparse decomposition

Minimize functional J_{L+S} :

$$J_{L+S}(L, S) = \frac{1}{2} \| \mathcal{R}(L+S) - m^\eta \|_2^2 + \mu_L \| L \|_* + \mu_S \| \tilde{W}S \|_1$$

- stempo_seq8x45_2d_b8.mat data, $T = 85$, each with 24 projections.



Future development

- More data!

Future development

- **More data!**
- Random angles, multiple source-detector pairs

Future development

- **More data!**
- Random angles, multiple source-detector pairs
- More difficult moving and static objects

Future development

- **More data!**
 - Random angles, multiple source-detector pairs
 - More difficult moving and static objects
 - Far future: true 3D motion, spectral CT, deformations...

Summary

- Real data is important for validation

Summary

- Real data is important for validation
- Dynamic tomography data is limited

Summary

- Real data is important for validation
- Dynamic tomography data is limited
- STEMPO is a computer controlled device which can produce repeatable measurements

Summary

- Real data is important for validation
- Dynamic tomography data is limited
- STEMPO is a computer controlled device which can produce repeatable measurements
- Goal: variety of easy to use data sets for many dynamic tomography problems

Summary

- Real data is important for validation
- Dynamic tomography data is limited
- STEMPO is a computer controlled device which can produce repeatable measurements
- Goal: variety of easy to use data sets for many dynamic tomography problems

