From Tables and Spreadsheets to Data Cubes

- A **data warehouse** is based on a multidimensional data model which views data in the form of a data cube
- A data cube, such as sales, allows data to be modeled and viewed in multiple dimensions
  - **Dimension tables**, such as item (item_name, brand, type), or time(day, week, month, quarter, year)
  - **Fact table** contains **measures** (such as dollars_sold) and keys to each of the related dimension tables
- **Data cube**: A lattice of cuboids
  - In data warehousing literature, an n-D base cube is called a **base cuboid**
  - The top most 0-D cuboid, which holds the highest-level of summarization, is called the **apex cuboid**
  - The lattice of cuboids forms a **data cube**.

2D สองมิติ

Table 4.2: A 2-D view of sales data for *AllElectronics* according to the dimensions *time* and *item*, where the sales are from branches located in the city of Vancouver. The measure displayed is *dollars_sold* (in thousands).

location = *"Vancouver"*

	item (type) มุมมองด้านชนิดของสินค้า			
time (quarter) มุมมองด้านเวลา	*home entertainment*	*computer*	*phone*	*security*
Q1	605	825	14	400
Q2	680	952	31	512
Q3	812	1023	30	501
Q4	927	1038	38	580

3D

อันนี้มีมุมมองอีกมุมมองนึงว่า แต่ละสาขาต้องเลขไหนบ้าง

Table 4.3: A 3-D view of sales data for *AllElectronics*, according to the dimensions *time*, *item*, and *location*. The measure displayed is *dollars_sold* (in thousands).

	location = "Chicago"				***location*** = "New York"				***location*** = "Toronto"				***location*** = "Vancouver"			
	item				***item***				***item***				***item***			
time	*home ent.*	*comp.*	*phone*	*sec.*	*home ent.*	*comp.*	*phone*	*sec.*	*home ent.*	*comp.*	*phone*	*sec.*	*home ent.*	*comp.*	*phone*	*sec.*
Q1	854	882	89	623	1087	968	38	872	818	746	43	591	605	825	14	400
Q2	943	890	64	698	1130	1024	41	925	894	769	52	682	680	952	31	512
Q3	1032	924	59	789	1034	1048	45	1002	940	795	58	728	812	1023	30	501
Q4	1129	992	63	870	1142	1091	54	984	978	864	59	784	927	1038	38	580

3D



Q1 von location Chicago = 623.

Figure 4.3: A 3-D data cube representation of the data in Table 4.3, according to the dimensions *time*, *item*, and *location*. The measure displayed is *dollars_sold* (in thousands).

4D



Figure 4.4: A 4-D data cube representation of sales data, according to the dimensions *time*, *item*, *location*, and *supplier*. The measure displayed is *dollars_sold* (in thousands). For improved readability, only some of the cube values are shown.

Typical OLAP Operations