Spoofing Earth Observation Satellites through Radio
Overshadowing
—Motivation

Implications

Using only an off-the-shelf SDR and open source software, attackers car:

* Read confidential maritime data and internet traffic, Pacer

* Executing on Installar traffic and cals (?)

Certain natifies designed to be invarion-proted, q.a.

Implications Data secrety

EOS fleet: Terra, Aqua, Aura, etc.
 Amateur radio satellites e.g. SO-50, QO-100
 Freeview TV

Lack of crypto has resulted in lots of work into eavesdropping

Spoofing Earth Observation Satellites through Radio
Overshadowing
Motivation
Implications

Implications
Data saftwristing and intentity

Specifying attacks have been about a gainst:

- OSSS to manipulate calculated scannot P, 21

- OSSS to manipulate calculated scannot P, 21


- Moseur, no work considers the consequence of specifies facility. Moseur can work considers the consequences of specifies facility calculated scannot P, 22

- Moseur, no work considers the consequences of specifies facility calculated scannot P, 22

- Moseur, no work considers the consequences of specifies facility calculated scannot P, 22

- Moseur, no work considers the consequences of specifies for the variable scannot perform the consequences of specifies and the consideration of the consequences of specifies and the consideration of the consequences of specifies and the consequences of spe

No work considers overshadowing in a more general case



· Exploit or disrupt downlink processing stages

- Inject false data, disrupting automated detection systems.
- · Mask real data, denying people information.
- Achieve denial of service, e.g. by causing pipeline stages to crash.
- Execute arbitrary code, e.g. by exploiting processing stages that call the shell.

Affecting the derived dataset

It's not as easy as drawing dots on

Spoofing Earth Observation Satellites through Radio Overshadowing

Case Study: FIRMS

Exploiting processing stages

Exploiting processing stages

Construct payload packet

Exploiting processing stages

Number of causes of concern: LO to L1 made of many disparate components, interacting across boundaries with access to the shell. Using C programs that don't pay huge attention to managing memory correctly, and using a slightly buggy protocol header parser.

-Attack consequences



Cryptography is infeasible because of reasons discussed earlier