

1. 判断系统时间时段（早 / 中 / 晚）

在终端输入 `gedit time_check.sh` 创建脚本文件，粘贴代码后保存并退出

```
#!/bin/bash
hour = `date +%H`
case $hour in
0[1-9] | 1[01] )
echo "Good morining !!"
;;
1[234567] )
echo "Good afternoon !!"
;;
* )
echo "Good evening !! "
;;
Esac
```

赋予执行权限：`chmod +x time_check.sh`，运行脚本：`./time_check.sh`，终端会根据当前时间输出对应问候语

```
b23041310matao@b23041310matao-virtual-machine:~$ gedit time_check.sh
b23041310matao@b23041310matao-virtual-machine:~$ chmod +x time_check.sh
b23041310matao@b23041310matao-virtual-machine:~$ ./time_check.sh
./time_check.sh: 行 2: hour: 未找到命令
./time_check.sh: 行 13: 未预期的符号 `newline' 附近有语法错误
./time_check.sh: 行 13: `Esac'
b23041310matao@b23041310matao-virtual-machine:~$
```

存在错误：

变量赋值错误：`hour = `date +% H``中等号两侧有空格（Shell 变量赋值不能有空格）

结束符错误：`Esac`应为小写 `esac`（Shell 语法区分大小写）

修改代码

```
#!/bin/bash
hour=`date +%H`
case $hour in
0[1-9] | 1[01] )
echo "Good morining !!"
;;
1[234567] )
echo "Good afternoon !!"
;;
* )
echo "Good evening !! "
;;
esac
```

赋予执行权限并运行脚本

```
b23041310matao@b23041310matao-virtual-machine:~$ gedit time_check.sh
b23041310matao@b23041310matao-virtual-machine:~$ chmod +x time_check.sh
b23041310matao@b23041310matao-virtual-machine:~$ ./time_check.sh
./time_check.sh: 行 2: hour: 未找到命令
./time_check.sh: 行 13: 未预期的符号 `newline' 附近有语法错误
./time_check.sh: 行 13: `Esac'
b23041310matao@b23041310matao-virtual-machine:~$ gedit time_check.sh
b23041310matao@b23041310matao-virtual-machine:~$ chmod +x time_check.sh
b23041310matao@b23041310matao-virtual-machine:~$ ./time_check.sh
Good afternoon !!
b23041310matao@b23041310matao-virtual-machine:~$
```

2. 比较两个整数大小

创建文件：`gedit num_compare.sh`，写入代码并保存退出

```
#!/bin/sh
echo "Enter the first integer:"
read first
echo "Enter the second integer:"
read second
if [ "$first" -gt "$second" ]
then
echo "$first is greater than $second"
elif [ "$first" -lt "$second" ]
then
echo "$FIRST is less than $second"
else
echo "$FIRST is equal to $second"
fi
```

添加权限：chmod +x num_compare.sh，运行脚本：./num_compare.sh，按提示输入两个整数（如 5 和 3），终端会输出比较结果

```
b23041310matao@b23041310matao-virtual-machine:~$ gedit num_compare.sh
b23041310matao@b23041310matao-virtual-machine:~$ chmod +x num_compare.sh
b23041310matao@b23041310matao-virtual-machine:~$ ./num_compare.sh
Enter the first integer:
5
Enter the second integer:
3
5 is greater than 3
b23041310matao@b23041310matao-virtual-machine:~$
```

3. 查找列表中的最小值

创建文件：gedit find_min.sh，写入代码并保存退出

```
#!/bin/bash
smallest=10000
for i in 8 2 18 0 -3 87
do
if test $i -lt $smallest
then
smallest=$i
fi
done
echo $smallest
```

授权运行：chmod +x find_min.sh，执行脚本：./find_min.sh，终端会输出列表最小值-3

```
b23041310matao@b23041310matao-virtual-machine:~$ gedit find_min.sh
b23041310matao@b23041310matao-virtual-machine:~$ chmod +x find_min.sh
b23041310matao@b23041310matao-virtual-machine:~$ ./find_min.sh
-3
b23041310matao@b23041310matao-virtual-machine:~$
```

4. 统计当前目录可执行文件数量

创建文件：gedit count_exec.sh，写入代码并保存退出

```
#!/bin/bash
count=0
for i in *
do
if test -x $i
then
count=`expr $count + 1`
fi
done
echo Total of $count files executable
```

授权运行：chmod +x count_exec.sh，执行脚本：./count_exec.sh，终端会输出当前目录可执行文件总数

```
b23041310matao@b23041310matao-virtual-machine:~$ gedit count_exec.sh
b23041310matao@b23041310matao-virtual-machine:~$ chmod +x count_exec.sh
b23041310matao@b23041310matao-virtual-machine:~$ ./count_exec.sh
Total of 16 files executable
b23041310matao@b23041310matao-virtual-machine:~$
```

直接输入命令：ls，按下回车，终端会显示当前目录下的文件列表

```
b23041310matao@b23041310matao-virtual-machine:~$ ls
aes_test.txt      cipher.txt        matao2.txt        rsa_private.key
B23041310         count_exec.sh    num_compare.sh    rsa_public.key
B23041310.txt     decrypt1.txt     page_rep          sample
ca.crt            decrypt2.txt     page_replacement.c sample.c
cbc_base64.enc    ecb_base64.enc  page.txt          sample.o
cbc_no_base64.enc ecb_no_base64.enc process_image      sign.sha256
cert.p12           examples.desktop process_image.c    time_check.sh
cipher.enc         find_min.sh      result.txt         公共的
```

模板
视频
图片
文档
下载
音乐
桌面

输入以下命令并回车：ls -l | grep -E "^-.*x"，终端显示的就是当前目录下普通文件中具有可执行权限的文件（排除了目录）

```
b23041310matao@b23041310matao-virtual-machine:~$ ls -l | grep -E "^-.*x"
-rw-rw-r-- 1 b23041310matao b23041310matao 112 11月 22 21:34 aes_test.txt
-rw-rw-r-- 1 b23041310matao b23041310matao 78 11月 22 22:31 B23041310.txt
-rw-rw-r-- 1 b23041310matao b23041310matao 184 11月 22 21:36 cipher.txt
-rwxrwxr-x 1 b23041310matao b23041310matao 123 12月 3 14:27 count_exec.sh
-rw-rw-r-- 1 b23041310matao b23041310matao 0 11月 22 21:55 decrypt1.txt
-rw-rw-r-- 1 b23041310matao b23041310matao 0 11月 22 21:58 decrypt2.txt
-rw-r--r-- 1 b23041310matao b23041310matao 8980 11月 13 14:01 examples.desktop
-rwxrwxr-x 1 b23041310matao b23041310matao 119 12月 3 14:22 find_min.sh
-rw-rw-r-- 1 b23041310matao b23041310matao 12 11月 21 10:15 matao2.txt
-rwxrwxr-x 1 b23041310matao b23041310matao 285 12月 3 14:13 num_compare.sh
-rwxrwxr-x 1 b23041310matao b23041310matao 17256 11月 30 19:37 page_rep
-rw-rw-r-- 1 b23041310matao b23041310matao 257 11月 30 19:45 page.txt
-rwxrwxr-x 1 b23041310matao b23041310matao 8576 11月 30 18:52 process_image
-rw-rw-r-- 1 b23041310matao b23041310matao 1546 11月 30 19:45 result.txt
-rwxrwxr-x 1 b23041310matao b23041310matao 8192 11月 30 16:26 sample
-rwxrwxr-x 1 b23041310matao b23041310matao 198 12月 3 14:06 time_check.sh
b23041310matao@b23041310matao-virtual-machine:~$
```

共有 16 个

5. 判断数字是否为质数，需自定义函数

创建文件：gedit check_prime.sh，写入代码并保存退出

```
#!/bin/bash
# 定义质数判断函数
prime()
{
    flag=1
    j=2
    # 处理输入为1的特殊情况 (1不是质数)
    if [ $1 -eq 1 ]
    then
        flag=0
    else
        while [ $j -le `expr $1 / 2` ]
        do
            if [ `expr $1 % $j` -eq 0 ]
            then
                flag=0
                break
            fi
            j=`expr $j + 1`
        done
        fi
        if [ $flag -eq 1 ]
        then
            return 1
        else
            return 0
        fi
    fi
}

# 调用函数 (需传入命令行参数)
if [ $# -ne 1 ]
then
    echo "Usage: $0 <positive_integer>"
    exit 1
fi

prime $1
if [ $? -eq 1 ]
then
    echo "$1 is a prime!"
else
    echo "$1 is not a prime!"
fi
```

授权运行: `chmod +x check_prime.sh`, 执行脚本: `./check_prime.sh ?`, 需传入一个正整数参数, 若无参数: 输出 `Usage: ./check_prime.sh <positive_integer>` 提示用法

```
b23041310matao@b23041310matao-virtual-machine:~$ gedit check_prime.sh
b23041310matao@b23041310matao-virtual-machine:~$ chmod +x check_prime.sh
b23041310matao@b23041310matao-virtual-machine:~$ ./check_prime.sh 7
7 is a prime!
b23041310matao@b23041310matao-virtual-machine:~$ ./check_prime.sh 4
4 is not a prime!
b23041310matao@b23041310matao-virtual-machine:~$ ./check_prime.sh 1
1 is not a prime!
b23041310matao@b23041310matao-virtual-machine:~$ ./check_prime.sh
Usage: ./check_prime.sh <positive_integer>
b23041310matao@b23041310matao-virtual-machine:~$
```