

Using CASE with a CTE(common table expression)

```
WITH temps_collapsed (station_name, max_temperature_group) AS
  (SELECT station_name,
    CASE WHEN max_temp >= 90 THEN 'Hot'
    WHEN max_temp >= 70 AND max_temp <= 90 THEN 'Warm'
    WHEN max_temp >= 50 AND max_temp <= 70 THEN 'Pleasant'
    WHEN max_temp >= 33 AND max_temp <= 50 THEN 'Cold'
    WHEN max_temp >= 20 AND max_temp <= 33 THEN 'Frigid'
    WHEN max_temp < 20 THEN 'Inhumane'
    ELSE 'No Reading'
    END
  FROM temperature_readings)
SELECT station_name, max_temperature_group, count(*)
FROM temps_collapsed
GROUP BY station_name, max_temperature_group
ORDER BY station_name, count(*) DESC;
```

SQL

station_name	max_temperature_group	count
text	text	bigint
CHICAGO NORTHERLY ISLAND IL US	Warm	133
CHICAGO NORTHERLY ISLAND IL US	Cold	92
CHICAGO NORTHERLY ISLAND IL US	Pleasant	91
CHICAGO NORTHERLY ISLAND IL US	Frigid	30
CHICAGO NORTHERLY ISLAND IL US	Inhumane	8
CHICAGO NORTHERLY ISLAND IL US	Hot	8
SEATTLE BOEING FIELD WA US	Pleasant	198
SEATTLE BOEING FIELD WA US	Warm	98
SEATTLE BOEING FIELD WA US	Cold	50
SEATTLE BOEING FIELD WA US	Hot	3

This example reclassifies the temperatures and then counts and groups by station name to find General climate classifications of each city. The WITH keyword defines the CTE of temps_collapsed (with two columns station_name and max_temperature_group). The SELECT query on the CTE is straightforward using COUNT(*) and GROUP BY on both columns.