
Hook manufacturing control

A clear view of outsourced inputs and
ELCRO-managed value-added operations



ELCRO controls molding and finishing



01 Weaving



02 PU coating



03 Hook molding



04 Bonding



05 Cutting



06 Lamination



07 Die cutting



08 Packing

The operating model is mixed - not fully in-house

Process	ELCRO model	Alternative model
Fabric weaving	Outsourced	Outsourced
PU coating	Outsourced	Outsourced
Hook molding	Managed in production	Outsourced
Bonding	Outsourced	Outsourced
Cutting	Managed in production	Outsourced
Lamination	Managed in production	Outsourced
Die cutting	Managed in production	Outsourced
Packing / shipment	Managed in production	Outsourced

Competitor names are anonymized for customer-facing use.

Direct control increases after hook molding

EXTERNALLY SOURCED INPUTS

- Fabric weaving
- PU coating
- Selected bonding operations

Supplier controls should focus on incoming material, coating consistency and bond integrity.

ELCRO-MANAGED VALUE-ADDED WORK



- Hook molding
- Cutting and lamination
- Die cutting and shipment

Implication: ELCRO has more direct control over product geometry and downstream conversion.

Quality gates should follow the product

01

Incoming textile

Width, basis weight, appearance

02

Coating

Coat weight and uniformity

03

Hook geometry

Profile, pitch and engagement

04

Conversion

Cut and die-cut tolerance

05

Release

Traceability and packaging

Proposed validation framework - not a statement of current certification.

Use a controlled sample-to-approval path

1

Data pack

Specifications,
drawings and
material
declarations

2

Samples

Production-intent
parts with lot
traceability

3

Validation

Bench tests and PU
foam trial

4

Commercial

MOQ, lead time and
landed quotation

5

Approval

Customer-required
supplier process

Request a technical review, sample definition and RFQ

Ulsan, Korea | +82 52 264 9104-5