

Reproduction Instructions

How to bring this platform up from a blank Lovable Cloud project.

1. Prerequisites

- Lovable workspace with **Lovable Cloud** enabled (auto-provisions Supabase + storage + auth).
- (Optional but recommended) **Resend** account for the Communications module — you only need the API key.
- (Optional) **Stripe** for ticketing.
- (Optional) **Meta** + **LinkedIn** developer apps for the Social Command Center.

2. Clone the project structure

The project uses the standard Lovable TanStack Start template. After cloning into a fresh project:

```
bun install
```

3. Apply database migrations in order

All schema lives in `supabase-migrations/` . Open Supabase → SQL Editor and run each file **in numeric order**:

```
001_* → 002_* → ... → 038_communications_surveys.sql
```

Latest schema as of writing: `038_communications_surveys.sql` (campaigns, surveys, survey questions/responses, RLS, grants).

The migration files are idempotent (`create table if not exists` , etc.) and safe to re-run if anything is partially applied.

4. Configure secrets

In **Project Settings** → **Secrets**, add what you need:

Secret	Required for	Notes
LOVABLE_API_KEY	Everything	Auto-provisioned
SUPABASE_SERVICE_ROLE_KEY	Server-only writes	Auto-provisioned

Secret	Required for	Notes
RESEND_API_KEY	Communications module	From resend.com
RESEND_FROM	Communications (optional)	e.g. City Events <hello@yourdomain.com> — defaults to onboarding@resend.dev for testing
SITE_URL	Unsubscribe links (optional)	Defaults to deployed URL
DISPATCH_SECRET	Scheduled-campaign cron (optional)	Shared secret for /api/public/dispatch-due
STRIPE_SECRET_KEY	Ticketing	From stripe.com
STRIPE_WEBHOOK_SECRET	Ticketing webhooks	From the Stripe webhook setup

Build secrets (Workspace Settings → Build Secrets) are only needed for private npm packages — not used by this project.

5. Create the first admin user

1. Visit `/signup` and create an account.
2. In Supabase SQL editor, promote yourself to admin:

```
insert into public.user_roles (user_id, role)
values ('<your-auth-user-id>', 'admin');
```

3. Reload the app. You should now see the **Event Ops** sidebar at `/staff`.

6. Bootstrap a department

1. Go to `/staff/admin/departments` → create a department.
2. Go to `/staff/admin/permissions` → assign yourself a department role (`super_admin` or `dept_admin`).
Department admins automatically receive every page-level permission, scoped by RLS to their department.
3. Configure the department's enabled modules at `/staff/admin/tenants` (modules table).
4. Set branding at `/staff/admin/branding`.

7. Configure optional modules

Communications

1. Add `RESEND_API_KEY` to Project Settings.

2. (Optional) Add `RESEND_FROM` with a verified sender. Without it, emails go from `onboarding@resend.dev` (Resend test sender, max 100/day).
3. Grant `page.communications` to staff under **Admin** → **Permissions**.
4. (Optional, for scheduled sends) Set up a per-minute `pg_cron` job in Supabase:

```
select cron.schedule(
  'dispatch-due-campaigns',
  '* * * * *',
  $$select net.http_post(
    url := 'https://YOUR-DOMAIN/api/public/dispatch-due',
    headers := '{"x-dispatch-secret":"YOUR_SECRET"}'::jsonb
  )$$
);
```

Surveys

- No setup needed beyond migration 038 and the `page.surveys` permission.

Social Command Center

1. Create Meta + LinkedIn developer apps (see in-app guide at `/manual#admin-social`).
2. Paste OAuth credentials at `/staff/admin/social-integrations`.
3. Grant `page.social_command` to staff.

Ticketing & Payments

1. Add `STRIPE_SECRET_KEY`, `STRIPE_WEBHOOK_SECRET`.
2. Configure webhook → `https://YOUR-DOMAIN/api/public/stripe-webhook`.

8. Smoke test

After setup, verify each surface loads:

- `/` — home page (CMS-driven, may need content seeded via `/staff/admin/home`)
- `/events` — public event listing
- `/manual` — full visual user manual
- `/staff` — staff dashboard
- `/staff/admin/permissions` — admin panel
- `/staff/communications` — campaigns list (requires `page.communications`)
- `/staff/surveys` — surveys list (requires `page.surveys`)
- `/survey/<some-active-survey-id>` — public anonymous form

9. Publishing

Click **Publish** in Lovable to push to `https://your-project.lovable.app`. The server routes (incl. `/api/public/*`) deploy with the app — no separate edge-function deploy step.

Troubleshooting

“Failed to resolve import” on a route file — make sure the file exists *before* the import statement runs. Run `bun install` and restart the dev server.

new row violates row-level security policy — check that the user is signed in and that the migration’s `GRANT` statements ran (every public-schema table needs explicit grants in addition to RLS policies).

Campaign stays in `scheduled` status forever — cron job isn’t pinging `/api/public/dispatch-due` . Either set up `pg_cron` (step 7 above) or trigger manually with `curl`.

Email comes from `onboarding@resend.dev` — that’s the Resend test sender. Set `RESEND_FROM` to your verified domain.

Survey link returns “Survey not available” — the survey is toggled `Inactive` . Open it in `/staff/surveys/$id` and flip the Active switch.