https://mail.google.com/mail/u/1?ik=a4dada916d&view=pt&search=all&permmsgid=msg-f%3A1711158940326187736&simpl=msg-f%3A1711158940... 3/3

09/21/2021 CSCI-212

Assignment-4

Section 8.6

Note:- Will come back to this section later.

Section 9.4

1. Ans It works. Returns non-zero integer. Ran it with gdb. gdb uses octal to display the exit code.

2. Ans:- @ f.s
@ does nothing but return zero to caller.

@ Define my Raspberry Pi
- cpu cortex-a53
- fpu neon-fp-armv8
- syntax unified @modern syntax

@ Program code
- .text
- .align 2
- .global f
- type f, %function

f:
```
stp   fp, lr, [sp, -48]!   @ save caller frame
                           @ pointer
add   fp, sp, 0            @ establish own frame
                           @ pointer
mov   r0, 0                @ return values go in r0
sub   sp, fp, 0            @ delete allocated memory
ldp   fp, lr, [sp], 48     @ restore caller's frame pointer
                           @ back to caller
```

...vasd <collegeapps1x1@gmail.com>
...AS Screening Notification

3. Ans:

```
@ g.c
@ Returns 123 to caller.

@ Defining my Raspberry Pi
    - cpu cortex-a53
    - fpu neon-fp-armv8
    - syntax unified          @ modern syntax
@ Program code
    .text
    .align 2
    .global g
    .type g, %function

g:
    stmfd sp!, {fp, lr}       @ save caller frame
                              @ pointer
    add fp, sp, #0            @ establish own frame pointer
    mov r0, #123              @ return value 123 in r0
    sub sp, fp, #0            @ delete allocated memory
    ldmfd sp!, {fp, lr}       @ restore caller's frame
                              @ pointer
    bx lr                     @ back to caller
```

4. Ans:

```
/* checkRetNos.c
 * calls three assembly language functions and
 * prints their return numbers.
 */

#include <stdio.h>
int positiveNumber(void);
int negativeNumber(void);
int zeroNumber(void);
```

P.T.O

Exp. No.	Experiment/Subject	Date	
Name	Lab Partner	Locker/ Desk No.	Course & Section No.

```
int main()
{
    int x;
    x = positiveNumber();
    printf("Here is a positive constant: %i\n", x);
    x = negativeNumber();
    printf("a negative constant: %i\n", x);
    x = maxNumber();
    printf("and the maximum number: %i\n", x);
    return 0;
}
```

@ positiveNumber.s
@ Returns +100 to caller.
@ Define my Raspberry Pi
- cpu cortex-a53
- fpu neon-fp-armv8
- syntax unified @ modern syntax
@ Program code
- text
- align 2
- global positiveNumber
- type positiveNumber, %function

```
positiveNumber:
    str     fp, [sp, -4]!   @ save caller frame pointer
    add     fp, sp, 0       @ establish our frame pointer
    mov     r0, 100         @ return +100
    sub     sp, fp, 0       @ restore stack pointer
    ldr     fp, [sp], 4     @ restore caller's frame pointer
    bx      lr              @ back to caller
```

Exp. No. | Experiment Subject | Date

Name | Lab Partner | Locker/Desk No. | Course & Section No.

@ negative_numbers.s
@ Returns -100 to caller.

@ Before my Raspberry Pi
- cpu cortex-a53
- fpu neon-fp-armv8
- system unified @modern system

@ Program code
- .text
- .align 2
- .global negative_numbers
- .type negative_numbers, %function

negative_numbers:
stp fp, [sp, -48]! @ save caller frame pointer
add fp, sp, 0 @ establish own frame pointer
mov x0, -100 @ return -100
sub sp, fp, 0 @ restore stack pointer
ldp fp, [sp], 48 @ restore caller's frame
@ pointer
ret lr @ back to caller

@ max_numbers.s
@ Returns the largest "immediate data" constant to caller
@ which is 8 bits.

@ Before my Raspberry Pi
- cpu cortex-a53
- fpu neon-fp-armv8
- system unified @ modern system

Signature	Date	Witness/TA	Date

@ Program code

```
.text
.align 2
.global maxNumber
.type maxNumber, %function

maxNumber:
    str   fp, [sp, -4]!   @ save caller frame
                          @ pointer
    add   fp, sp, 0       @ establish our frame pointer
    mov   r0, 0xff        @ only 8 bits available for
                          @ immediate
    sub   sp, fp, 0       @ restore stack pointer
    ldr   fp, [sp], 4     @ restore caller's frame
                          @ pointer
    bx    lr              @ back to caller
```

Q. Ans:

```
#include <stdio.h>
int A(void);
int Z(void);
int hashtag(void);

int main()
{
    char aCharacter;
    aCharacter = A();
    printf("Here some characters : %c, ", aCharacter);
    aCharacter = Z();
    printf("%c, ", aCharacter);
    aCharacter = hashtag();
    printf("and %c\n", aCharacter);
    return 0;
}
```

Exp. No.	Experiment/Subject	Date

Name	Lab Partner	Locker/Desk No.	Course & Section No.

@ A.S
@ Returns 'A' to caller.

@ Define my Raspberry Pi
- Cpu cortex-a53
- Cpu neon-fp-armv8
- syntax unified @ modern syntax

@ Program code
- text
- align 2
- global A
- type A, % function

A:
str fp, [sp,-4]! @ save caller frame pointer
add fp, sp, 0 @ establish own frame pointer
mov r0, 'A' @ return 'A'
sub sp, fp, 0 @ restore stack pointer
ldr fp, [sp], 4 @ restore caller's frame pointer
bx lr @ back to caller

@ z.S
@ Returns 'z' to caller

@ Define my Raspberry Pi
- Cpu cortex-a53
- Cpu neon-fp-armv8
- syntax unified @ modern syntax

@ Program code

```
.text
.align 2
.global z
.type z, %function
```

z:

```
str fp, [sp, -4]! @ save caller frame pointer
add fp, sp, 0 @ establish our frame pointer
mov r0, 'z @ return 'z'
sub sp, fp, 0 @ restore stack pointer
ldr fp, [sp], 4 @ restore caller's frame pointer
bx lr @ back to caller
```

@ hashtag:
@ Returns '#' to caller

@ Define my Raspberry Pi
```
.cpu cortex-a53
.fpu neon-fp-armv8
.syntax unified @ modern syntax
```
@ Program code
```
.text
.align 2
.global hashtag
.type hashtag, %function
```

hashtag:

```
str fp, [sp, -4]! @ save caller frame pointer
add fp, sp, 0 @ establish our frame pointer
mov r0, #'# @ return hashtag
sub sp, fp, 0 @ restore stack pointer
ldr fp, [sp], 4 @ restore caller's frame
                @ pointer
bx lr @ back to caller
```

Signature	Date	Witness/TA	Date

Section 8.6

1. Ans Written record of the register :-

0x10464
0x1046c
0x10474
0x10478
0x10480
0x10488
0x10498
0x1049a4
0x1049a8
0x76e6718

8 bytes of machine code are in each of the C statements in this program.

2. Ans:- In any instance of the program, Register R4 is being used for swap.

(a) 0x10488

(b) The contents of the register is on loss (44) than the integer 5 entered when the program prompted me(45).

(c) The C statement uses 12 bytes of program memory

Exp. No.	Experiment/Subject	Date
Name	Lab Partner	Locker/ Desk No.
		Course & Section No.