

1. In the experiment, the input current is set to $I_{in} = I k_A$ (where k_A is the amplifier gain):

$$V_{out} = 130 \times 10^{-3} \cdot B$$

For DC operation,

$$\left(\frac{V_{out}}{I_{in}} \right) = \left(\frac{130 \times 10^{-3} B}{I k_A} \right)$$

2. Extending to all six poles:

$$B = \frac{1}{I k_A} \begin{pmatrix} 130 \times 10^{-3} B_{11} & \cdots & 130 \times 10^{-3} B_{16} \\ 130 \times 10^{-3} B_{21} & \cdots & \vdots \\ \vdots & \ddots & \vdots \\ 130 \times 10^{-3} B_{61} & \cdots & 130 \times 10^{-3} B_{66} \end{pmatrix}$$

Equivalently, the scalar factor can be folded into each entry:

$$= \frac{1}{k_A} \underbrace{\begin{pmatrix} \frac{130 \times 10^{-3}}{I} B_{11} & \cdots & \frac{130 \times 10^{-3}}{I} B_{16} \\ \frac{130 \times 10^{-3}}{I} B_{21} & \cdots & \vdots \\ \vdots & \ddots & \vdots \\ \frac{130 \times 10^{-3}}{I} B_{61} & \cdots & \frac{130 \times 10^{-3}}{I} B_{66} \end{pmatrix}}_{\bar{B}}$$