8255A/8255A-5

Programmable peripheral interface

a. Pin configuration



b. 8255A block diagram



c. Pin names

D_7–D_0	Data Bus (Bi-Directional)
RESET	Reset Input
$\overline{CS}$	Chip Select
$\overline{RD}$	Read Input
$\overline{WR}$	Write Input
A0, A1	Port Address
PA7–PA0	Port A (BIT)
PB7–PB0	Port B (BIT)
PC7–PC0	Port C (BIT)
V_{CC}	+5 Volts
GND	0 Volts

d. Mode definition summary

	MODE 0		MODE 1		MODE 2	
	IN	OUT	IN	OUT	GROUP A ONLY	
PA_0	IN	OUT	IN	OUT	↔	
PA_1	IN	OUT	IN	OUT	↔	
PA_2	IN	OUT	IN	OUT	↔	
PA_3	IN	OUT	IN	OUT	↔	
PA_4	IN	OUT	IN	OUT	↔	
PA_5	IN	OUT	IN	OUT	↔	
PA_6	IN	OUT	IN	OUT	↔	
PA_7	IN	OUT	IN	OUT	↔	
PB_0	IN	OUT	IN	OUT	—	MODE 0 OR MODE 1 ONLY
PB_1	IN	OUT	IN	OUT	—	
PB_2	IN	OUT	IN	OUT	—	
PB_3	IN	OUT	IN	OUT	—	
PB_4	IN	OUT	IN	OUT	—	
PB_5	IN	OUT	IN	OUT	—	
PB_6	IN	OUT	IN	OUT	—	
PB_7	IN	OUT	IN	OUT	—	
PC_0	IN	OUT	$INTR_B$	$INTR_B$	I/O	
PC_1	IN	OUT	IBF_B	$\overline{OBF}_B$	I/O	
PC_2	IN	OUT	$\overline{STB}_B$	$\overline{ACK}_B$	I/O	
PC_3	IN	OUT	$INTR_A$	$INTR_A$	$INTR_A$	
PC_4	IN	OUT	$\overline{STB}_A$	I/O	$\overline{STB}_A$	
PC_5	IN	OUT	IBF_A	I/O	IBF_A	
PC_6	IN	OUT	I/O	$\overline{ACK}_A$	$\overline{ACK}_A$	
PC_7	IN	OUT	I/O	$\overline{OBF}_A$	$\overline{OBF}_A$	

e. 8255 Basic operation

$\overline{RD}$	$\overline{WR}$	$\overline{CS}$	A_1	A_0	Input (Read) cycle
0	1	0	0	0	Port A to Data bus
0	1	0	0	1	Port B to Data bus
0	1	0	1	0	Port C to Data bus
0	1	0	1	1	CWR to Data bus

$\overline{RD}$	$\overline{WR}$	$\overline{CS}$	A_1	A_0	Output (Write) cycle
1	0	0	0	0	Data bus to Port A
1	0	0	0	1	Data bus to Port B
1	0	0	1	0	Data bus to Port C
1	0	0	1	1	Data bus to CWR

$\overline{RD}$	$\overline{WR}$	$\overline{CS}$	A_1	A_0	Function
X	X	1	X	X	Data bus tristated
1	1	0	X	X	Data bus tristated

f. Basic mode definitions and bus interface



g. Control word format



h. Bit set/reset format – port C



i. Input control signal definitions in Mode 1



j. Output control signal definitions in Mode 1



k. Control signal definitions Mode 2



l. Mode 1 status word



m. Mode 2 status word